OPERATING SYSTEMS MIDTERM

Under the Guidance of Prof. GOPINATH M.P.

17BCE0581 SATYAM SINGH CHAUHAN

QUESTION - 6

CODE

```
#include<pthread.h>
#include<semaphore.h>
#include<stdio.h>
#include<stdlib.h>
pthread_mutex_t x,wsem;
pthread_t tid;
int readcount:
void intialize()
{
    pthread mutex init(&x,NULL);
    pthread_mutex_init(&wsem,NULL);readcount=0;
}
void * reader (void * satyam)
    int waittime;
    waittime = rand() % 5;
    printf("\nReader is trying to enter");
    pthread_mutex_lock(&x);
    readcount++;
    if(readcount==1)
         pthread_mutex_lock(&wsem);
    printf("\nReader: %d is inside ",readcount);
    pthread_mutex_unlock(&x);
    sleep(waittime);
    pthread_mutex_lock(&x);
    readcount--;
    if(readcount==0)
         pthread_mutex_unlock(&wsem);
    pthread_mutex_unlock(&x);
    printf("\nReader: %d is Leaving",readcount+1);
}
void * writer (void * satyam)
    int waittime;
    waittime=rand() % 3;
    printf("\nWriter is trying to enter");
    pthread_mutex_lock(&wsem);
    printf("\nWrite has entered");
```

```
sleep(waittime);
    pthread_mutex_unlock(&wsem);
    printf("\nWriter is leaving");
    sleep(30);
    exit(0);
}
int main()
{
    intialize();
    int n1,n2,i;
    printf("\nEnter How Many Readers are there: ");
    scanf("%d",&n1);
    printf("\nEnter How Many Writers are there: ");
    scanf("%d",&n2);
    for(i=0;i<n1;i++)
         pthread_create(&tid,NULL,reader,NULL);
    for(i=0;i< n2;i++)
         pthread create(&tid,NULL,writer,NULL);
    sleep(30);
    printf("\n");
    exit(0);
}
                  🔊 🖃 📵 matlab@sjt419scs005: ~
```

```
matlab@sjt419scs005:~$ vi 17BCE0581_Q6.c
matlab@sjt419scs005:~$ gcc 17BCE0581_Q6.c -lpthread
matlab@sjt419scs005:~$ ./a.out
Enter How Many Readers are there: 4
Enter How Many Writers are there: 3
Reader is trying to enter
Reader: 1 is inside
Writer is trying to enter
Reader is trying to enter
Reader: 2 is inside
Reader is trying to enter
Reader: 3 is inside
Writer is trying to enter
Writer is trying to enter
Reader is trying to enter
Reader: 4 is inside
Reader: 4 is Leaving
Reader: 3 is Leaving
Reader: 2 is Leaving
Reader: 1 is Leaving
Write has entered
Writer is leaving
Write has entered
Writer is leaving
Write has entered
Writer is leaving
matlab@sjt419scs005:~$
```

 $matlab@sjt419scs005:~\$ vi 17BCE0581_Q6.c \\ matlab@sjt419scs005:~\$ gcc 17BCE0581_Q6.c -lpthread \\ matlab@sjt419scs005:~\$./a.out$

Enter How Many Readers are there: 4

Enter How Many Writers are there: 3

Reader is trying to enter

Reader: 1 is inside

Writer is trying to enter

Reader is trying to enter

Reader: 2 is inside

Reader is trying to enter

Reader: 3 is inside

Writer is trying to enter

Writer is trying to enter

Reader is trying to enter

Reader: 4 is inside

Reader: 4 is Leaving

Reader: 3 is Leaving

Reader: 2 is Leaving

Reader: 1 is Leaving

Write has entered

Writer is leaving

Write has entered

Writer is leaving

Write has entered

Writer is leaving

matlab@sjt419scs005:~\$