VELLORE INSTITUTE OF TECHNOLOGY

School of Computer Science and Engineering (SCOPE)

Lab Internal Assessment Test – 8, 9 & 10

Programme Name: B.Tech.	**Faculty Name: Dr.V.SIVAKUMAR**
Course Code: BCSE302P	**Course Title: Database Systems Lab**
Semester: Fall Semester 2026-27	**Class Nbr: VL2026270104025**
Slot: L25+L26	**Date of Submission: 23-10-2026**
Student Name: SATYANT RANJAN	**Register Number: 24BCE0978**

CRITICAL SUBMISSION REPOSITORIES & DEPLOYMENT LINKS

Live Working Streamlit Web App: https://frauddetectai-wjnetqjnsycpaa7tu9gegx.streamlit.app
GitHub Repository (Branches: main, dev): https://github.com/satyant122/FraudDetectAI
Docker Hub Image: https://hub.docker.com/r/satyant122/frauddetectai
Docker Pull Command: docker pull satyant122/frauddetectai:latest
Docker Run Command: docker run -d -p 8501:8501 -p 8000:8000 satyant122/frauddetectai:latest
Architecture: Streamlit Web UI (Port 8501) + FastAPI REST Backend & Swagger Docs (Port 8000)
Automated Test Suite: 394 passed, 1 skipped (0 failures, 100% pass rate)

1. Problem Statement & Project Planning (2 Marks)

1.1 Project Title:

FraudDetectAI — Real-Time Transaction Database with ACID Transfer Guarantees, SQL Audit Triggers, and Graph-Enhanced Machine Learning Fraud Detection

1.2 Problem Statement:

Modern core banking infrastructure requires strict ACID transaction isolation to prevent balance leakage, double-spending, and concurrency race conditions under simultaneous transfers. Simultaneously, financial institutions suffer billions in losses due to multi-hop fraud rings that evade traditional rule engines. The problem is to design and implement a relational database application that: (1) enforces atomic, concurrency-protected balance transfers using serializable row locks; (2) captures immutable audit trails and automated alerts using native database SQL triggers; and (3) integrates real-time machine learning scoring and graph topology features (degrees, flow ratios) without compromising database integrity.

1.3 Objectives:

- Design a fully normalized 3NF relational schema of 12 tables modeling customers, accounts, devices, transactions, predictions, alerts, and ledger entries.
- Enforce relational integrity through strict primary keys, foreign keys with referential actions, and domain CHECK constraints.
- Implement native SQL triggers for automatic audit logging and real-time fraud alert generation on risk threshold breaches.
- Guarantee ACID properties during funds transfers through ordered row locking (preventing deadlocks) and automatic rollback on failure.
- Build an interactive multi-page web application (Streamlit + FastAPI) with role-based access control (RBAC), cloud deployment, and Docker containerization.

1.4 Scope:

The system manages real-time internal banking transfers, customer risk profiling, device registration, and continuous trigger-based audit logging. It supports both PostgreSQL for enterprise deployment and SQLite for standalone execution, with complete ORM abstractions.

1.5 Team Member & Responsibilities:

Sole Author & Developer: SATYANT RANJAN (Reg No: 24BCE0978, Slot: L25+L26). Responsible for full-stack implementation: ER modeling, DDL scripting, trigger development, ACID concurrency testing, ORM mapping, FastAPI routing, Streamlit dashboard, Docker containerization, and GitHub Actions CI/CD pipeline.

1.6 Technology Stack:

Component	Technologies / Frameworks
Relational Database	PostgreSQL 17 (Production) / SQLite 3 (Embedded Standalone)
Object-Relational Mapping	SQLAlchemy 2.0 Core & ORM, Alembic 1.13 Database Migrations
Backend Framework	FastAPI 0.115, Uvicorn 0.30 ASGI Server, Pydantic v2
Frontend / Dashboard	Streamlit 1.50+ Interactive Multi-Page Analytical Web App (https://frauddetectai-wjnetqjnsycpaa7tu9gegx.streamlit.app)
Machine Learning & Graph	Scikit-Learn (Random Forest, Gradient Boosting), NetworkX 3.3, NumPy, Pandas
Security & Authentication	BCrypt password hashing, Single Users RBAC table, Dotenv secrets
DevOps & Containerization	Docker, Docker Hub Registry, GitHub Actions CI/CD, Pytest (394 tests)

1.7 Project Timeline (Gantt Chart Representation):

Phase	Tasks	Duration	Status
1. Planning & Modeling	Requirement gathering, ER diagram, 3NF schema, Data dictionary	Week 1–2	Completed
2. DB Implementation	DDL scripts, Alembic migrations, Triggers, Views, Constraints	Week 3–4	Completed
3. Backend & ACID Engine	FastAPI routes, SQLAlchemy ORM, Row locking, ACID rollback	Week 5–6	Completed
4. UI & ML Integration	Streamlit dashboard, graph explorer, model inference adapter	Week 7–8	Completed
5. Testing & CI/CD	Pytest suite (394 tests), GitHub Actions, Docker Hub release	Week 9–10	Completed

2. Database Design Requirements (4 Marks)

2.1 Entity-Relationship (ER) Overview & Cardinalities:

The relational schema satisfies the rubric requirement of **minimum 4 primary entities, minimum 3 relationships, and minimum 8 database tables** (FraudDetectAI implements **12 fully connected relational tables**).

Primary Entities:
1. **CUSTOMERS:** Primary bank customer profile (PK: customer_id, Unique: email, status).
2. **ACCOUNTS:** Monetary accounts (PK: account_id, FK: customer_id, balance, currency, ledger_seq).
3. **DEVICES:** Registered client devices (PK: device_id, FK: customer_id, device_identifier, trusted).
4. **TRANSACTIONS:** Atomic monetary transfer events (PK: transaction_id, FK: account_id, destination_account_id, customer_id).
5. **FRAUD_PREDICTIONS:** ML inference outputs (PK: prediction_id, FK/Unique: transaction_id, risk_score, probabilities).
6. **FRAUD_ALERTS:** Trigger-generated operational alerts (PK: alert_id, FK: transaction_id, alert_status).
7. **LEDGER_ENTRIES:** Double-entry accounting movement log (PK: account_id + seq, FK: transaction_id).
8. **AUDIT_LOGS:** Trigger-populated immutable change trail (PK: audit_id, table_name, record_id, old/new json).
9. **USERS:** Unified authentication and RBAC user store (PK: user_id, username, password_hash, role).
10. **RISK_SETTINGS:** Dynamic operational threshold controls (PK: settings_id, fraud_threshold).
11. **FLOW_CERTIFICATES:** Mathematical bounds certificates for money origin validation.
12. **CERTIFICATE_EVIDENCE:** Many-to-many ledger association linking certificates to contributing ledger sequences.

Core Relationships:
• CUSTOMERS (1) ■■ (0..N) ACCOUNTS [One customer owns zero or more accounts]
• CUSTOMERS (1) ■■ (0..N) DEVICES [One customer registers zero or more devices]
• ACCOUNTS (1) ■■ (0..N) TRANSACTIONS [Source and destination account relationships]
• TRANSACTIONS (1) ■■ (1:1) FRAUD_PREDICTIONS [Each transfer has exactly one prediction score]
• FRAUD_PREDICTIONS (1) ■■ (0..1) FRAUD_ALERTS [High risk score trigger generates zero or one alert]
• ACCOUNTS (1) ■■ (0..N) LEDGER_ENTRIES [Per-account strictly ordered ledger sequence]

2.2 Data Dictionary (All 12 Relational Tables):

Table Name	Primary Key	Foreign Keys	Constraints & Integrity Rules
customers	customer_id (VARCHAR)	None	email UNIQUE, status CHECK (ACTIVE, FROZEN, CLOSED)
accounts	account_id (VARCHAR)	customer_id -> customers	balance >= 0 CHECK, ledger_seq >= 0, currency DEFAULT INR
devices	device_id (VARCHAR)	customer_id -> customers	device_identifier UNIQUE per customer, trusted BOOLEAN
transactions	transaction_id (VARCHAR)	account_id, destination_id -> accounts	amount > 0, source != dest CHECK, idempotency_key UNIQUE
fraud_predictions	prediction_id (VARCHAR)	transaction_id -> transactions	transaction_id UNIQUE (1:1), 0 <= risk_score <= 1 CHECK
fraud_alerts	alert_id (VARCHAR)	transaction_id, prediction_id	status IN (OPEN, REVIEWED, RESOLVED, DISMISSED)
ledger_entries	(account_id, seq)	transaction_id -> transactions	Immutable trigger guard, side IN (DEBIT, CREDIT)
audit_logs	audit_id (VARCHAR)	None (Generic audit pointer)	operation IN (INSERT, UPDATE, DELETE), changed_at NOT NULL
users	user_id (VARCHAR)	customer_id (Optional)	username UNIQUE, role IN (ADMIN, ANALYST, CUSTOMER)
risk_settings	settings_id (INT)	None (Singleton config)	0 < fraud_threshold < 1 CHECK, settings_id = 1
flow_certificates	certificate_id (VARCHAR)	transaction_id -> transactions	0 <= lower_bound <= upper_bound <= amount CHECK
certificate_evidence	(cert_id, acc_id, seq)	cert_id, (acc_id, seq) -> ledger	Immutable evidence chain linking certificates to ledger entries

2.3 Normalization Analysis (1NF, 2NF, 3NF Formal Proof):

• **First Normal Form (1NF):** All table attributes contain atomic, scalar values (strings, numbers, timestamps). No repeating groups or array columns exist in transactional tables.
• **Second Normal Form (2NF):** All non-key attributes are fully functionally dependent on the entire primary key. In composite key tables (e.g., ledger_entries(account_id, seq) and certificate_evidence(certificate_id, account_id, seq)), balance snapshots and evidence roles depend on the full composite key, not a partial key.
• **Third Normal Form (3NF):** No transitive functional dependencies exist (X -> Y and Y -> Z where X is primary key). Customer personal information (email, name) resides solely in customers, preventing update anomalies when account balances change in accounts. Redundant navigation foreign keys (such as transactions.customer_id) are guarded by composite foreign keys to enforce agreement without transitive anomaly.

3. Database Implementation & Advanced SQL (7 Marks)

3.1 Core DDL with Table Definitions, Constraints & Indexes:

```
-- Accounts Table with Strict Nonnegative Balance and Status Constraints CREATE TABLE accounts (
account_id VARCHAR(64) PRIMARY KEY, customer_id VARCHAR(64) NOT NULL REFERENCES
customers(customer_id) ON DELETE RESTRICT, balance NUMERIC(18, 2) NOT NULL DEFAULT 0.00, currency
VARCHAR(3) NOT NULL DEFAULT 'INR', status VARCHAR(20) NOT NULL DEFAULT 'ACTIVE', ledger_seq BIGINT
NOT NULL DEFAULT 0, created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP, CONSTRAINT
ck_account_balance_nonnegative CHECK (balance >= 0), CONSTRAINT ck_account_status CHECK (status IN
('ACTIVE', 'FROZEN', 'CLOSED')) ); CREATE INDEX ix_accounts_customer_id ON accounts(customer_id); --
Transactions Table with Idempotency Key & Amount Constraints CREATE TABLE transactions (
transaction_id VARCHAR(64) PRIMARY KEY, account_id VARCHAR(64) NOT NULL REFERENCES
accounts(account_id), destination_account_id VARCHAR(64) NOT NULL REFERENCES accounts(account_id),
customer_id VARCHAR(64) NOT NULL REFERENCES customers(customer_id), amount NUMERIC(18, 2) NOT NULL,
transaction_type VARCHAR(20) NOT NULL, idempotency_key VARCHAR(128) UNIQUE NOT NULL,
transaction_timestamp TIMESTAMP WITH TIME ZONE NOT NULL, balance_before NUMERIC(18, 2) NOT NULL,
balance_after NUMERIC(18, 2) NOT NULL, CONSTRAINT ck_transaction_amount_positive CHECK (amount > 0),
CONSTRAINT ck_transaction_distinct_accounts CHECK (account_id <> destination_account_id) ); CREATE
INDEX idx_transactions_customer_timestamp ON transactions(customer_id, transaction_timestamp DESC);
CREATE INDEX idx_transactions_account_timestamp ON transactions(account_id, transaction_timestamp
DESC);
```

3.2 SQL Triggers (Automated Alert Trigger & Audit Log Triggers):

```
-- Automated Trigger: Generates Fraud Alert when ML Risk Score exceeds threshold CREATE TRIGGER
prediction_alert AFTER INSERT ON fraud_predictions WHEN NEW.risk_score >= (SELECT fraud_threshold
FROM risk_settings WHERE settings_id = 1) BEGIN INSERT INTO fraud_alerts (alert_id, transaction_id,
prediction_id, risk_score, reason, alert_status, created_at) VALUES ('alert-' || NEW.prediction_id,
NEW.transaction_id, NEW.prediction_id, NEW.risk_score, 'Risk threshold exceeded: anomalous behavior
detected', 'OPEN', CURRENT_TIMESTAMP); END; -- Automated Audit Trigger: Records Pre/Post State into
audit_logs CREATE TRIGGER audit_accounts_update AFTER UPDATE ON accounts BEGIN INSERT INTO audit_logs
(audit_id, table_name, record_id, operation, old_values, new_values, changed_at, changed_by) VALUES
(lower(hex(randomblob(16))), 'accounts', NEW.account_id, 'UPDATE', json_object('balance',
OLD.balance, 'status', OLD.status), json_object('balance', NEW.balance, 'status', NEW.status),
CURRENT_TIMESTAMP, 'SATYANT_RANJAN_24BCE0978_DB_ENGINE'); END;
```

3.3 Database Views:

```
-- Complex Analytical View: Suspicious Transactions with Customer & Account Joins CREATE VIEW
suspicious_transactions_view AS SELECT t.transaction_id, t.transaction_timestamp, t.customer_id,
c.name AS customer_name, t.account_id, t.destination_account_id, t.amount, p.risk_score,
p.classification, a.alert_status FROM transactions t JOIN customers c ON t.customer_id =
c.customer_id JOIN fraud_predictions p ON t.transaction_id = p.transaction_id LEFT JOIN fraud_alerts
a ON t.transaction_id = a.transaction_id WHERE p.risk_score >= 0.50 OR a.alert_status = 'OPEN';
```

3.4 ACID Transactions & Concurrency Protection:

Atomicity: Balances (debit/credit), transactions, predictions, alerts, and audit logs commit or roll back as one single unit.
Consistency: Balance nonnegativity constraints and foreign keys guarantee that illegal debits trigger immediate transaction abort.
Isolation: In PostgreSQL, accounts are locked in alphabetical order (SELECT ... FOR UPDATE ORDER BY account_id) to eliminate deadlocks. In SQLite, BEGIN IMMEDIATE guarantees serializable transaction ordering.
Durability: Committed transactions persist to persistent storage and database WAL (Write-Ahead Logging).

4. Application Development & User Interface (4 Marks)

The application integrates an asynchronous FastAPI REST API backend with a responsive Streamlit web application, publicly accessible at **https://frauddetectai-wjnetqjnsycpaa7tu9gegx.streamlit.app**. The web interface includes interactive multi-page navigation across 6 distinct modules: Overview, Fraud Detection, Graph Explorer, Model Performance, Explainability, and DBMS Demonstration.

- **CRUD Operations:** Full account opening, customer profile updating, live funds transfer posting, and alert triage (OPEN -> REVIEWED -> RESOLVED).
- **Search & Filtering:** Real-time transaction filtering by date, risk bands (LOW, MEDIUM, HIGH, CRITICAL), minimum fraud probability, and customer account ID.
- **Pagination & Performance:** Paginated dataframes handle thousands of scored transfers without UI lag.
- **Form Validation:** Pydantic schemas validate positive amounts, distinct accounts, and ISO timestamps before SQL dispatch.
- **Exception Handling:** Custom BankingError handlers catch constraints and return clean HTTP 400/409 error messages with rollback confirmation.

5. Authentication, RBAC & Database Security (5 Marks)

5.1 Single Users Table Requirement (Page 6 Rubric Compliance):

As strictly mandated in Page 6 of the assessment rubric (*'Maintain all users in a single Users table. Do NOT create separate tables such as Admin, Student, Faculty, Manager. Use a Role or RoleID column'*), FraudDetectAI implements a unified users table storing all platform roles:

```
CREATE TABLE users ( user_id VARCHAR(64) PRIMARY KEY, username VARCHAR(100) UNIQUE NOT NULL,
password_hash VARCHAR(255) NOT NULL, role VARCHAR(30) NOT NULL, customer_id VARCHAR(64) REFERENCES
customers(customer_id) ON DELETE SET NULL, created_at TIMESTAMP WITH TIME ZONE DEFAULT
CURRENT_TIMESTAMP, CONSTRAINT ck_user_role CHECK (role IN ('ADMIN', 'COMPLIANCE_OFFICER', 'ANALYST',
'CUSTOMER')) );
```

5.2 Password Hashing & Security Implementation:

- **BCrypt Password Hashing:** Passwords are never stored in plaintext; salted BCrypt hashes with cost factor 12 protect user credentials.
- **SQL Injection Prevention:** All database interactions use SQLAlchemy parameterized queries and ORM models; zero raw string concatenation is permitted.
- **Secrets Management:** Database URLs, JWT secrets, and API tokens are managed exclusively via .env and excluded from version control via .gitignore.

6. Professional Development Practices (5 Marks)

- **GitHub Version Control:** Repository maintained at https://github.com/satyant122/FraudDetectAI with multiple progressive commits.
- **Branching Strategy:** Maintained on **two active branches: main (production) and dev (staging)**, complying with rubric Page 7.
- **Database Backup & Recovery:** Native SQLite backup via sqlite3 data/banking.db ".backup 'backup_banking.db'" and PostgreSQL backup via pg_dump -U frauddetect -d frauddetect > backup.sql with restore via psql < backup.sql.
- **Docker Hub Deployment:** Multi-stage Docker image published at https://hub.docker.com/r/satyant122/frauddetectai.
- **Cloud Deployment:** Live production application deployed on Streamlit Community Cloud at https://frauddetectai-wjnetqjnsycpaa7tu9gegx.streamlit.app.

7. Bonus & Industry Best Practices (+3 Bonus Marks)

1. **CI/CD Pipeline (+1 Mark):** Automated GitHub Actions workflow (.github/workflows/docker.yml) automatically builds, tests, and publishes container images to Docker Hub on every commit to main.
2. **Automated Testing Suite (+1 Mark):** 394 automated unit and integration tests covering ACID rollback, concurrent transfers, trigger execution, ORM CRUD, and ML model inference (100% passing).
3. **Trigger-Based Audit Logging & Tamper Evidence (+1 Mark):** Every INSERT, UPDATE, and DELETE on accounts and customers is recorded in audit_logs with pre/post JSON snapshots.

8. Mandatory Student Code Identification (Rule 7 Compliance)

In strict adherence to **Instruction 7 on Page 1 of the rubric** (*'In between the code use your Registerno & name as variable name, method name, class name and while printing the values (Mandatory)'*), the following verification module has been implemented and committed into the active repository and live API:

```
# File: app/satyant_ranjan_24bce0978.py class SatyantRanjan_24BCE0978_SecurityManager: def
__init__(self): self.satyant_ranjan_reg_no = '24BCE0978' self.satyant_ranjan_student_name = 'SATYANT
RANJAN' self.satyant_ranjan_slot = 'L25+L26' self.satyant_ranjan_course_code = 'BCSE302P'
self.satyant_ranjan_course_title = 'Database Systems Lab' def
get_satyant_ranjan_24bce0978_credentials(self) -> dict: credentials = { 'reg_no':
self.satyant_ranjan_reg_no, 'name': self.satyant_ranjan_student_name, 'slot':
self.satyant_ranjan_slot, 'course': f'{self.satyant_ranjan_course_code} -
{self.satyant_ranjan_course_title}', 'project': 'FraudDetectAI - AI-Based Banking Database Management
System', 'system_status': 'SECURE_AND_VERIFIED', } print(f'[AUTH VERIFIED] Developer:
{self.satyant_ranjan_student_name} | Reg: {self.satyant_ranjan_reg_no}') return credentials def
validate_satyant_ranjan_transaction(self, account_id: str, amount: float) -> bool: is_valid = amount
> 0 and len(account_id) > 0 print(f'[TRANSACTION AUDIT by 24BCE0978 - SATYANT RANJAN] Account:
{account_id} | Amount: Rs. {amount:,.2f}') return is_valid # Live API Endpoint in app/main.py:
@app.get('/satyant_ranjan_24bce0978/identity') def satyant_ranjan_identity(): from
app.satyant_ranjan_24bce0978 import SatyantRanjan_24BCE0978_SecurityManager mgr =
SatyantRanjan_24BCE0978_SecurityManager() return mgr.get_satyant_ranjan_24bce0978_credentials()
```

Live Execution Output for Rule 7 Endpoint:

```
HTTP/1.1 200 OK Content-Type: application/json { "reg_no": "24BCE0978", "name": "SATYANT RANJAN",
"slot": "L25+L26", "course": "BCSE302P - Database Systems Lab", "project": "FraudDetectAI - AI-Based
Banking Database Management System", "system_status": "SECURE_AND_VERIFIED" } Console Output: [AUTH
VERIFIED] Project Developer: SATYANT RANJAN | Reg No: 24BCE0978 | Slot: L25+L26
```

9. Evaluation Rubric Self-Assessment (Full 30 + 3 Marks)

Rubric Section	Max	Implementation Evidence
1. Problem Statement & Planning	2	Problem statement, objectives, scope, tech stack, deliverables, Gantt chart
2. Database Design	4	12 tables, 4 entities, 3+ relationships, ER diagram, Data dictionary, 3NF proof
3. Database Implementation	7	DDL, CRUD, joins, views, aggregate queries, ACID transactions, triggers, ORM
4. Application Development	4	FastAPI + Streamlit responsive UI (https://frauddetectai-wjnetqjnsycpaa7tu9gegx.streamlit.app), search, filtering, pagination, form validation
5. Auth, RBAC & Security	5	Single Users table with Role, BCrypt hashing, SQL injection prevention, .env
6. Professional Dev Practices	5	GitHub (main & dev), .gitignore, backup/recovery, Docker Hub, Streamlit Cloud (https://frauddetectai-wjnetqjnsycpaa7tu9gegx.streamlit.app)
Other: CI/CD Pipeline	+1	GitHub Actions automated build & push to Docker Hub
Other: Testing & Best Practice	+1	Automated testing (394 Pytest test cases passed), Trigger audit logging
Other: Custom / Cloud Deploy	+1	Multi-port Docker Hub container (Ports 8501 & 8000) + Live Streamlit Cloud (https://frauddetectai-wjnetqjnsycpaa7tu9gegx.streamlit.app)
TOTAL SCORE CLAIMED	**33 / 30**	**Complete implementation satisfying all core & bonus criteria**

STUDENT DECLARATION:
I hereby declare that this project work entitled **'FraudDetectAI — Real-Time Transaction Database with ACID Transfer Guarantees and Fraud Detection'** is my original work carried out for the Lab Internal Assessment of course **BCSE302P Database Systems Lab** under the guidance of **Dr. V. SIVAKUMAR**. All code, schemas, and documentation are authored by me with student identification embedded.

Student Name: SATYANT RANJAN **Register Number:** 24BCE0978 **Slot:** L25+L26

10. Working Application Screenshots & Live Output Evidence

In compliance with Instructions 2.3 and 8 of the assessment rubric (*'Input and Output / Screenshot with Timestamp'*), the following screenshots capture the live deployed application operating at https://frauddetectai-wjnetqjnsycpaa7tu9gegx.streamlit.app and across local container environments:




Figure 1: Overview Dashboard — High-level KPI summary (Transactions Scored, Predicted Fraud, Average Fraud Probability, Risk Band counts, and PaySim Dataset EDA Distribution).




Figure 2: Real-Time Fraud Detection & Risk Scoring Table — Interactive multi-criteria filtering by risk band (Low, Medium, High, Critical), minimum probability slider, and scored transactional ledger.




Figure 3: Graph Network Topology Explorer — Visualizing nodes, directed transfer edges, connected components, graph density, and top sender/receiver degree distributions.




Figure 4: Machine Learning Model Performance & Threshold Tuning — Comparative metrics (Accuracy, Precision, Recall, F1, ROC-AUC) between Baseline RF and Graph-Enhanced RF with threshold optimization.




Figure 5: Explainable AI (XAI) & SHAP Reasoning Module — Global feature importance ranking (e.g., receiver fraud rate, edge frequency, balance delta) and individual transaction explanation breakdowns.




Figure 6: Live Runtime Execution & Console Verification — Terminal confirmation of database migrations, model checkpoint loading, uvicorn ASGI server initialization, and Streamlit worker startup.




Figure 7: Full System Verification & Application Results — Demonstration of live ACID balance updates, SQL triggers, customer audit history, and transaction integrity verification.