

Conditional Statements



CONTENT

01

Introduction

02

If Statement

03

If...else Statement

04

If...else if...else Statement

05

Switch Statement

06

Ternary Operator





01

Introduction

What are Conditional Statements?

Conditional statements are used to make decisions in your code — based on whether an expression is true or false.

allow your program to choose different paths of execution based on conditions — like real-life "if this happens, do that"





02

If Statement

If Statement

Executes a block of code **only if the condition is true.**

Syntax :

If() {-----→ Opening
};-----→ Closing

```
JS index.js  X
JS index.js > ...
1  let age = 20;
2
3  if (age >= 18) {
4    console.log("You are an adult");
5  }
6
```

Output :

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS Filter

```
[Running] node "c:\Users\Lenovo\Desktop\prac\index.js"
You are an adult

[Done] exited with code=0 in 0.087 seconds
```





03

If...else Statement

If...else Statement

Executes one block if true, another if false.

Output :

```
[Running] node "c:\Users\Lenovo\Desktop\prac\index.js"  
You are Minor
```

```
[Done] exited with code=0 in 0.123 seconds
```

JS index.js ×

JS index.js > ...

```
1  let age = 17;  
2  
3  if (age >= 18) {  
4    console.log("You are an adult");  
5  }else{  
6    console.log("You are Minor");  
7  
8  }  
9
```





04

If...else if...else Statement

If...else if...else Statement

Checks **multiple conditions** in sequence.

Output :

```
JS index.js  X
JS index.js > ...
1  let marks = 75;
2
3  if (marks > 90) {
4    console.log("Grade: A");
5  } else if (marks >= 70) {
6    console.log("Grade: B");
7  } else {
8    console.log("Grade: C");
9  }
10
```

```
[Running] node "c:\Users\Lenovo\Desktop\prac\index.js"
```

```
Grade: B
```

```
[Done] exited with code=0 in 0.081 seconds
```





05

Switch Statement

Switch Statement

Best for **comparing one value** against multiple **exact match** cases.

Output :

```
[Running] node "c:\Users\Lenovo\Desktop\prac\index.js"  
Start of the week
```

```
[Done] exited with code=0 in 0.102 seconds
```

```
JS index.js  X  
  
JS index.js > ...  
1  let day = "Monday";  
2  
3  switch (day) {  
4    case "Monday":  
5      console.log("Start of the week");  
6      break;  
7    case "Friday":  
8      console.log("Almost weekend");  
9      break;  
10   default:  
11     console.log("Just another day");  
12  }
```





05

Ternary Operator

Ternary Operator

Short-hand for simple if...else

Output :

JS index.js ×

JS index.js > ...

```
1 let age = 20;  
2  
3 let status = (age >= 18) ? "Adult" : "Minor";  
4 console.log(status)
```

[Running] node "c:\Users\Lenovo\Desktop\prac\index.js"
Adult

[Done] exited with code=0 in 0.094 seconds

