

# Com.Dbconnection

## Dbconnection.java

```
package com.Dbconnection;

import java.sql.*;

public class Dbconnection {

    public static Connection GetConnection()

    {

        Connection con = null;

        try

        {

            Class.forName("com.mysql.cj.jdbc.Driver");

            con = DriverManager.getConnection("jdbc:mysql://localhost:3306/flyawayp",
            "root", "Saurabh@12");

        }

        catch (Exception ex)

        {

            System.out.println(ex);

        }

        return con;

    }

}
```

# Com.Servlets

## AdminLogin.java

```
package com.Servlets;

import java.io.IOException;
import java.sql.Connection;
import java.sql.ResultSet;
import java.sql.Statement;

import javax.servlet.ServletException;
import javax.servlet.annotation.WebServlet;
import javax.servlet.http.HttpServlet;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;
import javax.servlet.http.HttpSession;

import com.Dbconnection.Dbconnection;

/**
 * Servlet implementation class AdminLogin
 */
@WebServlet("/AdminLogin")
public class AdminLogin extends HttpServlet {
    private static final long serialVersionUID = 1L;

    /**
     * @see HttpServlet#HttpServlet()
     */
    public AdminLogin() {
```

```

    super();

    // TODO Auto-generated constructor stub
}

/**
 * @see HttpServlet#service(HttpServletRequest request, HttpServletResponse response)
 */
protected void service(HttpServletRequest request, HttpServletResponse response) throws
ServletException, IOException {

    String email = request.getParameter("email");
    String pwd = request.getParameter("password");

    int z =0;

    try
    {
        Connection con = Dbconnection.GetConnection();
        Statement st = con.createStatement();

        ResultSet rs = st.executeQuery("select * from adminlogin where ademail='"+ email
+ "'" and adpwd='"+ pwd+ "'");

        while(rs.next())
        {

            HttpSession session = request.getSession();
            session.setAttribute("email", email);
            response.sendRedirect("AdminDashboard.jsp");

        }
    }
}

```

```

        if(email.equals(email) && pwd.equals(pwd))
        {
            response.sendRedirect("AdminLogin.jsp?msg=notexist");
        }

    }

    catch(Exception ex)
    {
        System.out.println(ex);
    }
}

/**
 * @see HttpServlet#doGet(HttpServletRequest request, HttpServletResponse response)
 */
protected void doGet(HttpServletRequest request, HttpServletResponse response) throws
ServletException, IOException {
    // TODO Auto-generated method stub
    response.getWriter().append("Served at: ").append(request.getContextPath());
}

/**
 * @see HttpServlet#doPost(HttpServletRequest request, HttpServletResponse response)
 */
protected void doPost(HttpServletRequest request, HttpServletResponse response) throws
ServletException, IOException {
    // TODO Auto-generated method stub
    doGet(request, response);
}
}

```

# CustomerLogin.java

```
package com.Servlets;

import java.io.IOException;
import java.sql.Connection;
import java.sql.ResultSet;
import java.sql.Statement;

import javax.servlet.ServletException;
import javax.servlet.annotation.WebServlet;
import javax.servlet.http.HttpServlet;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;
import javax.servlet.http.HttpSession;

import com.Dbconnection.Dbconnection;

/**
 * Servlet implementation class CustomerLogin
 */
@WebServlet("/CustomerLogin")
public class CustomerLogin extends HttpServlet {

    private static final long serialVersionUID = 1L;

    /**
     * @see HttpServlet#HttpServlet()
     */
    public CustomerLogin() {
        super();
        // TODO Auto-generated constructor stub
    }
}
```

```
}
```

```
/**
```

```
 * @see HttpServlet#service(HttpServletRequest request, HttpServletResponse response)
```

```
 */
```

```
protected void service(HttpServletRequest request, HttpServletResponse response) throws  
ServletException, IOException {
```

```
    String email = request.getParameter("email");
```

```
    String pwd = request.getParameter("password");
```

```
    int z = 0;
```

```
    try
```

```
    {
```

```
        Connection con = Dbconnection.GetConnection();
```

```
        Statement st = con.createStatement();
```

```
        ResultSet rs = st.executeQuery("select * from passenger where email='"+ email +"'  
and passwd='"+ pwd+ "'");
```

```
        while(rs.next())
```

```
        {
```

```
            HttpSession session = request.getSession();
```

```
            session.setAttribute("email", email);
```

```
            response.sendRedirect("CustomerDashboard.jsp");
```

```
        }
```

```
        if(email.equals(email) && pwd.equals(pwd))
```

```
        {
```

```

        response.sendRedirect("CustomerDashboard.jsp?msg=notexist");
    }

}

    catch(Exception ex)
    {
        System.out.println(ex);
    }
}

/**
 * @see HttpServlet#doGet(HttpServletRequest request, HttpServletResponse response)
 */
protected void doGet(HttpServletRequest request, HttpServletResponse response) throws
ServletException, IOException {
    // TODO Auto-generated method stub
    response.getWriter().append("Served at: ").append(request.getContextPath());
}

/**
 * @see HttpServlet#doPost(HttpServletRequest request, HttpServletResponse response)
 */
protected void doPost(HttpServletRequest request, HttpServletResponse response) throws
ServletException, IOException {
    // TODO Auto-generated method stub
    doGet(request, response);
}

}

```

# FlightAdd.java

```
package com.Servlets;

import java.io.IOException;
import java.sql.Connection;
import java.sql.PreparedStatement;

import javax.servlet.ServletException;
import javax.servlet.annotation.WebServlet;
import javax.servlet.http.HttpServlet;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;

import com.Dbconnection.Dbconnection;

/**
 * Servlet implementation class FlightAdd
 */
@WebServlet("/FlightAdd")
public class FlightAdd extends HttpServlet {

    private static final long serialVersionUID = 1L;

    /**
     * @see HttpServlet#HttpServlet()
     */
    public FlightAdd() {
        super();
        // TODO Auto-generated constructor stub
    }
}
```



```

/**
 * @see HttpServlet#service(HttpServletRequest request, HttpServletResponse response)
 */
protected void service(HttpServletRequest request, HttpServletResponse response) throws
ServletException, IOException {

    String airport = request.getParameter("airport");

    String airline = request.getParameter("airline");

    String source = request.getParameter("source");

    String destination = request.getParameter("destination");

    String seats = request.getParameter("seats");

    String price = request.getParameter("price");


    try
    {
        Connection con = Dbconnection.GetConnection();

        PreparedStatement ps = con.prepareStatement("insert into
flight(Airport,airline,source,destination,seats,price) value(?,?,?,?,?,?)");

        ps.setString(1, airport);

        ps.setString(2, airline);

        ps.setString(3, source);

        ps.setString(4, destination);

        ps.setInt(5, Integer.parseInt(seats));

        ps.setInt(6, Integer.parseInt(price));

        ps.executeUpdate();

        response.sendRedirect("Airline.jsp?msg=done");

    }

    catch(Exception ex)

    {

        response.sendRedirect("Airline.jsp?msg=wrong");

    }
}

```

```
}

/**
 * @see HttpServlet#doGet(HttpServletRequest request, HttpServletResponse response)
 */
protected void doGet(HttpServletRequest request, HttpServletResponse response) throws
ServletException, IOException {
    // TODO Auto-generated method stub
    response.getWriter().append("Served at: ").append(request.getContextPath());
}

/**
 * @see HttpServlet#doPost(HttpServletRequest request, HttpServletResponse response)
 */
protected void doPost(HttpServletRequest request, HttpServletResponse response) throws
ServletException, IOException {
    // TODO Auto-generated method stub
    doGet(request, response);
}

}
```

# SearchFunt.java

```
package com.Servlets;

import java.io.IOException;
import java.sql.Connection;
import java.sql.ResultSet;
import java.sql.Statement;
import java.util.HashMap;

import javax.servlet.RequestDispatcher;
import javax.servlet.ServletException;
import javax.servlet.annotation.WebServlet;
import javax.servlet.http.HttpServlet;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;
import javax.servlet.http.HttpSession;

import com.Dbconnection.Dbconnection;

/**
 * Servlet implementation class SearchFunt
 */
@WebServlet("/SearchFunt")
public class SearchFunt extends HttpServlet {
    private static final long serialVersionUID = 1L;

    /**
     * @see HttpServlet#HttpServlet()
     */
    public SearchFunt() {
```

```

super();

// TODO Auto-generated constructor stub
}

/**
 * @see HttpServlet#doPost(HttpServletRequest request, HttpServletResponse response)
 */
protected void doPost(HttpServletRequest request, HttpServletResponse response) throws
ServletException, IOException {
try{

        String soure = request.getParameter("sourc");

        String desti = request.getParameter("destin");

        Connection con = Dbconnection.GetConnection();

        Statement st = con.createStatement();

        ResultSet rs = st.executeQuery("select * from flight where sourcee
="" +soure+"" and destination = ""+desti+""");

        while(rs.next())
        {

                rs.getString(1);

                rs.getString(2);

                rs.getString(3);

                rs.getString(4);

                rs.getString(5);

                rs.getString(6);

                response.sendRedirect("RegisterPassenger.jsp?book=" +
rs.getString(1));

```

```

        HashMap<String, String> booking = new HashMap<String, String>();
        booking.put("airpt", rs.getString(1));
        booking.put("airlir", rs.getString(2));
        booking.put("soe", rs.getString(3));
        booking.put("desit", rs.getString(4));
        booking.put("seait", rs.getString(5));
        booking.put("prct", rs.getString(6));

        HttpSession session = request.getSession();
        session.setAttribute("bkdetil", booking);

        RequestDispatcher dispatcher =
request.getRequestDispatcher("FinalPage.jsp");
        dispatcher.forward(request, response);

    }

}

catch(Exception ex)
{

}

}

}

```

# AdminDashboard.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
pageEncoding="UTF-8"%>

<%@ page import="com.Servlets.*" %>

<!DOCTYPE html>

<html>

<head>

<meta charset="UTF-8">

<title>Admin Dashboard</title>

<link rel="stylesheet" href="style.css" >

</head>

<body>

<h1>Welcome <%=session.getAttribute("email").toString() %></h1>

<a href="AdminLogin.jsp"> Logout</a>

<a href="Airline.jsp">Add airline</a>

<a href="ViewAllFlight.jsp">ViewAllFlight</a>

<a href="Changepass.jsp">Change Password</a>

</body>

</html>
```

# AdminLogin.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
pageEncoding="UTF-8"%>

<!DOCTYPE html>

<html>

<head>

<meta charset="UTF-8">

<title>Admin Login</title>

<link rel="stylesheet" href="style.css" >

</head>

<body >

<form action="Airline.jsp" method="post">

<h1>Admin Login</h1>

<label>Email</label>

<input type="text" name="email" placeholder="Email">

<br>

<label>Password</label>

<input type="text" name="password" placeholder="Password">

<input type="submit" value="Login">

</form>

<%

String msg = request.getParameter("msg");

if("notexist".equals(msg))

{

%>

<h1>Password Invalid/User Not Exist</h1>

<%}%>
```

```
</body>
```

```
</html>
```

# Airline.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
```

```
pageEncoding="UTF-8"%>
```

```
<%@ page import="com.Servlets.*" %>
```

```
<%@include file="AdminDashboard.jsp" %>
```

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<meta charset="UTF-8">
```

```
<title>Airline Adding</title>
```

```
</head>
```

```
<body>
```

```
<form action="FlightAdd" method="post">
```

```
<h2>Add Airline</h2>
```

```
<label>Airport Name</label>
```

```
<input type="text" name="airport" placeholder="Airport">
```

```
<br>
```

```
<br>
```

```
<label>Airline Name</label>
```

```
<input type="text" name="airline" placeholder="Airline">
```

```
<br>
```

```
<br>
```

```
<label>Source</label>
```

```
<input type="text" name="source" placeholder="Source">
```

```
<br>
```



```
<br>

<label>Destination</label>

<input type="text" name="destination" placeholder="Destination">

<br>

<br>

<br>

<br>

<label>Seats</label>

<input type="text" name="seats" placeholder="Seats">

<br>

<br>

<label>Price</label>

<input type="text" name="price" placeholder="Price">

<input type="submit" value="Add">

</form>

<%

String msg = request.getParameter("msg");

if("done".equals(msg))

{

%>

<h3>Operation Successful</h3>

<%}%>

<%

if("wrong".equals(msg))

{ %>

<h3>Invalid Data</h3>

<% } %>

</body>
```

```
</html>
```

# Carddetails.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
pageEncoding="UTF-8"%>

<!DOCTYPE html>

<html>

<head>

<meta charset="UTF-8">

<title>Card Details</title>

<link rel="stylesheet" href="style.css" >

</head>

<body>

<h3 style="text-align:center;">Enter Payment Details</h3>

<form action="FinalPage.jsp" method="post">

<label>Card Holder Name</label>

<input type="text" Placeholder="Holder Name">

<br>

<label>Card Number</label>

<input type="text" Placeholder="Card Number">

<br>

<label>Card Number</label>

<input type="number" min="1" max="12" >/

<input type="number" min="1" max="31" >

<br>

<input type="submit">

</form>

</body>
```

```
</html>
```

# ChangeFun.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
    pageEncoding="UTF-8"%>

<%@page import="java.sql.*"%>

<%@ page import="com.Servlets.*" %>

<%@ page import="com.Dbconnection.*" %>

<%

String email = request.getParameter("email");

String password = request.getParameter("pass");

try{

Connection con = Dbconnection.GetConnection();

PreparedStatement ps = con.prepareStatement("update adminlogin set
adpwd='"+ password+"' where ademail='"+ email +"'");

ps.executeUpdate();

response.sendRedirect("AdminDashboard.jsp");

}catch(Exception ex)

{

System.out.print(ex);

}

%>
```

# Changepass.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
pageEncoding="UTF-8"%>

<%@include file="AdminDashboard.jsp" %>

<!DOCTYPE html>

<html>

<head>

<meta charset="UTF-8">

<title>Change Password</title>

<link rel="stylesheet" href="style.css" >

</head>

<body>

<form action="ChangeFun.jsp" method="post">

<label>Your Email</label>

<input type="text" name="email"
value="<%=session.getAttribute("email").toString() %>">

<label>Password</label>

<input type="text" name="pass" placeholder="Enter New Password">

<input type="submit" value="Submit">

</form>

</body>

</html>
```

# CustomerDashboard.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
pageEncoding="UTF-8"%>

<%@ page import="com.Servlets.*" %>

<!DOCTYPE html>

<html>

<head>

<meta charset="UTF-8">

<title>Customer Dashboard</title>

<link rel="stylesheet" href="style.css" >

</head>

<body>

<h1>Welcome <%=session.getAttribute("email").toString() %></h1>

<a href="SearchF.jsp"> Search Flight</a>

<a href="CustomerLogin.jsp">Logout</a>

<br>

<br>

<h2>Thank You For Choosing FlyAway</h2>

</body>

</html>
```

# CustomerLogin.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
pageEncoding="UTF-8"%>

<!DOCTYPE html>

<html>

<head>

<meta charset="UTF-8">

<title>Customer Login</title>

<link rel="stylesheet" href="style.css" >

</head>

<body >

<form action="CustomerLogin" method="post">

<h1>Customer Login</h1>

<label>Email</label>

<input type="text" name="email" placeholder="Email">

<br>

<label>Password</label>

<input type="text" name="password" placeholder="Password">

<input type="submit" value="Login">

</form>

<%

String msg = request.getParameter("msg");

if("notexist".equals(msg))

{

%>

<h1>Password Invalid/User Not Exist</h1>

<%}%>
```

```
</body>
```

```
</html>
```

## EditFlight.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
    pageEncoding="UTF-8"%>

<%@page import="java.sql.*"%>

<%@ page import="com.Servlets.*" %>

<%@ page import="com.Dbconnection.*" %>

<%

String id = request.getParameter("id");

try{

Connection con = Dbconnection.GetConnection();

PreparedStatement ps = con.prepareStatement("delete from flight where
Airport='"+ id+"'");

ps.executeUpdate();

response.sendRedirect("ViewAllFlight.jsp");

}catch(Exception ex)

{

System.out.print(ex);

}

%>
```

# EditUpdate.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
pageEncoding="UTF-8"%>

<%@page import="java.sql.*"%>

<%@ page import="com.Servlets.*" %>

<%@ page import="com.Dbconnection.*" %>

<%@include file="AdminDashboard.jsp" %>

<%

String id = request.getParameter("id");

String airp = request.getParameter("airportt");

String airline = request.getParameter("airlinee");

String sour = request.getParameter("sourcee");

String desti = request.getParameter("destinatione");

String seat = request.getParameter("seatse");

String prices = request.getParameter("pricee");

//System.out.println("source dsa= " + id+" airport= "+ airp+" airp= "+
airline+" airline= "+ sour+" sour= "+ desti+" desti= "+ seat+" seat="+
prices);

try{

Connection con = Dbconnection.GetConnection();

Statement st = con.createStatement();

st.executeUpdate("update flight set Airport='" + airp + "',
airline='"+airline+"', sourcee='"+ sour + "', destination='"+ desti + "',
seats='"+ seat+ "', price='"+prices+"' where Airport="+id+"'");

response.sendRedirect("ViewAllFlight.jsp?msg=done");

}

catch(Exception ex)

{

System.out.println(ex);
```



```
response.sendRedirect("ViewAllFlight.jsp?msg=wrong");

}

%>
```

## FinalPage.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
    pageEncoding="UTF-8"%>

<%@page import="java.util.HashMap"%>

<%@page import="java.sql.*"%>

<%@ page import="com.Servlets.*" %>

<%@ page import="com.Dbconnection.*" %>

<!DOCTYPE html>

<html>

<head>

<meta charset="UTF-8">

<title>Ticket Details</title>

<link rel="stylesheet" href="style.css" >

</head>

<%

HashMap<String, String> booking = (HashMap)session.getAttribute("bkdetil");

HashMap<String, String> person =
(HashMap)session.getAttribute("persondata");

String airpo = "";

String airli = "";

String soure = "";

String desti = "";

String seats = "";

String price = "";
```

```
String pname = "";

String gend = "";

String loca = "";

String phone = "";

String trave = "";

String nofp = "";

String email = "";

if(booking!=null && person!=null)

{

    airpo =booking.get("airpt");

    airli =booking.get("airlir");

    soure =booking.get("soe");

    desti =booking.get("desit");

    seats =booking.get("seait");

    price=booking.get("prct");

    pname =person.get("pername");

    gend =person.get("gende");

    loca =person.get("locash");

    phone =person.get("phn");

    trave =person.get("trac");

    nofp =person.get("notr");

    email =person.get("emili");

}

else{

    airpo = null;

    airli = null;

    soure = null;

    desti = null;
```

```
seats = null;

price= null;

pname = null;

gend = null;

loca = null;

phone = null;

trave = null;

nofp = null;

email = null;

}

%>

<body>

<h1 text-align:center;>Conformation Page</h1>

<br>

<br>

<br>

<br>

<table width="100%" border="1">

<tr>

<th>Airport Name</th>

<th>Airline Name</th>

<th>Source</th>

<th>Destination</th>

<th>Seats </th>

<th>Price</th>

<th>Remark</th>

</tr>

<tr>
```

```
<td><%=airpo %></td>

<td><%=airli %></td>

<td><%=soure %></td>

<td><%=desti %></td>

<td><%=seats %></td>

<td><%=price %></td>

<td>Happy Journey</td>

</tr>

<tr>

<th>Person Name</th>

<th>Gender</th>

<th>location</th>

<th>Phone</th>

<th>Travel Date </th>

<th>No of Person</th>

<th>Email</th>

</tr>

<tr>

<td><%=pname %></td>

<td><%=gend %></td>

<td><%=loca %></td>

<td><%=phone %></td>

<td><%=trave %></td>

<td><%=nofp %></td>

<td><%=email %></td>

</tr>

</table>

<div text-align: center;>
```

```
<a href="Welcome.jsp">Back To HomePage</a>

</div>

</body>

</html>
```

## PassengerFun.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
    pageEncoding="UTF-8"%>

<%@page import="java.util.HashMap"%>

<%@page import="java.sql.*"%>

<%@ page import="com.Servlets.*" %>

<%@ page import="com.Dbconnection.*" %>

<%

String pname = request.getParameter("pname");

String gender = request.getParameter("gender");

String locae = request.getParameter("Location");

String phone = request.getParameter("Phone");

String travel = request.getParameter("traveld");

String nofp = request.getParameter("nofp");

String email = request.getParameter("Email");

String passwd = request.getParameter("pwd");

try{

Connection con = Dbconnection.GetConnection();

PreparedStatement ps = con.prepareStatement("insert into passenger(pname,
gender, location, phoneno, datee, noofperson, email,
passwd)value('"+pname+"','"+gender+"',
'"+locae+"','"+phone+"','"+travel+"','"+nofp+"','"+email+"','"+passwd+"')");
;

ps.executeUpdate();

response.sendRedirect("Carddetails.jsp");
```

```

HashMap<String, String> personde = new HashMap<String, String>();

personde.put("pername", pname);

personde.put("gende", gender);

personde.put("locash", locae);

personde.put("phn", phone);

personde.put("trac", travel);

personde.put("notr", nofp);

personde.put("emili", email);

session.setAttribute("persondata", personde);

RequestDispatcher dispatcher =
request.getRequestDispatcher("FinalPage.jsp");

}

catch(Exception ex)

{

}

%>

```

## RegisterPassenger.jsp

```

<%@ page language="java" contentType="text/html; charset=UTF-8"

pageEncoding="UTF-8"%>

<!DOCTYPE html>

<html>

<head>

<meta charset="UTF-8">

<title>Passenger Details</title>

<link rel="stylesheet" href="style.css" >

</head>

<body>

```

```
<h2>Passenger Details</h2>

<form action="Passengerfun.jsp" method="post">

<label>Passenger name</label>

<input type="text" name="pname" >

<br>

<label>Gender</label>

<input type="radio" name="gender" value="Male" >Male

<input type="radio" name="gender" value="Female" >Female

<br>

<label>Location</label>

<input type="text" name="Location" >

<br>

<label>Phone No</label>

<input type="text" name="Phone" >

<br>

<label>Date of Travel</label>

<input type="date" name="traveld" >

<br>

<label>No of Persons</label>

<input type="text" name="nofp" >

<br>

<label>Email</label>

<input type="text" name="Email" >

<br>

<label>Password</label>

<input type="text" name="pwd" >

<input type="submit" value="Submit" >

</form>
```

```
</body>
```

```
</html>
```

## SearchF.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
```

```
pageEncoding="UTF-8"%>
```

```
<%@page import="java.sql.*"%>
```

```
<%@ page import="com.Servlets.*" %>
```

```
<%@ page import="com.Dbconnection.*" %>
```

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<meta charset="UTF-8">
```

```
<title>Search Flight</title>
```

```
<link rel="stylesheet" href="style.css" >
```

```
</head>
```

```
<body>
```

```
<h3 style="text-align:center;">Searching Flight</h3>
```

```
<form action="SearchFun.jsp" method="post">
```

```
<label for="sour">Source</label>
```

```
<select id="sour" name="sour">
```

```
<option value="-1">Select Source</option>
```

```
<option value="Nagpur">Nagpur</option>
```

```
<option value="Delhi">Delhi</option><u>Kolkata
```

```
<option value="Kolkata">Kolkata</option>
```

```
</select>
```

```
<br>
```

```
<br>
```



```
<select id="desti" name="destin">

<option value="-1">Select Destination</option>

<option value="Nagpur">Nagpur</option>

<option value="Delhi">Delhi</option>

<option value="Kolkata">Kolkata</option>

</select>

<input type="submit" value="Submit">

</form>

</body>

</html>
```

## SearcFun.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
pageEncoding="UTF-8"%>

<%@page import="java.util.HashMap"%>

<%@page import="java.sql.*"%>

<%@ page import="com.Servlets.*" %>

<%@ page import="com.Dbconnection.*" %>

<!DOCTYPE html>

<html>

<head>

<meta charset="UTF-8">

<title>Avilable Flight</title>

<link rel="stylesheet" href="style.css" >

</head>

<body>

<h3 style="text-align:center;">Avilable Flight</h3>

<br>
```

```

<%

int z=0;

try{

String soure = request.getParameter("sourc");

String desti = request.getParameter("destin");

Connection con = Dbconnection.GetConnection();

Statement st = con.createStatement();

ResultSet rs = st.executeQuery("select * from flight where sourcee
='"+soure+"' and destination = '"+desti+"'");

while(rs.next())

{

%>

<table width="70%" border="1">

<tr>

<th>Airport Name</th>

<th>Airline Name</th>

<th>Source</th>

<th>Destination</th>

<th>Seats</th>

<th>Price</th>

<th>Operations</th>

</tr>

<tr>

<td><%=rs.getString(1) %></td>

<td><%=rs.getString(2) %></td>

<td><%=rs.getString(3) %></td>

<td><%=rs.getString(4) %></td>

<td><%=rs.getString(5) %></td>

```

```

<td><%=rs.getString(6) %></td>

<td><a href="RegisterPassenger.jsp?book=<%=rs.getString(1)
%>">Book</a></td>

</tr>

</table>

<%

HashMap<String, String> booking = new HashMap<String, String>();

booking.put("airpt", rs.getString(1));

booking.put("airlir", rs.getString(2));

booking.put("soe", rs.getString(3));

booking.put("desit", rs.getString(4));

booking.put("seait", rs.getString(5));

booking.put("prct", rs.getString(6));

session.setAttribute("bkdetil", booking);

RequestDispatcher dispatcher =
request.getRequestDispatcher("FinalPage.jsp");

%>

<% }

}

catch(Exception ex)

{

}

%>

</body>

</html>

```

# Style.css

```
@charset "UTF-8";

*{

padding: 0;

margin: 0;

text-decoration: none;

list-style: none;

box-sizing: border-box;

}

body{

font-family: montserrat;

background-image: url('sss.jpg');

background-repeat: no-repeat;

background-attachment: fixed;

background-size: cover;

margin: auto;

width: 640px;

padding: 50px;

font-family: 'Lexend Deca', sans-serif;

color: #2E475D;

}

a:link, a:visited {

background-color: #DCDCDC;

color: black;

border: 1px solid black;

padding: 10px 15px;

text-align: center;
```

```
text-decoration: none;

display: inline-block;

}

a:hover, a:active {

background-color: orange;

color: white;

}

h1{ margin-right: 120px; }

.buttons{

position: absolute;

top:30%;

right: 0;

width: 120px;

transform: translateY(-50%);

}

* {

box-sizing: border-box;

}

input[type=text], select, textarea {

width: 100%;

padding: 12px;

border: 1px outset #ccc;

border-radius: 4px;

resize: vertical;

}

label {

padding: 12px 12px 12px 0;

display: inline-block;
```

```
}

input[type=submit] {

background-color: #04AA6D;

color: white;

padding: 12px 20px;

border: none;

border-radius: 4px;

cursor: pointer;

float: right;

}

input[type=submit]:hover {

background-color: #45a049;

}

.container {

border-radius: 50px;

background-color: #f2f2f2;

width:50%;

margin-left: auto;

margin-right: auto;

padding: 70px;

}

.col-25 {

float: left;

width: 20%;

margin-top: 6px;

}

.col-75 {

float: left;
```

```

width: 75%;

margin-top: 6px;

}

/* Clear floats after the columns */

.row::after {

content: "";

display: table;

clear: both;

}

/* Responsive layout - when the screen is less than 600px wide, make the
two columns stack on top of each other instead of next to each other */

@media screen and (max-width: 600px) {

.col-25, .col-75, input[type=submit] {

width: 50%;

margin-top: 0;

}

}

```

## ViewAllFlight.jsp

```

<%@ page language="java" contentType="text/html; charset=UTF-8"

pageEncoding="UTF-8"%>

<%@page import="java.sql.*"%>

<%@ page import="com.Servlets.*" %>

<%@ page import="com.Dbconnection.*" %>

<%@include file="AdminDashboard.jsp" %>

<!DOCTYPE html>

<html>

<head>

```

```

<meta charset="UTF-8">

<title>All Listed Flight</title>

<hr>

</head>

<body>

<table width="100%" border="1">

<tr>

<th>Airport Name</th>

<th>Airline Name</th>

<th>Source</th>

<th>Destination</th>

<th>Seats</th>

<th>Price</th>

<th>Operations</th>

</tr>

<%

try{

Connection con = Dbconnection.GetConnection();

Statement st = con.createStatement();

ResultSet rs = st.executeQuery("select * from flight");

while(rs.next())

{

%>

<tr>

<td><%=rs.getString(1) %></td>

<td><%=rs.getString(2) %></td>

<td><%=rs.getString(3) %></td>

<td><%=rs.getString(4) %></td>

```



```

<td><%=rs.getInt(5) %></td>

<td><%=rs.getInt(6) %></td>

<td><a href="EditFlight.jsp?id=<%=rs.getString(1) %>">Delete Flight</a>
</td>

</tr>

<%

}

}

catch(Exception ex)

{

}

%>

</table>

</body>

</html>

```

## Welcome.jsp

```

<%@ page language="java" contentType="text/html; charset=UTF-8"

pageEncoding="UTF-8"%>

<!DOCTYPE html>

<html>

<head>

<meta charset="UTF-8">

<title style="color:#000000;" >Welcome FlyAway</title>

<link rel="stylesheet" href="style.css" >

</head>

<body>

<br>

```

[illegible]

platform includes a search form that allows users to enter their travel  
<br>  
details, including the source, destination. Based on the search criteria  
<br>  
entered, the platform presents users with a list of available flights with  
<br>  
their ticket prices. Once the user selects a flight, they are taken to a  
<br>  
registration page where they can enter their personal information. The user  
<br>  
is then presented with the flight details, payment information, and  
payment<br>  
gateway. After the payment is completed, the user is shown a confirmation  
page  
with the details of their booking.</p>  
</body>  
</html>