```
No.      Time                      Source              Destination           Protocol Length Info
     19 2019-03-31 13:15:29.096032    128.119.245.12      192.168.200.8         HTTP     535    HTTP/1.1 200 OK  (text/html)
Frame 19: 535 bytes on wire (4280 bits), 535 bytes captured (4280 bits) on interface 0
    Interface id: 0 (\Device\NPF_{B7882E4A-EBB8-48D4-BDFB-137D7C3DB3DB})
    Encapsulation type: Ethernet (1)
    Arrival Time: Mar 31, 2019 13:15:29.096032000 Eastern Daylight Time
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1554052529.096032000 seconds
    [Time delta from previous captured frame: 0.000000000 seconds]
    [Time delta from previous displayed frame: 0.000000000 seconds]
    [Time since reference or first frame: 1.479472000 seconds]
    Frame Number: 19
    Frame Length: 535 bytes (4280 bits)
    Capture Length: 535 bytes (4280 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:tcp:http:data-text-lines]
    [Coloring Rule Name: HTTP]
    [Coloring Rule String: http || tcp.port == 80 || http2]
Ethernet II, Src: Verizon_d0:13:e4 (20:c0:47:d0:13:e4), Dst: IntelCor_47:b8:32 (ac:ed:5c:47:b8:32)
    Destination: IntelCor_47:b8:32 (ac:ed:5c:47:b8:32)
        Address: IntelCor_47:b8:32 (ac:ed:5c:47:b8:32)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: Verizon_d0:13:e4 (20:c0:47:d0:13:e4)
        Address: Verizon_d0:13:e4 (20:c0:47:d0:13:e4)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 192.168.200.8
Transmission Control Protocol, Src Port: 80, Dst Port: 54707, Seq: 4381, Ack: 429, Len: 481
    Source Port: 80
    Destination Port: 54707
    [Stream index: 1]
    [TCP Segment Len: 481]
    Sequence number: 4381    (relative sequence number)
    [Next sequence number: 4862    (relative sequence number)]
    Acknowledgment number: 429    (relative ack number)
    0101 .... = Header Length: 20 bytes (5)
    Flags: 0x018 (PSH, ACK)
        000. .... .... = Reserved: Not set
        ...0 .... .... = Nonce: Not set
        .... 0... .... = Congestion Window Reduced (CWR): Not set
        .... .0.. .... = ECN-Echo: Not set
        .... ..0. .... = Urgent: Not set
        .... ...1 .... = Acknowledgment: Set
        .... .... 1... = Push: Set
        .... .... .0.. = Reset: Not set
        .... .... ..0. = Syn: Not set
        .... .... ...0 = Fin: Not set
        [TCP Flags: ·······AP···]
    Window size value: 237
    [Calculated window size: 30336]
    [Window size scaling factor: 128]
    Checksum: 0xa4d4 [unverified]
    [Checksum Status: Unverified]
    Urgent pointer: 0
    [SEQ/ACK analysis]
        [iRTT: 0.021446000 seconds]
        [Bytes in flight: 4861]
        [Bytes sent since last PSH flag: 4861]
    [Timestamps]
        [Time since first frame in this TCP stream: 0.039987000 seconds]
        [Time since previous frame in this TCP stream: 0.000000000 seconds]
    TCP payload (481 bytes)
    TCP segment data (481 bytes)
[4 Reassembled TCP Segments (4861 bytes): #15(1460), #17(1460), #18(1460), #19(481)]
Hypertext Transfer Protocol
    HTTP/1.1 200 OK\r\n
    Date: Sun, 31 Mar 2019 17:15:29 GMT\r\n
    Server: Apache/2.4.6 (CentOS) OpenSSL/1.0.2k-fips PHP/5.4.16 mod_perl/2.0.10 Perl/v5.16.3\r\n
    Last-Modified: Sun, 31 Mar 2019 05:59:01 GMT\r\n
    ETag: "1194-5855d99bb136c"\r\n
    Accept-Ranges: bytes\r\n
    Content-Length: 4500\r\n
    Keep-Alive: timeout=5, max=100\r\n
    Connection: Keep-Alive\r\n
    Content-Type: text/html; charset=UTF-8\r\n
    \r\n
    [HTTP response 1/2]
    [Time since request: 0.017668000 seconds]
    [Request in frame: 12]
    [Next request in frame: 23]
    [Next response in frame: 24]
    File Data: 4500 bytes
Line-based text data: text/html (98 lines)
```