

Made by: Quiroz Gonzalez Saul Abraham

Add Request

```
<?xml version='1.0'?>
  <methodCall>
    <methodName>add</methodName>
    <params>
      <param>
        <value>
          <int>5</int>
        </value>
      </param>
      <param>
        <value>
          <int>2</int>
        </value>
      </param>
    </params>
  </methodCall>
```

Add Response

```
<?xml version='1.0'?>
  <methodResponse>
    <params>
      <param>
        <value>
          <int>7</int>
        </value>
      </param>
    </params>
  </methodResponse>
```

Sus Request

```
<?xml version='1.0'?>
  <methodCall>
    <methodName>sus</methodName>
    <params>
      <param>
        <value>
          <int>5</int>
        </value>
      </param>
      <param>
        <value>
          <int>2</int>
        </value>
      </param>
    </params>
```

Made by: Quiroz Gonzalez Saul Abraham

```
</methodCall>
```

Sus Response

```
<?xml version='1.0'?>
  <methodResponse>
    <params>
      <param>
        <value>
          <int>3</int>
        </value>
      </param>
    </params>
  </methodResponse>
```

Mul Request

```
<?xml version='1.0'?>
  <methodCall>
    <methodName>mul</methodName>
    <params>
      <param>
        <value>
          <int>5</int>
        </value>
      </param>
      <param>
        <value>
          <int>2</int>
        </value>
      </param>
    </params>
  </methodCall>
```

Mul Response

```
<?xml version='1.0'?>
  <methodResponse>
    <params>
      <param>
        <value>
          <int>10</int>
        </value>
      </param>
    </params>
  </methodResponse>
```

Div Request

```
<?xml version='1.0'?>
  <methodCall>
    <methodName>div</methodName>
    <params>
      <param>
```

Made by: Quiroz Gonzalez Saul Abraham

```
        <value>
          <int>5</int>
        </value>
      </param>
      <param>
        <value>
          <int>2</int>
        </value>
      </param>
    </params>
  </methodCall>
```

Div Response

```
<?xml version='1.0'?>
  <methodResponse>
    <params>
      <param>
        <value>
          <double>2.5</double>
        </value>
      </param>
    </params>
  </methodResponse>
```

XMLRPC Data Types

Type	Value	Examples
int or i4	32-bit integers between - 2,147,483,648 and 2,147,483,647.	<int>27</int>
		<i4>27</i4>
double	64-bit floating-point numbers	<double>27.31415</double>
		<double>-1.1465</double>
Boolean	true (1) or false (0)	<boolean>1</boolean>
		<boolean>0</boolean>
string	ASCII text, though many implementations support Unicode	<string>Hello</string>
		<string>bonkers! @</string>
dateTime.iso8601	Dates in ISO8601 format: CCYYMMDDTHH:MM:SS	<dateTime.iso8601>

Made by: Quiroz Gonzalez Saul Abraham

20021125T02:20:04

</dateTime.iso8601>

<dateTime.iso8601>

20020104T17:27:30

</dateTime.iso8601>

base64

Binary information encoded as Base 64, as
defined in RFC 2045

<base64>SGVsbG8sIFdvcmxkIQ==</
base64>