

Note to other teachers and users of these slides: We would be delighted if you found this our material useful in giving your own lectures. Feel free to use these slides verbatim, or to modify them to fit your own needs. If you make use of a significant portion of these slides in your own lecture, please include this message, or a link to our web site: <http://www.mmmds.org>

Recommender Systems: Content-based Systems & Collaborative Filtering

Mining of Massive Datasets


Jure Leskovec, Anand Rajaraman, Jeff Ullman

Stanford University

<http://www.mmmds.org>



Example: Recommender Systems




■ Customer X

- Buys Metallica CD
- Buys Megadeth CD

■ Customer Y

- Does search on Metallica
- Recommender system suggests Megadeth from data collected about customer X

Recommendations



Examples:

amazon.com.



StumbleUpon

del.icio.us



movie lens
helping you find the *right* movies

last.fm™
the social music revolution

Google™
News


YouTube

XBOX
LIVE

From Scarcity to Abundance

- Shelf space is a scarce commodity for traditional retailers
 - Also: TV networks, movie theaters,...
- Web enables near-zero-cost dissemination of information about products
 - From scarcity to abundance
- More choice necessitates better filters
 - Recommendation engines
 - How **Into Thin Air** made **Touching the Void** a bestseller: <http://www.wired.com/wired/archive/12.10/tail.html>

Sidenote: The Long Tail



Types of Recommendations

- **Editorial and hand curated**
 - List of favorites
 - Lists of “essential” items
- **Simple aggregates**
 - Top 10, Most Popular, Recent Uploads
- **Tailored to individual users**
 - Amazon, Netflix, ...

Formal Model

- X = set of **Customers**
- S = set of **Items**
- **Utility function** $u: X \times S \rightarrow R$
 - R = set of ratings
 - R is a totally ordered set
 - e.g., 0-5 stars, real number in $[0,1]$

Utility Matrix

	Avatar	LOTR	Matrix	Pirates
Alice	1		0.2	
Bob		0.5		0.3
Carol	0.2		1	
David				0.4

Key Problems

- **(1) Gathering “known” ratings for matrix**
 - How to collect the data in the utility matrix
- **(2) Extrapolate unknown ratings from the known ones**
 - Mainly interested in high unknown ratings
 - We are not interested in knowing what you don't like but what you like
- **(3) Evaluating extrapolation methods**
 - How to measure success/performance of recommendation methods

(1) Gathering Ratings

■ Explicit

- Ask people to rate items
- Doesn't work well in practice – people can't be bothered

■ Implicit

- Learn ratings from user actions
 - E.g., purchase implies high rating
- What about low ratings?

(2) Extrapolating Utilities

- **Key problem:** Utility matrix U is sparse
 - Most people have not rated most items
 - **Cold start:**
 - New items have no ratings
 - New users have no history
- **Three approaches to recommender systems:**
 - 1) Content-based
 - 2) Collaborative
 - 3) Latent factor based

Content-based Recommender Systems


Content-based Recommendations

- **Main idea:** Recommend items to customer x similar to previous items rated highly by x

Example:

- **Movie recommendations**
 - Recommend movies with same actor(s), director, genre, ...
- **Websites, blogs, news**
 - Recommend other sites with “similar” content

Plan of Action



Item Profiles

- For each item, create an **item profile**
- **Profile is a set (vector) of features**
 - **Movies:** author, title, actor, director,...
 - **Text:** Set of “important” words in document
- **How to pick important features?**
 - Usual heuristic from text mining is **TF-IDF**
(Term frequency * Inverse Doc Frequency)
 - **Term ... Feature**
 - **Document ... Item**

User Profiles and Prediction

■ User profile possibilities:

- Weighted average of rated item profiles
- Variation: weight by difference from average rating for item
- ...

■ Prediction heuristic:

- Given user profile x and item profile i , estimate

$$u(x, i) = \cos(x, i) = \frac{x \cdot i}{\|x\| \cdot \|i\|}$$

Pros: Content-based Approach

- **+: No need for data on other users**
 - No cold-start or sparsity problems
- **+: Able to recommend to users with unique tastes**
- **+: Able to recommend new & unpopular items**
 - No first-rater problem
- **+: Able to provide explanations**
 - Can provide explanations of recommended items by listing content-features that caused an item to be recommended

Cons: Content-based Approach


- -: **Finding the appropriate features is hard**
 - E.g., images, movies, music
- -: **Recommendations for new users**
 - **How to build a user profile?**
- -: **Overspecialization**
 - Never recommends items outside user's content profile
 - People might have multiple interests
 - **Unable to exploit quality judgments of other users**

Collaborative Filtering

Harnessing quality judgments of other users

Collaborative Filtering

- Consider user x
- Find set N of other users whose ratings are “similar” to x 's ratings
- Estimate x 's ratings based on ratings of users in N



Finding “Similar” Users

$$\begin{aligned}r_x &= [* , _, _, *, ***] \\r_y &= [* , _, **, **, _]\end{aligned}$$

- Let r_x be the vector of user x 's ratings

- Cosine similarity measure**

- $\text{sim}(x, y) = \cos(r_x, r_y) = \frac{r_x \cdot r_y}{\|r_x\| \cdot \|r_y\|}$

r_x, r_y as points:

$$r_x = \{1, 0, 0, 1, 3\}$$

$$r_y = \{1, 0, 2, 2, 0\}$$

- Pearson correlation coefficient**

- S_{xy} = items rated by both users x and y

$$\text{sim}(x, y) = \frac{\sum_{s \in S_{xy}} (r_{xs} - \bar{r}_x)(r_{ys} - \bar{r}_y)}{\sqrt{\sum_{s \in S_{xy}} (r_{xs} - \bar{r}_x)^2} \sqrt{\sum_{s \in S_{xy}} (r_{ys} - \bar{r}_y)^2}}$$

$\bar{r}_x, \bar{r}_y \dots$ avg.
rating of x, y

Rating Predictions

From similarity metric to recommendations:

- Let r_x be the vector of user x 's ratings
- Let N be the set of k users most similar to x who have rated item i
- Prediction for item s of user x :

$$r_{xi} = \frac{1}{k} \sum_{y \in N} r_{yi}$$

Shorthand:

$$s_{xy} = sim(x, y)$$

$$r_{xi} = \frac{\sum_{y \in N} s_{xy} \cdot r_{yi}}{\sum_{y \in N} s_{xy}}$$

- Other options?
- Many other tricks possible...

Item-Item Collaborative Filtering

- So far: User-user collaborative filtering
- Another view: Item-item
 - For item i , find other similar items
 - Estimate rating for item i based on ratings for similar items
 - Can use same similarity metrics and prediction functions as in user-user model

$$r_{xi} = \frac{\sum_{j \in N(i; x)} s_{ij} \cdot r_{xj}}{\sum_{j \in N(i; x)} s_{ij}}$$

s_{ij} ... similarity of items i and j

r_{xj} ... rating of user u on item j

$N(i; x)$... set items rated by x similar to i


Item-Item CF ($|N|=2$)

	users											
	1	2	3	4	5	6	7	8	9	10	11	12
1	1			3				5			5	4
2				5	4			4			2	1
3	2	4		1	2			3		4	3	5
4		2	4		5			4			2	
5			4	3	4	2					2	5
6	1		3		3			2			4	

- unknown rating - rating between 1 to 5

Item-Item CF ($|N|=2$)

	users											
	1	2	3	4	5	6	7	8	9	10	11	12
1	1		3		?	5			5		4	
2			5	4			4			2	1	3
3	2	4		1	2		3		4	3	5	
4		2	4		5			4			2	
5			4	3	4	2					2	5
6	1		3		3			2			4	



- estimate rating of movie 1 by user 5

Item-Item CF ($|N|=2$)

	users												
	1	2	3	4	5	6	7	8	9	10	11	12	$\text{sim}(1,m)$
1	1		3		?	5			5		4		1.00
2			5	4			4			2	1	3	-0.18
3	2	4		1	2		3		4	3	5		<u>0.41</u>
4		2	4		5			4			2		-0.10
5			4	3	4	2					2	5	-0.31
6	6	1		3	3			2			4		<u>0.59</u>

Neighbor selection:

Identify movies similar to
movie 1, rated by user 5

Here we use Pearson correlation as similarity:

- 1) Subtract mean rating m_i from each movie i
 $m_1 = (1+3+5+5+4)/5 = 3.6$
row 1: [-2.6, 0, -0.6, 0, 0, 1.4, 0, 0, 1.4, 0, 0.4, 0]
- 2) Compute cosine similarities between rows

Item-Item CF ($|N|=2$)

	users												
	1	2	3	4	5	6	7	8	9	10	11	12	$\text{sim}(1,m)$
1	1		3		?	5			5		4		1.00
2			5	4			4			2	1	3	-0.18
3	2	4		1	2		3		4	3	5		<u>0.41</u>
4		2	4		5			4			2		-0.10
5			4	3	4	2					2	5	-0.31
6	6	1	3		3			2			4		<u>0.59</u>

Compute similarity weights:

$$\mathbf{s}_{1,3}=0.41, \mathbf{s}_{1,6}=0.59$$

Item-Item CF ($|N|=2$)

	users											
	1	2	3	4	5	6	7	8	9	10	11	12
1	1		3		2.6	5			5		4	
2			5	4			4			2	1	3
3	2	4		1	2		3		4	3	5	
4		2	4		5			4			2	
5			4	3	4	2					2	5
6	1		3		3			2			4	

Predict by taking weighted average:

$$r_{1.5} = (0.41*2 + 0.59*3) / (0.41+0.59) = 2.6$$

$$r_{ix} = \frac{\sum_{j \in N(i;x)} s_{ij} \cdot r_{jx}}{\sum s_{ij}}$$

Pros/Cons of Collaborative Filtering

- + Works for any kind of item
 - No feature selection needed
- - Cold Start:
 - Need enough users in the system to find a match
- - Sparsity:
 - The user/ratings matrix is sparse
 - Hard to find users that have rated the same items
- - First rater:
 - Cannot recommend an item that has not been previously rated
 - New items, Esoteric items
- - Popularity bias:
 - Cannot recommend items to someone with unique taste
 - Tends to recommend popular items

Latent Factor Models


Remarks & Practical Tips

- Evaluation
- Error metrics

Evaluation


movies					
users	1	3	4		
		3	5		5
			4	5	5
				3	
				3	
	2			2	2
					5
		2	1		1
			3		3
	1				

Evaluation



Evaluation

Matrix R



$$\text{RMSE} = \frac{1}{|R|} \sqrt{\sum_{(i,x) \in R} (\hat{r}_{xi} - r_{xi})^2}$$

Evaluating Predictions

- **Compare predictions with known ratings**

- **Root-mean-square error (RMSE)**

- $\sqrt{\sum_{x \text{ on } i} (r_{xi} - r_{xi}^*)^2}$ where r_{xi} is predicted, r_{xi}^* is the true rating of x on i

- **Rank Correlation:**

- Spearman's *correlation* between system's and user's complete rankings

- **Another approach: 0/1 model**

- **Coverage:**

- Number of items/users for which system can make predictions

- **Precision:**

- Accuracy of predictions

Problems with Error Measures

- **Narrow focus on accuracy sometimes misses the point**
 - Prediction Diversity
 - Prediction Context
 - Order of predictions
- **In practice, we care only to predict high ratings:**
 - RMSE might penalize a method that does well for high ratings and badly for others

Tip: Add Data

- **Leverage all the data**
 - Don't try to reduce data size in an effort to make fancy algorithms work
 - Simple methods on large data do best
- **Add more data**
 - e.g., add IMDB data on genres
- **More data beats better algorithms**

<http://anand.typepad.com/datawocky/2008/03/more-data-usual.html>

NetFlix Prize: Performance of Various Methods (RMSE)

