Joins

We will run through some SQL practice problems that will provide hands-on experience with the different kinds of join operations.

How does a CROSS JOIN (also known as Cartesian Join) statement syntax look?

```
SELECT column_name(s)
FROM table1
CROSS JOIN table2;
```

How does an INNER JOIN statement syntax look?

```
SELECT column_name(s)
FROM table1
INNER JOIN table2
ON table1.column_name = table2.column_name;
WHERE condition;
```

How does a LEFT OUTER JOIN statement syntax look?

```
SELECT column_name(s)
FROM table1
LEFT OUTER JOIN table2
ON table1.column_name = table2.column_name
WHERE condition;
```

How does a RIGHT OUTER JOIN statement syntax look?

```
SELECT column_name(s)
FROM table1
RIGHT OUTER JOIN table2
ON table1.column_name = table2.column_name
WHERE condition;
```

How does a FULL OUTER JOIN statement syntax look?

```
SELECT column_name(s)
FROM table1
FULL OUTER JOIN table2
ON table1.column_name = table2.column_name
WHERE condition;
```

How does a SELF JOIN statement syntax look?

```
SELECT column_name(s)
FROM table1 T1, table1 T2
WHERE condition;
```

Software Used in this Lab

In this lab, you will use an <u>IBM Db2 Database</u>. Db2 is a Relational Database Management System (RDBMS) from IBM, designed to store, analyze and retrieve data efficiently.

To complete this lab you will utilize a Db2 database service on IBM Cloud.

Database Used in this Lab

The database used in this lab is an internal database. You will be working on a sample HR database. This HR database schema consists of 5 tables called **EMPLOYEES**, **JOB_HISTORY**, **JOBS**, **DEPARTMENTS** and **LOCATIONS**. Each table has a few rows of sample data. The following diagram shows the tables for the HR database:

SAMPLE HR DATABASE TABLES

EMPLOYE	EES									
EMP_ID	F_NAME	L_NAME	SSN	B_DATE	SEX	ADDRESS	JOB_ID	SALARY	MANAGER_ID	DEP_ID
E1001	John	Thomas	123456	1976-01-09	M	5631 Rice, OakPark,IL	100	100000	30001	2
E1002	Alice	James	123457	1972-07-31	F	980 Berry In, Elgin,IL	200	80000	30002	5
E1003	Steve	Wells	123458	1980-08-10	М	291 Springs, Gary, IL	300	50000	30002	5

JOB_HISTO	ISTORY		
EMPL_ID	START_DATE	JOBS_ID	DEPT_ID
E1001	2000-01-30	100	2
E1002	2010-08-16	200	5
E1003	2016-08-10	300	5

JOBS			
JOB_IDENT	JOB_TITLE	MIN_SALARY	MAX_SALARY
100	Sr. Architect	60000	100000
200	Sr.SoftwareDeveloper	60000	80000
300	Jr.SoftwareDeveloper	40000	60000

DEPT_ID_DEP	DEP_NAME	MANAGER_ID	LOC_ID
2	Architect Group	30001	L0001
5	Software Development	30002	L0002
7	Design Team	30003	L0003
5	Software	30004	L0004

LOCT_ID	DEP_ID_LOC
L0001	2
L0002	5
L0003	7

Objectives

Performing different kinds of join operations

Instructions

When you approach the exercises in this lab, follow the instructions to run the queries on Db2:

Go to the <u>Resource List</u> of IBM Cloud by logging in where you can find the Db2 service instance that you created in a previous lab under **Services** section. Click on the **Db2-xx service**. Next, open the Db2 Console by clicking on **Open** Console button. Click on the 3-bar menu icon in the top left corner and go to the **Run SQL** page. The Run SQL tool enables you to run SQL statements.

Exercise

1. Problem:

Select the names and job start dates of all employees who work for the department number 5.

Solution:

```
select E.F_NAME, E.L_NAME, JH.START_DATE
from EMPLOYEES as E
INNER JOIN JOB_HISTORY as JH on E.EMP_ID=JH.EMPL_ID
where E.DEP_ID = '5';
```



Select the names, job start dates, and job titles of all employees who work for the department number 5.

Solution:


```
select E.F_NAME,E.L_NAME, JH.START_DATE, J.JOB_TITLE
from EMPLOYEES as E
INNER JOIN JOB_HISTORY as JH on E.EMP_ID=JH.EMPL_ID
INNER JOIN JOBS as J on E.JOB_ID=J.JOB_IDENT
where E.DEP_ID ='5';
```



Perform a Left Outer Join on the EMPLOYEES and DEPARTMENT tables and select employee id, last name, department id and department name for all employees.

Solution:


select E.EMP_ID,E.L_NAME,E.DEP_ID,D.DEP_NAME
from EMPLOYEES AS E
LEFT OUTER JOIN DEPARTMENTS AS D ON E.DEP_ID=D.DEPT_ID_DEP;



Re-write the previous query but limit the result set to include only the rows for employees born before 1980.

Solution:

```
select E.EMP_ID,E.L_NAME,E.DEP_ID,D.DEP_NAME
from EMPLOYEES AS E
LEFT OUTER JOIN DEPARTMENTS AS D ON E.DEP_ID=D.DEPT_ID_DEP
where YEAR(E.B_DATE) < 1980;</pre>
```




Re-write the previous query but have the result set include all the employees but department names for only the employees who were born before 1980.

Solution:

```
select E.EMP_ID,E.L_NAME,E.DEP_ID,D.DEP_NAME
from EMPLOYEES AS E
LEFT OUTER JOIN DEPARTMENTS AS D ON E.DEP_ID=D.DEPT_ID_DEP
AND YEAR(E.B_DATE) < 1980;</pre>
```

Output:




Show Less

Perform a Full Join on the EMPLOYEES and DEPARTMENT tables and select the First name, Last name and Department name of all employees.

Solution:

select E.F_NAME,E.L_NAME,D.DEP_NAME
from EMPLOYEES AS E
FULL OUTER JOIN DEPARTMENTS AS D ON E.DEP_ID=D.DEPT_ID_DEP;



Re-write the previous query but have the result set include all employee names but department id and department names only for male employees.

Solution:

```
select E.F_NAME,E.L_NAME,D.DEPT_ID_DEP, D.DEP_NAME
from EMPLOYEES AS E
FULL OUTER JOIN DEPARTMENTS AS D ON E.DEP_ID=D.DEPT_ID_DEP AND E.SEX = 'M';
```

