

1. Write a NumPy program to convert a given array into a list and then convert it into a numpy array again.

```
import numpy as np
x= np.arange(6).reshape(3, 2)
print("Original array elements:")
print(x)
print("Array to list:")
print(x.tolist())
```

```
Original array elements:
[[0 1]
 [2 3]
 [4 5]]
Array to list:
[[0, 1], [2, 3], [4, 5]]
```

2. Create a 5X2 integer array from a range between 100 to 200 such that the difference between each element is 10.

```
import numpy

print("Creating 5X2 array using numpy.arange")
sampleArray = numpy.arange(100, 200, 10)
sampleArray = sampleArray.reshape(5,2)
print (sampleArray)
```

```
↳ Creating 5X2 array using numpy.arange
[[100 110]
 [120 130]
 [140 150]
 [160 170]
 [180 190]]
```

3. Add the two 2D NumPy arrays and modify the resulting array by calculating the square root of each element

4. Create an 8X3 integer array from a range between 10 to 34 such that the difference between each element is 1 and then Split the array into four equal-sized sub-arrays.

```
import numpy
```

```
import numpy
```

```
print("Creating 8X3 array using numpy.arange")
sampleArray = numpy.arange(10, 34, 1)
sampleArray = sampleArray.reshape(8,3)
print (sampleArray)

print("\nDividing 8X3 array into 4 sub array\n")
subArrays = numpy.split(sampleArray, 4)
print(subArrays)
```

```
Creating 8X3 array using numpy.arange
```

```
[[10 11 12]
 [13 14 15]
 [16 17 18]
 [19 20 21]
 [22 23 24]
 [25 26 27]
 [28 29 30]
 [31 32 33]]
```

```
Dividing 8X3 array into 4 sub array
```

```
[array([[10, 11, 12],
       [13, 14, 15]]), array([[16, 17, 18],
       [19, 20, 21]]), array([[22, 23, 24],
       [25, 26, 27]]), array([[28, 29, 30],
       [31, 32, 33]])]
```

5. Consider the following array: `sampleArray = numpy.array([[34,43,73],[82,22,12],[53,94,66]])`

i. Sort above array by second row

```
import numpy as np
sampleArray = np.array([[34,43,73],[82,22,12],[53,94,66]])
print(sampleArray)
sorted_array = sampleArray[:, sampleArray[1].argsort()]
print(sorted_array)
```

```
[[34 43 73]
 [82 22 12]
 [53 94 66]]
[[73 43 34]
 [12 22 82]
 [66 94 53]]
```

ii. Sort above array by second column

```
import numpy as np
sampleArray = np.array([[34,43,73],[82,22,12],[53,94,66]])
print(sampleArray)
```

```
sorted_array = sampleArray[np.argsort(sampleArray[:, 1])]
print(sorted_array)
```

```
[[34 43 73]
 [82 22 12]
 [53 94 66]]
[[82 22 12]
 [34 43 73]
 [53 94 66]]
```

iii. Print max from axis 0 and min from axis 1

```
import numpy as np
sampleArray = np.array([[34,43,73],[82,22,12],[53,94,66]])
print(sampleArray)
print(sampleArray.max(axis=0))
print(sampleArray.min(axis=1))
```

```
[[34 43 73]
 [82 22 12]
 [53 94 66]]
[82 94 73]
[34 12 53]
```

iv. Delete col 2 and insert new Column numpy.array([[10,10,10]]) in its place

```
import numpy as np
sampleArray = np.array([[34,43,73],[82,22,12],[53,94,66]])
sampleArray=np.delete(sampleArray,obj=1,axis=1)
sampleArray = np.insert(sampleArray, 1, [10],axis=1)
print(sampleArray)
```

```
[[34 10 73]
 [82 10 12]
 [53 10 66]]
```

6. Remove all the elemnets from an array that exist in another array?

```
import numpy as np
A=np.arange(10,20)
B=np.arange(1,15)
#A=[i for i in A if i not in B]
np.setdiff1d(A,B)
print(A)
```

```
[10 11 12 13 14 15 16 17 18 19]
```

## 7. Swap two columns in a 2d NumPy array

```
import numpy as np
sampleArray = np.array([[34,43,73],[82,22,12],[53,94,66]])
#sampleArray[:,0],sampleArray[:,1] = sampleArray[:,1],sampleArray[:,0]
sampleArray[:,[0, 1]] = sampleArray[:,[1, 0]]
print(sampleArray)
```

```
[[43 34 73]
 [22 82 12]
 [94 53 66]]
```

## 8. Swap two rows in a 2d NumPy array

```
import numpy as np
sampleArray = np.array([[34,43,73],[82,22,12],[53,94,66]])
sampleArray[[0, 1],:] = sampleArray[[1, 0],:]
print(sampleArray)
```

```
[[82 22 12]
 [34 43 73]
 [53 94 66]]
```

## 9. Reverse the order of rows of a 2D array

```
import numpy as np
sampleArray = np.array([[34,43,73],[82,22,12],[53,94,66]])
#sampleArray[:,:] = sampleArray[::-1,: ]
sampleArray[:] = sampleArray[::-1]
print(sampleArray)
```

```
[[53 94 66]
 [82 22 12]
 [34 43 73]]
```

## 10. Reverse the order of columns of a 2D array

```
import numpy as np
sampleArray = np.array([[34,43,73],[82,22,12],[53,94,66]])
sampleArray[:,:] = sampleArray[:,::-1]
print(sampleArray)
```

```
[[73 43 34]
 [12 22 82]
 [66 94 53]]
```

### 11. Retrieve common items between two python NumPy arrays?

```
import numpy as np
A=np.arange(10,20)
B=np.arange(1,15)
print(np.intersect1d(A, B))
```

```
[10 11 12 13 14]
```

### 12. Retrieve indices where elements of two arrays match

```
import numpy as np
A=np.array([1,2,3,4,5,6,7,8])
B=np.array([1,1,2,3,5,6,9,8])
print(np.where(A == B))
```

```
(array([0, 4, 5, 7]),)
```

### 13. Get all items between 5 and 10 from an array

```
import numpy as np
A=np.arange(1,20)
print(np.where((A>5) & (A<10)))
#print(np.where(np.logical_and(A>5, A<10)))
```

```
(array([5, 6, 7, 8]),)
```

### 14. For a 1D array with numeric values, find minimum, maximum, mean, median, standard deviation, 5th and 95th percentile, unique values, count of unique values, and the most frequent value.

```
import numpy as np
import statistics
A=np.arange(10,20)
A = np.concatenate((A, np.arange(1,15),[10]))
A=np.sort(A)
print(np.amin(A))
print(np.amax(A))
print(np.mean(A))
print(np.median(A))
print(np.std(A))
print(np.percentile(A,[5,95]))
print(np.unique(A))
print(np.count_nonzero(A))
```

```

print(np.mean(A))
print(np.median(A))
print(np.std(A))
print(np.percentile(A,5))
print(np.percentile(A,95))
print(np.unique(A))
print(len(np.unique(A)))
print(statistics.mode(A))

```

```

1
19
10.4
11.0
4.882622246293481
2.2
17.799999999999997
[ 1  2  3  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19]
19
10

```

15. Write a NumPy program to create a 10x10 matrix, in which all the elements on the borders should be equal to 1, and rest others should be 0.

```

import numpy as np
A = np.ones((10, 10))
A[1:-1, 1:-1] = 0
print(A)

```

```

[[1.  1.  1.  1.  1.  1.  1.  1.  1.  1.]
 [1.  0.  0.  0.  0.  0.  0.  0.  0.  1.]
 [1.  0.  0.  0.  0.  0.  0.  0.  0.  1.]
 [1.  0.  0.  0.  0.  0.  0.  0.  0.  1.]
 [1.  0.  0.  0.  0.  0.  0.  0.  0.  1.]
 [1.  0.  0.  0.  0.  0.  0.  0.  0.  1.]
 [1.  0.  0.  0.  0.  0.  0.  0.  0.  1.]
 [1.  0.  0.  0.  0.  0.  0.  0.  0.  1.]
 [1.  0.  0.  0.  0.  0.  0.  0.  0.  1.]
 [1.  1.  1.  1.  1.  1.  1.  1.  1.  1.]]

```

16. Write a NumPy program to create a 5x5 zero matrix with elements on the main diagonal equal to 1, 2, 3, 4, 5

```

import numpy as np
#A = np.eye(5)
A=np.diagflat([1,2,3,4,5])
print(A)

```

```

[[1 0 0 0 0]

```

```
[0 2 0 0 0]
[0 0 3 0 0]
[0 0 0 4 0]
[0 0 0 0 5]]
```

17. Count the number of elements in a numpy array which are greater than 10. Further, multiply all such elements with value 10.

```
import numpy as np
A=np.arange(10,20)
A = np.concatenate((A, np.arange(1,15),[10]))
print(np.count_nonzero(A>10))
A[np.nonzero(A>10)]=A[np.nonzero(A>10)]*10
print(A)
```

```
13
[ 10 110 120 130 140 150 160 170 180 190   1   2   3   4   5   6   7   8
   9  10 110 120 130 140  10]
```