

A Survey on Temporal Databases and Data mining

Vangipuram Radhakrishna
Faculty of Information Technology
VNR Vignana Jyothi Institute of
Engineering & Technology
Hyderabad, INDIA
vrkrishna2014@gmail.com

P.V.Kumar
Professor of CSE
University College of Engg
Osmania University
Hyderabad, INDIA
pvkumar58@gmail.com

V.Janaki
Head & Professor of CSE
Vaagdevi College of Engineering
Warangal
INDIA
janakicse@yahoo.com

Abstract

Temporal database is a database which captures and maintains past, present and future data. Conventional databases are not suitable for handling such time varying data. In this context temporal database has gained a significant importance in the field of databases and data mining. The major objective of this research is to perform a detailed survey on temporal databases and the various temporal data mining techniques and explore the various research issues in temporal data mining. We also throw light on the temporal association rules and temporal clustering works carried in literature.

Categories and Subject Descriptors

F.4.1 [Mathematical Logic]: Temporal logic; D.2.11 [Software Architectures]: Patterns; H.2.8 [Database Applications]: Data mining

General Terms

Novel Approach, Survey, Methodology

Keywords

Temporal Database, Conventional Database, Outliers

1 INTRODUCTION

Traditionally Databases are designed to maintain organization data and to handle its activities. Databases were primarily responsible for maintaining data consistency and correctness so that necessary information may be extracted from the underlying data which is suitable or required for various applications. In other words, the Conventional databases were originally designed with the only aim of capturing the recent data and not the time varying data. We call the recent data as present data or current data. The most common operations which are performed on databases include insert, update, delete, and modify to name a few. It is common for a database to undergo changes as the changes to the databases

are inevitable unless the changes are strictly restricted. With the availability of new data values through various update operations, the past values are removed from the databases. Because of this reason, the traditional databases only capture a snapshot of reality. This is where the conventional databases fall prey.

The main problem with the conventional databases coins out when there is an essential need to store the past, present and future data values. This is because the conventional databases are not suitable for storing such type of historical information. In essence, what we require is the database which is capable of capturing past, present and the future data. Such a database should support the historical storage and also facilitate for querying the time varying information. In a broader sense, any database which supports past, present and future data may be defined as a temporal database. The attribute which differentiates between conventional and temporal databases is the time attribute. The attribute time may be viewed in two different views. It may be continuous or discrete. In both the cases, time attribute follows linear ordering. Practically speaking time is continuous in nature. Formally, Continuous time may be mapped isomorphically to real valued numbers while discrete time may be a subset of real numbers or may also be isomorphic to natural numbers. For any two time unequal instants, say t_1 and t_2 either t_1 must occur before t_2 or t_2 must occur before t_1 . This simple principle makes the time attribute satisfy the linear ordering property. Of the two views of time, the temporal database researchers practiced the use of discrete notion of time. This is mainly because of the simplicity of discrete notion of time followed by the ease of implementation. A discrete time is a set of ordered time points which are equally spaced usually denoted by T and represented as a set, $T = 0, 1, 2, 3 \dots n$.

Temporal database was originally coined by Richard Snodgrass [1, 2] in 1992. Tansel, 2004 defines the term temporal database as "The database applications are stored in to the database with the aspect of time". Section-2 of this paper introduces the importance of temporal databases and how it coined in the literature. Section-3 includes detailed literature survey performed on various temporal data mining tasks and techniques. Section 4 concentrates on the temporal data mining tasks and challenges involved. Section 5 discusses various research issues in temporal data mining. Finally, Section-6 concludes the paper.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from Permissions@acm.org.

ICEMIS '15, September 24-26, 2015, Istanbul, Turkey
©2015 ACM. ISBN 978-1-4503-3418-1/15/09 ...\$15.00
DOI: <http://dx.doi.org/10.1145/2832987.2833064>

2 TAXANOMY

In the last 40 years, a significant contribution from researchers of database community is towards studying the temporal databases and various aspects of temporal information systems. In the year 1986, summaries of temporal database research which were discussed in various symposiums and workshops followed by universities and work carried out at various research labs was first published in ACM SIGMOD Record. The importance of the area has come in to the existence with the IEEE Data Engineering devoting a complete issue for temporal databases in 1988. Consequently in the year 1990 and 1992, two research papers contributing to survey in temporal databases were published. In this paper, we restrict our survey to the research contributions towards temporal frequent items, association rules and temporal association patterns for the discussions.

3 TEMPORAL ASSOCIATION PATTERNS AND RULES

In this section, we discuss the various significant research works published in the literature in specific to finding frequent items in temporal databases, temporal association rules and discovering temporal association patterns.

In [16] the authors consider handling the time series problem by the use of time expressions to find the temporal association rules. Finally the authors propose a incremental approach to find the temporal association rules, given a transaction database. Most of the existing algorithms in the literature considered only the events existing at a single instance of time. They do not consider the time interval based events. Given an interval based data, the authors Edi Winarko, Roddick in [17], propose ARMADA, an efficient method for discovering relatively richer temporal association rules. In [18] the authors define a fuzzy calendar algebra which allows the user to input the temporal requirements. The authors propose a border based algorithm which can efficiently find the hidden fuzzy temporal association rules.

Most of the existing algorithms address the problem of mining association rules in non-temporal sense. The support value considered usually is not a function of utility value, temporal varying feature. In [20], the authors address the problem of mining the utility oriented temporal association rules by using the support which is a function of time interval or time period and utility value. The problem of mining temporal association rules in temporal documents collection is handled in [24]. The problem of handling calendar based temporal association rules is discussed in [21, 23]. The transaction databases in reality, inherently exhibit the time varying behavior and temporal characteristic which makes temporal data mining active area for research. In [25], the authors use the concept of p-tree and t-tree to discover the association rules from the underlying time dependent data. For a given time interval, the algorithm designed by the authors yields a smaller dataset and hence reduces the overall processing time.

In [19], an approach for discovering the temporal association rules on evolving attributes is discussed. The

importance of this work includes considering an extra attribute called density in addition to support and strength which are used in the traditional association rule mining algorithms. The traditional association rule finding algorithms are not suitable to find the temporal association rules from publication databases. In publication database each item consists its own exhibition period. The problem of discovering temporal association rules from the publication databases is discussed by the authors in [22] which over comes the limitation of conventional temporal association rule mining algorithms. Some of the significant research contributions in discovering temporal association rules include [26, 27-32] but are not exhaustive.

4 TEMPORAL DATA MINING - TASKS

4.1 Temporal Clustering

Conventional Clustering technique is basically a unsupervised learning process which aims to group the underlying data in to a finite set of strongly cohesive groups with least coupling and strong cohesion. In short, it is a data mining technique which is used to place sets of similar data in to one single group. Classical Clustering process is widely studied in the literature. [2,39, 40-42] Temporal clustering may be defined as a temporal data mining task which aims at placing subsets of similar temporal data in to one group and dissimilar temporal data into a separate group. Temporal Clustering has its own challenges and limitations.

1. Choosing an appropriate temporal distance measure or dissimilarity measure, which may be used to cluster the temporally varying data or dataset.
2. Finding temporal frequent patterns in a temporal database requires handling itemsets whose support values are numeric sequences.
3. Temporal Clustering requires forming the new clusters as the data is added periodically.
4. Temporal Clustering and Classification requires choice of appropriate distance measure.
5. Conventional frequent pattern mining algorithms which are used to find the frequent items and association rules do not require distance measure; however finding temporal association patterns requires the use of a suitable distance measure.
6. The conventional pattern search algorithms are not applicable to find the required pattern of interest in the temporal databases, time series databases.
7. The choice of suitable clustering algorithm is also one of the few challenges in the temporal context.
8. In context of text clustering, temporal clustering of documents has its own challenges as it requires computation of frequent patterns dynamically from the time varying document collection.

4.2 Temporal Classification

Another task in temporal data mining is the temporal classification. Temporal classification is a supervised learning process which is used to classify the temporal data to one




Figure 1. Outline of typical Temporal Clustering process

of the known labeled classes. Temporal Classification also requires the choice of a proper distance measure which can efficiently and accurately serve the need. Temporal Classification may also be carried out by the choice of the temporal association rules by properly adopting them to classify the underlying temporal data.

The problem of temporal classification is not applied and dealt extensively w.r.t text processing. Most of the earlier researches include sentimental analysis, email classification, Question & Answering systems, temporal ordering of events, text based temporal reasoning, topic classification to name a few. A temporal approach for text classification using predicted writing time and document creation time is discussed in [52]. Another significant work in temporal classification includes [53] in which the authors propose an unsupervised learning approach for extraction of periodicity information from the underlying text data. The authors make use of natural language property where the word frequency count exhibits both the periodic and non-periodic behavior if the data is analyzed as a time series. An approach for temporal classification using the concept of linear classifiers is discussed in [54]. However the temporal classification using non-linear classifiers is not applied extensively in the literature and has a good scope for active research. Most of the real world data is not static and varies temporally. Also expressing the real world datasets in terms of features statically is not efficient and some times not feasible. We may have to represent the features in a temporal sense. An approach for temporal classification w.r.t multivariate time series is discussed in [55]. The figure 1 shows the outline of temporal clustering and classification process.

4.3 Temporal Frequent Items and Patterns

The algorithms used to find the frequent items in a static database are not applicable for finding the frequent temporal itemsets in the temporal databases. Conventional frequent item set finding algorithms use the concept of support and confidence to find the frequent itemsets and the corresponding association rules. This is not true w.r.t temporal databases. This is because in temporal databases, we must also consider the time at which the transaction occurs. Due to this reason, the itemsets which are frequent earlier may not be frequent later. We need to consider the periodicity property when discovering the temporal frequent itemsets.

An approach for finding local frequent sets, periodical frequent sets and periodical association rules is handled in [56]. Another significant research recently is the approach for finding the temporal maximum utility itemsets from the data streams [57]. The salient features of their work include single pass database scan, efficient and easy to maintain tree called TMUI tree applied to data streams. Also finding the temporal association patterns w.r.t a given reference sequence requires the use of a distance measure to find the similarity between the generated patterns. Given a reference sequence, the problem of finding temporal frequent patterns or itemsets from the temporal databases requires using a suitable distance measure to compute the degree of similarity between the temporal itemsets and the reference sequence.

This coins the need for coming up with various methods and approaches to find the temporal association patterns. There is a scope for research towards defining the suitable temporal distance measures to discover the temporal association patterns. These temporal patterns which are discovered using a similarity measure are called the similarity profiled temporal association patterns [51].

4.4 Temporal Pattern Discovery

Temporal pattern discovery is concerned with the discovery of temporal patterns of interest and depends essentially on the underlying application and domain. The diverse nature of such applications, has given scope for coming up with various temporal pattern discovery frameworks. The most popular temporal pattern discovery frameworks are sequence mining, frequent episode discovery, temporal association rule discovery. The problem of temporal association pattern mining is an extension of temporal pattern mining which is useful in mining the behavioral aspects of underlying temporal data.

4.5 Handling Temporal Sequences

One of the important subfield of data mining is the sequence pattern mining. Temporal sequence pattern mining is one of the research topics which is gaining a lot of practical importance presently. Given a time interval based data, the problem is to find the temporal patterns in the work of the authors [37]. For this the authors define two representations called end point and end time. Given a temporal sequence, the problem is to find the temporal associations among the sequences or within a sequence. In [33], the authors propose a method to discover patterns in temporal sequences which uses the interval properties for mining the temporal patterns of user interest. Other contribution on temporal sequences include [35, 36, 58, and 59].

4.6 Temporal Outlier Detection

The problem of outlier detection in time series has been widely studied in statistics [43]. With the rapid advances in software and hardware technologies, from a computational perspective there is scope for research in discovering temporal outliers. The most recent survey by the popular authors Han, Guo and Gupta contributes a detailed survey in temporal outlier detection [43, 44].

5 RESEARCH ISSUES IN TEMPORAL DATA MINING

5.1 Choice of Temporal Similarity Measure

The first challenge before the temporal data mining researchers is the choice of temporal similarity measure which may be used for clustering temporal data. The distance measures such as Euclidean, Cosine, Jaccard, Manhattan used for finding distance and also for clustering non-temporal data are not much effective when handling temporal data. For example, the distance value computed using the popular Euclidean distance measure has lower bound but does not consist the upper bound. The lower bound value is a minimum value equal to zero but the upper bound value is not finite (i.e infinite). Though several researchers have been proposing solutions towards finding similar temporal patterns, but no effort is made to design a new similarity measure suitable for temporal data. Very few researchers contributed to the design of new temporal similarity measures which are countable [11,12, 13, 14]. With a comparatively less research effort put in this direction, hence there is a scope and also the need for coming up with effective and efficient temporal distance measures for handling the temporal data. We call this distance measure also as a temporal similarity measure.

5.2 Deciding on Temporal Clusters

The second challenge for the temporal data mining researchers is coming up with the decision on the number of clusters to be obtained from the underlying temporal data which is provided as the input for temporal clustering algorithms. This problem becomes more complex when we do not know in advance or practically if the number of clusters cannot be estimated in advance.

5.3 Choice of Temporal Clustering Algorithm

It is the time to revisit the conventional clustering algorithms designed for handling the non-temporal data available in the literature and to come out with the design of new clustering approaches for handling the temporal data. The trivial clustering algorithms such as k-means may not be effective for clustering temporal data as that of non-temporal data.

5.4 Temporal Classification

Another task in temporal data mining is the temporal classification. Temporal classification is a supervised learning process which is used to classify the temporal data to one of the known labeled classes. Temporal Classification also requires the choice of a proper distance measure which can efficiently and accurately serve the need. Temporal Classification may also be carried out by the choice of the temporal association rules and properly adopting them to classify the underlying temporal data.

5.5 Temporal Frequent Patterns

Finding temporal frequent patterns or temporal similar patterns of interest requires the use of suitable distance measure which may be applied even for temporal data. This is because the items or itemsets are usually represented in the form of numeric sequences. The traditional frequent item finding algorithms such as apriori, fp-tree, incremental frequent item set to name a few do not require the use of distance measures. Due to this reason, the algorithms and methods used to find the frequent patterns are not suitable

for finding temporal frequent patterns from the temporal database.

6 CONCLUSION

Temporal data mining is the process of discovering the unknown and hidden knowledge from the huge temporal data. In this research, our main intention is to come up with a detailed survey which essentially introduces the importance of temporal databases, temporal data mining and discuss the various techniques involved in handling temporal data. This is followed by discussing some of the research challenges when handling temporal data. We hope this survey shall help the researchers in temporal data mining community to understand the need of temporal databases and the research issues in handling temporal data.

7 References

- [1] Tansel Clifford, Gadia JaJodia, Segeu Snodgaass. Temporal Databases. Theory, Design and Implementation. Benjamin Cummings Publishing. 1993
- [2] Srivatsan Laxman, P S Sastry. A survey of temporal data mining. Sadhana Vol. 31, Part 2, April 2006, pp. 173198
- [3] Matteo Golfarelli, Stefano Rizzi. A Survey on Temporal data Warehousing. International Journal of Data Warehousing and Mining, 5(1), 1-7, 2009.
- [4] Gultekin Ozsoyolu and Richard T. Snodgrass. Temporal and Real-Time Databases: A Survey. IEEE TRANSACTIONS ON KNOWLEDGE AND DATA ENGINEERING, VOL. 7, NO. 4, 1995
- [5] Kjetil Nrvig, Trond ivind Eriksen, Kjell-Inge Skogstad, Mining Association Rules in Temporal Document Collections, Springer Foundations of Intelligent Systems, Volume 4203, pp 745-754, 2006
- [6] Komate Amphawan, Philippe Lenca. Mining top-k frequent-regular closed patterns. Expert Systems with Applications, Volume 42, Issue 21, Pages 7882-7894
- [7] Terenziani, P., "Symbolic user-defined periodicity in temporal relational databases," in IEEE Transactions on Knowledge and Data Engineering, , vol.15, no.2, pp.489- 509,
- [8] Ozsoyoglu, G.; Snodgrass, R.T., "Temporal and real-time databases: a survey," IEEE Transactions on Knowledge and Data Engineering, , vol.7, no.4, pp.513-532.
- [9] Terenziani, Paolo, "Coping with Events in Temporal Relational Databases," IEEE Transactions on Knowledge and Data Engineering, , vol.25, no.5, pp.1181-1185.
- [10] Jae-Woo Chang, Rabindra Bista, Young-Chang Kim, and Yong-Ki Kim. 2007. Spatio-temporal similarity measure algorithm for moving objects on spatial networks. In Proceedings of the 2007 international conference on Computational science and its applications Vol. 3. Springer-Verlag, 1165-1178.
- [11] Carlo Combi, Matteo Gozzi, Barbara Oliboni, Jose M. Juarez, and Roque Marin. 2009. Temporal similarity

measures for querying clinical workflows. *Artif. Intell. Med.* 46, 1 (May 2009), 37-54.

- [12] Man-Kwan Shan and Suh-Yin Lee. 2001. A framework for temporal similarity measures of content-based scene retrieval. *Pattern Recogn. Lett.* 22, 5 (April 2001), 517-532.
- [13] Rui Cai, Lie Lu, and Hong-Jiang Zhang. 2003. Using structure patterns of temporal and spectral feature in audio similarity measure. In *Proceedings of the eleventh ACM international conference on Multimedia*. 219-222.
- [14]] Mark B. Cartwright and Bryan Pardo. 2012. Novelty measures as cues for temporal salience in audio similarity. In *Proceedings of the second international ACM workshop on Music information retrieval with user-centered and multimodal strategies (MIRUM '12)*. 51-56.
- [15] Jensen, Christian S.; Snodgrass, R.T.; Soo, M.D., "Extending existing dependency theory to temporal databases," *IEEE Transactions on Knowledge and Data Engineering*, vol.8, no.4, pp.563-582.
- [16] Tarek F. Gharib, Hamed Nassar, Mohamed Taha, and Ajith Abraham. 2010. An efficient algorithm for incremental mining of temporal association rules. *Data Knowl. Eng.* 69, 8 (August 2010), 800-815.
- [17] Edi Winarko and John F. Roddick. 2007. ARMADA - An algorithm for discovering richer relative temporal association rules from interval-based data. *Data Knowl. Eng.* 63, 76-90.
- [18] Wan-Jui Lee and Shie-Jue Lee. 2004. Discovery of fuzzy temporal association rules. *Trans. Sys. Man Cyber. Part B* 34, 6, 2330-2342.
- [19] TAR: Temporal Association Rules on Evolving Numerical Attributes. In the *Proceedings of the 17th International Conference on Data Engineering (ICDE '01)*. IEEE Computer Society, Washington, DC, USA, Pg 283.
- [20] G. Maragatham and M. Lakshmi. 2015. UTARM: an efficient algorithm for mining of utility-oriented temporal association rules. *Int. J. Knowl. Eng. Data Min.* Volume 3, Issue 2, 208-237.
- [21] Keshri Verma and O. P. Vyas. 2005. Efficient calendar based temporal association rule. *SIGMOD Rec.* Volume 34, 3, 63-70.
- [22] Chang-Hung Lee, Ming-Syan Chen, and Cheng-Ru Lin. 2003. Progressive Partition Miner: An Efficient Algorithm for Mining General Temporal Association Rules. *IEEE Trans. on Knowl. and Data Eng.* Volume 15, Issue 4, 1004-1017.
- [23] Yingjiu Li, Peng Ning, X. Sean Wang, and Sushil Jajodia. 2001. Discovering Calendar-Based Temporal Association Rules. In *Proceedings of the Eighth International Symposium on Temporal Representation and Reasoning (TIME'01)*
- [24] Kjetil Nrvg, Trond ivind Eriksen, and Kjell-Inge Skogstad. Mining association rules in temporal document collections. In *Proceedings of the 16th international conference on Foundations of Intelligent Systems (ISMIS'06)*, Springer-Verlag, 745-754.
- [25] Keshri Verma, O. P. Vyas, and Ranjana Vyas. 2005. Temporal approach to association rule mining using t-tree and p-tree. In *Proceedings of the 4th international conference on Machine Learning and Data Mining in Pattern Recognition (MLDM'05 Springer-Verlag*, 651-659.
- [26] Jen-Wei Huang, Bi-Ru Dai, and Ming-Syan Chen. 2007. Twain: Two-end association miner with precise frequent exhibition periods. *ACM Trans. Knowl. Discov. Data* 1, 2, Article 8.
- [27] Akshat Surana, R. Uday Kiran, and P. Krishna Reddy. 2011. An efficient approach to mine periodic-frequent patterns in transactional databases. In *Proceedings of the 15th international conference on New Frontiers in Applied Data Mining (PAKDD'11)*, 254-266.
- [28] Ehsan Nazerfard, Parisa Rashidi, and Diane J. Cook. 2011. Using association rule mining to discover temporal relations of daily activities. In *Proceedings of the 9th international conference on Toward useful services for elderly and people with disabilities: smart homes and health telematics (ICOST'11)*, 49-56.
- [29] Stephen G. Matthews, Mario A. Gongora, Adrian A. Hopgood, and Samad Ahmadi. 2013. Web usage mining with evolutionary extraction of temporal fuzzy association rules. *Know.-Based Syst.* Volume 54 ,66-72.
- [30] Panu Korpipaa 2001. Visualizing constraint-based temporal association rules. *Artif. Intell. Eng. Des. Anal. Manuf.* 15, 5 (November 2001), 401-410.
- [31] Tzung-Pei Hong, Yi-Ying Wu, and Shyue-Liang Wang. 2009. An effective mining approach for up-to-date patterns. *Expert Syst. Appl.* 36, 6 (August 2009), 9747-9752.
- [32] Stefano Concaro, Lucia Sacchi, Carlo Cerra, Pietro Fratino, and Riccardo Bellazzi. 2009. Mining Healthcare Data with Temporal Association Rules: Improvements and Assessment for a Practical Use. In *Proceedings of the 12th Conference on Artificial Intelligence in Medicine: Artificial Intelligence in Medicine (AIME '09)*, 16-25.
- [33] Bouandas, K.; Osmani, A., "Mining Association Rules in Temporal Sequences," in *Computational Intelligence and Data Mining*, 2007. CIDM 2007. IEEE Symposium on, vol., no., pp.610-615.
- [34] Ru Miao; Xia-Jiong Shen, "Construction of periodic temporal association rules in data mining," in *Fuzzy Systems and Knowledge Discovery (FSKD)*, 2010 Seventh International Conference on , vol.5, no., pp.2133-2137
- [35] Hong, Pengyu; Ray, S.R.; Huang, T., "A new scheme for extracting multi-temporal sequence patterns," in *Neural Networks*, 1999. IJCNN '99. International Joint

Conference on , vol.4, no., pp.2643-2648 vol.4.

- [36] Zhiyong Shen; Ping Luo; Yuhong Xiong; Jun Sun; Yidong Shen, "Topic Modeling for Sequences of Temporal Activities," in Data Mining, 2009. ICDM '09. pp.980-985.
- [37] Jiadong Ren; Haiyan Tian, "Sequential Pattern Mining with Inaccurate Event in Temporal Sequence," in Networked Computing and Advanced Information Management, 2008. NCM '08. vol.2, pp.659-664.
- [38] Chen, Yi-Cheng; Peng, Wen-Chih; Lee, Suh-Yin, "Mining Temporal Patterns in Time Interval-based Data," in Knowledge and Data Engineering, IEEE Transactions on , vol.PP, no.99, pp.1-1
- [39] Araujo, R.; Kamel, M.S., "Semi-supervised Kernel-Based Temporal Clustering," ICMLA 2014, pp.123-128.
- [40] Adomavicius, G.; Bockstedt, J., "C-TREND: Temporal Cluster Graphs for Identifying and Visualizing Trends in Multiattribute Transactional Data," in Knowledge and Data Engineering, IEEE Transactions on, vol.20, no.6, pp.721-735, June 2008
- [41] Jayashri, M.; Chitra, P., "Topic clustering and topic evolution based on temporal parameters," in Recent Trends In Information Technology (ICRTIT), 2012 International Conference on , vol., no., pp.559-564, 19-21 April 2012
- [42] Policker, S.; Geva, A.B., "A new algorithm for time series prediction by temporal fuzzy clustering," in Pattern Recognition, 2000. Proceedings. 15th International Conference on , vol.2, no., pp.728-731 vol.2, 2000
- [43] Gupta, M.; Jing Gao; Aggarwal, C.C.; Jiawei Han, "Outlier Detection for Temporal Data: A Survey," in IEEE Transactions on Knowledge and Data Engineering, vol.26, no.9, pp.2250-2267, 2014.
- [44] Gupta, M.; Gao, J.; Aggarwal, C.; Han, J., "Outlier Detection for Temporal Data," in Outlier Detection for Temporal Data , 1, Morgan & Claypool, 2014, pp.129
- [45] Snodgrass, R.; Ilsoo Ahn, "Temporal Databases," in Computer , vol.19, no.9, pp.35-42, Sept. 1986
- [46] Terenziani, P. "Symbolic user-defined periodicity in temporal relational databases" IEEE Transactions on Knowledge and Data Engineering, vol.15, no.2, pp.489-509.
- [47] Schluter, T.; Conrad, S., "Mining Several Kinds of Temporal Association Rules Enhanced by Tree Structures," in Information, Process, and Knowledge Management, 2010. EKNOW '10. Pp.86-93.
- [48] Yo-Ping Huang; Li-Jen Kao; Sandnes, F.-E., "A prefix tree-based model for mining association rules from quantitative temporal data," IEEE International Conference on Systems, Man and Cybernetics, vol.1 ,pp.158-163 .
- [49] Lal, K.; Mahanti, N.C., "Temporal Association Rules Mining in T-databases Using Pipeline Technique," IEEE 14th International Conference on Computational Science and Engineering (CSE), pp.392-400, 2011.
- [50] Guo-Cheng Lan; Tzung-Pei Hong; Pei-Shan Wu; Tsumoto, S., "Mining hierarchical temporal association rules in a publication database," 2013 12th IEEE International Conference on Cognitive Informatics & Cognitive Computing (ICCI*CC), pp.503-508.
- [51] Jin Soung Yoo; Shashi Shekhar, "Similarity-Profiled Temporal Association Mining," in Knowledge and Data Engineering, IEEE Transactions on , vol.21, no.8, pp.1147-1161, Aug. 2009
- [52] Angelo Dalli. 2006. Temporal classification of text and automatic document dating. In Proceedings of the Human Language Technology Conference of the NAACL, Companion Volume: Short Papers (NAACL-Short '06). Association for Computational Linguistics, Stroudsburg, PA, USA, 29-32.
- [53] Angelo Dalli and Yorick Wilks. 2006. Automatic dating of documents and temporal text classification. In Proceedings of the Workshop on Annotating and Reasoning about Time and Events (ARTE '06). Association for Computational Linguistics, Stroudsburg, PA, USA, 17-22.
- [54] Peter Revesz and Thomas Triplet. 2011. Temporal data classification using linear classifiers. Inf. Syst. Volume 36, Issue 1,Pg.30-41.
- [55] Mohammed Waleed Kadous. 2002. Temporal Classification: Extending the Classification Paradigm to Multivariate Time Series. Ph.D. Dissertation. University of New South Wales, New South Wales, Australia, Australia. AAI0806481.
- [56] A. Kakoti Mahanta, F. A. Mazarbhuiya, and H. K. Baruah. 2005. Finding locally and periodically frequent sets and periodic association rules. In Proceedings of the First international conference on Pattern Recognition and Machine Intelligence (PRMI'05) Springer-Verlag, 576-582.
- [57] Bai-En Shie, Vincent S. Tseng, and Philip S. Yu. 2010. Online mining of temporal maximal utility itemsets from data streams. In Proceedings of the 2010 ACM Symposium on Applied Computing (SAC '10). ACM, New York, NY, USA, 1622-1626.
- [58] Mohammed J. Zaki. 2001. SPADE: An Efficient Algorithm for Mining Frequent Sequences. Mach. Learn. Volume 42, Issue 1-2, Pg 31-60.
- [59] Minghua Zhang, Ben Kao, David W. Cheung, and Kevin Y. Yip. 2007. Mining periodic patterns with gap requirement from sequences. ACM Trans. Knowl. Discov. Data Volume 1, Issue 2, Article 7
- [60] Adam Perer and Fei Wang. 2014. Frequency: interactive mining and visualization of temporal frequent event sequences. In Proceedings of the 19th international conference on Intelligent User Interfaces (IUI '14). ACM, New York, NY, USA, 153-162.