

# Core Concepts

---

Part of the [React curriculum](#). This document covers components, props, state, hooks, and the custom-hook pattern for data fetching.

## 1. What a single-page application (SPA) is, and why use one

---

A single-page application loads once, then updates the page in-place (via JavaScript) as the user navigates and interacts, rather than requesting a whole new HTML page from a server for every action. **React** is a library for building the UI of an SPA out of reusable **components** — small, self-contained pieces of UI, each responsible for rendering some piece of the page from data passed into it.

Choosing this approach over a single-process dashboard framework ([Streamlit curriculum](#)) trades faster initial development for a richer, more customizable UI, real component reuse, and a UI layer that's fully decoupled from — and testable independently of — the backend serving its data.

## 2. Components and props

---

```
interface KpiCardProps {
  label: string;
  value: string;
}

function KpiCard({ label, value }: KpiCardProps) {
  return (
    <div className="kpi-card">
      <span className="kpi-label">{label}</span>
      <span className="kpi-value">{value}</span>
    </div>
  );
}

// used as: <KpiCard label="Total" value="1,234" />
```

A component is just a function that takes **props** (its inputs, passed like HTML attributes) and returns what should be rendered. Components compose — a page is usually a component that renders several smaller components, each with its own props. Props are **read-only** from the receiving component's perspective — a component should never mutate its own props directly; if it needs to change something, that change belongs in the parent that owns the data (or in the component's own local state, §3).

## 3. State

---

**State** is data a component owns and can change over time, triggering a re-render when it does:

```
import { useState } from 'react';

function Counter() {
  const [count, setCount] = useState(0); // [currentValue, setterFunction]

  return <button onClick={() => setCount(count + 1)}>Clicked {count} times</button>;
}
```

`useState(initialValue)` returns a pair: the current value, and a setter function. Calling the setter schedules a re-render with the new value — React does **not** mutate the existing value in place; it replaces it, which is why you call `setCount(count + 1)` rather than `count++`.

### 3.1 Controlled vs. uncontrolled inputs

A **controlled** input's value is driven entirely by React state — the input always shows exactly what state says it should, and every keystroke updates that state:

```
function ControlledInput() {
  const [value, setValue] = useState('');
  return <input value={value} onChange={(e) => setValue(e.target.value)} />;
}
```

An **uncontrolled** input instead manages its own internal DOM state, and you read its current value only when you need it (typically via a `ref`, §6):

```
function UncontrolledInput() {
  const inputRef = useRef<HTMLInputElement>(null);
  const handleSubmit = () => console.log(inputRef.current?.value);
  return <input ref={inputRef} defaultValue="" />;
}
```

Controlled inputs are the more common default in React — they keep a single source of truth (React state) rather than letting the DOM and your application state potentially disagree — but uncontrolled inputs are simpler for cases where you genuinely don't need to react to every keystroke (e.g., a form you only read on submit).

## 4. Effects

---

```
import { useState, useEffect } from 'react';

function Example() {
  const [count, setCount] = useState(0);

  useEffect(() => {
    // runs after render, and again whenever a dependency in the array below changes
    document.title = `Count: ${count}`;
  }, [count]);

  return <button onClick={() => setCount(count + 1)}>Clicked {count} times</button>;
}
```

`useEffect` lets a component "hook into" the browser/DOM or perform side effects (fetching data, setting a document property, subscribing to an external event) that aren't a pure function of props/state alone. Its dependency array ( `[count]` above) controls when the effect re-runs; an empty array ( `[]` ) means "run once, after the first render only"; omitting the array entirely means "run after every single render" (rarely what you want).

## 4.1 Cleanup functions

An effect can return a **cleanup function**, which React runs before the effect re-runs (due to a dependency changing) and when the component unmounts:

```
useEffect(() => {
  const timer = setInterval(() => console.log('tick'), 1000);
  return () => clearInterval(timer); // cleanup: stop the timer when this effect is superseded or
  the component unmounts
}, []);
```

Forgetting cleanup for anything that persists beyond a single render (timers, subscriptions, in-flight requests) is one of the most common sources of subtle bugs and memory leaks in React apps.

## 5. A custom hook for data fetching

---

The `useState/useEffect` pattern above is exactly what's needed to fetch data from an API and track its loading/error/success state — and since almost every page in a data dashboard needs this same pattern, it's usually extracted into a reusable **custom hook**:

```

import { useEffect, useState } from 'react';

interface AsyncState<T> {
  data: T | null;
  error: string | null;
  loading: boolean;
}

function useAsync<T>(fn: () => Promise<T>, deps: unknown[]): AsyncState<T> {
  const [state, setState] = useState<AsyncState<T>>>({ data: null, error: null, loading: true });

  useEffect(() => {
    let cancelled = false;
    setState((s) => ({ ...s, loading: true, error: null }));
    fn()
      .then((data) => { if (!cancelled) setState({ data, error: null, loading: false }); })
      .catch((err) => { if (!cancelled) setState({ data: null, error: err.message, loading: false }); });
    return () => { cancelled = true; }; // cleanup: runs when deps change or the component
    unmounts
  }, deps);

  return state;
}

// used in a page component:
function OverviewPage() {
  const { data, error, loading } = useAsync(() => fetchOverview(), []);
  if (loading) return <Spinner />;
  if (error) return <ErrorMessage text={error} />;
  return <div>{/* render data */}</div>;
}

```

The `cancelled` flag in the cleanup function matters: without it, a slow request that resolves *after* the component has already unmounted (or after a newer request has started, because `deps` changed) would still call `setState` on a component that's no longer mounted — a common source of warnings and subtle bugs in real React apps. This loading/error/data three-state pattern is worth internalizing — it's the shape almost every data-driven page in an app like this will need. A custom hook is just a regular function whose name conventionally starts with `use` and which itself calls other hooks — this is what makes it reusable across components rather than copy-pasted logic.

## 6. Other hooks worth knowing

---

```
import { useContext, useMemo, useCallback, useRef } from 'react';
```

- **useRef** — holds a mutable value that persists across renders *without* triggering a re-render when it changes (unlike state). Commonly used to reference a DOM element directly (§3.1's uncontrolled input example), or to store a value you need to remember between renders but that shouldn't itself cause a re-render (like the cancelled flag's conceptual cousin, if you needed it accessible outside the effect closure).
- **useMemo** — recomputes an expensive derived value only when its dependencies change, rather than on every render: `const sorted = useMemo(() => [...items].sort(), [items])`. A performance optimization — reach for it once you've identified an actual expensive recomputation happening unnecessarily often, not as a default on every derived value.
- **useCallback** — like `useMemo`, but memoizes a *function* rather than a value; useful when passing a callback down to a child component that itself uses `React.memo` or a dependency array that would otherwise see a "new" function reference on every render.
- **useContext** — reads a value provided higher up the component tree via `React.createContext` — see [Routing & API Integration, §5](#) for how this is used for state that needs to be shared broadly without manually passing props through every intermediate component ("prop drilling").

## 7. Design systems: tokens, themes, and components

A **design system** is more than a component library: it is the set of *decisions* about how an interface looks and behaves (colours, spacing, type, component states, accessibility rules) captured as data and code, so every application that consumes it looks and behaves consistently. A typical one has four parts: **design tokens** (the named values), a **component library** (buttons, tables, charts, app shell), **themes** (alternative token sets), and **conventions plus tests** that keep all of it coherent. This project's front end is built on one, the Syena Design System, a separately maintained repository shared by several apps; its own reference is `DESIGN.md` in that repository (token architecture, theming model, the 65-component catalog, testing conventions). This section explains the principles; consult that document for specifics.

### 7.1 Tokens are the contract

Rather than writing `color: #0A6E8C` in an app, a design system exposes **semantic tokens** as CSS custom properties (`--_s9cmpx-interactive-fill-primary*`, `--_s9cmpx-static-text-weak`, `--_s9cmpx-chart-surface`). Tokens are layered:

| Layer         | What it holds                                                                                                                |
|---------------|------------------------------------------------------------------------------------------------------------------------------|
| Reset         | Normalises browser defaults; loaded first                                                                                    |
| Base theme    | The token source of truth: colour ramps, semantic tokens, type scale, per-component values, chart palettes, shadows, z-index |
| Component CSS | Class rules that <i>consume</i> tokens through component-level variables                                                     |
| Overrides     | The design system's own bug-fix layer (every consumer must import it)                                                        |

| Layer           | What it holds                                                     |
|-----------------|-------------------------------------------------------------------|
| Theme overrides | Small sets of tokens scoped under <code>[data-theme="..."]</code> |

The component's job is only to map props to class names (`variant="primary" → __s9cmpx-button--primary`) — components never emit their own styles. The consequences for an application:

- **Use semantic tokens, never raw colours**, in your own CSS. A hard-coded hex works until the user switches theme, and then it is the one thing on the page that doesn't change.
- **Add app-level tokens sparingly and by purpose** (a warning colour, a link colour that must differ per theme), named for what they mean, defined once per theme.
- **Prefer a semantic name to a visual one**, so that "weak text" can be retuned per theme to meet contrast without touching any component.

## 7.2 Themes: one switch, applied once

A theme is a set of token overrides scoped to an attribute:

```
<div data-theme="analytics-bright-tidewater"> ...the whole app... </div>
```

Apply it **once, at the root of the app**; individual pages never opt in or out. Switching between a bright and a dark theme is then changing that one attribute (see [Patterns for Data-Heavy Dashboards, §7](#)). Two theme shapes exist: a **minimal override** (~30 tokens: brand ramp and primary button states) that falls through to the base theme for everything else, and a **full-coverage** theme (complete token set, as the dark data-visualisation themes need). Principles that came out of building and adopting them:

- **Choose brand hues that don't collide with semantic colours.** If green and red already mean "fell" and "rose" in the product, a green brand competes with that meaning; a water/atmosphere hue avoids it and keeps magnitude colour ramps unambiguous.
- **Charts often need their own surface.** Several light themes keep chart panels *dark* so a vivid categorical palette keeps the luminance separation it was validated for; chart components then read a `chart-surface` token rather than the page background. Put your own chart-adjacent elements on that token inside a chart panel.
- **A theme must set its own text colour at its root.** A vendor reset that hard-codes a body colour leaves any component without an explicit `color` inheriting a literal light-mode grey, nearly invisible on a dark surface. If a component is unreadable in only one theme, check inheritance before assuming the theme is incomplete.
- **A fix to one full-coverage theme must be ported by hand to a copied sibling** — note it when you create one.

## 7.3 Namespacing and white-labelling

All classes, tokens and block names live under a deliberately meaningless prefix (`__s9cmpx-`), and components that need branding take it as **required props with no default** (a footer's `copyright`, a logo's `markSrc` and `wordmark`, a chatbot's `title`). A forgotten override is then a *type error*, not a silent brand leak; a unit test that

greps component sources and styles for the vendor's name enforces the rule. The lesson for any shared library: make the thing you want consumers to supply impossible to omit.

## 7.4 Consuming a design system

How the application takes the dependency matters operationally:

- **Sourced vs. published.** Here the app aliases the design system straight to its `src/` directory — no published package, no version to bump. A change merged to the design system is live in the app the moment its checkout is pulled and the app rebuilt. That is fast and also means the checkout must be updated *before* the app is built ([Deployment, §8](#)). A published, versioned package is the opposite trade-off: slower to adopt, but reproducible and rollback-able.
- **One React instance.** A component library running inside your bundle must share your copy of `react / react-dom`; two copies break hooks. Alias both explicitly.
- **Import the overrides file yourself.** A bug once shipped to a consumer because a bug-fix stylesheet was imported only by the design system's own preview tool.
- **Fix gaps upstream, not per app.** When a component is unreadable in a theme, an icon has no contrast, or a header wraps on a phone, the fix belongs in the design system (and its tests) so every consumer benefits; the app records the request. App-specific decisions belong in the app's own docs, not the shared ones.

## 7.5 Accessibility and testing are part of the system

A design system earns trust by testing what it ships:

- **Stories are tests.** Each component's documentation story is also an automated test that mounts it, runs any `play` interaction script (keyboard navigation, focus traps, clamping, open/close), and runs an automated accessibility check (axe) that *fails* on a violation. Interaction logic is tested in the story rather than in a separate file; purely presentational components are mount-and-a11y only, by decision, and that is documented rather than hidden.
- **Contrast is a token property.** One shared-token fix once resolved 338 of 345 contrast violations. Compute replacements with the WCAG relative-luminance formula; and write down known gaps (a theme not yet contrast-checked) where adopters will see them.
- **Keyboard behaviour is designed.** For example, a data grid suppresses cell focus (tab-stopping every cell of an informational table is worse for keyboard users) and offers an explicit row-activate handler that wires click *and* Enter/Space to the same action — use it rather than a mouse-only row-click handler.
- **In the app, stub the heavy parts.** The chart component wraps a browser-only plotting library; page tests stub it and leave its own rendering to the design system's tests ([Testing, §6](#)).

## 7.6 Gotchas worth knowing before you theme anything

These cost real debugging time and generalise beyond this library:

- **Custom-property cascade is per element.** A token you set at the theme root is silently ignored if the vendor stylesheet re-declares the same property on a *nearer* element (a navigation container, say). Target the same or a more specific selector as the vendor rule.

- **Some colours are written as inline SVG attributes** by a charting library and can't be reached by a normal CSS rule; they need a `fill: ... !important` override.
- **Fonts need every font-family token, plus the grid library separately.** Repointing only the primary family leaves other text styles — and AG Grid, which ignores them all — in the old font; the consumer must also import the font files, and a different typeface may need a `font-size-adjust` to match optical size.
- **Fixed-height headers and long wordmarks.** Truncate with `max-width` plus ellipsis, not `min-width: 0`: overriding a grid item's automatic minimum can collapse its whole column.
- **Header-adjacent controls must not inherit the header's ink**, or a dark header can swallow a button whose colour resolves to the same value.

## 8. Core libraries summary

---

| Library    | Used for                                        |
|------------|-------------------------------------------------|
| React      | components, hooks, state, rendering             |
| TypeScript | static typing across components and their props |

## See also

---

- [React curriculum index](#)
- [Routing & API Integration](#) — building on these concepts to navigate between pages and talk to a backend