Silence Is Not Violation: Measuring and Reducing False Violation Errors in LLM Compliance Checking of Vendor Data Processing Agreements under India's DPDP Act

Saurabh Pandey
Dept. of Artificial Intelligence
MPSTME, SVKM's NMIMS
Mumbai, India
saurabh.pandey20@nmims.in

Siddhant Nikam
Dept. of Artificial Intelligence
MPSTME, SVKM's NMIMS
Mumbai, India
siddhant.nikam16@nmims.in

Nabiya Inamdar
Dept. of Artificial Intelligence
MPSTME, SVKM's NMIMS
Mumbai, India
nabiya.inamdar69@nmims.in

Anagha Raich
Dept. of Artificial Intelligence
MPSTME, SVKM's NMIMS
Mumbai, India
anagha.raich@nmims.edu

Kapil Rathor
Dept. of Artificial Intelligence
MPSTME, SVKM's NMIMS
Mumbai, India
kapil.rathor@nmims.edu

Abstract—Large language models (LLMs) are increasingly used to check commercial contracts against regulations. We identify and measure a specific, recurring failure: a checker that judges each clause in isolation reports a contract's silence on a requirement as a violation of it. We observed this failure while building PactScan, an LLM- and knowledge-graph-based compliance system for vendor Data Processing Agreements (DPAs) under India's Digital Personal Data Protection (DPDP) Act, 2023, where a fully compliant contract received 19 findings. We release a minimal-pair benchmark of 138 synthetic DPAs (1,752 graded contract–requirement pairs) in which each contract follows, omits or breaks exactly one obligation, including "trap" contracts whose amendments hide or cure a violation. We compare the original clause-level checker with a method that (i) instructs the model that silence is neutral, (ii) checks each requirement only against clauses on its subject, (iii) reads each clause together with the provisions that override it, and (iv) decides at the level of the whole contract. On gpt-oss-120b the false violation rate falls from 60.9% to 19.6% while no mandatory gap is missed and 99% of violations are still caught; the same pattern holds on gpt-oss-20b (60.8%→27.1%) and qwen3.8-27b (61.2%→14.1%), and in all 18 of 18 company×model units (sign test $p = 7.6 \times 10^{-6}$), and it holds in each of five independent runs. An ablation shows that the prompt alone barely helps: it shifts the model's verdicts from "contradicts" (65%) to "neutral" (64%), but a clause-level decision rule still turns those neutral verdicts into findings. The decision unit, not the prompt, is what fixes the error. The same holds when existing contracts are re-checked against new regulations: flagging every non-entailing clause flags 100% of compliant contracts, flagging only contradictions misses 96% of gaps, and the contract-level rule misses none (F1 76.5%). Residual false alarms concentrate on compound requirements that bundle several duties into one rule.

Index Terms—legal NLP, contract compliance, large language models, natural language inference, data protection, DPDP Act, GDPR, benchmark

I. Introduction

Companies sign Data Processing Agreements (DPAs) with every vendor that handles personal data on their behalf, and India's Digital Personal Data Protection (DPDP) Act, 2023 [1] makes the company (the Data Fiduciary) accountable for what its vendors (Data Processors) do. Reviewing a portfolio of such contracts against the Act, an internal playbook and, for many firms, the EU GDPR [2] is slow and repetitive, which makes it an obvious target for automation with large language models (LLMs).

A natural design—and the one most systems start from—is to split the contract into clauses and ask a model, for every clause and every relevant requirement, whether the clause entails, contradicts or is neutral to it, in the style of contract natural language inference [3]. This paper is about a failure of that design that is easy to miss and expensive in practice: a clause that simply does not deal with a requirement is reported as violating it. A cross-border-transfer clause is flagged for not restating breach-notification duties; a confidentiality clause is flagged for not mentioning children's data. Each such alarm is defensible in isolation ("this clause does not secure X") and wrong for the contract as a whole, which secures X elsewhere.

We met this failure while building PactScan, a working compliance platform that parses vendor DPAs into a Neo4j knowledge graph and checks them with an LLM. The first version produced 19 findings on a contract we had written to be fully compliant. Later, a regulation-update feature produced 9 and then 13 findings for a single

amendment on a two-page contract. A first fix—report only explicit contradictions—stopped the flood but also hid a real problem: a contract that never mentions a newly mandatory protection. These incidents, recorded in the project's development log, motivate the study.

Contributions.

1) We characterise the silence-as-violation error and its opposite failure, the missed gap, and define a pair of metrics that measure both.
2) We release a minimal-pair benchmark of 138 synthetic vendor DPAs under the DPDP Act (with GDPR as a second standard): 1,752 graded contract–requirement pairs, including trap contracts in which an amendment hides or cures a violation. To our knowledge it is the first compliance benchmark for DPDP contracts.
3) We evaluate a four-part method—a conservative prompt, subject routing, override-aware reading and a contract-level decision rule—with a step-by-step ablation, across three open models, with conservative statistics.
4) We show that the decisive component is the unit of decision, not the prompt, and that residual errors concentrate on compound requirements, which suggests a concrete next step.

II. Related Work

Contract understanding and NLI. CUAD [4] provides expert clause annotations for 510 contracts; we use its category names as a taxonomy reference only. ContractNLI [3] frames contract review as document-level NLI [5] with an explicit NotMentioned label—the same three-way distinction our metrics rely on, and the contract analogue of unanswerable questions in reading comprehension [6]. LexGLUE [7] and LegalBench [8] collect legal-understanding tasks, CLAUDETTE [9] detects potentially unfair clauses in terms of service, and Polisis [10] classifies privacy-policy text. CLAUSE [11] perturbs CUAD and ContractNLI contracts with ten categories of embedded flaws and finds that LLMs often miss subtle discrepancies and struggle to justify them legally. Our benchmark differs in jurisdiction (DPDP), document type (vendor DPAs) and purpose: it is built to separate silence from violation in matched pairs rather than to detect flaws in general.

Compliance checking of DPAs. Amaral et al. [12] and Azeem and Abualhaija [13] check GDPR DPAs for completeness with NLP and machine learning, and Hassani et al. [14] argue that LLM-based compliance analysis should use a broader context than the single sentence. These works establish that completeness (what is missing) is a distinct question from conformity (what is wrong); we study what happens when a checker conflates the two. Work on the DPDP Act so far checks website privacy policies against the Act with access-control rules [15] or embeds DPDP compliance logic in software agents [16]; we found no study of compliance checking for DPDP contracts.

Reliability of LLM legal and compliance verdicts. LLMs hallucinate on legal questions at substantial rates [17], including in commercial legal research tools built on retrieval [18], [19]. For compliance specifically, verdicts are often invariant when the governing rule is deleted, swapped or negated [20], and recent pipelines use NLI only as a screening step before verification by a panel of LLM judges [21]. Regulatory-change monitoring with knowledge-graph-augmented gap detection has been studied for financial institutions' policies [22]. Our study is complementary: we hold the rule fixed and vary how verdicts are turned into findings.

Minimal pairs. Our benchmark follows the logic of behavioural testing with CheckList [23] and contrast sets [24]: small, controlled edits whose correct effect on the output is known in advance.

III. The System and the Problem

A. PactScan's Detect pipeline

PactScan parses an uploaded contract, extracts clauses with an LLM into a fixed taxonomy (e.g. Breach Notification, Data Processing, Sub-processor Obligations), and writes them into a Neo4j knowledge graph used for graph-based retrieval [25]. When a clause contains override language ("notwithstanding", "supersedes"), an LLM confirms whether it changes another clause, and an Overrides edge is stored. Detect then checks each clause against the requirements relevant to its type: 8 internal playbook rules and 5 regulation clauses (DPDP Sections 4, 8 and 9; GDPR Articles 6 and 8). Each check is one batched structured-output call returning, per requirement, a label Entails/Contradicts/Neutral, a confidence and an explanation. Findings feed human-approved redlining; nothing in this paper touches that later stage.

B. Three outcomes, two errors

For a contract c and requirement r, the correct outcome is one of:

- NONE: nothing is wrong—some clause satisfies r, or r does not bind c;
- VIOLATES: a clause goes against r;
- GAP: r is mandatory and nothing in c addresses it.

A checker flags (c, r) if it produces at least one finding for r in c. The false violation rate (FVR) is the share of NONE pairs that are flagged—the error this paper is about. The missed gap rate (MGR) is the share of GAP pairs that are not flagged—the error an over-cautious fix creates. We also report violation recall (share of VIOLATES pairs flagged) and precision, recall and F1 over all problems (VIOLATES $\cup$ GAP).

C. How the problem appeared

The original Detect prompt (preserved in the project's history) instructed the model that "a clause that is vague

or silent on a specific mandatory protection … CONTRADICTS the requirement rather than being NEUTRAL", and the decision rule turned every contradiction, and every neutral verdict given with high confidence, into a finding. The first live run produced 19 findings on the clean contract. The prompt was rewritten ("merely silent on an adjacent obligation is NEUTRAL, never CONTRADICTS"), routing was narrowed, and a cross-clause check suppressed a children's-data gap when another clause covered it. Months later the regulation-update feature, which re-checks existing contracts against a newly added rule, flagged every non-entailing clause and produced 9, then 13, findings for one amendment; restricting it to explicit contradictions removed the legitimate case of a contract silent on a new mandatory requirement. The final rule, introduced below, decides per contract.

IV. Method

We compose four changes, each addressing one way silence leaks into findings.

(1) Conservative prompt. The model is told that a clause that "does not deal with this requirement's subject" or is "merely silent on an adjacent obligation" is Neutral, and that Contradicts is reserved for a clause that itself creates the problem.

(2) Subject routing. Each requirement is checked only against clauses of the type that governs its subject (e.g. breach notification only against Breach Notification clauses), instead of a broad map that checks, say, every data-processing clause against every regulation.

(3) Override-aware reading. A clause is classified on its effective text: its own text followed by every provision that overrides it, found by traversing Overrides edges up to three hops in the graph.

(4) Contract-level decision. Let $V(c, r)$ be the multiset of verdicts for r over the clauses of c routed to r. The number of findings is

$$f(c,r) = \begin{cases} \#\{\text{Contradicts} \in V\} & \text{if one contradicts } r, \\ 0 & \text{else if one entails } r, \\ 1 & \text{else if } r \text{ mandatory}, \\ 0 & \text{otherwise.} \end{cases} \tag{1}$$

A violation is still reported on the clause that causes it; silence becomes at most one gap finding, and only for a mandatory requirement that nothing in the contract satisfies (Fig. 1).

Whether a requirement is mandatory is a property of the rule set by the playbook author, not of the contract.

Configurations. We add the changes one at a time: A the original checker (original prompt, broad routing, clause-level rule); B A + conservative prompt; C B + subject routing; D C + contract-level decision (the full method). D−ET is D without override-aware reading. P is PactScan's Detect agent as deployed, run unmodified; its gap logic covers only the two children's-data requirements.




Fig. 1. The same verdicts, two decision rules, for a mandatory requirement r ("notify breaches within 72 hours"). The clause-level rule reports silence as violation in both contracts; the contract-level rule reports nothing in (a) and a single gap in (b).

TABLE I
The benchmark.

Base contracts (one per sector)	6
Contracts	138
Requirements (8 playbook, 3 DPDP, 2 GDPR)	13
Graded (contract, requirement) pairs	1,752
correct answer NONE	1,599
correct answer VIOLATES	96
correct answer GAP	57
Pairs excluded as ambiguous	42
Traps: hidden violation / hidden fix	12 / 12

All configurations use the same batched call, client, temperature and model.

V. Benchmark

Construction. Six base DPAs pair a fictional Indian company with a vendor in different sectors (health-tech, retail, ed-tech, fintech, HR/payroll, logistics), differing in parties, data categories, locations, notification windows and liability floors, and written in three drafting styles. Each base contains nine topic clauses—breach notification, liability cap, processing details, children's data, sub-processors, data location, deletion on termination, audit rights, lawful basis—plus four filler clauses (services, confidentiality, indemnity, governing law), and complies with all 13 requirements. From each base we derive 23 contracts: the base itself, nine silent variants (one topic clause removed), nine breaks variants (one topic clause rewritten to break its requirements) and four trap variants in which a later amendment either hides a violation behind a compliant clause or cures a non-compliant one (for breach notification and deletion). Every variant differs from its base in exactly one place, so any change in a checker's output is attributable to that change.

Labels. Each requirement belongs to one topic; the correct answer follows from which topic was changed and how. Seven topics are mandatory; two are not: a contract silent on the liability cap breaks nothing (the rule forbids a cap that is too low, and no cap means unlimited liability), and a contract silent on the lawful basis breaks nothing (having a lawful ground is the Data Fiduciary's own statutory duty). The children's-data rules do not bind

the payroll base, which processes only employees' data. All labels were reviewed clause by clause against the requirement texts before any model was run; the review rewrote three breaking clauses that also touched another topic's rule, and excluded 42 pairs on which careful readers could disagree (Table I).

What the benchmark isolates. The checker receives the benchmark's own clauses, clause types and override links, so parsing and extraction errors are excluded and only the verdict step is measured.

VI. Experimental Setup

Models. gpt-oss-120b and gpt-oss-20b [26] and qwen3.8-27b [27], served by GroqCloud. Each run is pinned to one model with no fallback to another, at temperature 0.2.

Controls. Each run has a private response cache, so repeated runs never reuse each other's answers; within a run an identical question under the same system prompt is answered once, so each distinct clause text receives exactly one verdict. Because the system's cache key does not include the system prompt, each prompt version has its own cache. Every verdict is stored with the model and timestamp; runs are resumable.

Statistics. We report 95% confidence intervals from a bootstrap [28] over contracts (2,000 resamples) and exact McNemar tests [29] on per-pair correctness. Because variants of one base share 12 of their 13 clauses, pairs are not independent and these figures overstate certainty; we therefore also report a conservative sign test in which each (base, model) combination is a single unit. Agreement across runs and models is reported as the share of pairs answered identically and Fleiss' κ [30].

Experiments. E1 runs all configurations on gpt-oss-120b over all 138 contracts. E2 runs A and C/D on the two other models. E3 runs A and C/D five independent times on two bases (46 contracts); it was run on gpt-oss-20b because the free daily token quota for gpt-oss-120b was exhausted by E1 and E4. E4 re-checks contracts against four simulated DPDP amendments through PactScan's regulation-update path.

VII. Results

A. E1: the error and the ablation

Table II and Fig. 2a show the error in full. The original checker flags 60.9% of the pairs on which nothing is wrong and raises 21.7 findings on a contract that complies with everything—close to the 19 observed during development. It also misses half the gaps: for a removed clause, a mandatory requirement often has no clause of a routed type left to ask about. The full method reduces the false violation rate to 19.6%, misses no gap, keeps violation recall at 99% and raises 2.5 findings on a clean contract. The difference between A and D is significant on matched pairs (691 pairs correct only under D vs. 1 only under A; McNemar $p = 6.7 \times 10^{-206}$) and under the conservative per-base sign test reported in E2.




Fig. 2. (a) Adding the four changes one at a time: only the contract-level decision (D) removes most false violations, and it is also the only configuration that misses no gap. (b) The original checker makes the error at the same rate on every model; the full method reduces it on all three.

The prompt is not the fix. Moving from A to B changes the false violation rate by only one point (McNemar $p = 0.004$), although the prompt changes the model's behaviour dramatically (Table III): the share of Contradicts verdicts falls from 65.0% to 7.4% and Neutral rises from 4.0% to 64.4%. The clause-level rule, however, still turns a neutral verdict given with high confidence into a finding, so the silence that the prompt correctly relabels is reported anyway. Subject routing (C) removes some of these checks (51.7%), and the contract-level decision (D) removes the rest: 549 pairs become correct and none become incorrect between C and D ($p = 1.1 \times 10^{-165}$).

Override-aware reading matters for hidden changes. On trap contracts in which an amendment hides a violation, D catches 94.4% of violated pairs; without override-aware reading only 27.8% ($p = 8.0 \times 10^{-7}$ on trap pairs). When an amendment cures a non-compliant clause, reading the clause alone wrongly flags every such pair (100%), against 33.3% with override-aware reading.

The deployed system. P raises the fewest alarms (14.1%) but misses 80.7% of gaps, because its gap logic covers only the children's-data rules; overall, D and P are not significantly different in pair accuracy ($p = 0.21$) but make opposite errors. D trades a modest number of extra alarms for complete gap coverage, which is the right trade for a compliance tool.

B. E2: does it hold across models?

All three models make the error at the same rate under A (60.8–61.2%), which locates it in the checker's

TABLE II
E1 on gpt-oss-120b, 138 contracts (%; 95% bootstrap CI in brackets). "Clean" = mean findings on the six fully compliant base contracts.

Configuration	False violation rate	Missed gap rate	Violation recall	F1	Clean
A original checker	60.9 [59.9, 61.8]	52.6 [38.6, 69.8]	100.0	19.7	21.7
B + conservative prompt	59.9 [58.9, 60.9]	52.6 [38.6, 69.8]	100.0	19.9	21.8
C + subject routing	51.7 [50.4, 52.8]	63.2 [46.4, 81.2]	99.0	21.2	12.5
D + contract-level decision (full)	19.6 [17.4, 21.7]	0.0	99.0	49.2	2.5
D−ET full, no override-aware reading	20.3 [18.1, 22.5]	0.0	86.5	45.3	2.5
P PactScan as deployed	14.1 [12.1, 16.1]	80.7 [67.7, 95.2]	77.1	36.6	1.8

TABLE III
Share of raw verdicts by label (gpt-oss-120b, %).

Prompt, routing	Contradicts	Entails	Neutral
A original, broad	65.0	30.9	4.0
B conservative, broad	7.4	28.2	64.4
C/D conservative, by subject	10.1	40.3	49.6

TABLE IV
E2: original (A) vs. full method (D) on three models (%, 95% CI).

Model		FVR	MGR	Viol. recall
gpt-oss-120b	A	60.9 [59.9, 61.8]	52.6	100.0
	D	19.6 [17.4, 21.7]	0.0	99.0
gpt-oss-20b	A	60.8 [59.8, 61.7]	52.6	100.0
	D	27.1 [24.7, 29.4]	0.0	99.0
qwen3.8-27b	A	61.2 [60.3, 62.1]	52.6	99.0
	D	14.1 [12.7, 15.6]	0.0	88.5

TABLE V
E3: five independent runs of gpt-oss-20b on 46 contracts (584 pairs). FVR range is the lowest–highest per-run false violation rate (%).

Set-up	All runs agree (%)	Fleiss' κ	FVR range
A	99.3	0.99	60.5–61.1
C	83.4	0.85	45.9–56.6
D	78.4	0.79	22.6–30.8

TABLE VI
E4: re-checking 46 contracts against four simulated DPDP amendments (gpt-oss-120b, 184 checks, %).

Rule	FVR	MGR	F1	Findings/check
Every non-entailing clause	100.0	0.0	50.4	12.15
Contradictions only	31.1	96.2	21.4	0.31
Contract-level (final)	31.1	0.0	76.5	0.58

design rather than in a particular model, and all three improve under D (Table IV, Fig. 2b) without missing a gap. McNemar tests give $p < 10^{-168}$ for each model. Under the conservative test, D has a lower false violation rate than A in 18 of 18 (base, model) units (exact sign test, $p = 7.6 \times 10^{-6}$). Qwen reaches the lowest false violation rate but also the lowest violation recall (88.5%), and catches only 38.9% of hidden violations in trap contracts, so the method's gains do not remove model-specific weaknesses.

Agreement is not accuracy. Under A the three models answer 99.3% of pairs identically (Fleiss' $\kappa = 0.99$), largely because they all flag nearly everything; under D they agree on 82.0% ($\kappa = 0.70$), disagreeing on the genuinely subtle pairs. High agreement among models should not be read as evidence of correctness.

C. E3: are the results stable?

We ran A and C/D five independent times on gpt-oss-20b over the 46 contracts of two bases (584 graded pairs): the E2 run restricted to these contracts and four further runs, each with its own empty cache (Table V).

The headline result is stable: in every run D's false violation rate is about half of A's or lower (30.8% against 60.9% in the worst run; mean 26.5% against 60.8%), D misses no gap in any run, and its violation recall stays between 96.9% and 100%. A is almost perfectly repeatable, again because it flags nearly everything. D varies more ($\kappa = 0.79$; 21.6% of pairs change answer in at least one of the five runs), and its false violation rate moves by up to eight points between runs—the same pairs that models disagree on in E2 are the ones a single model is unsure about, consistent with the observation that agreement across samples tracks a model's reliability [31]. A deployment should therefore treat findings that are not stable across a re-run as candidates for human review rather than as settled verdicts.

D. E4: re-checking contracts when the law changes

PactScan's regulation-update path embeds a newly added rule, retrieves the related clauses of each existing contract (top-15 by cosine similarity, threshold 0.35), classifies each against the rule, and turns the verdicts into findings. We simulated four DPDP amendments—a 72-hour processor breach-notice duty, erasure within 30 days with written confirmation, a transfer restriction that also requires naming storage locations, and a brand-new duty to name a grievance contact in India—and re-checked the 46 contracts of two bases (184 checks: 122 NONE, 10 VIOLATES, 52 GAP) under the three rules the system actually went through (Table VI).

The first rule reproduces the incident from development: every compliant contract is flagged, with 12.15 findings per check on average. Restricting findings to

TABLE VII
False violation rate of D per requirement (%; requirements with 0% on all models omitted).

Requirement	120b	20b	qwen
DPDP s8 (security, accuracy, breach notice)	84.3	100.0	52.8
GDPR Art. 8 (child consent, age threshold)	84.3	65.4	81.9
DPDP s9 / playbook: parental consent	19.7	17.3	17.3
DPDP s4 (grounds for processing)	16.7	65.9	0.0
GDPR Art. 6 (lawful basis)	16.7	31.0	0.0
Playbook: liability cap	15.9	15.9	15.9
Playbook: processing details	1.9	50.9	0.0

contradictions removes 69 points of false alarms but misses 96.2% of gaps—including every contract silent on the new grievance-contact duty—which is exactly the over-correction we observed. The contract-level rule keeps the lower false alarm rate and recovers every gap (F1 76.5%). Violation recall is 100% under all three rules, and retrieval surfaced the relevant clause for every real violation; the retrieval threshold is permissive (12.8 related clauses per check on average), so errors here come from the verdict and the decision rule, not from retrieval.

The remaining false alarms are instructive. For the erasure amendment, 36 of 40 compliant contracts were flagged because the model marked the processing-details clause, which states that data is deleted within 30 days, as contradicting the amendment for not also requiring written confirmation—while the contract's deletion clause does require certified deletion. Under the contract-level rule any contradiction takes precedence, so a merely incomplete neighbouring clause outvotes the clause that satisfies the rule: the same silence-as-violation error, moved into the Contradicts label. The other two false alarms are contracts whose deletion or breach clause is cured by a later amendment; this path, unlike Detect, classifies clauses without their overrides.

E. Where the remaining false alarms come from

D's remaining false alarms are not spread evenly (Table VII). Five playbook rules, each stating a single duty (breach-notification window, sub-processor approval, data location, deletion on termination, audit rights), have a false violation rate of 0% on every model. The worst two are compound requirements. DPDP Section 8 bundles security measures, data accuracy and breach notification; the models mark a compliant breach clause as contradicting it because it does not also address data accuracy—a duty of the Data Fiduciary, not the processor. GDPR Article 8 includes an age threshold; the models mark a clause requiring verifiable parental consent for every child as incomplete because it does not state the threshold, although it is stricter than the article. Both are the same silence-as-violation error, now inside a single requirement. Excluding these two requirements, D's false violation rate on gpt-oss-120b would be 8.4%. The liability-cap figure is one base's liability clause judged non-compliant by the model (not the same base for every model), repeated across the variants of that base that share the clause. The hardest base for every model is the ed-tech contract, the only one that actually processes children's data (D: 44.4% on gpt-oss-120b against 10.8–16.2% elsewhere).

VIII. Discussion

Decide at the right unit. The central lesson is that the error comes less from what the model says than from how its answers are aggregated. A clause-level rule asks a question the contract-level answer does not depend on; a better prompt changes the model's words but not the rule's output. Self-reported confidence does not rescue the clause-level rule either: although models can partly estimate their own correctness [32], the original rule's use of "high-confidence Neutral" as a trigger is exactly what turned correctly relabelled silence back into findings. Moving the decision to the contract, while keeping violations attached to the clause that causes them, removed most false alarms without losing gaps. The same lesson applied in PactScan's regulation-update feature, where changing what is flagged (every non-entailing clause → contradictions only) traded one error for another, while changing the unit flagged (clause → contract) fixed both.

Split compound requirements. The residual errors suggest a cheap next step: express each requirement as atomic duties (security; accuracy; breach notification) and aggregate per duty, so that silence on one duty cannot contradict another.

Let a satisfying clause answer an incomplete one. E4 shows a second residual pattern: a clause that addresses part of a requirement is labelled Contradicts for omitting the rest, and the contract-level rule lets that label override a clause that does satisfy the requirement. Checking each contradiction against the contract's satisfying clauses before reporting it—or, again, decomposing the requirement—is the natural refinement.

Recommendation for the system. The deployed checker should extend its contract-level gap rule from the two children's-data requirements to every mandatory requirement, which E1 shows closes an 80.7% missed-gap rate at the cost of a few extra alarms.

IX. Threats to Validity and Limitations

Synthetic contracts. The benchmark is synthetic, with six bases in three drafting styles; real DPAs are longer and messier. Its matched design is what makes silence measurable, but results on real contracts may differ.

Labels. Labels were written and reviewed against the requirement texts by the project team, not by practising lawyers, and inter-annotator agreement has not yet been measured; we release a blind annotation sheet of 120 stratified pairs over 83 anonymised contracts, with a script that reports Cohen's κ [33], so that it can be. Two topics are treated as non-mandatory and GDPR is applied as a

second standard regardless of territorial scope; these are stated assumptions.

Verdict step only. Clause types and override links are given, so 36 of the 57 gaps involve a requirement with no clause of its subject left in the contract and are decided without the model; the remaining 21 gaps were decided from model verdicts, and all 21 were caught. End-to-end accuracy with automatic extraction is not measured.

Dependence. Variants share clauses and each distinct question is answered once per run, so pair-level tests overstate certainty; the per-base sign test is our conservative check.

Models and settings. Three open models on one provider, at a single temperature; free-tier quotas limited E3 and E4 to two bases and moved E3 to gpt-oss-20b. E4's amendments are simulated, and its re-check path classifies clauses without their overrides.

X. Conclusion

Clause-by-clause LLM compliance checking mistakes silence for violation: on a matched benchmark of DPDP vendor DPAs, about 61% of pairs on which nothing is wrong were flagged by every model tested. A conservative prompt changes the model's verdicts but not this outcome; deciding at the level of the contract, with subject routing and override-aware reading, cuts false violations to 14–27% across models, misses no mandatory gap and keeps violation recall at 88–99%, and the gain repeats across independent runs, although about one pair in five changes answer in at least one of five runs. When contracts are re-checked against new regulations, the same contract-level rule avoids both the flood of false alarms and the hidden gaps that the two earlier rules produced. The remaining errors point to compound requirements, and to incomplete clauses read as contradictions, as the next targets. We release the benchmark, harness and raw verdicts to support further work on compliance checking under the DPDP Act.

Data and Code Availability

The benchmark, the experiment harness, the raw model verdicts and the scripts that produce every number in this paper are in the research/ folder of the project repository, https://github.com/saurabh-1702/PactScan-AI (branch research/silence-not-violation).

References

[1] Government of India, "The digital personal data protection act, 2023 (no. 22 of 2023)," Gazette of India, Ministry of Law and Justice, 2023.

[2] European Parliament and Council of the European Union, "Regulation (EU) 2016/679 (general data protection regulation)," Official Journal of the European Union, L 119, 2016.

[3] Y. Koreeda and C. D. Manning, "ContractNLI: A dataset for document-level natural language inference for contracts," in Findings of the Association for Computational Linguistics: EMNLP 2021, 2021, pp. 1907–1919.

[4] D. Hendrycks, C. Burns, A. Chen, and S. Ball, "CUAD: An expert-annotated NLP dataset for legal contract review," in Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks, 2021.

[5] S. R. Bowman, G. Angeli, C. Potts, and C. D. Manning, "A large annotated corpus for learning natural language inference," in Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing (EMNLP), 2015, pp. 632–642.

[6] P. Rajpurkar, R. Jia, and P. Liang, "Know what you don't know: Unanswerable questions for SQuAD," in Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (ACL), 2018, pp. 784–789.

[7] I. Chalkidis, A. Jana, D. Hartung, M. Bommarito, I. Androutsopoulos, D. M. Katz, and N. Aletras, "LexGLUE: A benchmark dataset for legal language understanding in English," in Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (ACL), 2022, arXiv:2110.00976.

[8] N. Guha et al., "LegalBench: A collaboratively built benchmark for measuring legal reasoning in large language models," in Advances in Neural Information Processing Systems (Datasets and Benchmarks Track), 2023, arXiv:2308.11462.

[9] M. Lippi, P. Pałka, G. Contissa, F. Lagioia, H.-W. Micklitz, G. Sartor, and P. Torroni, "CLAUDETTE: an automated detector of potentially unfair clauses in online terms of service," Artificial Intelligence and Law, vol. 27, pp. 117–139, 2019.

[10] H. Harkous, K. Fawaz, R. Lebret, F. Schaub, K. G. Shin, and K. Aberer, "Polisis: Automated analysis and presentation of privacy policies using deep learning," in 27th USENIX Security Symposium, 2018, arXiv:1802.02561.

[11] M. R. Choudhury, A. Chandramouli, M. Anand, and V. Gupta, "Better call CLAUSE: A discrepancy benchmark for auditing LLMs legal reasoning capabilities," 2025, arXiv:2511.00340.

[12] O. Amaral, M. I. Azeem, S. Abualhaija, and L. C. Briand, "NLP-based automated compliance checking of data processing agreements against GDPR," IEEE Transactions on Software Engineering, 2023, arXiv:2209.09722.

[13] M. I. Azeem and S. Abualhaija, "A multi-solution study on GDPR AI-enabled completeness checking of DPAs," Empirical Software Engineering, 2024, arXiv:2311.13881.

[14] S. Hassani, M. Sabetzadeh, D. Amyot, and J. Liao, "Rethinking legal compliance automation: Opportunities with large language models," 2024, arXiv:2404.14356.

[15] A. Dhakar, A. Sinha, and S. Sural, "Privacy as permissible operations: An ABAC framework for policy-law compliance," 2026, arXiv:2604.10832.

[16] A. Kulkarni and C. Ramanathan, "An agentic software framework for data governance under DPDP," 2026, arXiv:2601.01101.

[17] M. Dahl, V. Magesh, M. Suzgun, and D. E. Ho, "Large legal fictions: Profiling legal hallucinations in large language models," Journal of Legal Analysis, vol. 16, no. 1, pp. 64–93, 2024.

[18] V. Magesh, F. Surani, M. Dahl, M. Suzgun, C. D. Manning, and D. E. Ho, "Hallucination-free? Assessing the reliability of leading AI legal research tools," 2024, arXiv:2405.20362.

[19] P. Lewis, E. Perez, A. Piktus, F. Petroni, V. Karpukhin, N. Goyal et al., "Retrieval-augmented generation for knowledge-intensive NLP tasks," in Advances in Neural Information Processing Systems 33 (NeurIPS), 2020.

[20] S. Sadhu, A. Sengupta, V. K. Sankarapu, and P. Seth, "Verdict without the rule: Diagnosing and auditing regulatory rule sensitivity in LLM compliance systems," 2026, arXiv:2610.12313.

[21] T. Brackin, "Privacy washing: Detecting internal contradictions in privacy policies," 2026, arXiv:2609.02055.

[22] D. Guo, J. Wu, and S. M. Yiu, "ComplianceNLP: Knowledge-graph-augmented RAG for multi-framework regulatory gap detection," 2026, arXiv:2604.23585.

[23] M. T. Ribeiro, T. Wu, C. Guestrin, and S. Singh, "Beyond accuracy: Behavioral testing of NLP models with CheckList," in Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL), 2020, pp. 4902–4912.

[24] M. Gardner et al., "Evaluating models' local decision boundaries via contrast sets," in Findings of the Association for Computational Linguistics: EMNLP 2020, 2020, pp. 1307–1323.

[25] D. Edge et al., "From local to global: A graph RAG approach to query-focused summarization," 2024, arXiv:2404.16130.
[26] OpenAI, "gpt-oss-120b & gpt-oss-20b model card," 2025, arXiv:2508.10925.
[27] A. Yang et al., "Qwen3 technical report," 2025, arXiv:2505.09388.
[28] B. Efron and R. J. Tibshirani, An Introduction to the Bootstrap. Chapman & Hall, 1993.
[29] Q. McNemar, "Note on the sampling error of the difference between correlated proportions or percentages," Psychometrika, vol. 12, no. 2, pp. 153–157, 1947.
[30] J. L. Fleiss, "Measuring nominal scale agreement among many raters," Psychological Bulletin, vol. 76, no. 5, pp. 378–382, 1971.
[31] X. Wang, J. Wei, D. Schuurmans, Q. Le, E. Chi, S. Narang, A. Chowdhery, and D. Zhou, "Self-consistency improves chain of thought reasoning in language models," in International Conference on Learning Representations (ICLR), 2023.
[32] S. Kadavath et al., "Language models (mostly) know what they know," 2022, arXiv:2207.05221.
[33] J. Cohen, "A coefficient of agreement for nominal scales," Educational and Psychological Measurement, vol. 20, no. 1, pp. 37–46, 1960.