



Silergy CM0 Flash Utility

RELEASE NOTES

June 2022

1 General Instructions

Silergy CM0 Flash Utility (SCFU) is a standalone windows-based command line tool to erase, program and read flash contents of Silergy metering ICs based on ARM Cortex M0. The utility accepts Intel hex record file format for programming (.hex file) and produces similar file format for the flash read command.

Please refer to the readme.txt file for package contents and usage of SCFU.exe.

2 Device and Host Integration

The utility is a Windows-based application and talks to any CMSIS DAP compliant debuggers like uLink2 and uLink-ME over USB.

3 Testing Coverage

- This software was tested on Windows 7 and Windows 10 systems.
- The software was tested with SY7T108G, SY7T211H parts.
- The software was tested with uLink2 and uLink-ME debuggers.

4 Build Environment

This code was developed and built using Visual Studio 2022.

5 Changes or Revision History

June 2022 – SCFU_V0202

- ELF parser is integrated.
- The utility takes FLM files as inputs instead of hex files for flash drivers.

January 2022 – SCFU_V0201

- Optimized the flash operation performance.
- Disabled ADCs and CE before programming flash.
- Added checks to make sure the hex file to be programmed is present before erasing flash.

- Added check to make sure the flash driver files are present when the application is launched.

March 2021 – SCFU_V0200

- Added flash programming feature

February 2021 – SCFU_V0100

- First release of SCFU. Supports flash erase and read

6 Known Issues or Cautions

- The utility does not support JLink adapter as this adapter is not CMSIS-DAP compliant.
- The utility dumps the flash contents starting from address = 0x00. It dumps the entire flash contents based on the selected flash size via the '-n' option.
- The utility configures the CMSIS_DAP debugger to run at 1 MHz clock frequency.
- If the utility tries to read the flash region beyond its physical memory, an error will be displayed as - "Target Error, Unexpected DAP Response". Error at address 0xXXXXX. Flash contents stored successfully in file."
In this case, the utility has successfully read the flash contents up to 0x0001 FFFF. However, the user shall reset the power before start using it.
- The utility will display an error if the user tries to program the flash beyond its physical memory as "Target Error, Data mismatch @ 0x20000." OR "Error : 3 at input line XXXX – data out of Flash space."
- The maximum length of the input or output file path name is limited to 64 characters.