Trainer Setup Guide for Lab 5: Azure Key Vault

Learners share one Key Vault. Each learner adds their own secrets and creates their own secret scope linked to the vault. Allow about 20 minutes.

Part A: Create the Key Vault

1. In the Azure portal, go to **Key vaults** > **Create**.
2. Basics: same subscription, resource group and region as the Databricks workspace. Enter a vault name. Pricing tier: Standard.
3. Access configuration: set Permission model to **Vault access policy**. Key Vault-backed secret scopes expect this model.
4. Networking: **Allow public access from all networks** for the lab.
5. **Review + create** > **Create**.
6. Open the vault > **Settings** > **Properties** and copy the **Vault URI** and **Resource ID**. Learners need both.

Part B: Learner access to the vault

Both assignments use the uc-lab-learners Entra group from the Lab 2 setup.

B1. Contributor on the vault (to create a scope)

1. Open the vault > **Access control (IAM)** > **Add role assignment**.
2. Role: **Contributor** (Privileged administrator roles tab). Members: uc-lab-learners. Review + assign.

Why: creating a Key Vault-backed scope requires Contributor or Owner on the vault. When a learner creates a scope, Databricks adds Get and List permissions for its own service to the vault.

B2. Access policy (to add secrets)

1. Open the vault > **Access policies** > **Create**.
2. Secret permissions: **Get, List, Set, Delete**. Leave key and certificate permissions empty.
3. Principal: uc-lab-learners. Create.

> **Check:** Access policies lists uc-lab-learners. After the first learner creates a scope, an entry for AzureDatabricks also appears.

Part C: Test as one learner

1. Sign in to the Azure portal as one learner and add a secret named precheck with any value.
2. Open https://<workspace-url>/#secrets/createScope and create a scope precheck-scope with Manage Principal Creator and the vault's DNS Name and Resource ID.
3. In a Python notebook on Serverless compute, run:

```
print(dbutils.secrets.get("precheck-scope", "precheck"))   # [REDACTED]

from databricks.sdk import WorkspaceClient
WorkspaceClient().secrets.delete_scope("precheck-scope")
```

4. Delete the precheck secret in Key Vault.

> Check: The notebook prints [REDACTED] and the scope is deleted without error.

Before the session

- Share the vault name, Vault URI and Resource ID with learners.
- Confirm engineer1 can create a notebook on Serverless compute (Lab 1 gave engineers Workspace access).
- Confirm analyst1 can use the shared SQL warehouse (Lab 2, Step 6).

After the session (optional clean-up)

Each learner can delete their scope from a notebook:

```
from databricks.sdk import WorkspaceClient
WorkspaceClient().secrets.delete_scope("<prefix>-kv-scope")
```

Then delete the Key Vault, or delete the lab secrets and remove the Contributor role and access policy for uc-lab-learners. A deleted vault stays soft-deleted and can be purged from Key vaults > Manage deleted vaults.