

SQL Functions

The SQL MIN() and MAX() Functions

The MIN() function returns the smallest value of the selected column.

The MAX() function returns the largest value of the selected column.

MIN() Syntax

```
SELECT MIN(column_name)
FROM table_name
WHERE condition;
```

MAX() Syntax

```
SELECT MAX(column_name)
FROM table_name
WHERE condition;
```

Demo Database

Below is a selection from the "Products" table in the Northwind sample database:

ProductID	ProductName	SupplierID	CategoryID	Unit	Price
1	Chais	1	1	10 boxes x 20 bags	18
2	Chang	1	1	24 - 12 oz bottles	19
3	Aniseed Syrup	1	2	12 - 550 ml bottles	10
4	Chef Anton's Cajun Seasoning	2	2	48 - 6 oz jars	22
5	Chef Anton's Gumbo Mix	2	2	36 boxes	21.35

MIN() Example

The following SQL statement finds the price of the cheapest product:

```
SELECT MIN(Price) AS SmallestPrice
FROM Products;
```

MAX() Example

The following SQL statement finds the price of the most expensive product:

```
SELECT MAX(Price) AS LargestPrice
FROM Products;
```

The SQL COUNT(), AVG() and SUM() Functions

The COUNT() function returns the number of rows that matches a specified criterion.

The AVG() function returns the average value of a numeric column.

The SUM() function returns the total sum of a numeric column.

COUNT() Syntax

```
SELECT COUNT(column_name)
FROM table_name
WHERE condition;
```

```
SELECT COUNT(ProductID)
FROM Products;
```

AVG() Syntax

```
SELECT AVG(column_name)
FROM table_name
WHERE condition;
```

```
SELECT AVG(Price)
FROM Products;
```

SUM() Syntax

```
SELECT SUM(column_name)
FROM table_name
WHERE condition;
```

```
SELECT SUM(Quantity)
FROM OrderDetails;
```

SQL Aliases

SQL aliases are used to give a table, or a column in a table, a temporary name.

Aliases are often used to make column names more readable.

An alias only exists for the duration of the query.

Alias Column Syntax

```
SELECT column_name AS alias_name  
FROM table_name;
```

```
SELECT Name as Fname  
FROM Students;
```