

GNUPlot – Basics via Examples

Saurish Chakrabarty

Acharya Prafulla Chandra College

Contents

1	Plotting Functions	2
2	Modifying the Appearance of Graphs	2
3	Set, Unset, Reset, Load, Save, Replot	3
4	Exporting Plots	3
5	Polar Plots	3
6	Parametric Plots	4
7	Importing Multicolumn Data	4
8	Fitting Data	4
9	Surface Plots	4
10	Contour Plots	4

1 Plotting Functions

Try these out.

- `plot cos(x)`
You should be able to see a plot of $\cos x$.
- `plot cos(x) linewidth 3 linestyle 2`
The linewidth and linestyle may be mentioned. Linestyle includes color and symbol.
- `test`
This is a command that can be used to check out the available options.
- `plot [0:2*pi] [-2:2] cos(x), cos(x-pi/4) lw 3 lt 8 dashtype 2, cos(x-pi/2) lw 3 lt 7 dt 3`
Multiple functions can be plotted together using different linewidths, linetypes and dashtypes.
- `plot [-2:2] [-.5:.5] x**4-x**2 with points lt 8 pointsize 2 pointtype 7`
`plot [-2:2] [-.5:.5] x**4-x**2 w p lt 8 ps 2, x**3-x w linespoints pt 7 ps 2 lw 2`
By default, for functions, GNU Plot draws lines connecting the sampled points. Points can be shown by specifying “with points”, or in short, just “w p” The lines can be simultaneously shown using “w lp”. The point size may also be specified, *e.g.*, “ps 3”.
- `p(x)=exp(-x**2/2)/(2*pi)**0.5`
`w=3`
`plot [-3:3] p(x) lw w, 2*p(2*x) lw w dt w, p(x/2)/2 lw w dt 4`
The first line defines a standard normal (Gaussian) probability density function. Using this, some plots are made. Note that the line width is chosen to be a variable.
- `f(x)=x<-1?0:(x<0?1+x:(x<1?1-x:0))`
`p [-2:2] f(x) lw 2, 2*f(2*x) dt 2 lw 3, f(x-0.7) dt 4 lw 2`
The first line defines a simple triangular pulse centered around the origin. Using this, some plots are made in the next line.
- `p(x)=exp(-(x-m/s)**2/2)/s/(2*pi)**0.5`
`plot [-3:10] m=0 s=1 p(x), m=4 s=2 p(x), m=8 p(x)`
See what this does.

As seen at various instances above, GNU Plot can guess word completions from context.

2 Modifying the Appearance of Graphs

- `set zeroaxis`
Show the axes.
- `plot [-1:3] [-0.5:1] 1-exp(-x) title 'growth', x-x**2/2 title 'model'`
Change the labels shown in the legend.
- `set size square`
This is to make a plot with 1:1 aspect ratio.
- `set samples 1000`
This is to set the number of samples (data points) used for plotting (default: 100).
- `set xlabel 'Radius'`
`set ylabel 'Volume'`
To set axis labels.
- `set title 'Volume vs Radius'`
To set the title.

- `set term wxt font ",20"`
This is to set the global font size to 20.
- `set title 'Volume vs Radius' font ",30"`
To set the font size of just the title (or for any one field).
- `set logscale`
For logarithmic axes.
- `set logscale x`
To set logarithmic x -axis.
- `unset logscale`
To turn off logarithmic axes.

3 Set, Unset, Reset, Load, Save, Replot

- “show”: see the current value of an option.
“set”: set value.
“unset”: turn off the set value of an option.
“reset”: restore everything to default values except “terminal” and “output”.
- “load *file.gp*”: load a file named *file.gp*.
- “save *file.gp*”: save current commands into a file named *file.gp*.
- “replot”: repeat last plot.

4 Exporting Plots

- `set terminal pdfcairo`
`set output "graph.pdf"`
Setting pdf terminal and the name of the output file.
- `set terminal wxt`
`set output`
Reset to the usual terminal.

5 Polar Plots

- `set polar`
Setting polar plot. The independent variable, θ , is denoted by t .
- `plot 1`
Circle.
- `plot 1/(1+0.5*cos(t))`
Ellipse.
- `set angles degrees`
If needed. Default: radians.
- `set size square`
`set tics` (or “rtics”)
`set grid polar`
`set grid polar lt 8 lw 0.4`
Useful settings for polar plots.

6 Parametric Plots

- `set parametric`
Setting parametric plot. The parameter is denoted by t .
- `p [0:2*pi] cos(t), sin(t), 1.2*cos(t), 0.8*sin(t)`
A circle and an ellipse.
- `p [0:2*pi] cos(5*t), 0.8*sin(3*t)`
Lissajous figure.

7 Importing Multicolumn Data

In a linux terminal, run the following command.

```
awk 'BEGIN{for(i=0;i<100;i++)print i,exp(-0.05*i)+(rand()-0.5)/10,
                                     2*i+(rand()-0.5)*10}' > xy.dat
```

- `p "xy.dat"`
- `p "xy.dat" u 1:3`
- `p "xy.dat" u 1:cos($3)`
- `p "xy.dat" u 1:(cos($3/10)) w 1, "xy.dat" u 1:(sin($3/10)) w 1`

8 Fitting Data

```
f(x,m,c)=m*x+c
fit f(x,m,c) "xy.dat" u 1:3 via m,c
p "xy.dat" u 1:3, f(x,m,c)
print m,c
```

9 Surface Plots

10 Contour Plots