

SRM INSTITUTE OF SCIENCE AND TECHNOLOGY

School of Computing — Department of Computer Science & Engineering

Student Name: Sautrik Roy	Reg No: RA2511003010052
Course: 21CSC203P — Advanced Programming Practice	Department: Computer Science and Engineering

Unit III | Session 4 | SLO 1: Thread Priorities and Daemon Threads (Code: 3041)

Q: 1. Fill in the blank:

The default priority of a thread in Java is _____.

Ans: Answer: 5 (Thread.NORM_PRIORITY)

Q: 2. True or False:

Daemon threads continue running even after all user threads have finished execution.

Ans: Answer: False (JVM terminates automatically when all user threads finish).

Q: 3. Multiple Choice:

Which method is used to set the priority of a thread?

A) setOrder() B) setLevel() C) setPriority() D) setThreadLevel()

Ans: Answer: C) setPriority()

Q: 4. Fill in the blank:

The priority range for threads in Java is from _____ to _____.

Ans: Answer: 1 (MIN_PRIORITY) to 10 (MAX_PRIORITY)

Q: 5. Programming – Find output:

```
Thread t = new Thread(() -> System.out.println(Thread.currentThread().isDaemon()));  
t.setDaemon(true); t.start();
```

Ans: Output: A) true

Q: 6. True or False:

Calling setDaemon(true) on a thread after start() has been called will throw an exception.

Ans: Answer: True (IllegalThreadStateException)

Q: 7. Multiple Choice:

Which thread type is typically used for background services like garbage collection?

A) Foreground B) User thread C) Daemon thread D) High-priority

Ans: Answer: C) Daemon thread

Q: 8. Fill in the blank:

The method _____ returns whether a thread is a daemon.

Ans: Answer: isDaemon()

Q: 9. Identify Error:

```
Thread t = new Thread(() -> System.out.println("Running")); t.start(); t.setDaemon(true);
```

Ans: Answer: C) IllegalStateException (setDaemon must precede start()).

Q: 10. Fill in the blank:

Threads with higher priority are _____ likely to be scheduled before lower priority threads.

Ans: Answer: more