

# YearsExperience\_Vs\_Salary\_Prediction\_LinearRegression (1)

February 22, 2025

## 1 A Regression Model to predict Salary based on employee's years of experience in working using Simple Linear Regression

**Step 1: Importing the required libraries** 1. Pandas 2. Numpy 3. Pyplot from Matplotlib 4. Linear Regression from Scikit Learn 5. Evaluation Metrics viz. MAE, MSE, RMSE, R-2


```
[ ]: #Importing required libraries
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from sklearn.linear_model import LinearRegression
from sklearn.model_selection import train_test_split
import seaborn as sns
from sklearn.metrics import mean_squared_error, r2_score, mean_absolute_error
import joblib
```

**Step 2: Load the dataset**

```
[ ]: #Step 1: Loading the dataset
df=pd.read_csv('/content/drive/MyDrive/Colab Notebooks/ML-DSE4/Project_College/
↳salary_data - salary_data (1).csv')
df.head()
```

```
[ ]:   YearsExperience   Salary
0             1.1  39343.0
1             1.3  46205.0
2             1.5  37731.0
3             2.0  43525.0
4             2.2  39891.0
```

```
[ ]: df.plot(kind='scatter', x='YearsExperience', y='Salary', s=32, alpha=.8)
plt.gca().spines[['top', 'right']].set_visible(False)
```



### Step 3: Exploring the dataset

1. Displaying first 5 rows of the dataset
2. Displaying the meta info of the dataset
3. Describing the dataset features using 5 number summary

```
[ ]: #Step 2: Exploring the data
      print(df.head())
```

	YearsExperience	Salary
0	1.1	39343.0
1	1.3	46205.0
2	1.5	37731.0
3	2.0	43525.0
4	2.2	39891.0

```
[ ]: print(df.info())
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 35 entries, 0 to 34
Data columns (total 2 columns):
#   Column          Non-Null Count  Dtype
---

```

```

0    YearsExperience    33 non-null    float64
1    Salary             32 non-null    float64
dtypes: float64(2)
memory usage: 692.0 bytes
None

```

```
[ ]: print(df.describe())
```

```

      YearsExperience    Salary
count      33.000000    32.000000
mean         5.603030  101252.812500
std          3.141206  127989.469434
min          1.100000   37731.000000
25%          3.200000   56878.250000
50%          5.000000   66983.500000
75%          7.900000  106544.250000
max         14.500000  780000.000000

```

**Step 4: Checking for number of null values present for both feature columns**

```
[ ]: df.isnull().sum()
```

```

[ ]: YearsExperience    2
      Salary           3
      dtype: int64

```

Dropping the missing values as it won't affect the training of our model

```

[ ]: # Step 3: Handle missing values
      df.dropna(inplace=True) # Drop remaining missing values (optional)

```

Rechecking for number of missing values present for both feature columns still now.

```
[ ]: df.isnull().sum()
```

```

[ ]: YearsExperience    0
      Salary           0
      dtype: int64

```

**Step 5: Separately loading the independent feature column (Years of Experience) into X and Dependent feature column (Salary) into y**

```

[ ]: X=df[['YearsExperience']]
      y=df['Salary']

```

**Step 6: Splitting the dataset into test and train sets for both features and training the model**

```

[ ]: # Step 5: Split the dataset
      X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2,
      random_state=42)

```

```
[ ]: #Step 6: Initializing the linear regression model
model=LinearRegression()

#Step 7: Training the model with training data
model.fit(X_train,y_train)
```

```
[ ]: LinearRegression()
```

**Step 7: Predicting salary for test set years of experience**

```
[ ]: #Step 8: Make Predictions
y_pred=model.predict(X_test)
```

**Step 8: Evaluating the model to get Mean Absolute Error, Mean Square Error, Root Mean Square Error and R<sup>2</sup> score. More the R<sup>2</sup> score, more better is the model trained.**

```
[ ]: #Step 9: Evaluate the model
mse=mean_squared_error(y_test,y_pred)
mae=mean_absolute_error(y_test,y_pred)
rmse=np.sqrt(mse)
r2=r2_score(y_test,y_pred)

print(f"MAE: {mae}")
print(f"MSE: {mse}")
print(f"RMSE: {rmse}")
print(f"R2 Score: {r2}")
```

```
MAE: 6491.059203246807
MSE: 45321601.19587368
RMSE: 6732.131994834451
R2 Score: 0.9270297836251701
```

**Step 9: Taking user input of years of experience from user to predict their salary using the above model**

```
[ ]: #Take user input of years of experience from user to predict their salary using
    ↳ the above model
years_of_experience = float(input("Enter the number of years of experience: "))
predicted_salary = model.predict([[years_of_experience]])
print(f"The Predicted Salary for {years_of_experience} years of experience is:
    ↳ Rupees {predicted_salary[0]}")
```

```
Enter the number of years of experience: 9.8
The Predicted Salary for 9.8 years of experience is: Rupees 122763.63050840801

/usr/local/lib/python3.11/dist-packages/sklearn/utils/validation.py:2739:
UserWarning: X does not have valid feature names, but LinearRegression was
fitted with feature names
warnings.warn(
```

Step 10: Plotting the Actual Vs Predicted Price regression line output

```
[ ]: # Step 15: Visualization - Actual vs. Predicted Prices
plt.figure(figsize=(8, 6))
sns.scatterplot(x=y_test, y=y_pred, alpha=0.7)
plt.xlabel("Actual Prices")
plt.ylabel("Predicted Prices")
plt.title("Actual vs. Predicted Salaries")
plt.grid()
plt.axline([0, 0], slope=1, color="red", linestyle="--") # Reference line
plt.show()
```

