

```
IOSs-Mac-mini:Test sauvik.dolui$ jazzy --help config
```

By default, jazzy looks for a file named ".jazzy.yaml" in the source directory and its ancestors. You can override the config file location with --config.

(The source directory is the current working directory by default. You can override that with --source-directory.)

The config file can be in YAML or JSON format. Available options are:

OUTPUT

Config file: output
Command line: -o, --output FOLDER

Folder to output the HTML docs to
Default: docs

CLEAN

Config file: clean
Command line: -c, --[no-]clean

Delete contents of output directory before running.

WARNING: If --output is set to ~/Desktop, this will delete the ~/Desktop directory.

OBJC MODE

Config file: objc
Command line: --[no-]objc

Generate docs for Objective-C.

UMBRELLA HEADER

Config file: umbrella_header
Command line: --umbrella-header PATH

Umbrella header for your Objective-C framework.

FRAMEWORK ROOT

Config file: framework_root
Command line: --framework-root PATH

The root path to your Objective-C framework.

SDK

Config file: sdk
Command line: --sdk [iphone|watch|appletv][os|simulator]|macosx

The SDK for which your code should be built.
Default: macosx

HIDE DECLARATIONS

Config file: hide_declarations
Command line: --hide-declarations [objc|swift]

Hide declarations in the specified language. Given that generating Swift

docs only generates

Swift declarations, this is only really useful to display just the Swift declarations & names

when generating docs for an Objective-C framework.

CONFIG FILE

Config file: `config`

Command line: `--config PATH`

Configuration file (.yaml or .json)

Default: `.jazzy.yaml` in source directory or ancestor

XCODEBUILD ARGUMENTS

Config file: `xcodebuild_arguments`

Command line: `-x, --xcodebuild-arguments arg1,arg2,...argN`

Arguments to forward to xcodebuild

Default: `[]`

SOURCEKITTEN SOURCEFILE

Config file: `sourcekitten_sourcefile`

Command line: `-s, --sourcekitten-sourcefile FILEPATH`

File generated from sourcekitten output to parse

SOURCE DIRECTORY

Config file: `source_directory`

Command line: `--source-directory DIRPATH`

The directory that contains the source to be documented

Default: `/Users/sauvik.dolui/Documents/Sauvik.Dolui/EffectiveDigital/Projects/Samples/Test`

EXCLUDED FILES

Config file: `exclude`

Command line: `-e, --exclude filepath1,filepath2,...filepathN`

Source file pathnames to be excluded from documentation. Supports wildcards.

Default: `[]`

INCLUDED FILES

Config file: `include`

Command line: `-i, --include filepath1,filepath2,...filepathN`

Source file pathnames to be included in documentation. Supports wildcards.

Default: `[]`

SWIFT VERSION

Config file: `swift_version`

Command line: `--swift-version VERSION`

AUTHOR NAME

Config file: `author`

Command line: `-a, --author AUTHOR_NAME`

Name of author to attribute in docs (e.g. Realm)

AUTHOR URL

Config file: `author_url`

Command line: `-u, --author_url URL`

Author URL of this project (e.g. <https://realm.io>)

MODULE NAME

Config file: `module`

Command line: `-m, --module MODULE_NAME`

Name of module being documented. (e.g. RealmSwift)

VERSION

Config file: `module_version`

Command line: `--module-version VERSION`

module version. will be used when generating docset
Default: 1.0

COPYRIGHT

Config file: `copyright`

Command line: `--copyright COPYRIGHT_MARKDOWN`

copyright markdown rendered at the bottom of the docs pages

README PATH

Config file: `readme`

Command line: `--readme FILEPATH`

The path to a markdown README file

DOCUMENTATION GLOB

Config file: `documentation`

Command line: `--documentation GLOB`

Glob that matches available documentation

ABSTRACT GLOB

Config file: `abstract`

Command line: `--abstract GLOB`

Glob that matches available abstracts for categories

PODSPEC

Config file: `podspec`

Command line: `--podspec FILEPATH`

A CocoaPods Podspec that describes the Swift library to document

DOCSET ICON

Config file: `docset_icon`

Command line: `--docset-icon FILEPATH`

DOCSET PATH

Config file: `docset_path`
Command line: `--docset-path DIRPATH`

The relative path for the generated docset

ROOT URL

Config file: `root_url`
Command line: `-r, --root-url URL`

Absolute URL root where these docs will be stored

DASH URL

Config file: `dash_url`
Command line: `-d, --dash-url URL`

Location of the dash XML feed e.g. <https://realm.io/docsets/realm.xml>

GITHUB URL

Config file: `github_url`
Command line: `-g, --github-url URL`

GitHub URL of this project (e.g. <https://github.com/realm/realm-cocoa>)

GITHUB FILE PREFIX

Config file: `github_file_prefix`
Command line: `--github-file-prefix PREFIX`

GitHub URL file prefix of this project (e.g. <https://github.com/realm/realm-cocoa/tree/v0.87.1>)

DISABLE SEARCH

Config file: `disable_search`
Command line: `--disable-search`

Avoid generating a search index. Search is available in some themes.

SKIP DOCUMENTATION

Config file: `skip_documentation`
Command line: `--skip-documentation`

Will skip the documentation generation phase.

MIN ACL

Config file: `min_acl`
Command line: `--min-acl [private | fileprivate | internal | public | open]`

minimum access control level to document
Default: public

SKIP UNDOCUMENTED

Config file: skip_undocumented
Command line: --[no-]skip-undocumented

Don't document declarations that have no documentation comments.

HIDE DOCUMENTATION COVERAGE

Config file: hide_documentation_coverage
Command line: --[no-]hide-documentation-coverage

Hide "(X% documented)" from the generated documents

CUSTOM CATEGORIES

Config file: custom_categories

Custom navigation categories to replace the standard “Classes, Protocols, etc.”

Types not explicitly named in a custom category appear in generic groups at the end.

Example: <https://git.io/v4Bcp>

Default: []

CUSTOM HEAD

Config file: head
Command line: --head HTML

Custom HTML to inject into <head></head>.

THEME DIRECTORY

Config file: theme

Command line: --theme [apple | fullwidth | jony | DIRPATH]

Which theme to use. Specify either 'apple' (default), one of the other built-in theme names,

or the path to your mustache templates and other assets for a custom theme.

Default: apple

USE SAFE FILENAMES

Config file: use_safe_filenames
Command line: --use-safe-filenames

Replace unsafe characters in filenames with an encoded representation. This will reduce human readability of some URLs, but may be necessary for projects that expose filename-unfriendly functions such as /(_:_:)

TEMPLATE DIRECTORY

Config file: template_directory
Command line: -t, --template-directory DIRPATH

DEPRECATED: Use --theme instead.

ASSETS DIRECTORY

Config file: assets_directory
Command line: --assets-directory DIRPATH

DEPRECATED: Use --theme instead.

UNDOCUMENTED TEXT

Config file: `undocumented_text`

Command line: `--undocumented-text UNDOCUMENTED_TEXT`

Default text for undocumented symbols. The default is "Undocumented", put "" if no text is required

Default: Undocumented