



#### EC-SP22016

- 6"Middle/High Speed Dome Camera
- 540TVL,Optical 22x,Digital 10x Camera inside
- set the maximum 256 preset points,  
Preset accuracy: 0.5°,Two line sweep:90°
- Rotation angle:360°Vertical angle:90°
- 3 class lightning defend,built-in  
3000V lightning proof,surge resistant
- Double Aluminum design IP 66 Outdoor Cover,  
Built-in constant temperature system

#### Specification

##### **【Product Feature】**

Image recognition technology, automatic search and track moving targets; identification and tracking number of targets can be set

tracking fast,sensitive,target multiples automatic zoom,motion,and the loss of target Parameters can be set; tracking mode and multi-scene patrol tracking;the number of identification tracking and moving targets can be set

OSD menu display both in English and Chinese for setting conveniently

Screen display include time position(pan and tilt) temperature

Continuous 360°pan turning, 90° tilt turning (180° auto flip). region

Protocol compatible;RS-485 interface

8 channels alarm input (8 preset points linkage alarm) and 4 channels relay output (Optional)

Pan: 0.01 ° - 300 ° / sec; Tilt: 0.01 ° - 300 ° / sec,

Turning speed automatically adjusts along with lens zooming to locate object Exactly by large magnification

Built-in memory to store the setting data, which can not be lost after power off

256 presets,6 tour routes

8 area indicate function 8 privacy protection area

Display temperature inside high speed dome camera

Fan on/off,temperature adjustable

Abnormal automatic recovery, network outages automatically connect function

540TVL,Optical 22x ,Digital 10x Camera inside

##### **【Product Parameters】**

Pan Movement: 360 °continuous pan rotation

Vertical Movement:180°turn over automatically, no shadow region

Pan: 0.01 °-300 ° / secretary Tilt: 0.01 ° -300 ° / sec

Preset point:256 ; Address range:0-255

Cruising route:6,16 presets each route

Scanning:Support auto scan between any 2 or more points,duration adjustable

Fixed point scanning: yes

Cruising style: variety

Camera recognition: HITACHI, SONY, SANYO, SAMSUNG, LG, CNB, CANON

Baud Rate: (RS-485) 2400/4800/9600/19200bps

Operation menu:OSD menu both in Chinese and English

Pixel:2000000=1920×1080 or 1600×1200 2.0MP High Speed Dome IP camera

##### **【Structural Parameters】**

Upper shield:high strength double layer aluminum alloy,high temperature resistance, corrosion resistant

Lower shield: high class acrylic bubble, Iu

Installation method: wall mounting/lifting/inseting/ceiling

Environment: indoor/outdoor

Input Voltage: AC24V±5V

Power Consumption :10W indoor, 50W outdoor