

## **Products**

- ▼ DVR NVR HVR KITS
- ▼ AHD series

  Hybrid AHD DVR

  AHD camera
- ▼ CVI series CVI camera
- ▼ Professional IP Camera

3.0~5.0MP IP camera

1080P IP Camera

960P IP Camera

720P IP Camera

IP Speed Dome

IPC Module

- ▼ Household IP Camera
- ▼ Network Video Recorder(NVR)
- ▼ Analog Camera

Weatherproof IR Camera

Vandal proof Dome Camera

Plastic Dome Camera

PTZ Camera

Specialty Camera

- ▼ Digital Video Recorder(DVR)
  - 24&32 Channels
- ▼ Peripheral

POE Switch

UTP Video Balun

Power supply

Cable&Connector

Tools



NKIT8104W

4ch WIFI kits built-in WIFI AP 4 pcs HD WIFI cameras

4 ch WIFI NVR

support 1HDD. Max 4T

臺Print





## Specification

WIFI NVR Support embedded Linux OS Built-in Wireless AP,install without WIFI router 2.4G All wireless Transfer video avoid from wiring problems Support HDMI,VGA Sync 1080P video output Support HD preview, all channels support Main stream Support Zoom function of preview Support event,playback,backup recording ,support picture playback and search
Support embedded Linux OS  Built-in Wireless AP,install without WIFI router  2.4G All wireless Transfer video avoid from wiring problems  Support HDMI,VGA Sync 1080P video output  Support HD preview, all channels support Main stream  Support Zoom function of preview  Support event,playback,backup recording ,support picture playback and search
2.4G All wireless Transfer video avoid from wiring problems Support HDMI,VGA Sync 1080P video output Support HD preview, all channels support Main stream Support Zoom function of preview Support event,playback,backup recording ,support picture playback and search
Support HDMI,VGA Sync 1080P video output Support HD preview, all channels support Main stream Support Zoom function of preview Support event,playback,backup recording ,support picture playback and search
Support HD preview, all channels support Main stream Support Zoom function of preview Support event,playback,backup recording ,support picture playback and search
Support Zoom function of preview Support event,playback,backup recording ,support picture playback and search
Support event, playback, backup recording , support picture playback and search
Support One-key setup and recording
System
Main processor High performance embedded microprocessor
Operating system Embedded LINUX OS
Video spec.
Video compression format H.264
Display Image Resolution 720P 1~30FPS
Playback Image Resolution 4*720P 1~30FPS
can setup 396(22×18)pcs motion detection area
Motion Detection each channeland multi-level sensitivity(0-100 levels adjustable)
Recording Mode
Recording Mode Manual Recording, Time Recording, Motion Recording
Recording storage HDD,Network
Frame rate 1~30 fps
Playback Max support 4ch 720P synchronously playback
Backup Mode Support HDD,USB Flash Disk store & backup
Video
Video Input 4CH 720P IPC
Video output 1ch HDMI, 1ch VGA
Other
2.4Ghz Wireless AP,10/100Mbps Ethernet port;
WIFI Barrier-free transport 100 Meters, wall transfers 30 Meters
USB 2 USB 2.0 ports
HDD support 1 SATA HDD (MAX 4TB)
Power DC12V 3A
Power consumption 16W-18W(not include HDD)
4*IP WIFI cameras
Camera Type 720P IP Camera
Image Sensor 1/4 inch 1 Megapixel CMOS sensor
Camera DSP HI3518 DSP 32 dual-core , pure hardware compression

1 sur 2 01/02/2016 11:00

	IR-LED	36 PCS IR LEDS
	Illuminate Distance	30m IR distance
	Day/Night	IR-CUT filter
	Min.Illumination	Color 0.6Lux/F1.2,B/W 0.08 Lux/F1.2
	Electronic Shutter	1/50(1/60)s-1/100,000s
	Lens	3.6/6mm Fixed Lens
	Lens Mount	CS Mount
	Digital Zoom	10X Digital Zoom
Video	Compression standard	H.264
	Compression technology	Dual-stream compression technology
	Video frames	Real-time PAL 25fps,NTSC 30fps 1-30fpsAdjustable
	output bit rate	32Kbps~5000Kbps Adjustable
Image	Resolution	Main Stream:1280×720(video resolution);
		Sub Stream:640×360, 480×270,320×180;
Network	protocol	DHCP、TCP/IP、HTTP、UDP、DNS
	Alarm	Support Motion Detection, Linkage Alarm,
	Privacy Mask	Support
Vedio port	Video output	1CH Video output,RJ45/WIFI,PAL/NTSC Optional
	Network interface	RJ4510M/100M Ethernet port /WIFI 2.4GHz
Other	Power supply	DC 12V
	Waterproof Criterion	IP66
KITS		
Work environment	-10°C~60°C90%RH	
Package Size		
Net Weight		

Copyright © 2007 CCDCAM Security Systems | E-mail:sales@ccdcam.cn | TEL:+86 755 83106630 | FAX:+86 755 81093177 | 粤ICP备05064898号

2 sur 2