Products

- ▼ DVR NVR HVR KITS
- ▼ AHD series Hybrid AHD DVR AHD camera
- ▼ CVI series CVI camera
- ▼ Professional IP Camera

3.0~5.0MP IP camera

1080P IP Camera

960P IP Camera

720P IP Camera

IP Speed Dome

IPC Module

- ▼ Household IP Camera
- ▼ Network Video Recorder(NVR)
- ▼ Analog Camera

Weatherproof IR Camera

Vandal proof Dome Camera

Plastic Dome Camera

PTZ Camera

Specialty Camera

- ▼ Digital Video Recorder(DVR) 24&32 Channels

▼ Peripheral

POE Switch

UTP Video Balun

Power supply

Cable&Connector

Tools



NVK08W

8ch WIFI NVR kits 8pcs 1MP WIFI IP camera 8pcs DC12V Power Adapter Excluding wifi switche

憂Print



Specification

NVK08W NVR

Support embedded Linux OS

Support IPC Sync Input

Support HDMI,VGA Sync video output

Support HD preview, all channels support Main stream

Support Zoom function of preview and playback

Support event, playback, backup recording, support picture playback and search

Support One-key recording

Support fast playback

Support P2P

Support 4ch 720P simultaneous playback

Camera Type

Camera

System			
Main processor	High performance embedded microprocessor		
Operating system	Embedded LINUX OS		
Video spec.			
Video compression format	H.264		
Display Image Resolution	720P 25FPS		
Playback Image Resolution	4*720P 25FPS		
Motion Detection	can setup 192(16×12)pcs motion detection area		
	each channeland multi-level sensitivity(1-6 levels adjustable)		
Privacy Masking	Support		
Recording Mode			
Recording Mode	Manual Recording, Motion Detection Recording, Time Recording, Alarm Recording		
Recording storage	HDD,Network		
Frame rate	30 fps NTSC;25fps PAL		
Playback	Max support 4ch 720P synchronously playback		
Backup Mode	Support HDD,USB Flash Disk store & backup		
Video			
Video Input	8CH 720P IPC		
Video output	1ch HDMI, 1ch VGA		
Other			
Network	1x100Mbps,RJ45 port;		
USB	2 USB 2.0 ports		
HDD	support 1 SATA HDD (MAX 4TB)		
Power	input: DC12V		
Power consumption	16W-18W(not include HDD)		
8*IP WIFI cameras			

720P IP Camera

1/4 inch 1 Megapixel CMOS sensor

1 sur 2 01/02/2016 11:02

Image Sensor

	DSP	HI3518 DSP 32 dual-core , pure hardware compression
	IR-LED	36 PCS IR LEDS
	Illuminate Distance	30m IR distance
	Day/Night	IR-CUT filter
	Min.Illumination	Color 0.6Lux/F1.2,B/W 0.08 Lux/F1.2
	Electronic Shutter	1/50(1/60)s-1/100,000s
	Lens	3.6/6mm Fixed Lens
	Lens Mount	CS Mount
	Digital Zoom	10X Digital Zoom
Video	Compression standard	H.264/M-JPEG
	Compression technology	Dual-stream compression technology
	Video frames	Real-time PAL 25fps,NTSC 30fps 1-30fpsAdjustable
	output bit rate	32Kbps~8000Kbps Adjustable
Image	Danalutian	Main Stream:1280×720(video resolution);
	Resolution	Sub Stream:640×360, 480×270,320×180;
Network	protocol	DHCP、TCP/IP、HTTP、UDP、DNS
	Alarm	Support Motion Detection, Linkage Alarm,
	Alailli	Linkage recording, sensor trigger alarm functions
	Privacy Mask	Support
Vedio port	Video output	1CH Video output,RJ45/WIFI,PAL/NTSC Optional
	Network interface	RJ4510M/100M Ethernet port /WIFI
Other	Power supply	DC 12V
	Waterproof Criterion	IP66
KITS	, ,	
Other	Work environment	-10°C~60°C90%RH

Copyright © 2007 CCDCAM Security Systems | E-mail:sales@ccdcam.cn | TEL:+86 755 83106630 | FAX:+86 755 81093177 | 粤ICP备05064898号

2 sur 2