CloudNotes Project Report

INT378: Advancements in Cloud and DevOps

Lovely Professional University
Savinay Singh

14 October 2026

Cloud-native application, infrastructure, delivery, and operations

Contents

- Executive Summary
- 1. Introduction
- 2. Application and System Design
- 3. Runtime and Deployment Architecture
- 4. Infrastructure as Code
- 5. CI/CD and DevSecOps
- 6. Observability
- 7. Security, Reliability, and Risks
- 8. Verification and Acceptance Plan
- 9. INT378 Course Outcome Alignment
- 10. Conclusion and Future Work
- References
- Appendix A. Repository guide

Executive Summary

CloudNotes is a small full-stack note-taking application used to demonstrate an end-to-end DevOps workflow. Users can create, list, search, update, and delete notes through a browser interface. The application is composed of a static Nginx frontend, a Flask REST API, and PostgreSQL persistence. Docker packages the application services, Docker Compose provides a local multi-service environment, Kubernetes manifests describe a cluster deployment, and Terraform provisions AWS infrastructure. Jenkins automates validation, image publication, and deployment. Prometheus collects backend metrics and Grafana presents a dashboard in the Compose environment.

The project emphasizes reproducible delivery and operational visibility. Its scope is an academic demonstration: the AWS topology uses a single public subnet and a single K3s application host; the API has no authentication; and example credentials in configuration must be replaced. Repository configuration documents intended behavior, while a live AWS endpoint is not guaranteed to remain available because public IPs and infrastructure state can change.

1. Introduction

Manual setup makes application environments hard to reproduce and releases difficult to audit. CloudNotes applies infrastructure as code, containers, CI/CD, orchestration, and metrics to a practical application so each step from source change to running service can be examined. The note-taking domain is intentionally simple; the focus is on how services are packaged, deployed, monitored, and updated.


1.1 Objectives

- Implement note creation, listing, search, update, and deletion with persistent storage.
- Package the frontend and backend independently and run the complete local stack with Compose.
- Describe a Kubernetes deployment with health checks, persistent database storage, ingress, and horizontal scaling.
- Provision AWS network, EC2, and S3 resources using Terraform.
- Automate backend tests, security scans, image publication, and Kubernetes rollout through Jenkins.
- Collect HTTP and business metrics with Prometheus and visualize them with Grafana.

1.2 Scope and limitations

The project is not a production-ready notes service. There is no user authentication, authorization, multi-tenant note ownership, TLS configuration, multi-AZ cluster, managed database, or tested disaster-recovery process. The Terraform security groups and example deployment values require review before public use. Resource claims below distinguish repository configuration from runtime evidence.

2. Application and System Design



CloudNotes system architecture

The browser downloads static assets from Nginx. Nginx proxies `/api` requests to Flask. Flask validates requests, reads or writes the Note model using SQLAlchemy, and stores data in PostgreSQL. The API also exposes `/api/health` for health checks and `/metrics` for Prometheus. The frontend does not connect to the database directly.

2.1 Technology stack

Area	Technology	Responsibility
Frontend	HTML, CSS, JavaScript, Nginx	Note UI and browser-facing reverse proxy
API	Flask, Flask-SQLAlchemy, Gunicorn	REST operations, persistence logic, health, and metrics
Database	PostgreSQL 15	Persistent note records
Local orchestration	Docker Compose	Starts app, database, Prometheus, and Grafana
Cluster orchestration	Kubernetes, K3s, KEDA, Nginx Ingress	Services, rollout, ingress, recovery, and traffic-based replica scaling
Infrastructure	Terraform and AWS	VPC, public subnet, security groups, EC2, S3, and billing alarm
Delivery	Jenkins, GitHub, Docker Hub	CI checks, image publishing, and cluster deployment
Monitoring	Prometheus, Grafana	Metrics, alert rules, and visual dashboard

2.2 Data model


The `note` table contains `id` (integer primary key), `title` (required string up to 100 characters), `body` (required text), and `created_at` (UTC timestamp). The API returns JSON and timestamps in ISO format. PostgreSQL is used in Compose and Kubernetes; the application has a SQLite fallback when `DATABASE_URL` is unset.

2.3 REST API

Method	Path	Behavior	Success response
GET	`/api/health`	Health probe	`200`, `{"status":"ok"}`
GET	`/api/notes`	List notes	`200`, JSON array
GET	`/api/notes?search=<text>`	Search title and body	`200`, matching JSON array
POST	`/api/notes`	Create with JSON `title` and `body`	`201`, id and message
PUT	`/api/notes/<id>`	Update supplied fields	`200`, id and message
DELETE	`/api/notes/<id>`	Delete a note	`200`, message
GET	`/metrics`	Prometheus exposition	`200`, Prometheus text format

Missing title/body on create returns `400`; requests for unknown note IDs return `404`. The API is unauthenticated and should not be exposed to untrusted users without an identity and authorization layer.

3. Runtime and Deployment Architecture



Service component architecture

3.1 Docker Compose

`docker/docker-compose.yml` defines `db`, `backend`, `frontend`, `prometheus`, and `grafana` services on a private bridge network. PostgreSQL data is stored in the named `pgdata` volume. The host ports are 80 (frontend), 5000 (backend), 9091 (Prometheus), and 3001 (Grafana). Compose waits for the database health check before starting the backend. The `.env.example` file is a template; a local `.env` must contain non-placeholder values and must remain untracked.

3.2 Kubernetes

The manifests create a `cloudnotes` namespace, backend and frontend Deployments and Services, a PostgreSQL Deployment and Service, a PersistentVolumeClaim, a Secret, an Ingress, Prometheus, and KEDA ScaledObjects. The backend Deployment starts with two replicas and uses liveness/readiness probes against `/api/health`. The frontend starts with two replicas. Ingress routes `/api` to the backend and `/` to the frontend for host `cloudnotes.local`.

KEDA polls Prometheus every 15 seconds and scales the backend between 2 and 5 replicas and the frontend between 2 and 4 based on the aggregate Flask HTTP request-rate metric. A 60-second cooldown is configured. This is horizontal pod scaling; the CPU and memory requests/limits are scheduling and resource-bound settings, not vertical autoscaling. KEDA and an ingress controller must be installed in the cluster before their custom resources and ingress rules can function.

`kubernetes/monitoring.yaml` deploys Prometheus and configures the backend scrape and alert rules. Grafana and its provisioned dashboard are present in the local Compose setup; the Kubernetes manifests do not deploy Grafana.

3.3 AWS infrastructure

Terraform modules create a VPC, one public subnet in `ap-south-1a`, an internet gateway and route table, security groups, two EC2 instances, and an S3 bucket. The Jenkins EC2 instance runs Jenkins in Docker. The application EC2 instance bootstraps K3s, KEDA, and Nginx Ingress. Terraform outputs expose the current public IPs and bucket name. Because the subnet and app cluster are single-node, this topology has no multi-AZ or node-level high availability. Review `terraform/modules/vpc/main.tf` before applying: several ingress rules accept public traffic for demonstration purposes.

3.4 Deployment models

Model	Intended use	Main entry point
Docker Compose	Local development and monitoring demonstration	`docker compose -f docker/docker-compose.yml up --build -d`
Minikube / Kubernetes	Cluster resource and scaling demonstration	`kubectl apply -f kubernetes/` after installing ingress and KEDA
AWS	Cloud infrastructure and remote Jenkins/K3s demonstration	Terraform; optional Windows wrapper `start_mumbai.bat`

4. Infrastructure as Code

Terraform configuration is under `terraform/`. `main.tf` composes the VPC, Jenkins EC2, application EC2, and S3 modules; `outputs.tf` exposes addresses. `billing_alarm.tf` configures cost-alert resources. The SSH public key, AWS credentials, state, and any environment-specific values must be supplied outside version control. The checked-in SSH key variable default is a placeholder and is not usable for deployment.

Typical review sequence:


```
terraform -chdir=terraform init
terraform -chdir=terraform plan
terraform -chdir=terraform apply
terraform -chdir=terraform output
```

Destroy resources when the environment is no longer needed, after reviewing what Terraform will remove:

```
terraform -chdir=terraform destroy
```

Actual charges may continue for resources outside the Terraform state or resources retained by AWS. Confirm cleanup in the account rather than assuming the destroy command guarantees a zero bill.

5. CI/CD and DevSecOps




Jenkins delivery sequence

The root `Jenkinsfile` is pipeline-as-code. A GitHub push trigger starts checkout, builds a backend test image and runs pytest, scans the workspace for verified secrets with TruffleHog, builds versioned backend/frontend images, scans the backend image with Trivy, pushes version and `latest` tags to Docker Hub, then uses SSH and `kubectl` to apply manifests and deploy the build-number-tagged images. The pipeline waits for Deployment rollouts and checks `/api/health` through ingress. Concurrent builds are disabled.

The current Trivy invocation uses `--exit-code 0`, so findings are reported but do not block the build. Jenkins credentials are referenced by ID (`dockerhub-credentials`, `app-server-ssh-key`) and must be configured in Jenkins. The target app host is supplied through `APP_SERVER_IP` in the pipeline configuration and must match the current Terraform output. Jenkins connectivity, webhook setup, Docker Hub access, and SSH access are prerequisites; checked-in pipeline code alone is not evidence that a deployment succeeded.

6. Observability



CloudNotes observability architecture

The Flask exporter supplies HTTP request metrics and custom counters `notes_created_total`, `notes_updated_total`, and `notes_deleted_total`. Prometheus scrapes the backend `/metrics` endpoint every 15 seconds. Local Prometheus configuration also loads alert rules for backend availability, high 5xx error rate, high p95 request latency, and an hour without note creation after prior activity. Grafana provisions a Prometheus data source and a dashboard with backend status, note counters, error rate, request rate, p95 latency, and backend memory panels.

Prometheus metrics support KEDA's request-rate scaling trigger. Monitoring alerts in this configuration define conditions; notification delivery requires a separately configured Alertmanager receiver. No such receiver is configured in the repository.

7. Security, Reliability, and Risks

Area	Current implementation	Remaining risk / improvement
Secrets	Jenkins credential bindings, `.env.example`, Kubernetes Secret template, TruffleHog scan	Replace placeholders; rotate any exposed credentials; use managed secret storage; Kubernetes Secret values are not encrypted by the YAML format alone
Image security	Trivy scans backend image for HIGH/CRITICAL CVEs	Current scan is non-blocking; make policy explicit and scan both images
Network	AWS security groups and Kubernetes Services	Restrict public SSH, Jenkins, API, and monitoring exposure; add TLS
Application access	Frontend escapes rendered note content; API validates create fields	No authentication/authorization or rate limiting; add identity and per-user note ownership
Runtime health	Backend liveness/readiness probes and Jenkins rollout checks	Health endpoint does not verify database connectivity; add a readiness dependency check
Data	PostgreSQL PVC and Compose named volume	No automated backup/restore or migration framework; single database replica
Availability	Kubernetes restarts unhealthy pods and maintains multiple app replicas	AWS app cluster is a single node in one subnet; node failure can interrupt service
Cost	Terraform billing alarm and destroy workflow	Review alarm configuration and retained resources; monitor actual account charges

8. Verification and Acceptance Plan

The repository includes backend tests at `app/backend/tests/test_app.py` for health, create validation, listing, search, update, deletion, and missing IDs. End-to-end browser automation is under `tests/e2e/`. The results below record the AWS run completed on 14 October 2026; they distinguish checks that ran from features that were not measured.

Area	Verification	Recorded result
Application	Request `/`, `/api/health`, and `/api/notes` through the AWS Ingress with Host `cloudnotes.local`	HTTP 200 for all three; health body `{"status":"ok"}` and notes body `[]`. Without the required host header, ingress returned HTTP 404.
CI/CD	Execute the CloudNotes Jenkins pipeline	Build #2 succeeded; backend tests, TruffleHog, Trivy, Docker Hub image push, Kubernetes rollout, and ingress health check ran. Trivy is configured as non-blocking.
Kubernetes	Deploy application, database, monitoring, ingress, and KEDA manifests	K3s node and platform pods reached Ready; Jenkins completed rollout and health checks.
Infrastructure	Apply and destroy the Terraform configuration	14 resources created in `ap-south-1`; Terraform reported all 14 destroyed after verification.
Scaling	Observe replicas while generating sustained API traffic	Not measured during this run. The KEDA configuration exists, but no scaling event is claimed.

The AWS public IP used for this demonstration was `15.206.117.49`; it is historical and no longer identifies a running deployment. This run verifies a deployment and short health check, not a long-duration production workload.

9. INT378 Course Outcomes and Practical Alignment

The following mapping uses the official outcomes and practical topics in the INT378 course module. It separates what the repository configures from what remains outside the project or needs live demonstration evidence.

INT378 outcome	Relevant CloudNotes work	Coverage and limits
CO1: Recall cloud computing concepts/models and security	AWS VPC, EC2, S3, Terraform provisioning, container and Kubernetes architecture; security discussion in this report	Demonstrates selected AWS and cloud-native concepts. IAM users, groups, roles, MFA, and RBAC are not configured in the repository.
CO2: Analyze methods/tools for scalability in cloud solutions	Kubernetes Deployments and KEDA Prometheus scaler using API request rate	Configuration defines horizontal replica bounds. A sustained-load experiment and captured scaling evidence are still required for a demonstrated result.
CO3: Explain network security and authentication in cloud environments	VPC/security groups, Kubernetes Services/Ingress, and discussion of authentication gaps	Network controls exist but some AWS ingress is public. The app has no authentication or authorization, and no IAM/MFA implementation is included.
CO4: Evaluate cost optimization and cloud-native development	Containerized services, API separation, Terraform, billing alarm, and destroy workflow	Cloud-native deployment and basic cost awareness are present. Cost Explorer analysis, AWS Budgets, and measured optimization recommendations are not included.
CO5: Apply security practices in development and deployment	TruffleHog secret scan, Trivy image scan, Jenkins credential bindings, Kubernetes Secret template, health probes	Security checks are configured; Trivy is non-blocking, sample Kubernetes credentials are placeholders, and a managed secrets solution is absent.
CO6: Explore emerging cloud trends and governance	K3s/Kubernetes, KEDA metric-based scaling, Prometheus/Grafana observability	Demonstrates selected cloud-native practices. Formal compliance auditing, governance policy enforcement, serverless deployment, and CloudFormation comparison are outside scope.

The project covers several practical themes through Docker/Docker Hub, Terraform, Jenkins automation, DevSecOps scans, and Prometheus/Grafana. It does not implement IAM/MFA, CloudFormation, Node Exporter infrastructure monitoring, Lambda/serverless, or Cost Explorer/AWS Budgets analysis. Successful cloud provisioning, pipeline execution, and scaling should be supported by evidence from a current run.

10. Conclusion and Future Work

CloudNotes combines a working CRUD application with container packaging, declarative infrastructure, Kubernetes orchestration, Jenkins delivery automation, security scanning, and metrics-based operations. In the recorded AWS run, Jenkins build #2 successfully deployed the application, the frontend and API health endpoints returned HTTP 200 through the host-routed Ingress, and Terraform destroyed all 14 managed resources afterward. This is a verified demonstration run, not an always-on service or a production availability claim.

Recommended future work, aligned with INT378, includes IAM roles and MFA, application authentication and authorization, TLS and private network boundaries, CloudFormation comparison, managed secrets, Node Exporter and infrastructure dashboards, AWS Budgets/Cost Explorer analysis, a serverless extension, governance/compliance checks, database backups, a multi-node/multi-AZ cluster, blocking vulnerability policies, and repeatable load/scaling evidence.

References

Technical references: Docker; Kubernetes; Terraform AWS Provider; Jenkins; Prometheus; Grafana; KEDA.

Appendix A. Repository guide

Path	Contents
`app/backend/`	Flask API, SQLAlchemy model, requirements, Dockerfile, unit tests
`app/frontend/`	HTML, CSS, JavaScript, Nginx configuration, Dockerfile
`docker/`	Compose files, environment template, recovery script
`kubernetes/`	Namespace, app/database/monitoring resources, ingress, KEDA scaling
`terraform/`	AWS root module, VPC/EC2/S3 modules, outputs, billing alarm
`jenkins/`, `Jenkinsfile`	Jenkins image/configuration and pipeline
`monitoring/`	Local Prometheus config/alerts and Grafana provisioning/dashboard
`diagrams/`	Architecture, deployment, scaling, and sequence diagrams
`tests/e2e/`	Puppeteer end-to-end browser automation