

* Practical 13, 14, 15

* Default.aspx

```
<%@ Page Language = 'c#' AutoEventWireup = "true"
    CodeFile = "Default.aspx.cs" Inherits = "_Default" %>

<html>
  <head runat = "server">
    <title> CRUD WebApp </title>
  </head>
  <body>
    <form id = "form1" runat = "server">
      <div>
        <table style = "width: 100%;">
          <tr>
            <td colspan = "2"> Student Login Info </td>
            <td> &nbsp; </td>
          </tr>
          <tr>
            <td class = "auto-style1"> Enter Name </td>
            <td>
              <asp:TextBox ID = "TextBox1" runat =
                "server"> </asp:TextBox>
            </td>
            <td> &nbsp; </td>
          </tr>
          <tr>
            <td class = "auto-style1"> Enter Pass. </td>
            <td>
              <asp:TextBox ID = "TextBox2"
                runat = "server"> </asp:TextBox>
            </td>
          </tr>
        </table>
      </div>
    </form>
  </body>
</html>
```



```

</td>
<td>&nbsp;&nbsp;&nbsp;</td>
</tr>
<tr>
<td class = "auto-style1">&nbsp;&nbsp;&nbsp;</td>
<td>
<asp:Button ID="Button1" runat="server"
OnClick = "Button1_Click"
Text = "InsertData" />
<asp:Button ID = "Button2" runat="server"
OnClick = "Button2_Click"
Text = "Find Record" />
<asp:ButtonID = "Button3" runat = "server"
OnClick = "Button3_Click"
Text = "Update Record" />
<asp:ButtonID = "Button4" runat = "server"
OnClick = "Button4_Click"
Text = "Delete" />
</td>
<td>&nbsp;&nbsp;&nbsp;</td>
</tr>
</table>
</div>

<table style = "width:100%">
<tr>
<td>&nbsp;&nbsp;&nbsp;</td>
<td>&nbsp;&nbsp;&nbsp;</td>
<td>&nbsp;&nbsp;&nbsp;</td>
</tr>

```




```

<tr>
    <td> &nbsp; </td>
    <td> &nbsp; </td>
    <td> &nbsp; </td>
</tr>
<tr>
    <td colspan="3">
        <asp:GridView ID="GridView1"
            runat="server" >
        </asp:GridView>
    </td>
</tr>
</table>
</form>
</body>
</html>

```

* Default.aspx.cs

```

using System;
using System.Collections.Generic;
using System.Linq;
using System.Web;
using System.Web.UI;
using System.Web.UI.WebControls;
using System.Data.SqlClient;
using System.Configuration;
using System.Data;

```




```
public partial class _Default: System.Web.UI.Page {
    protected void Page_Load(object sender, EventArgs e)
    {
        protected void Button1_Click(object sender, EventArgs e)
        {
            SqlConnection conn = new
            SqlConnection(ConfigurationManager.ConnectionStrings
            ["ConnectionString"].ConnectionString);
            conn.Open();

            String Sql = "INSERT INTO [dbo].[info]
                           [Name], [Password]
                           VALUES (@Name, @pass)";
            SqlCommand cmd = new SqlCommand(Sql, conn);
            cmd.Parameters.AddWithValue
            C"@Name", TextBox1.Text);
            cmd.Parameters.AddWithValue
            C"@Pass", TextBox2.Text);
            cmd.ExecuteNonQuery();
            TextBox1.Text = "";
            TextBox2.Text = "";
            conn.Close();
            Response.Write C"<script> alert ('Data
                           Inserted Successfully');
                           </script>";
        }
        dataRetrive();
    }
}
```




```

void dataretrieve()
{
    SqlConnection conn = new
    SqlConnection (ConfigurationManager.ConnectionStrings
    ["ConnectionString"].ConnectionString);
    conn.Open();

    String sql = "select * from info";

    SqlDataAdapter da = new SqlDataAdapter(Csql,conn);
    DataTable dt = new DataTable();
    da.Fill (dt);
    GridView1.DataSource = dt;
    GridView2.DataBind ();
}

```

```

protected void Button2_Click (Object sender,
                                EventArgs e)
{
    SqlConnection conn = new
    SqlConnection(ConfigurationManager.ConnectionStrings
    ["ConnectionString"].ConnectionString);
    conn.open();
    String sql = "select * from info where Name
    = " + TextBox1.Text + " ";

    SqlDataAdapter da = new SqlDataAdapter(Csql,conn);
    DataTable dt = new DataTable();
    da.Fill (dt);
    GridView1.DataSource = dt;
    GridView1.DataBind();
}

```




```
protected void Button3_Click (Object sender,
                                EventArgs e)
{
    SqlConnection conn = new
    SqlConnection (ConfigurationManager.ConnectionStrings
    ["ConnectionString"].
    ConnectionString);
    conn.Open();
    String Sql = "update [dbo].[info] set
    [Password] = @pass where Id=@id";
    SqlCommand cmd = new SqlCommand (Sql, conn);
    cmd.Parameters.AddWithValue ("@id", TextBox1.Text);
    cmd.Parameters.AddWithValue ("@pass", TextBox2.Text);
    cmd.ExecuteNonQuery();
    TextBox1.Text = "";
    TextBox2.Text = "";

    conn.Close();
    Response.Write ("<script>alert ('Data update
    Successfully'); </script>");
    dataretrieve();
}
```

```
protected void Button4_Click (Object sender,
                                EventArgs e)
{
    SqlConnection conn = new
    SqlConnection (ConfigurationManager.
    ConnectionStrings["ConnectionString"].
    ConnectionString);
    conn.Open();
```




```
String Sql = "delete from [dbo].[info]  
              where Id = @id";  
SqlCommand cmd = new SqlCommand(Sql, conn);  
cmd.Parameters.AddWithValue("@id",  
                             TextBox1.Text);  
cmd.ExecuteNonQuery();  
TextBox1.Text = " ";  
TextBox2.Text = " ";  
  
conn.Close();  
Response.Write("<script>  
                alert('Data Deleted Successfully')  
                </script>");  
  
dataretrieve();  
}
```

}

* dbo.info

```
CREATE TABLE [dbo].[info] (  
    [Id] INT IDENTITY (1,1) NOT NULL,  
    [Name] VARCHAR (50) NULL,  
    [Password] VARCHAR (50) NULL,  
    PRIMARY KEY CLUSTERED ([Id] ASC)  
);
```