



jQuery - Add Elements

[< Previous](#)[Next >](#)

With jQuery, it is easy to add new elements/content.

Add New HTML Content

We will look at four jQuery methods that are used to add new content:

- `append()` - Inserts content at the end of the selected elements
- `prepend()` - Inserts content at the beginning of the selected elements
- `after()` - Inserts content after the selected elements
- `before()` - Inserts content before the selected elements

jQuery `append()` Method

The jQuery `append()` method inserts content AT THE END of the selected HTML elements.

Example

```
$("#p").append("Some appended text.");
```



jQuery prepend() Method

The jQuery `prepend()` method inserts content AT THE BEGINNING of the selected HTML elements.

Example

```
$("p").prepend("Some prepended text.");
```

[Try it Yourself »](#)

Add Several New Elements With `append()` and `prepend()`

In both examples above, we have only inserted some text/HTML at the beginning/end of the selected HTML elements.

However, both the `append()` and `prepend()` methods can take an infinite number of new elements as parameters. The new elements can be generated with text/HTML (like we have done in the examples above), with jQuery, or with JavaScript code and DOM elements.

In the following example, we create several new elements. The elements are created with text/HTML, jQuery, and JavaScript/DOM. Then we append the new elements to the text with the `append()` method (this would have worked for `prepend()` too) :

Example



```
var txt3 = document.createElement( "p" ); // Create with DOM  
txt3.innerHTML = "Text.";   
$( "body" ).append( txt1, txt2, txt3 ); // Append the new elements  
}
```

[Try it Yourself »](#)

jQuery after() and before() Methods

The jQuery `after()` method inserts content AFTER the selected HTML elements.

The jQuery `before()` method inserts content BEFORE the selected HTML elements.

Example

```
$( "img" ).after( "Some text after" );  
  
$( "img" ).before( "Some text before" );
```

[Try it Yourself »](#)

Add Several New Elements With after() and before()

Also, both the `after()` and `before()` methods can take an infinite number of new elements as parameters. The new elements can be generated with text/HTML (like we have done in the example above), with jQuery, or with JavaScript code and DOM elements.



Example

```
function afterText() {  
  var txt1 = "<b>I </b>";           // Create element with HTML  
  var txt2 = $("<i></i>").text("love "); // Create with jQuery  
  var txt3 = document.createElement("b"); // Create with DOM  
  txt3.innerHTML = "jQuery!";  
  $("img").after(txt1, txt2, txt3); // Insert new elements after  
<img>  
}
```

[Try it Yourself »](#)

jQuery Exercises

Test Yourself With Exercises

Exercise:

Use a jQuery method to **insert** the text "YES!" at the end of a <p> element.

```
$("p").append("YES!");
```

[Submit Answer »](#)

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#)

jQuery HTML Reference

For a complete overview of all jQuery HTML methods, please go to our [jQuery HTML/CSS Reference](#).

[< Previous](#)[Next >](#)

W3schools Pathfinder

Track your progress - it's free!

[Sign Up](#)[Log in](#)

Lifelong Access to
**All Current
& Future
Courses**

Our certifications are
recognised worldwide.

Original price: \$1,465
Discount price: \$695

[Get the deal](#)

COLOR PICKER

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#)[SPACES](#)[UPGRADE](#)[AD-FREE](#)[NEWSLETTER](#)[GET CERTIFIED](#)[CONTACT US](#)

Top Tutorials

- [HTML Tutorial](#)
- [CSS Tutorial](#)
- [JavaScript Tutorial](#)
- [How To Tutorial](#)
- [SQL Tutorial](#)
- [Python Tutorial](#)
- [W3.CSS Tutorial](#)
- [Bootstrap Tutorial](#)
- [PHP Tutorial](#)
- [Java Tutorial](#)
- [C++ Tutorial](#)
- [jQuery Tutorial](#)

Top Examples

- [HTML Examples](#)
- [CSS Examples](#)
- [JavaScript Examples](#)
- [How To Examples](#)
- [SQL Examples](#)
- [Python Examples](#)
- [W3.CSS Examples](#)
- [Bootstrap Examples](#)
- [PHP Examples](#)
- [Java Examples](#)
- [XML Examples](#)
- [jQuery Examples](#)

Top References

- [HTML Reference](#)
- [CSS Reference](#)
- [JavaScript Reference](#)
- [SQL Reference](#)
- [Python Reference](#)
- [W3.CSS Reference](#)
- [Bootstrap Reference](#)
- [PHP Reference](#)
- [HTML Colors](#)
- [Java Reference](#)
- [Angular Reference](#)
- [jQuery Reference](#)

Get Certified

- [HTML Certificate](#)
- [CSS Certificate](#)
- [JavaScript Certificate](#)
- [Front End Certificate](#)
- [SQL Certificate](#)
- [Python Certificate](#)
- [PHP Certificate](#)
- [jQuery Certificate](#)
- [Java Certificate](#)
- [C++ Certificate](#)
- [C# Certificate](#)
- [XML Certificate](#)

[Tutorials](#) ▼[Exercises](#) ▼[Services](#) ▼[Sign Up](#)[Log in](#)[CSS](#)[JAVASCRIPT](#)[SQL](#)[PYTHON](#)[JAVA](#)[PHP](#)[HOW TO](#)[W3.CSS](#)[C](#)[FORUM](#) [ABOUT](#) [CLASSROOM](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning.

Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness

of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#).

[Copyright 1999-2024](#) by Refsnes Data. All Rights Reserved. [W3Schools is Powered by W3.CSS](#).