



jQuery - Set Content and Attributes

[< Previous](#)[Next >](#)

Set Content - text(), html(), and val()

We will use the same three methods from the previous page to **set content**:

- `text()` - Sets or returns the text content of selected elements
- `html()` - Sets or returns the content of selected elements (including HTML markup)
- `val()` - Sets or returns the value of form fields

The following example demonstrates how to set content with the jQuery `text()`, `html()`, and `val()` methods:

Example

```
$("#btn1").click(function(){
    $("#test1").text("Hello world!");
});
$("#btn2").click(function(){
    $("#test2").html("<b>Hello world!</b>");
});
$("#btn3").click(function(){
    $("#test3").val("Dolly Duck");
});
```



A Callback Function for text(), html(), and val()

All of the three jQuery methods above: `text()`, `html()`, and `val()`, also come with a callback function. The callback function has two parameters: the index of the current element in the list of elements selected and the original (old) value. You then return the string you wish to use as the new value from the function.

The following example demonstrates `text()` and `html()` with a callback function:

Example

```
$("#btn1").click(function(){
  $("#test1").text(function(i, origText){
    return "Old text: " + origText + " New text: Hello world!
    (index: " + i + ")";
  });
});

$("#btn2").click(function(){
  $("#test2").html(function(i, origText){
    return "Old html: " + origText + " New html: Hello <b>world!</b>
    (index: " + i + ")";
  });
});
```

[Try it Yourself »](#)

ADVERTISEMENT



Set Attributes - attr()

The jQuery `attr()` method is also used to set/change attribute values.

The following example demonstrates how to change (set) the value of the href attribute in a link:

Example

```
$("#button").click(function(){  
    $("#w3s").attr("href", "https://www.w3schools.com/jquery/");  
});
```

Try it Yourself »

The `attr()` method also allows you to set multiple attributes at the same time.

The following example demonstrates how to set both the href and title attributes at the same time:

Example

```
$("#button").click(function(){  
    $("#w3s").attr({  
        "href" : "https://www.w3schools.com/jquery/",
```

[Try it Yourself »](#)

A Callback Function for attr()

The jQuery method `attr()`, also comes with a callback function. The callback function has two parameters: the index of the current element in the list of elements selected and the original (old) attribute value. You then return the string you wish to use as the new attribute value from the function.

The following example demonstrates `attr()` with a callback function:

Example

```
$("#button").click(function(){  
  $("#w3s").attr("href", function(i, origValue){  
    return origValue + "/jquery/";  
  });  
});
```

[Try it Yourself »](#)

jQuery Exercises

Test Yourself With Exercises

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[≡](#) [CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#)

Use a jQuery method to **change** the text of a <div> element to "Hello World".

```
$("#div").      ("      ");
```

[Submit Answer »](#)[Start the Exercise](#)

jQuery HTML Reference

For a complete overview of all jQuery HTML methods, please go to our [jQuery HTML/CSS Reference](#).

[◀ Previous](#)[Next ▶](#)

W3schools Pathfinder

Track your progress - it's free!

[Sign Up](#)[Log in](#)

ADVERTISEMENT

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#)

Lifelong Access to
**All Current
& Future
Courses**

Our certifications are
recognised worldwide.

Original price: \$1,465
Discount price: \$695

[Get the deal](#)



Tutorials ▼

Exercises ▼

Services ▼



Sign Up

Log in



CSS

JAVASCRIPT

SQL

PYTHON

JAVA

PHP

HOW TO

W3.CSS

C



ADVERTISEMENT

ADVERTISEMENT

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[CSS](#)[JAVASCRIPT](#)[SQL](#)[PYTHON](#)[JAVA](#)[PHP](#)[HOW TO](#)[W3.CSS](#)[C](#)

ADVERTISEMENT

[SPACES](#)[UPGRADE](#)[AD-FREE](#)[NEWSLETTER](#)[GET CERTIFIED](#)[CONTACT US](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Get Certified

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[Front End Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[PHP Certificate](#)
[jQuery Certificate](#)

[Tutorials](#) ▼[Exercises](#) ▼[Services](#) ▼[Sign Up](#)[Log in](#)[CSS](#)[JAVASCRIPT](#)[SQL](#)[PYTHON](#)[JAVA](#)[PHP](#)[HOW TO](#)[W3.CSS](#)[C](#)[FORUM](#) [ABOUT](#) [CLASSROOM](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#).

Copyright 1999-2024 by Refsnes Data. All Rights Reserved. [W3Schools is Powered by W3.CSS](#).