edsmsm (WKND Replica) - Developer Guide

AEM Edge Delivery Services technical handover

Date: October 19, 2026

Adobe

Table of Contents

edsmsm (WKND Replica) - Developer Guide 3
Quick Reference 3
Architecture Overview 3
scripts/scripts.js Customizations 6
Local Development Setup 6
Design System 7
Blocks Reference 9
Migration Record: the `stardust/` folder 11
Known Risks and Open Items 12
Common Development Tasks 13
Environments 14
Git Workflow 14
Troubleshooting 14
Resources 15
Support Contacts 15

edsmsm (WKND Replica) - Developer Guide

This guide is for developers taking over the `edsmsm` AEM Edge Delivery Services project, a same-design re-platform of the WKND reference site (wknd.site). It covers how the code is organized, what was customized, the design system, every project block, and the risks that are still open.

Quick Reference

Resource	URL / Value
Code repository	GitHub `savitaagre/edsmsm` (default branch `main`)
Config Service org	`savitaagre`
Content source	Document Authoring (DA): `https://content.da.live/savitaagre/edsmsm`
Preview	https://main--edsmsm--savitaagre.aem.page/us/en
Live	https://main--edsmsm--savitaagre.aem.live/us/en
Feature branch preview	`https://{branch}--edsmsm--savitaagre.aem.page/{path}`
Local dev	http://localhost:3000/us/en
Last merged work	PR #1, WKND home replica (merge commit `71d7e86`)

Note: the home page is `/us/en`, matching the source URL `/us/en.html`. The root path `/` returns 404 because no root document exists.

Sites in the `savitaagre` Config Service org

The site list comes from `https://admin.hlx.page/config/savitaagre/sites.json`.

Site	Code	Content	Notes
`edsmsm`	`savitaagre/edsmsm` (this repo)	`content.da.live/savitaagre/edsmsm`	The site this guide documents
`ema`	`savitaagre/ema` (its own repo)	`content.da.live/savitaagre/ema`	MSM satellite (configured, not switched)
`savisite`	`savitaagre/savisite` (its own repo)	`content.da.live/savitaagre/savisite/`	MSM satellite (configured, not switched)

This is not a repoless or shared-code setup. Each site has its own GitHub repository and runs its own code, so a change merged here does not reach `ema` or `savisite`. Run `aem up` without `--pages-url`.

Architecture Overview

Tech Stack

- Vanilla JavaScript (ES modules), no framework
- CSS3 with custom properties, no preprocessor

- No build step: files are served exactly as committed. `package.json` has devDependencies only (ESLint, Stylelint).
- Content is authored in Document Authoring (DA) and edited visually in Experience Workspace
- Configuration lives in the Config Service (tools.aem.live / admin.hlx.page). The repo still contains a legacy `helix-query.yaml` and `helix-sitemap.yaml`, but those files are retired and no longer drive configuration (see Known Risks).

Project Structure

```
├── blocks/              # 27 block folders (22 customized, 4 new for the replica)
├── scripts/
│   ├── aem.js           # Core library (vendored, DO NOT MODIFY)
│   ├── scripts.js       # Page decoration + E-L-D orchestration (customized)
│   ├── magazine-sidebar.js  # Lazy two-column layout for magazine articles
│   ├── social-icons.js  # Shared label -> SVG icon helper
│   ├── consent-check.js # Delayed: dummy consent gate (boilerplate)
│   └── consented.js     # Placeholder for consented martech (empty)
├── styles/
│   ├── styles.css       # Critical global CSS, fallback faces, section scaffold
│   ├── brand.css        # Design tokens (imported by styles.css)
│   ├── fonts.css        # Self-hosted @font-face (loaded lazily)
│   └── lazy-styles.css  # Unchanged boilerplate (empty)
├── fonts/               # Asar, Source Sans Pro, wknd-icon-font (+ unused Roboto)
├── icons/               # search.svg, flags/*.svg (7 country flags)
├── head.html            # CSP, viewport, aem.js/scripts.js, styles.css, favicon
├── favicon.png          # WKND favicon (favicon.ico kept)
├── tools/importer/      # Import scripts/parsers/transformers used for the migration
├── catalog/             # Site-scope catalog JSON from the migration analysis
└── stardust/            # Migration record (excluded from serving, see below)
```

There are no `templates/` or `models/` folders. The landing page sets `Template: landing` in its metadata, which adds a body class through `decorateTemplateAndTheme()`, but there is no template JavaScript.

Three-Phase Loading (E-L-D)

Phase	Purpose	What loads in this project	Performance impact
Eager	Reach LCP fast	`styles.css` (+ `brand.css`), `decorateMain()`, first section (the `hero-carousel` on `/us/en`, whose first slide image is `loading=eager` + `fetchpriority=high`). `fonts.css` also loads here, but only at a width of 900px or more or when the session flag `fonts-loaded` is set.	Blocks LCP, so keep it minimal
Lazy	Everything else visible	Header (`/nav` fragment), remaining sections, `magazine-sidebar.js` (dynamic import, does nothing on non-article pages), footer (`/footer` fragment), `lazy-styles.css`, `fonts.css`	Runs after first paint
Delayed	Third-party code	`consent-check.js`, which loads `consented.js` only when `?consent=accept` is in the URL. There is no `delayed.js` in this project.	Never blocks rendering

Rules for developers:

- Never add third-party scripts to `scripts.js`. Put them in `consented.js` (behind the consent gate) or a new delayed module imported from `loadDelayed()`.
- Fonts never block first paint. The metric-matched `-fallback` faces in `styles.css` keep layout stable until `fonts.css` lands.

- The fixed header reserves no space itself. `main { padding-top: var(--nav-height) }` holds the space, so the late header load causes no layout shift. Keep it this way.

Key Files and How They Connect

File	Role	Connects to
`scripts/aem.js`	Vendored core: `buildBlock`, `createOptimizedPicture`, `decorateBlock(s)`, `decorateIcons`, `decorateSections`, `decorateTemplateAndTheme`, `getMetadata`, `loadBlock`, `loadCSS`, `loadHeader/loadFooter`, `loadScript`, `loadSection(s)`, `readBlockConfig`, `sampleRUM`, `toClassName`, `waitForFirstImage`, `wrapTextNodes`. **Never edit.** It does **not** process `section-metadata`.	Imported by `scripts.js` and blocks
`scripts/scripts.js`	Entry point; `decorateMain()`, auto blocks, buttons, section metadata, E-L-D	`aem.js`, `fragment.js` (dynamic), `magazine-sidebar.js`, `consent-check.js`
`blocks/fragment/fragment.js`	`loadFragment()`, the **only** allowed cross-block import	Used by header, footer, and fragment auto blocks
`scripts/social-icons.js`	`networkFromLabel()`, `SOCIAL_ICON_SVGS`: picks an icon from the link **label**, never the href	`contributors`, `social-links`
`scripts/magazine-sidebar.js`	Builds the two-column magazine-article layout and a related-articles list from `/query-index.json`. Publish dates are hard-coded per slug.	Called from `loadLazy()`
`styles/styles.css`	`@import 'brand.css'`, fallback faces, global type, buttons, section scaffold, section styles	All blocks
`head.html`	CSP (`nonce-aem`, `strict-dynamic`, trusted types), module scripts, `styles.css`, `<link rel="icon" href="/favicon.png">`	Every page

Execution flow: `scripts.js` → `loadEager()` (`decorateMain` → first section) → `loadLazy()` (header, sections, magazine sidebar, footer, lazy CSS, fonts) → `loadDelayed()` (consent check).

scripts/scripts.js Customizations

`decorateMain(main)` runs in this order. The order matters:

1. **`restoreImageTitles(main)`**: the delivery pipeline emits an authored image title as `data-title`. This copies it back to `img.title` and removes `data-title`.
2. `decorateIcons(main)`
3. **`buildAutoBlocks(main)`**: links containing `/fragments/` become inline fragments. `buildWidgetAutoBlocks` turns links containing `/widgets/` into `widget` blocks. This rewrites content **before** any block runs.
4. `decorateSections(main)`
5. **`applySectionMetadata(main)`** (project-owned, because the vendored `aem.js` does not handle section metadata): it reads each `section-metadata` block's `style` row, adds the comma-separated values as classes on the section (spaces become `-`, lowercased), removes the metadata block and its wrapper, and drops empty section children. It runs after `decorateSections` and before `decorateBlocks`, so the metadata table never becomes a block (which would also 404).
6. `decorateBlocks(main)`
7. **`decorateButtons(main)`** works in **bare-links-too** mode (see `stardust/runtime-contract.json`):
   - Any `<p>` whose only content is a single link becomes `p.button-wrapper > a.button.primary`. No `<strong>` or `<em>` is needed.
   - `<strong>` gives `primary`, `<em>` gives `secondary`, and both give `accent`.
   - It skips links inside `.breadcrumbs`, links that contain an `<img>`, and links whose text is their own URL.
   - **Aria-label promotion:** DA has no aria-label field. If an authored link `title` differs from the link text, it becomes `aria-label` and the `title` is removed. Otherwise `title` defaults to the link text.

Consequences for block authors: blocks that hold solo-link paragraphs which are *not* CTAs (card titles, chrome links) must undo the classes and the derived title themselves. `header`, `footer` and `image-list` each have an `unbutton`-style step. Header and footer fragments are decorated by `decorateMain` as well, so they get buttonized too.

Other behaviour: `document.documentElement.lang` is hard-coded to `en`, and a Trusted Types `default` policy strips `srcdoc` iframes and scripts from contextual fragments.

Local Development Setup

Prerequisites

- Node.js: there is no `.nvmrc` or `engines` field. CI (`.github/workflows`) uses **Node 24** (the step is mislabelled "Use Node.js 20"). Use Node 20 or later locally.
- AEM CLI: `npm install -g @adobe/aem-cli`, or use `npx -y @adobe/aem-cli up`

Setup Steps

```
git clone https://github.com/savitaagre/edsmsm.git
cd edsmsm
npm ci            # devDependencies only (lint tooling)
npx -y @adobe/aem-cli up
# open http://localhost:3000/us/en
```

The local server serves **local code** with **previewed content** from `main--edsmsm--savitaagre.aem.page`. A page must be previewed in DA before it renders locally. Before writing a block, look at the real backend markup: `curl http://localhost:3000/us/en.plain.html`.

Linting

```
npm run lint       # eslint (airbnb-base) + stylelint (stylelint-config-standard)
npm run lint:fix
```

Current state: lint passes with 0 errors. There is 1 ESLint warning (`no-console`) in `stardust/scripts/deploy/sanitise.js`. CI runs `npm ci && npm run lint` on every push.

Design System

All tokens are in `styles/brand.css`. They were extracted from wknd.site computed styles and the gated replica prototype. **Every pre-existing custom property was kept**, so older blocks and the 16 adventure and 5 magazine documents still resolve their tokens. New tokens were added alongside them.

Pre-existing tokens (kept)

```
--heading-font-family: asar, asar-fallback, georgia, "Times New Roman", times, serif;
--body-font-family: "Source Sans Pro", source-sans-pro-fallback, "Helvetica Neue",
helvetica, arial, sans-serif;
--background-color: #fff;   --text-color: #202020;   --dark-color: #202020;
--link-color: #0045ff;      --link-hover-color: #0035cc;
--accent-color: #ffea00;    --light-color: #f7f7f7;
--heading-font-size-xxl: 40px; /* h1 */  --heading-font-size-xl: 36px; /* h2 */
--heading-font-size-l: 24px;   /* h3 */  --heading-font-size-m: 16px;  /* h4 */
--heading-font-size-s: 14px;   /* h5 */  --heading-font-size-xs: 10px; /* h6 */
--body-font-size-m: 18px;  --body-font-size-s: 16px;  --body-font-size-xs: 14px;
```

Heading sizes are the same at every breakpoint, as on wknd.site.

Replica tokens (new)

```
--text: #202020;           --text-inverse: #ebebeb;   --text-muted: dimgray;
--link: #0045ff;           --brand-yellow: #ffea00;
--surface-grey: #ebebeb;   --surface-light: #f7f7f7;  --body-bg: #fff;
--font-sans: var(--body-font-family);  --font-serif: var(--heading-font-family);
--font-icon: wknd-icon-font;
--fs-small: 14px;          --fs-xsmall: 12px;
--button-size: 48px;       --utility-height: 25px;
--shell: 1164px;           /* content column at >= 1025px */
--gutter: 14px;            /* section wrapper side padding */
--max-width: 1680px;       /* page root cap for main + footer */
--nav-height: 200px;       /* >= 1025px; 130px at <= 1024px */
```

Two inline properties are set at runtime by `header.js` and are intentionally not declared: `--lang-flag` (falls back to the US flag) and `--flag` (one per country).

Global rules worth knowing

- **Body copy:** `p` is 18px with line-height 2.5, justified, with a 13.5px bottom margin. h1 to h3 use Asar 400. h4 to h6 use Source Sans Pro 600 uppercase.
- **Links:** `#0045ff`, with **no global hover** (wknd.site has none).
- **Images:** `img { display: block }` globally. Blocks whose geometry depends on inline images (header/footer logos, `hero-carousel`, `hero-teaser`, `featured-teaser`, `image-list`) set `display: inline` locally.

- **Buttons:** `a.button` is the WKND primary: flat `#ffea00`, 48px tall, `16px 32px` padding, label 14px/21px, 600 weight, uppercase, square corners, no hover. `.secondary` is a 2px inset outline. `.prosemirror-editor` rules repaint CTAs inside Experience Workspace edit mode.
- **Section title underline:** an h1 or h2 inside `.default-content-wrapper` gets an 84px yellow rule 8px below it (`::after`). Its descendant selectors keep it working in Experience Workspace.
- **Page shell:** `body > header` is `position: fixed` (z-index 1030). `main` and `body > footer` are capped at `--max-width`. The footer is `#202020` with a 48px top margin.

Section scaffold

- `main > .section { margin: 0 }`. Sections stack flush, and blocks own their own spacing.
- `main > .section > div` has `padding: 0 var(--gutter)` and `max-width: var(--shell)` at 1025px and up.
- **Full-bleed escape:** `.hero-carousel-wrapper` and `.hero-teaser-wrapper` get `max-width: none; padding: 0`.

Section styles (via section metadata `style`)

Class	Effect
`light`, `highlight`	`#f7f7f7` background, 40px vertical padding
`light-grey`	40px vertical padding (the grey is scoped inside `columns-featured`)
`faq`	Two-column grid (2fr / 1fr) at 900px and up, max-width 1136px: default content + accordion on the left, `faq-sidebar` on the right
`separator`	`main > .section.separator`: 64px vertical padding plus a 1px `--surface-grey` rule inside the shell. Author it as an empty section with `style: separator`, not with an authored `<hr>`

Breakpoints

The replica code follows wknd.site, not the boilerplate's 600/900/1200 scale:

Breakpoint	Usage
`width <= 1024px` / `width >= 1025px`	**Primary split**: header and mobile nav (`body.navPanel-visible`, a 275px slide), `--nav-height` 130/200px, the 1164px shell
`width >= 1165px`	Hero image with an overlapping white card (`hero-carousel`, `hero-teaser`)
`width >= 1201px`, `1025px to 1200px`	Header fine-tuning
`width <= 767px`	`featured-teaser` stacks, and other replica stacking
`width >= 900px`	Older blocks, the `.section.faq` grid, eager font loading in `scripts.js`
`width >= 600px` / `< 600px`, `<= 475px`	Older blocks (cards, filters, members-only)

Fonts

Fonts are self-hosted from `/fonts/` and declared in `styles/fonts.css`, which loads lazily. There are no third-party font requests.

Family	Weights / styles	File	Usage
Asar	400	`asar-400.woff2`	h1 to h3
Source Sans Pro	300, 400, 600 (normal + italic)	`source-sans-pro-*.woff2`	Body, h4 to h6, buttons
wknd-icon-font	400 (`font-display: block`)	`wknd-icon-font.ttf`	Header search/ menu/social glyphs, carousel arrows

The **metric-matched fallbacks** are declared in `styles.css` and are available at first paint:

- `source-sans-pro-fallback`: `local(Arial)`, size-adjust 94.16%, ascent 104.51%, descent 28.99%
- `asar-fallback`: `local(Times New Roman)`, 105.13%, 113.76%, 52.98%

Both are limited to the Latin unicode-range, so glyphs outside the subset (for example the footer's "©") fall through to the system stack, as on the live site.

The `roboto-*.woff2` files in `fonts/` are leftovers that nothing references. They are harmless, and you can delete them in a cleanup PR. They are listed in `stardust/rollout/foundation-freeze.json`, so re-freeze after deleting.

Blocks Reference

Every block follows the Experience Workspace editability rule. Blocks **move** authored nodes into generated wrappers and never rebuild or copy text, so inline editing keeps working. When a block needs a presentational copy, its JSDoc documents it with an `@ew-exempt` tag. Decorate defensively, because authors add and omit cells.

New blocks (WKND home replica, PR #1)

Block	Purpose	Authoring model	Key details
`hero-carousel`	Home hero: full-bleed teaser slides with a white card overlapping at 1165px and up	One row per slide: image | text (h1 or h2 title, description , CTA <a>)	Prev/next/indicator click with a 0.5s `fadeIn`. **No autoplay** (it is dead on live). State classes match the live site: `cmp-carousel__item--active` and `cmp-carousel__indicator--active`. Controls are generated with an aria-label only. Indicators carry a hidden copy of each slide title (`@ew-exempt`). The first slide image loads eagerly with high fetch priority. A flattened single cell is split at heading boundaries. Slide 1's title is the page's single <h1> (register R-01). Full-bleed.
`featured-teaser`	"Featured Article" band: grey 1/3 text column beside a 2/3 image (row-reverse), stacked at 767px and below	One row: image | text (pretitle , h2, description, CTA)	Template-slotted: the block creates empty slots (`.content > .pretitle/.title/.description/.actions`, `.image > .frame`) and moves nodes in by role. Link-free text before the heading becomes the pretitle; text after it becomes the description. The CTA is repainted as the source `.btn-teaser`.
`image-list`	4-up list of 260px cards ("Recent Articles", "Where do you want to go?")	One row per card: image | text (<a>Title , description)	Output: `ul.items > li.item > article > a.image-link` (a generated, text-free link to the title's href) + `.title` + `.description` (260px,

Block	Purpose	Authoring model	Key details
			nowrap, ellipsis). Removes the `decorateButtons` classes from title links, because a card link is not a CTA.
`hero-teaser`	Full-bleed image anchored at the bottom, with an overlapping white card at 1165px and up ("Climbing New Zealand")	One row: image | text (h2, description, CTA)	Template-slotted (`.content > .title/.description/.actions`, `.media`). Unclassified nodes land in `.description`. Full-bleed.

The schema contract for all four is in `stardust/eds-schema/us-en-html.json`.

Rebuilt chrome blocks

Block	Purpose	Document contract	Key details
`header`	Fixed WKND header loaded from the `/nav` fragment (path overridable via `nav` metadata)	5 sections by index: **0** account (greeting [hidden], Sign In, Sign Out [hidden]); **1** language (`en-US` toggle + country `<ul>` with nested locale links); **2** brand logo; **3** nav (`<ul><li>Home<ul>…</ul></li></ul>`, Home hidden); **4** tools (search link, icon-only, label kept for accessibility)	`body.scrolly` while `scrollY > 15` (the header shrinks, about 193.6 to 113.6px). Language menu: `left = toggle.position().left - 240`, toggles `showMenu/open`, closes on any outside click. At 1024px and below: slide-in panel via `body.navPanel-visible` (main and footer translate 275px, 0.5s). The closed panel is `visibility: hidden`, Escape closes it, and reduced motion drops the transitions. The mobile list is a stripped clone of the nav list (`@ew-exempt`). Undoes buttonization, and drops the webp `<source>` so SVG logos render as vectors. Flags come from `/icons/flags/*.svg`.
`footer`	WKND footer loaded from the `/footer` fragment	4 sections: **0** light logo; **1** nav (Home hidden + 4 links); **2** social (`<h4>Follow Us</h4>` + icon-only links whose `title` is the accessible name); **3** legal paragraphs. Extra content goes to the legal slot.	Template-slotted. Undoes buttonization, keeps SVG logos as vectors, nav links underline on hover. Header and footer both have a `README.md` and a `metadata.json`.

Interim chrome decisions (owner input needed):

- **D1:** Sign In and Sign Out link to `#sign-in` and `#sign-out`, with no backend.
- **D3:** Language-menu locale links keep the source paths (`/us/es.html`, `/ca/en.html` and so on). They 404 until those locale trees are migrated.

Pre-existing customized blocks (earlier template migrations)

Block	Purpose	Notes
`accordion`	FAQ accordion (block-collection pattern)	Used inside the `.section.faq` grid
`faq-sidebar`	"Need more help?" contact box	Demotes the heading to a styled `<p>` (heading order). Placement comes from `.section.faq`.

Block	Purpose	Notes
`adventure-cards`	Index-driven adventure rail ("All Trips")	Fetches `/query-index.json` and filters `/us/en/adventures/`. An optional first-cell number sets how many cards display (default 4).
`adventures-filter`	"Current Adventures" grid + category tabs	Builds its tabs from the index's comma-separated `category`, with a slug fallback
`magazine-cards`	Index-driven magazine rail	Fetches `/query-index.json` and filters `/us/en/magazine/`
`category-filter`	Static filter bar + card grid	Row 0 holds the filter labels; the other rows are image | content cards
`adventure-meta`	Label/value facts grid (Activity, Trip Length, Price…)	One row per pair, with a left accent border per item
`breadcrumbs`	Breadcrumb trail	Strips `.html` from internal hrefs. Skipped by `decorateButtons`. Separators are yellow arrow tips.
`carousel`	Adventure image galleries (16 adventure pages)	The reason the home hero got its own name, `hero-carousel`. Image-only gallery slides are 400px tall.
`cards`	Boilerplate cards with WKND styling	Not used by current content
`columns-featured`	Older homepage Featured Article promo (forked columns)	Superseded on `/us/en` by `featured-teaser`. Grey is scoped to the text column.
`hero`	CSS-only hero (`hero.js` is empty)	Used by the adventures listing. Not used on `/us/en`.
`contributors`	"Our Contributors" person cards	Social icons come from the label via `social-icons.js`
`members-only`	Locked magazine teasers with a corner lock badge	360px cards, gated content shown at 65% opacity
`quote`	Article pull quote	Pins its own line-height so the article's 2.5 doesn't leak in
`social-links`	Article share buttons	Icons from the label (hrefs are # placeholders)
`tabs`	Tabbed panels (adventure details)	List bullets are filled arrow tips
`writer-details`	Magazine author byline (avatar, h2 name, occupation)	Rows are matched by content, so a missing avatar degrades cleanly

Unchanged boilerplate (not documented further): `columns`, `fragment`, `widget`, `scripts/aem.js`, `consent-check.js`, `consented.js`, `lazy-styles.css`.

Migration Record: the `stardust/` folder

`stardust/` is committed but **not served**: `.hlxignore` excludes `stardust/`, `*.md`, dotfiles and `DESIGN.json`. It is the audit trail for the replica:

Path	Contents
`stardust/eds-conversion-log.md`	Step-by-step conversion log: naming and reuse decisions, foundation, fonts, chrome, blocks, gates, publish. **Read this first.**
`stardust/journal.md`	Chronological working journal
`stardust/prototypes/`	Gated replica prototype (`us-en-html.css/js`, assets) that the global rules were lifted from
`stardust/replica/progress.json`	Gate evidence summaries and the motion ledger
`stardust/replica/gates/`, `motion/`, `inconsistency-register.md`	Pixel/structure gate outputs, motion probes, and the register of allowed design deltas (R-01 only)
`stardust/runtime-contract.json`	The runtime contract blocks rely on (bare-links-too buttons, section metadata, fragment policy)
`stardust/eds-schema/`	Per-section schema of the landing archetype
`stardust/rollout/foundation-freeze.json`	SHA-256 freeze of `styles/`, `fonts/`, `scripts/`, `head.html`, `blocks/header/`, `blocks/footer/`
`stardust/plugin-improvement-notes.md`	Tooling notes
`stardust/deploy/content/`	Source HTML of the DA documents (`us/en.html`, `nav.html`, `footer.html`)

Fidelity versus live wknd.site (published-origin gate, final round): **1440px: 0.25% pixel diff, height delta 0. 360px: 1.73% pixel diff, height delta –1.** Header crops match 100.00% / 99.86%, motion matches 10/10 at desktop and 3/3 on mobile, and there are 0 structural defects. The remaining differences are image-rendition texture.

Publish state: `/us/en`, `/nav` and `/footer` were published live on the owner's request (commit `1ecdf2b`). A C-final line in the log still says "preview-only"; the later commit supersedes it. No other documents have been previewed on this code.

If you change the foundation: run the freeze check against `foundation-freeze.json` before and after, and re-freeze in the same PR.

Known Risks and Open Items

1. **The new foundation also affects the other 21 documents.** The new section scaffold (flush sections, 14px gutters, 1164px shell), the global `img { display: block }`, the 18px/2.5 justified `p`, the removed link hover, and the new header and footer apply to the **16 adventure and 5 magazine DA documents** too. Those were built on the old scaffold (40px section margins, 24 to 32px padding, 1680px wrappers) and **have not been previewed on this code**. `/us/en/adventures` and `/us/en/magazine` currently return 404 on main. Preview each one, compare it with wknd.site at 1440 and 360, and fix its spacing before publishing.
2. **The query index does not exist yet.** `adventure-cards`, `adventures-filter`, `magazine-cards` and `magazine-sidebar.js` all fetch `/query-index.json`, which returns 404 on main. `helix-query.yaml` in the repo is retired, so the index has to be defined in the Config Service (tools.aem.live) and the source pages previewed. Until then those rails render empty.
3. **MSM satellites are not live and do not share code.** `ema` and `savisite` are configured in the org's msm tab but **not switched to the MSM content provider**. Previewing through it without a signed-in author returned 401, so the switch was reverted. They also run their own repos (`savitaagre/ema`, `savitaagre/savisite`), so inherited `edsmsm` pages would lack `hero-carousel`, `featured-teaser`, `image-list`, `hero-teaser` and the rebuilt header/footer unless the code is shared (copy the blocks, or move the satellites to this repo as repoless sites).

4. **Some docs point at the old site.** `README.md`, `.github/pull_request_template.md` and the PR-link rule in `AGENTS.md` reference `edscapstoneajay--ajayajju2412`. The correct pattern is `https://{branch}--edsmsm--savitaagre.aem.page/{path}`. Fix these in a docs PR.
5. **Interim chrome links:** D1 (Sign In/Out have no backend) and D3 (locale links 404) are waiting on owner decisions.
6. **Non-code folders are served:** `tools/importer/`, `catalog/` and `images/` are committed and served because `.hlxignore` does not exclude them. Add them to `.hlxignore` if they should stay private.
7. **Residual content detail:** the Climbing NZ image title is not delivered, because the pipeline drops a title that equals the alt text.

Common Development Tasks

Add a New Block

1. Look at the delivered markup first: `curl localhost:3000/{path}.plain.html`. Remember that `buildAutoBlocks` and `decorateButtons` have already changed it.
2. Create `blocks/{name}/{name}.js` (`export default function decorate(block)`) and `{name}.css`, with every rule scoped under `.{name}`. The `-wrapper` and `-container` classes belong to sections.
3. Move authored nodes; never copy their text. Document any presentational copy with `@ew-exempt` in the JSDoc.
4. Handle missing and extra cells. If the block holds solo-link paragraphs that are not CTAs, undo the button classes.
5. Import only from `/scripts/` (and `fragment/fragment.js`). Never edit `scripts/aem.js`.
6. Run `npm run lint`, push a feature branch, and put the branch preview link in the PR.

Modify Global Styles

1. Add tokens to `styles/brand.css`. Never remove or rename an existing one, because other documents depend on them.
2. Global rules go in `styles/styles.css`. Re-check `/us/en` at 1440 and 360, plus a sample adventure and magazine page.
3. Watch for CLS: keep the header reservation on `main` and keep fonts lazy.
4. Update `foundation-freeze.json`.

Add a Section Style

Add `main .section.{name}` (or `main > .section.{name}`) in `styles.css`. Authors then set `style: {name}` in section metadata, and `applySectionMetadata()` adds the class.

Add Analytics or Marketing Tools

Put them in `scripts/consented.js`, which loads only after consent, or in a delayed import from `loadDelayed()`. Never add them to `scripts.js` or `head.html`. The CSP in `head.html` uses `strict-dynamic` with nonce `aem`, so scripts must be loaded by an already-trusted module.

Debug a Block

1. Check the console and the `data-block-status` attribute.
2. Compare the `.plain.html` input with the decorated DOM, looking for missing cells or unexpected `.button` classes.
3. Check whether section metadata classes landed on the section.

4. Check whether the wrapper is fighting the scaffold's `max-width` or `padding` (full-bleed blocks need the escape rule).

Environments

Environment	URL pattern	Purpose
Local	http://localhost:3000	Development (local code, pre-viewed content)
Feature branch	`https://{branch}--edsmsm--savitaagre.aem.page/{path}`	PR testing (required in every PR)
Preview	https://main–edsmsm–savitaagre.aem.page	Staging
Live	https://main–edsmsm–savitaagre.aem.live	Production

Merging to `main` ships code immediately (AEM Code Sync). Content is previewed and published separately from DA.

Git Workflow

- **Branches:** `feat/…` and `fix/…` (for example `feat/wknd-home-replica`). Keep names short, because the host label `{branch}--edsmsm--savitaagre` must be 63 characters or fewer.
- **Commits:** Conventional Commits (`feat(scope):`, `fix(scope):`, `docs(stardust):`, `chore:`).
- **PR requirements:**
  1. A `{branch}--edsmsm--savitaagre.aem.page/{path}` link (PRs without one are rejected)
  2. `npm run lint` passes (it is enforced by CI)
  3. Tested on the branch preview at 1440 and 360
  4. No console errors

Troubleshooting

Block not loading?

1. Check that the folder, file and class names match.
2. Check that the JS exports a default `decorate`.
3. Look for 404s in the Network tab.
4. Check whether an empty `section-metadata` table is showing up as a block. That would mean `applySectionMetadata` did not run.

Styles not applying?

1. Check the specificity against the `main > .section > div` scaffold.
2. Check whether the block sets `display: inline` where it needs inline images.
3. Run `npm run lint:css`.

Links unexpectedly yellow buttons?

That is bare-links-too buttonization. Either wrap the link with other text, or undo it in the block.

Content not updating?

1. Preview again from DA.
2. Hard-refresh the page.
3. Allow 1 to 2 minutes for the CDN.

Rails empty?

`/query-index.json` is missing. See Known Risks item 2.

Resources

Resource	URL
Edge Delivery Services documentation	https://www.aem.live/docs/
Developer tutorial	https://www.aem.live/developer/tutorial
Block collection	https://www.aem.live/developer/block-collection
E-L-D loading	https://www.aem.live/developer/keeping-it-100
Best practices	https://www.aem.live/docs/dev-collab-and-good-practices
Config Service / Admin API	https://www.aem.live/docs/admin.html
Source site	https://wknd.site/us/en.html

Support Contacts

Role	Contact
Repository owner	GitHub `savitaagre`
Project contacts	(add project-specific contacts)