Package ‘pdglasso’

April 23, 2026

Type Package

Title Graphical Lasso for Coloured Gaussian Graphical Models for Paired Data

Version 2.0

Date 2026-01-17

Description This package deals with RCON models for paired data and implements an Alternating Directions Method of Multipliers (ADMM) algorithm to solve the penalized likelihood method introduced by Ranciati and Roverato (2024). Also functions for the computation of maximum likelihood estimates and for the generation of simulated pdRCON models and data are provided.

License GPL (>= 2)

Imports Rcpp (>= 1.0.13), MASS

LinkingTo Rcpp, RcppEigen

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Contents

pdglasso-package . . . 2
admm.pdglasso . . . 4
compute.eBIC . . . 6
fMRI_parietal . . . 7
GGM.simulate . . . 8
lams.max . . . 9
pdColG.get . . . 10
pdRCON.mle . . . 11
pdRCON.select . . . 12
pdRCON.simulate . . . 14
plot.ADMMoutput . . . 16
plot.pdColG . . . 17
summary.pdColG . . . 18
toy_data . . . 19

Index **20**

`pdglasso-package` *pdglasso: Graphical Lasso for Coloured Gaussian Graphical Models for Paired Data*

Description

This package deals with RCON models for paired data and implements an Alternating Directions Method of Multipliers (ADMM) algorithm to solve the penalized likelihood method introduced by Ranciati and Roverato (2024). Also functions for the computation of maximum likelihood estimates and for the generation of simulated pdRCON models and data are provided.

Details

An RCON model for paired data (pdRCON model) is a coloured Gaussian Graphical Model (GGM) where the p variables are partitioned into a Left block L and a Right block R. The two blocks are not independent, every variable in the left block has an homologous variable in the right block and certain types of equality `R`estrictions on the entries of the `CON`centration matrix K are allowed. A pdRCON model is represented by a Coloured Graph for Paired Data (pdColG) with a vertex for every variable and where every vertex and edge is either *coloured* or *uncoloured*. More details on the equality constraints of pdRCON models, submodel classes of interest and on the usage of the package are given in the following.

pdRCON models - terminology and relevant submodel classes

A pdRCON model is a Gaussian Graphical Model (GGM) with additional equality restrictions on the entries of the concentration matrix. In the paired data framework, there are three different types of equality restrictions of interest, identified with the names *vertex*, *inside-block edge* and *across-block edge*, respectively. Relevant submodel classes can be specified both by allowing different combinations of restriction types and by forcing different types of fully symmetric structures. In this package, different submodel classes are identified by the arguments `type` and `force.symm` and models are represented by coloured graphs for paired data encoded in the form of a `pdColG` matrix.

- Every variable in L has an homologous variable in R and the corresponding diagonal entries of K can be constrained to have equal value. Such entries of K are represented by *coloured vertices* of the independence graph whereas the unconstrained diagonal entries are represented by *uncoloured vertices*. Different types of submodel classes of interest may be obtained by (i) not allowing coloured vertices, (ii) allowing both coloured and uncoloured vertices and (iii) allowing only coloured vertices.
- For every pair of variables in L there exists an homologous pair of variables in R, thereby identifying a pair of homologous edges. If both edges are present in the graph the corresponding off-diagonal entries of K can be constrained to have equal value. These type of edges are referred to as *coloured symmetric inside-block edges*. Different types of submodel classes of interest may be obtained by (i) not allowing coloured inside-block edges, (ii) allowing both coloured and uncoloured inside-block edges and (iii) allowing only coloured inside-block edges.
- We say that two variables are *across-block* if one variable belongs to L and the other to R. For every pair of non-homologous across-block variables there exists an homologous pair across-block variables, thereby identifying a pair of homologous edges. If both edges are present in the graph the corresponding off-diagonal entries of K can be constrained to have equal value. These type of edges are referred to as *coloured symmetric across-block edges*. Different types of submodel classes of interest may be obtained by (i) not allowing coloured

across-block edges, (ii) allowing both coloured and uncoloured across-block edges and (iii) allowing only coloured across-block edges, with the exception of edges joining a variable in L with its homologous in R.

- We remark that every coloured edge belongs to a pair of coloured symmetric edges, either inside- or across-blocks. On the other hand, for an uncolored edge its homologous edge may or may not be present in the graph. In the case where an uncoloured edge and its homologous are both present we say that they form a pair of *uncoloured symmetric edges*, either inside- or across-blocks.

Use of the arguments `type` and `force.symm` to specify submodel classes

The functions of this package make it possible to specify different types of pdRCON submodel classes of interest through the arguments `type` and `force.symm` which can both take as value any subvector of the character vector `c("vertex", "inside.block.edge", "across.block.edge")`; note that the names of the components can be abbreviated down, up to the first letter only, and are not case-sensitive. The argument `type` cannot be `NULL` and:

- If `type` contains the string `"vertex"` then coloured vertex symmetries are allowed and, if in addition also `force.symm` contains the string `"vertex"`, then all vertices are coloured.
- If `type` contains the string `"inside.block.edge"` then coloured inside-block edge symmetries are allowed and, if in addition also `force.symm` contains the string `"inside.block.edge"`, then only coloured edges are allowed inside blocks.
- If `type` contains the string `"across.block.edge"` then coloured across-block edge symmetries are allowed and, if in addition also `force.symm` contains the string `"across.block.edge"`, then only coloured edges are allowed across blocks, with the exception of edges joining a variable in L with its homologous in R.

Note that `force.symm` is a, possibly `NULL`, subvector of `type`. Elements of `force.symm` which are not elements of `type` are ignored.

Variables position and block structure of sample covariance matrices

The functions of this package assume that the positions occupied by variables follow certain rules. More specifically, the positions from 1 to $q = p/2$ correspond to the first group of variables, say L, whereas the positions from $q + 1$ to p are associated with the second group of variables, R. Furthermore, the variables of the first group are ordered in the same way as those of the second group, in the sense that for every $i = 1, \ldots, q$ the variable in position i is homologous to the variable in position $q + i$. Hence, for instance, the functions that receive in input a sample covariance matrix assume that the rows and columns of this matrix are ordered according to these rules, so that it can be partitioned into four $q \times q$ submatrices naturally associated with the inside- and across-block components. The same is true for the `pdColG` matrix described below.

Model representation through the `pdColG` matrix

Every pdRCON model is uniquely represented by a Coloured Graph for Paired Data (pdColG) implemented in the form of an object of class `pdColG` that is a $p \times p$ symmetric matrix where every entry is one of the values 0, 1 or 2, as follows:

- The diagonal entries of the pdColG matrix are all equal to either 1, for uncoloured vertices, or 2, for coloured vertices.
- The off-diagonal entries of the pdColG matrix are equal to 0 for missing edges and either 1 or 2 for present edges, where the value 2 is used to encode coloured edges.

Author(s)

Saverio Ranciati (ORCID: 0000-0001-7880-9465), Alberto Roverato (ORCID: 0000-0001-7984-3593), Anna Vesely (ORCID: 0000-0001-6696-2390), and Peter Majcen (ORCID: 0009-0009-7020-7246)
Maintainer: Anna Vesely anna.vesely2@unibo.it

References

Højsgaard, S. and Lauritzen, S. L. (2008). Graphical Gaussian models with edge and vertex symmetries. *Journal of the Royal Statistical Society Series B: Statistical Methodology*, *70*(5), 1005-1027.

Ranciati, S. and Roverato, A., (2024). On the application of Gaussian graphical models to paired data problems. *Statistics and Computing*, *34*(6), 1-19.

Ranciati, S., Roverato, A. and Luati, A. (2021). Fused graphical lasso for brain networks with symmetries. *Journal of the Royal Statistical Society Series C: Applied Statistics*, *70*(5), 1299-1322.

Roverato, A. and Nguyen, D.N. (2024). Exploration of the search space of Gaussian graphical models for paired data. *Journal of Machine Learning Research*, *25*(92), 1-41.

`admm.pdglasso` *ADMM graphical lasso algorithm for pdRCON models*

Description

Estimate of a concentration matrix within the pdRCON submodel class identified by the arguments `type` and `force.symm`, based on the pdglasso method with penalty terms `lambda1` and `lambda2` (Ranciati and Roverato, 2024). Optimization is implemented by an ADMM algorithm (see Boyd *et. al.* 2011). The output is an object of class `ADMMoutput` and the user may then call `pdColG.get` to obtain the Coloured Graph for Paired Data (pdColG) representing the selected model.

Usage

```
admm.pdglasso(
  S,
  lambda1,
  lambda2,
  type = c("vertex", "inside.block.edge", "across.block.edge"),
  force.symm = NULL,
  X.init = NULL,
  rho1 = 1,
  rho2 = 1,
  varying.rho1 = TRUE,
  varying.rho2 = TRUE,
  max_iter = 5000,
  eps.abs = 1e-06,
  eps.rel = 1e-06,
  rcpp = TRUE,
  print.type = TRUE,
  verbose = FALSE
)
```

Arguments

`S`	a sample covariance matrix with the block structure described in `pdglasso-package`.
`lambda1`	a non-negative scalar penalty that encourages sparsity in the concentration matrix.
`lambda2`	a non-negative scalar penalty that encourages equality constraints in the concentration matrix.
`type`, `force.symm`	two subvectors of `c("vertex", "inside.block.edge", "across.block.edge")` which identify the pdRCON submodel class of interest; see `pdglasso-package` for details.
`X.init`	a $p \times p$ concentration matrix to be used as starting point of the ADMM. If `NULL` a default value is used.
`rho1`	a postive scalar; tuning parameter of the ADMM algorithm to be used for the outer loop.
`rho2`	a positive scalar; tuning parameter of the ADMM algorithm to be used for the inner loop.
`varying.rho1`	a logical; if `TRUE` the parameter `rho1` is updated iteratively to speed-up convergence.
`varying.rho2`	a logical; if `TRUE` the parameter `rho2` is updated iteratively to speed-up convergence.
`max_iter`	an integer; maximum number of iterations for convergence.
`eps.abs`	a positive scalar; the absolute tollerance for the computation of primal and dual feasibility tollerances of the ADMM.
`eps.rel`	a positive scalar; the relative tollerance for the computation of primal and dual feasibility tollerances of the ADMM.
`rcpp`	a logical; if `TRUE`, computations are performed using the Rcpp (C++) implementation; if `FALSE`, a pure R implementation is used.
`print.type`	a logical; if `TRUE` the pdRCON submodel class considered, as specified by the arguments `type` and `force.symm`, is returned as printed output in the console. This option is only used when `rcpp = FALSE`; when `rcpp = TRUE`, no output is printed for efficiency.
`verbose`	a logical; if `TRUE` the progress (and internal convergence of inner loop) is shown in the console while the algorithm is running.

Value

A object of class `ADMMoutput` that is a list with the following components:

- `X` the estimated concentration matrix.
- `acronyms` a vector of strings identifying the pdRCON submodel class considered as identified by the arguments `type` and `force.symm`.
- `internal.par` a list of internal parameters passed to the function at the call, as well as convergence information.

References

Ranciati, S. and Roverato, A., (2024). On the application of Gaussian graphical models to paired data problems. *Statistics and Computing*, *34*(6), 1-19.

Boyd, S., Parikh, N., Chu, E., Borja, P. and Eckstein, J. (2011). Distributed optimization and statistical learning via the alternating direction method of multipliers. *Foundations and Trends in Machine learning*, *3*(1), 1-122.

Examples

```
# computation of the sample covariance
S <- cov(toy_data$sample.data)

# model with all types of symmetries allowed and no full symmetry required
admm.out <- admm.pdglasso(S, lambda1=4, lambda2=0.7)
G <- pdColG.get(admm.out)
summary(G)

# model with no across-block symmetries allowed and full vertex-symmetry required
admm.out <-admm.pdglasso(S, , lambda1=4, lambda2=0.7, type=c("v", "i"), force.symm = c("v"))
G <- pdColG.get(admm.out)
summary(G)
```

`compute.eBIC` *Extended Bayesian Information Criterion (eBIC) for pdRCON models*

Description

This function computes the value of the eBIC for a pdRCON model from the output of `admm.pdglasso`; see Eq.1 of Feygel and Drton (2010).

Usage

```
compute.eBIC(S, admm.out, n, gamma.eBIC = 0.5, max_iter = 5000, mle = TRUE)
```

Arguments

`S`	a sample covariance matrix with the block structure described in `pdglasso-package`.
`admm.out`	an object of class `ADMMoutput`, such as the output of a call to `admm.pdglasso`; see also `pdRCON.select`.
`n`	the sample size.
`gamma.eBIC`	a parameter governing the magnitude of the penalization term inside the criterion; it ranges from 0 to 1, where 0 makes the eBIC equivalent to BIC, with 0.5 being the value suggested by Feygel and Drton (2010).
`max_iter`	an integer; maximum number of iterations for convergence.
`mle`	a logical; if `TRUE`, the MLE are used otherwise the pdglasso estimator is used; see the "Details" section below.

Details

Details on the specification of the argument `mle`

The extended Bayesian Information Criterion implemented in this function requires that the parameters are estimated by maximum likelihood. However, the computation of MLEs may considerably slow down the procedure and, more seriously, in the high-dimensional setting MLEs may even not exist. For this reason, we provide the option that the eBIC is, naively, computed by using the pdglasso estimate.

Value

A vector containing three elements:

- the value of the eBIC,
- the log-likelihood,
- the number of parameters.

References

Foygel, R. and Drton, M. (2010). Extended Bayesian information criteria for Gaussian graphical models. *Advances in neural information processing systems*, 23.

Examples

```
S <- cov(toy_data$sample.data)
admm.out <- admm.pdglasso(S, lambda1=4, lambda2=0.7)
compute.eBIC(S, admm.out, n=60, gamma.eBIC=0.5)

compute.eBIC(S, admm.out, n=60, gamma.eBIC=0.5, mle=FALSE)
```

`fMRI_parietal` *fMRI Dataset*

Description

Put reference here.

Usage

```
fMRI_parietal
```

Format

`fMRI_parietal`:
A 404×10 matrix.

GGM.simulate *Random simulation of Gaussian graphical models (GGMs)*

Description

Randomly generates a GGM and, more specifically, the undirected graph G representing the model, a concentration matrix K adapted to G, that is a positive definite matrix whose zero pattern is specified by the missing edges of G, and a random sample from a multivariate normal distribution with zero mean vector and covariance matrix Sigma, that is the inverse of K.

Usage

```
GGM.simulate(
  p,
  concent.mat = TRUE,
  sample = TRUE,
  Sigma = NULL,
  sample.size = NULL,
  dens = 0.1
)
```

Arguments

p	an even integer, the number of variables of the generated model; see the "Details" section below.
concent.mat	a logical, if TRUE a concentration matrix K adapted to G is generated.
sample	a logical, if TRUE a sample from a normal distribution with zero mean vector and concentration matrix K is generated.
Sigma	a $p \times p$ positive definite matrix. This is the matrix argument of the rWishart function, which is used as starting point in the random generation of the concentration matrix, as described in the "Details" section of the function pdRCON.simulate. If NULL the identity matrix is used.
sample.size	a positive integer, size of the randomly generated sample. If NULL then sample.size=3*p.
dens	a value between zero and one used to specify the sparsity degree of the generated graph, as described in the "Details" section of the function pdRCON.simulate.

Details

A GGM is a pdRCON model with no parametric symmetries, and the purpose of this function is that of providing a simplified call to the function pdRCON.simulate, with the appropriate choice of arguments required to simulate a GGM. Note, however, that pdRCON models make sense only if the number of variables p is even, and this requirement is (unnecessarily) retained here.

Value

A list with the following components:

- G a randomly generated (symmetric) adjacency matrix of an undirected graph on p vertices.
- K either a randomly generated concentration matrix adapted to G or NULL if concent.mat=FALSE.

- sample.data either a data frame randomly generated from a multivariate normal distribution with mean vector zero and concentration matrix K or NULL if either sample=FALSE or concent.mat=FALSE.

Note that the variable are named V1,...,Vp.

Examples

```
# generates distribution and data from a GGM on 20 variables and graph density equal to 0.2
p <- 20
n <-100
set.seed(1234)
GenMod <- GGM.simulate(20, sample.size=n, dens=0.20)

# check graph sparsity degree
n.edges <- sum(GenMod$G[upper.tri(GenMod$G)])
n.edges/(p*(p-1)/2)

# check positive definiteness
min(eigen(GenMod$K)$values)

# computation of the partial correlation matrix
R <- -cov2cor(GenMod$K)
diag(R) <- 1
```

---

lams.max *Maximum theoretical values of* lambda1 *and* lambda2

Description

Computes the maximum theoretical values lambda1.max and lambda2.max of lambda1 and lambda2, respectively. For every lambda1 greater than lambda1.max the pdglasso estimator is a diagonal matrix whereas for every lambda2 greater than lambda2.max the pdglasso estimator is fully symmetric.

Usage

```
lams.max(S)
```

Arguments

S	a sample covariance matrix.

Value

A vector of two elements, lambda1.max and lambda2.max.

Examples

```
S <- cov(toy_data$sample.data)
lams.max(S)
```

pdColG.get *pdColG matrix from the output of a call to* admm.pdglasso

Description

This function returns the pdColG matrix representing the pdRCON model resulting from a call to admm.pdglasso; see also pdRCON.select.

Usage

```
pdColG.get(admm.out, th1 = NULL, th2 = NULL, model.dimension = FALSE)
```

Arguments

admm.out	an object of class ADMMoutput.
th1, th2	two positive scalars, the thresholds to identify edges (th1) and coloured edges (th2) in the graph, if NULL a default value is used; as describe in the "Details" section below. .
model.dimension	a logical, if TRUE the number of parameters of the model is returned.

Details

Details of the specification of the argument th1 and th2

Due to finite-precision arithmetic in computing, the fitted concentration matrix obtained from the ADMM has no exact zeros and no exact identical pairs of concentration values. Hence, th1 and th2 provide tollerances for values and differences, respectively, to be regarded as close enough to zero. If NULL tollerances are automatically derived from tollerance values used to check convergence of the ADMM. The function plot.ADMMoutput allows to visualize the role played by the default threshold as well as to specify facilitate the specification of suitable values for the personalized thresholds th1 and th2.

Value

Either an object of class pdColG, if model.dimension=FALSE, or a list with the following components if model.dimension=TRUE:

- pdColG an object of class pdColG, that is a matrix representing a coloured graph for paired data.
- n.par the number of parameters of the pdRCON model.

Examples

```
S <- cov(toy_data$sample.data)
admm.out <- admm.pdglasso(S, lambda1=4, lambda2=0.7)
pdColG.get(mod.out)
```

pdRCON.mle *Maximum likelihood estimate of a pdRCON model*

Description

Computes the maximum likelihood estimate of the concentration matrix of a pdRCON model.

Usage

```
pdRCON.mle(S, pdColG, eps.rel = 1e-06, eps.abs = 1e-06, max_iter = 5000)
```

Arguments

S	a sample covariance matrix with the block structure described in pdglasso-package.
pdColG	a pdColG matrix representing a coloured graph for paired data; see pdglasso-package for details.
eps.rel	a positive scalar; the relative tollerance for the computation of primal and dual feasibility tollerances of the ADMM.
eps.abs	a positive scalar; the absolute tollerance for the computation of primal and dual feasibility tollerances of the ADMM.
max_iter	an integer; maximum number of iterations for convergence.

Details

If the sample covariance matrix is not full-rank, then it is possible that the maximum likelihood estimate does not exist. The maximum likelihood estimate is computed by running the function admm.pdglasso with suitable penalties and, if it does not exist, then the ADMM algorithm fails to converge, a warning is produced and a NULL is returned.

Value

Either a matrix, that is the maximum likelihood estimate of $K = \Sigma^{-1}$ under the pdRCON model represented by pdColG, or NULL if the maximum likelihood estimate does not exist.

Examples

```
S <- var(toy_data$sample.data)
K.hat <- pdRCON.mle(S, toy_data$pdColG)
```

pdRCON.select *Selection and estimate of a pdRCON model according to eBIC*

Description

Performs a sequence of calls to admm.pdglasso on a sequence of values for lambda1 and lambda2. More specifically, firstly a path of lambda1 values, with lambda2=0, is considered to select a "best" lambda1 value according to eBIC. Next, a path of lambda2 values is considered, with lambda1 fixed to its previously selected value, and the final model is selected according to eBIC. The user may then call pdColG.get to obtain the Coloured Graph for Paired Data (pdColG) representing the selected model.

Usage

```
pdRCON.select(
  S,
  n,
  lams = NULL,
  gamma.eBIC = 0.5,
  type = c("vertex", "inside.block.edge", "across.block.edge"),
  force.symm = NULL,
  X.init = NULL,
  rho1 = 1,
  rho2 = 1,
  varying.rho1 = TRUE,
  varying.rho2 = TRUE,
  max_iter = 5000,
  eps.abs = 1e-08,
  eps.rel = 1e-08,
  verbose = FALSE,
  progress = TRUE,
  print.type = TRUE,
  mle.estimate = TRUE
)
```

Arguments

S	a sample covariance matrix with the block structure described in pdglasso-package.
n	the sample size.
lams	a 2x4 numeric matrix to specify the path of lambda values, if NULL default values are used; see the "Details" section below for additional information.
gamma.eBIC	parameter of eBIC with gamma.eBIC=0 corresponding to the classical BIC; see compute.eBIC for details..
type, force.symm	two subvectors of c("vertex", "inside.block.edge", "across.block.edge") which identify the pdRCON submodel class of interest; see pdglasso-package for details.
X.init	a $p \times p$ concentration matrix to be used as starting point of the ADMM. If NULL a default value is used.

rho1	a postive scalar; tuning parameter of the ADMM algorithm to be used for the outer loop.
rho2	a positive scalar; tuning parameter of the ADMM algorithm to be used for the inner loop.
varying.rho1	a logical; if TRUE the parameter rho1 is updated iteratively to speed-up convergence.
varying.rho2	a logical; if TRUE the parameter rho2 is updated iteratively to speed-up convergence.
max_iter	an integer; maximum number of iterations for convergence.
eps.abs	a positive scalar; the absolute tollerance for the computation of primal and dual feasibility tollerances of the ADMM.
eps.rel	a positive scalar; the relative tollerance for the computation of primal and dual feasibility tollerances of the ADMM.
verbose	a logical; if TRUE the progress (and internal convergence of inner loop) is shown in the console while the algorithm is running.
progress	a logical; if TRUE provides a visual update in the console about the grid search over lambda1 and lambda2
print.type	a logical; if TRUE the pdRCON submodel class considered, as specified by the arguments type and force.symm, is returned as printed output in the console. This option is only used when rcpp = FALSE; when rcpp = TRUE, no output is printed for efficiency.
mle	a logical; if TRUE, compute eBIC via the MLE, if FALSE the pdglasso estimator is used; see compute.eBIC for details.

Details

Details on the specification of the argument lams

The argument lams is a 2x4 matrix used to specified the grid of penalty terms. The first row of lams refers to lambda1 and second row to lambda2. For each row of the lams matrix entries are: the minimum and maximum value of the path (columns 1 and 2); the number of points of the path (column 3); 0 for linear spacing and 1 logarithmic spacing (column 4). If lams=NULL the default values are computed as follows: maximum lambda values are computed from lams.max and paths of 20 points are used form max.lams/20 to max.lams, with logarithm spacing.

Value

A list with the following components:

- model selected model; object of class ADMMoutput output of admm.pdglasso.
- lambda.grid the grid of values used for lambda1 and lambda2.
- best.lambdas the selected values of lambda1 and lambda2 according to eBIC.
- l1.path a matrix containing the path values for lambda1 as well as relevant quantities of the eBIC.
- l2.path a matrix containing the path values for lambda2 as well as relevant quantities of the eBIC.
- time.exec total execution time for the called function.

A warning is produced if at least one run of the algorithm for the grid searches has resulted in non-convergence (status can be checked by inspecting l1.path and l2.path).

Examples

```
S <- cov(toy_data$sample.data)
sel.mod <- pdRCON.select(S, n=60)
sel.mod$l1.path
sel.mod$l2.path
plot(sel.mod$model)
pdColG.get(sel.mod$model)
```

`pdRCON.simulate` *Random simulation of pdRCON models*

Description

Randomly generates a pdRCN model and, more specifically, the `pdColG` matrix representing the model, a concentration matrix `K` with the same zero pattern and equality constraints encoded by`pdColG`, and a random sample from a multivariate normal distribution with zero mean vector and covariance matrix `Sigma`, that is the inverse of `K`.

Usage

```
pdRCON.simulate(
  p,
  concent.mat = TRUE,
  sample = TRUE,
  Sigma = NULL,
  sample.size = NULL,
  type = c("vertex", "inside.block.edge", "across.block.edge"),
  force.symm = NULL,
  dens = 0.1,
  dens.vertex = NULL,
  dens.inside = NULL,
  dens.across = NULL,
  print.type = TRUE
)
```

Arguments

`p`	an even integer, the number of variables of the generated model.
`concent.mat`	a logical, if `TRUE` a concentration matrix `K` with the zero structure and symmetries encoded by `pdColG` is generated.
`sample`	a logical, if `TRUE` a sample from a normal distribution with zero mean vector and concentration matrix `K` is generated.
`Sigma`	a $p \times p$ positive definite matrix. This is the matrix argument of the `rWishart` function, which is used as starting point in the random generation of the concentration matrix, as described in the "Details" section below. If `NULL` the identity matrix is used.
`sample.size`	a positive integer, size of the randomly generated sample. If `NULL` then `sample.size=3*p`.
`type, force.symm`	two subvectors of `c("vertex", "inside.block.edge", "across.block.edge")` which identify the pdRCON submodel class of interest; see `pdglasso-package` for details.

dens, dens.vertex, dens.inside, dens.across
: four values between zero and one used to specify the sparsity degree of the generated graph, as described in the "Details" section below. The default dens.vertex=NULL is equivalent to dens.vertex=dens, and similarly for dens.inside and dens.across.

print.type
: a logical; if TRUE the pdRCON submodel class considered, as specified by the arguments type and force.symm, is returned as printed output in the console.

Details

Details on the sparsity degree of the generated graph

The argument dens.vertex specifies the proportion of coloured vertices among the p vertices. This is used if the string "vertex" is a component of type but not of force.symm. The string "vertex" not being a component of type is equivalent to dens.vertex=0 whereas the string "vertex" being a component of both type and force.symm is equivalent to dens.vertex=1.

The argument dens.inside specifies the proportion of coloured symmetric inside-block edges among the $q(q-1)$ inside-block edges, where $q = p/2$, . This is used if the string "inside.block.edge" is a component of type, otherwise it is equivalent to dens.inside=0. The overall density of inside-block edges is obtained by the sum of the densities of coloured and uncoloured inside-block edges. This is a value between dens.inside and dens.inside+dens. Furthermore, it is exactly equal to dens if "inside.block.edge" is not a component of type and to dens.inside if "inside.block.edge" is a component of both type and force.symm.

The argument dens.across specifies the proportion of coloured symmetric across-block edges among the potentially coloured $q(q-1)$ across-block edges. This is used if the string "across.block.edge" is a component of type, otherwise it is equivalent to dens.across=0. The overall density of across-block edges is obtained by the sum of the densities of coloured and uncoloured across-block edges. This is a value between dens.across and dens.across+dens. Furthermore, it is exactly equal to dens if "across.block.edge" is not a component of type.

The argument dens specifies the density of uncoloured edges. Note that the algorithm generates uncoloured edges first, which may be overwritten by coloured edges. For this reason the actual density of uncoloured edges is typically smaller than dens.

Details on the generating process of the concentration matrix

The concentration matrix is obtained by first generating a random Wishart matrix with matrix parameter Sigma and p degrees of freedom, which represents an initial unconstrained covariance matrix. This is inverted and adapted to a suitable coloured graph for paired data with sparsity degree according to the dens.xxx arguments.

Value

A list with the following components:

- pdColG a randomly generated a matrix of class pdColG representing a pdRCON model; see pdglasso-package for details.
- K either a randomly generated concentration matrix with the zero structure and symmetries encoded by pdColG or NULL if concent.mat=FALSE..
- sample.data either a data frame randomly generated from a multivariate normal distribution with mean vector zero and concentration matrix K or NULL if either sample=FALSE or concent.mat=FALSE.

Note that the variable in L are named L1,...,Lq and variables in R are are named R1,...,Rq where Li is homologous to Ri for every i=1,...,q.

Examples

```
# generates a pdRCON model on 10 variables in the form of a pdColG matrix

set.seed(123)
pdRCON.model <- pdRCON.simulate(10, concent=FALSE, sample=FALSE, dens=0.25)$pdColG

# generates a distribution from a pdRCON model on 20 variables, a concentration matrix
# for this model and a sample of size 50
# all vertices are coloured and no coloured across-block edge is allowed

set.seed(123)
GenMod <- pdRCON.simulate(20, type=c("v", "i"), force.symm=c("v"), sample.size=50, dens=0.20)

summary(GenMod$pdColG)

# computation of the partial correlation matrix
R <- -cov2cor(GenMod$K)
diag(R) <- 1
```

`plot.ADMMoutput` *Diagnostic plot for the output of the ADMM*

Description

A plot, with different panels, obtained from the output of `admm.pdglasso`, which is helpful to check the convergence of the ADMM. This function can be used to visualize the default threshold used by `pdColG.get` as well to identify specific `th1` and `th2` threshold values to be used in place of the default one.

Usage

```
## S3 method for class 'ADMMoutput'
plot(x, y = TRUE, th1 = NULL, th2 = NULL, logarith10 = TRUE, ...)
```

Arguments

`x`	an object of class `ADMMoutput` such as the output of a call to the `admm.pdglasso` function; see also `pdRCON.select`.
`y`	a logical, if `TRUE` the default threshold used in `pdColG.get` is represented (in log10-scale) in the plot.
`th1, th2`	two positive scalars as in `pdColG.get`, if not `NULL` they are represented (in log10-scale) in the plot.
`logarithm10`	a logical, if `TRUE` the values of `th1` and `th2` are expected to be provided in log10-scale. This facilitate interaction with the plot whose y-axis is in log10 scale.

Value

A plot is produced with different panels depending on the model `type`. More specifically:

- a panel with the values of the off-diagonal concentrations is always provided,
- a panel with the differences of homologous diagonal concentration values is provided if vertex symmetries are allowed,

- a panel with the differences of homologous inside-block concentration values is provided if inside-block symmetries are allowed,
- a panel with the differences of homologous across-block concentration values is provided if across-block symmetries are allowed

According to the values of the arguments y, th1 and th2, horizontal dashed lines with the corresponding thresholds are included in the panels.

The function returns an invisible vector with the values of th1, th2 and of the default threshold. The quantities th1 and th2 can directly given as input for the same arguments of pdColG.get. Consistently with the behavior of pdColG.get, a NULL value of th1 orth2 is replaced by the default threshold.

Examples

```
S <- cov(toy_data$sample.data)
mod.out <- pdRCON.select(S,n=60)$model
plot(mod.out)
```

---

plot.pdColG *Visual representation of a coloured graph for paired data*

Description

Heatmap-style graphical representation of an object of class pdColG, such as that raturned by a call to pdColG.get.

Usage

```
## S3 method for class 'pdColG'
plot(
  x,
  y = "everything",
  which.sym = c("structural", "parametric"),
  asym.edges = TRUE,
  export.plot = FALSE,
  fancy = TRUE,
  ...
)
```

Arguments

x	a matrix of class pdColG; see pdglasso-package for details.
y	a string; allows the user to specify which portion of the graph (a block) is to be plotted: possible mutually exclusive options are "left", "right", "across", "everything"; default is "everything", which means the entire graph is plotted.
which.sym	a string or a vector of strings; specifies which kind of symmetries are plotted (structural, parametric or both).
asym.edges	a logical; if TRUE, Asymmetric edges are plotted otherwise their symbol is suppressed

export.plot — a logical; if TRUE, a .pdf file is produced in the working director instead of plotting the graph as a new panel/window.

fancy — a logical value; if TRUE, symbols in the plot are used from the Latin1 encoding for characters; set to FALSE if characters are not properly displayed, so symbols are reverted to latin letters.

Value

Either a plot within the running R session or a .pdf file saved in the working directory if the option export.plot is set to TRUE.

Examples

```
plot(toy_data$pdColG)
```

---

summary.pdColG — *Structural properties of a coloured graph for paired data*

Description

Summary statistics relative to the structural properties of an object of class pdColG, such as that raturned by a call to pdColG.get.

Usage

```
## S3 method for class 'pdColG'
summary(object, print.summary = TRUE, ...)
```

Arguments

object — a matrix of class pdColG; see pdglasso-package for details.

print.summary — a logical, if TRUE the summary is printed on the console.

Value

An invisible list with the following components:

- overall a list with the number of vertices and edges.
- vertex a list with the number of coloured vertices.
- inside a list with the number of inside-block edges, the number of uncolored symmetric and coloured inside block edges.
- across a list with the number of across-block edges, the number of uncolored symmetric and coloured across block edges.

Examples

```
summary(toy_data$pdColG)
```

toy_data *Toy dataset generated through* pdRCON.simulate *function*

Description

Data simulated by the function pdRCON.simulate with parameters:

- p=20
- type=c("v", "i","a")
- force.symm=NULL
- dens=0.5
- Sigma a $p \times p$ matrix with unitary diagonal and 0.5 on off-diagonal elements.

Usage

```
toy_data
```

Format

toy_data**:**

A list with the following components:

- pdColG a matrix representing a coloured graph for paired data; see pdglasso-package for details.
- K, a concentration matrix adapted to pdColG.
- sample.data, a data frame with 250 rows and 20 columns from a multivariate normal distribution with zero mean vector and concentration matrix K.

Index

∗ **datasets**
    fMRI_parietal, 7
    toy_data, 19

admm.pdglasso, 4, *6*, *10–13*, *16*

compute.eBIC, 6, *12, 13*

fMRI_parietal, 7

GGM.simulate, 8

lams.max, 9, *13*

pdColG.get, *4*, 10, *12*, *16–18*
pdglasso *(*pdglasso-package*)*, 2
pdglasso-package, 2
pdRCON.mle, 11
pdRCON.select, *6*, *10*, 12, *16*
pdRCON.simulate, *8*, 14, *19*
plot.ADMMoutput, *10*, 16
plot.pdColG, 17

rWishart, *8*, *14*

summary.pdColG, 18

toy_data, 19