


Moments, Random Walks, and Limits for Spectrum Approximation

COLT 2023, Bangalore, India

Apoorv Vikram Singh
(NYU)



Yujia Jin
(Stanford)




Christopher Musco
(NYU)



Aaron Sidford
(Stanford)

Problem Setup

- Weighted graph G , with normalized adjacency matrix A




- Spectrum of $G \equiv$ Eigenvalues of A :

$$-1 \leq \lambda_n \leq \dots \leq \lambda_1 = 1.$$

Goal: “Estimate” the spectrum of G .

Problem Setup

- Weighted graph G , with normalized adjacency matrix A



- Spectrum of $G \equiv$ Eigenvalues of A


exactly compute $\approx n^{2.35}$

$$-1 \leq \lambda_n \leq \dots \leq \lambda_1 = 1.$$

Goal: “Estimate” the spectrum of G .

Problem Setup

- Weighted graph G , with normalized adjacency matrix A



- Spectrum of $G \equiv$ Eigenvalues of A :


$$-1 \leq \lambda_n \leq \dots$$

sublinear time: $\tilde{o}(n^2)$

Goal: “Estimate” the spectrum of G .

Spectral Density of G


(Graph G with normalized adjacency matrix A)




Graph G

Spectral Density of G

(Graph G with normalized adjacency matrix A)




Graph G




Spectral Density p

Spectral Density of G

(Graph G with normalized adjacency matrix A)



Graph G




Spectral Density p


Goal: Output q such that Wasserstein-1 distance: $W_1(p, q) \leq \varepsilon$.

Spectral Density of G

(Graph G with normalized adjacency matrix A)



Graph G



Spectral Density p

Goal: Output q such that Wasserstein-1 distance: $W_1(p, q) \leq \varepsilon$.

Equivalently: Output $\lambda'_n \leq \dots \leq \lambda'_1$ such that

$$\frac{1}{n} \sum_{i=1}^n |\lambda_i - \lambda'_i| \leq \varepsilon.$$

Existing Results

Given G with spectral density p and random-walk access to G :
random node and random neighbour

Random start node +
Transition to a random neighbour with probability \propto edge weight.

Existing Results

Given G with spectral density p and random-walk access to G :
random node and random neighbour

Random start node +
Transition to a random neighbour with probability \propto edge weight.

- [Cohen-Steiner et al. (2018)] Output q : $W_1(p, q) \leq \varepsilon$.
 - Takes $2^{\mathcal{O}(1/\varepsilon)}$ steps of random walks on G .
 - Running time: $2^{\mathcal{O}(1/\varepsilon)}$.

Existing Results

Given G with spectral density p and random-walk access to G :
random node and random neighbour

Random start node +
Transition to a random neighbour with probability \propto edge weight.

- [Cohen-Steiner et al. (2018)] Output q : $W_1(p, q) \leq \varepsilon$.
 - Takes $2^{\mathcal{O}(1/\varepsilon)}$ steps of random walks on G .
 - Running time: $2^{\mathcal{O}(1/\varepsilon)}$.

Our Results \Rightarrow [CKSV'18] cannot be improved.

Goal: Learn Distribution p

Explaining [CKSV'18]

Goal: Learn Distribution p

Explaining [CKSV'18]

- **Idea:** Estimate the moments m_j of the distribution p .

$$m_j = \mathbb{E}_{X \sim p}[X^j].$$

- **Question:** How many moments and to what accuracy?

Goal: Learn Distribution p

Explaining [CKSV'18]

- **Idea:** Estimate the moments m_j of the distribution p .

$$m_j = \mathbb{E}_{X \sim p}[X^j].$$

- **Question:** How many moments and to what accuracy?

[Kong and Valiant (2017)]: Estimate $m_1, \dots, m_{1/\varepsilon}$ moments of p to accuracy $\pm 2^{-\mathcal{O}(1/\varepsilon)}$ to output q such that $W_1(p, q) \leq \varepsilon$.

Goal: Learn Distribution p

Explaining [CKSV'18]

- **Idea:** Estimate the moments m_j of the distribution p .

$$m_j = \mathbb{E}_{X \sim p}[X^j].$$

- **Question:** How many moments and to what accuracy?

[Kong and Valiant (2017)]: Estimate $m_1, \dots, m_{1/\varepsilon}$ moments of p to accuracy $\pm 2^{-\mathcal{O}(1/\varepsilon)}$ to output q such that $W_1(p, q) \leq \varepsilon$.

Our Results \Rightarrow [KV'17] is tight!

Goal: Learn Distribution p

Explaining [CKSV'18]

- **Idea:** Estimate the moments m_j of the distribution p .

$$m_j = \mathbb{E}_{X \sim p}[X^j].$$

- **Question:** How many moments and to what accuracy?

[Kong and Valiant (2017)]: Estimate $m_1, \dots, m_{1/\varepsilon}$ moments of p to accuracy $\pm 2^{-\mathcal{O}(1/\varepsilon)}$ to output q such that $W_1(p, q) \leq \varepsilon$.

- **Aim:** Estimate $m_1, \dots, m_{1/\varepsilon}$ of p to accuracy $\pm 2^{-\mathcal{O}(1/\varepsilon)}$.

Our Results \Rightarrow [KV'17] is tight!

Goal: Learn Distribution p

Explaining [CKSV'18]

- **Idea:** Estimate the moments m_j of the distribution p .

$$m_j = \mathbb{E}_{X \sim p}[X^j].$$

- **Question:** How many moments and to what accuracy?


[Kong and Valiant (2017)]: Estimate $m_1, \dots, m_{1/\varepsilon}$ moments of p to accuracy $\pm 2^{-\mathcal{O}(1/\varepsilon)}$ to output q such that $W_1(p, q) \leq \varepsilon$.

- **Aim:** Estimate $m_1, \dots, m_{1/\varepsilon}$ of p to accuracy $\pm 2^{-\mathcal{O}(1/\varepsilon)}$.
- **Question:** How to estimate moments of Graph spectrum p ? What are your samples?

Our Results \Rightarrow [KV'17] is tight!


Moments and Random Walks

Graph G with normalized Adjacency A .



Moments and Random Walks


Graph G with normalized Adjacency A .



$$\cdot m_j := \mathbb{E}_{X \sim p}[X^j] = \frac{1}{n} \sum_{i=1}^n \lambda_i^j.$$

Moments and Random Walks


Graph G with normalized Adjacency A .



- $m_j := \mathbb{E}_{X \sim p}[X^j] = \frac{1}{n} \sum_{i=1}^n \lambda_i^j.$
- $\text{Tr}(A^j) = \sum_{i=1}^n \lambda_i^j.$
- $\text{Tr}(A^j) = \sum_{i=1}^n \mathbb{P}[\text{j-step rw from } i \text{ to } i].$

Moments and Random Walks

Graph G with normalized Adjacency A .




- $m_j := \mathbb{E}_{X \sim p}[X^j] = \frac{1}{n} \sum_{i=1}^n \lambda_i^j.$
- $\text{Tr}(A^j) = \sum_{i=1}^n \lambda_i^j.$
- $\text{Tr}(A^j) = \sum_{i=1}^n \mathbb{P}[\text{j-step rw from } i \text{ to } i].$

j -th moment of $p \equiv$
 $\mathbb{E}_i [\Pr (\text{walk of length } j \text{ ends at } i \mid \text{start at } i)].$

Moments and Random Walks

Graph G with normalized Adjacency A .




- $m_j := \mathbb{E}_{X \sim p}[X^j] = \frac{1}{n} \sum_{i=1}^n \lambda_i^j.$
- $\text{Tr}(A^j) = \sum_{i=1}^n \lambda_i^j.$
- $\text{Tr}(A^j) = \sum_{i=1}^n \mathbb{P}[\text{j-step rw from } i \text{ to } i].$

j -th moment of $p \equiv$
 $\mathbb{E}_i [\Pr (\text{walk of length } j \text{ ends at } i \mid \text{start at } i)].$

1. Choose a random node i
2. Take a walk of length j
3. Set $X = 1$ if it returns to i , 0 otherwise.

Moments and Random Walks

Graph G with normalized Adjacency A .



- $m_j := \mathbb{E}_{X \sim p}[X^j] = \frac{1}{n} \sum_{i=1}^n \lambda_i^j.$
- $\text{Tr}(A^j) = \sum_{i=1}^n \lambda_i^j.$
- $\text{Tr}(A^j) = \sum_{i=1}^n \mathbb{P}[\text{j-step rw from } i \text{ to } i].$

j -th moment of $p \equiv$
 $\mathbb{E}_i [\Pr (\text{walk of length } j \text{ ends at } i \mid \text{start at } i)].$

1. Choose a random node i
2. Take a walk of length j
3. Set $X = 1$ if it returns to i , 0 otherwise.

$$\mathbb{E}[X] = m_j$$

[CKSV'18] Algorithm


$$m_j = \mathbb{E}_i [\Pr (\text{walk of length } j \text{ ends at } i \mid \text{start at } i)].$$

- For each moment $j = 1, \dots, 1/\varepsilon$
 - Take $2^{\mathcal{O}(1/\varepsilon)}$ trials of rw of length j , starting at random node i .
 - Output the fraction of walks that return to the starting random node.

[CKSV'18] Algorithm

$$m_j = \mathbb{E}_i [\Pr (\text{walk of length } j \text{ ends at } i \mid \text{start at } i)].$$

- For each moment $j = 1, \dots, 1/\varepsilon$
 - . Take $2^{\mathcal{O}(1/\varepsilon)}$ trials of rw of length j , starting at random node i .
 - . Output the fraction of walks that return to the starting random node.



$$m_3 \approx (\# \text{ of returns}) / (\# \text{ of trials}).$$

Need $2^{\mathcal{O}(1/\varepsilon)}$ trials because we want accuracy $\pm 2^{-\mathcal{O}(1/\varepsilon)}$.

Scope of Improvement?

- Q1** Can we get away with lower accuracy in moment estimation?
([CKSV'18] needed first $1/\varepsilon$ moments to accuracy $2^{-\mathcal{O}(1/\varepsilon)}$)

Scope of Improvement?

- Q1** Can we get away with lower accuracy in moment estimation?
([CKSV'18] needed first $1/\varepsilon$ moments to accuracy $2^{-\mathcal{O}(1/\varepsilon)}$)

- Q2** Does higher moments help? I.e., Estimate more moments, each to lower accuracy.
(Estimate more than $1/\varepsilon$ moments to lower accuracy)

Scope of Improvement?

- Q1** Can we get away with lower accuracy in moment estimation?
([CKSV'18] needed first $1/\varepsilon$ moments to accuracy $2^{-\mathcal{O}(1/\varepsilon)}$)
- Q2** Does higher moments help? I.e., Estimate more moments, each to lower accuracy.
(Estimate more than $1/\varepsilon$ moments to lower accuracy)
- Q3** Does any other random walk based algorithm work better?
([CKSV'18] considers fraction of walks that return to starting node)

Scope of Improvement?

- Q1** Can we get away with lower accuracy in moment estimation?
([CKSV'18] needed first $1/\varepsilon$ moments to accuracy $2^{-\mathcal{O}(1/\varepsilon)}$)
- Q2** Does higher moments help? I.e., Estimate more moments, each to lower accuracy.
(Estimate more than $1/\varepsilon$ moments to lower accuracy)
- Q3** Does any other random walk based algorithm work better?
([CKSV'18] considers fraction of walks that return to starting node)

Our Results: NO!

Our Results

Lower bound for learning distributions.

Limits of Moment Based Methods

There exists distributions that cannot be approximated to accuracy ε in W_1 distance even if **all** of their moments are known to multiplicative accuracy $(1 \pm 2^{-\Omega(1/\varepsilon)})$.

Our Results

Lower bound for learning distributions.

Limits of Moment Based Methods

There exists distributions that cannot be approximated to accuracy ε in W_1 distance even if **all** of their moments are known to multiplicative accuracy $(1 \pm 2^{-\Omega(1/\varepsilon)})$.

Lower bound for learning graph spectrum.

Limit of Random-Walk Based Methods

There exists graphs G such that no algorithm based on $2^{\Omega(1/\varepsilon)}$ steps of random walks can approximate the spectrum of G to accuracy less than ε .

Our Results

Lower bound for learning distributions.

Limits of Moment Based Methods

There exists distributions that cannot be approximated to accuracy ε in W_1 distance even if **all** of their moments are known to multiplicative accuracy $(1 \pm 2^{-\Omega(1/\varepsilon)})$.

Lower bound for learning graph spectrum.

Limit of Random-Walk Based Methods

There exists graphs G such that no algorithm based on $2^{\Omega(1/\varepsilon)}$ steps of random walks can approximate the spectrum of G to accuracy less than ε .

Both results are constructive!

Lower Bound Goal

Aim:

- Generate G_1, G_2 that are ε away in W_1 distance, and
- Can't distinguish G_1, G_2 by rw of length $2^{\mathcal{O}(1/\varepsilon)}$ wp $> 3/4$.

Implies:


- Two probability distribution that are far away in W_1 distance but **all** of their moments are exponentially close.

j -th moment of $p \equiv$
 $\mathbb{E}_i [\Pr (\text{walk of length } j \text{ ends at } i \mid \text{start at } i)]$

Motivating Example

(Let $\ell = 1/\varepsilon$)

Consider two graphs: Weight of purple edge = $1/2$.




R_ℓ : Two disjoint cycles of length ℓ
 $R_{2\ell}$: Cycle of length 2ℓ

$\left. \begin{array}{l} \\ \end{array} \right\} W_1(R_\ell, R_{2\ell}) = 1/\ell.$

Motivating Example

(Let $\ell = 1/\varepsilon$)

Consider two graphs: Weight of purple edge = $1/2$.



R_ℓ : Two disjoint cycles of length ℓ
 $R_{2\ell}$: Cycle of length 2ℓ


$\left. \begin{array}{l} \\ \end{array} \right\} W_1(R_\ell, R_{2\ell}) = 1/\ell.$

- Generate two graphs that are $\Omega(1/\ell) = \Omega(\varepsilon)$ far in W_1 distance and
- Can't distinguish graphs by rw of length $2^{\mathcal{O}(\ell)}$ with constant probability.

Motivating Example

(Let $\ell = 1/\varepsilon$)

Consider two graphs: Weight of purple edge = $1/2$.



R_ℓ : Two disjoint cycles of length ℓ
 $R_{2\ell}$: Cycle of length 2ℓ


$\left. \begin{array}{l} \\ \end{array} \right\} W_1(R_\ell, R_{2\ell}) = 1/\ell.$

- Generate two graphs that are $\Omega(1/\ell) = \Omega(\varepsilon)$ far in W_1 distance and
- Can't distinguish graphs by rw of length $2^{\mathcal{O}(\ell)}$ with constant probability.
- Length $\ell - 1$ rw cannot distinguish them.

Motivating Example

(Let $\ell = 1/\varepsilon$)

Consider two graphs: Weight of purple edge = $1/2$.



R_ℓ : Two disjoint cycles of length ℓ
 $R_{2\ell}$: Cycle of length 2ℓ


$\left. \begin{array}{l} \\ \end{array} \right\} W_1(R_\ell, R_{2\ell}) = 1/\ell.$

- Generate two graphs that are $\Omega(1/\ell) = \Omega(\varepsilon)$ far in W_1 distance and
 - Can't distinguish graphs by rw of length $2^{\mathcal{O}(\ell)}$ with constant probability.
-
- Length $\ell - 1$ rw cannot distinguish them.
 - Length ℓ rw can distinguish with low probability $2^{-\ell}$.

Motivating Example

(Let $\ell = 1/\varepsilon$)

Consider two graphs: Weight of purple edge = $1/2$.




R_ℓ : Two disjoint cycles of length ℓ
 $R_{2\ell}$: Cycle of length 2ℓ

$\left. \begin{array}{l} \\ \end{array} \right\} W_1(R_\ell, R_{2\ell}) = 1/\ell.$

- Generate two graphs that are $\Omega(1/\ell) = \Omega(\varepsilon)$ far in W_1 distance and
 - Can't distinguish graphs by rw of length $2^{\mathcal{O}(\ell)}$ with constant probability.
-
- Length $\ell - 1$ rw cannot distinguish them.
 - Length ℓ rw can distinguish with low probability $2^{-\ell}$.
 - However, length ℓ^2 rw can distinguish with high probability.


Hypothetical Example

At every step, random walk “disappears” with probability 1/2.
Weight of purple edges = 1/4. Weight of grey “hair” = 1/2.



Hypothetical Example


At every step, random walk “disappears” with probability 1/2.
Weight of purple edges = 1/4. Weight of grey “hair” = 1/2.



- Suppose spectral density of G_1, G_2 are far in W_1 distance.
- Length $\ell - 1$ rw cannot distinguish them.

Hypothetical Example


At every step, random walk “disappears” with probability 1/2.
Weight of purple edges = 1/4. Weight of grey “hair” = 1/2.



- Suppose spectral density of G_1, G_2 are far in W_1 distance.
- Length $\ell - 1$ rw cannot distinguish them.
- Length ℓ rw can distinguish with low probability $4^{-\ell}$.

Hypothetical Example


At every step, random walk “disappears” with probability 1/2.
Weight of purple edges = 1/4. Weight of grey “hair” = 1/2.



- Suppose spectral density of G_1, G_2 are far in W_1 distance.
- Length $\ell - 1$ rw cannot distinguish them.
- Length ℓ rw can distinguish with low probability $4^{-\ell}$.
- Length ℓ^2 rw can distinguish with low probability $\approx 2^{-\ell}$.

Hypothetical Example



At every step, random walk “disappears” with probability 1/2.
Weight of purple edges = 1/4. Weight of grey “hair” = 1/2.



- Suppose spectral density of G_1, G_2 are far in W_1 distance.
- Length $\ell - 1$ rw cannot distinguish them.
- Length ℓ rw can distinguish with low probability $4^{-\ell}$.
- Length ℓ^2 rw can distinguish with low probability $\approx 2^{-\ell}$.
- No random walk can loop around with constant probability!

Making Random Walks “Disappear”


Repeated Cycles +



- $W_1(G_1, G_2) = \varepsilon.$
- Difference of first $1/\varepsilon - 1$ moments is 0.

Making Random Walks “Disappear”

Repeated Cycles + Weighted Complete Graph




w.p. $1/2$ rw goes to vertices of the cycle (purple edge), and
w.p. $1/2$ rw goes to a random vertex (grey edge)

- $W_1(G_1, G_2) = \varepsilon/2$.
- Difference of first $1/\varepsilon - 1$ moments is 0.

Making Random Walks “Disappear”

Repeated Cycles + Weighted Complete Graph



w.p. $1/2$ rw goes to vertices of the cycle (purple edge), and
w.p. $1/2$ rw goes to a random vertex (grey edge)

- $W_1(G_1, G_2) = \varepsilon/2$.
- Difference of first $1/\varepsilon - 1$ moments is 0.
- All other moments differ by at most $2^{-1/\varepsilon}$.

Open Problems

Adaptive Random Walks

- We get tight rates for all random walk based algorithms!
- Starting node of walk was random.

Open Problems

Adaptive Random Walks

- We get tight rates for all random walk based algorithms!
- Starting node of walk was random.
- What if you can specify the starting node of random walk?

Open Problems

Adaptive Random Walks

- We get tight rates for all random walk based algorithms!
- Starting node of walk was random.
- What if you can specify the starting node of random walk?

Adaptive random walks: Specify the starting node of random walk.

(Previously: Starting node was random)

We prove lower bound of $\Omega(1/\varepsilon^2)$ for adaptive random walks.

Open Problems

Adaptive Random Walks

- We get tight rates for all random walk based algorithms!
- Starting node of walk was random.
- What if you can specify the starting node of random walk?

Adaptive random walks: Specify the starting node of random walk.

(Previously: Starting node was random)

We prove lower bound of $\Omega(1/\varepsilon^2)$ for adaptive random walks.

P1: Improve lower bounds in adaptive setting.

P2: Better upper bounds in adaptive setting.

(all existing sublinear time algorithms use non-adaptive random walks)