





Ingress Resources






INGRESS IN KUBERNETES






INGRESS **RESOURCES**





SINGLE SERVICE




apiVersion: networking.k8s.io/v1beta1 kind: Ingress metadata: name: test-ingress spec: backend: serviceName: mail-svc servicePort: 80


DNS Entries


* -> 35.232.171.182 -> mail-svc



NAME BASED VIRTUAL HOSTING – **USING HOSTNAMES**







URL
http://mail.mycompany.com
http://news.mycompany.com



SIMPLE FANOUT - USING PATHS



apiVersion:

networking.k8s.io/v1beta1

kind: Ingress

metadata:

name: path-ingress

spec:

rules:

- host: mail.mycompany.com

http:

paths:"/inbox"

- backend:

serviceName: inbox-svc

servicePort: 4200

paths:"/sent"

- backend:

serviceName: sent-svc


servicePort: 8080

paths:"/"

- backend:

serviceName: mail-svc

servicePort: 8080



DNS Entries

```
https://mail.mycompany.com/inbox -> 35.232.171.182 -> /inbox -> inbox-svc:4200
https://mail.mycompany.com/sent -> 35.232.171.182 -> /sent -> sent-svc:8080
https://mail.mycompany.com/ -> 35.232.171.182 -> / -> mail-svc:8080
```

