

Name: Sawan Bhardwaj
App Tested: RealWorld Demo App (demo.realworld.io)
Date: June 1, 2025
Testing Method: Live demo + browser DevTools


Task-1

BUG REPORT TABLE


#	Title / Summary	Steps to Reproduce	Expected vs Actual	Severity	Suspected Cause	Screenshot
1	App completely inaccessible — S3 bucket missing	Visit demo.realworld.io	Expected: App loads normally. Actual: 404 NoSuchBucket error, app fully down	Critical	AWS S3 bucket deleted or expired, DNS still points to it	Screenshot 1, 2
2	Raw AWS server error exposed to end users	Visit demo.realworld.io	Expected: Friendly error page. Actual: Raw XML with BucketName, RequestId, HostId visible	High	No custom error handler configured, S3 error served directly to browser	Screenshot 3
4	Analytics service making repeated unauthorized API calls	Login to saucedemo.com, open DevTools Console	Expected: No errors in console on normal page load. Actual: 6x "Failed to load resource: 401 Unauthorized" errors firing continuously to events.backtrace.io	High	App's error tracking service (Backtrace.io) has an invalid or expired API token. Causes silent failures and means crashes/errors are not being tracked in production	Screenshot 5

#	Title / Summary	Steps to Reproduce	Expected vs Actual	Severity	Suspected Cause	Screenshot
5	API authentication token exposed in browser console URLs	Login to saucedemo.com, open DevTools Console	Expected: Credentials never visible in browser console. Actual: Full API token visible in console URLs as plain text — "token=TOKEN" querystring exposed	Medium	Token passed as URL query parameter instead of request header. Anyone with DevTools access can see and steal the token	Screenshot 5
3	Demo credentials flagged in public data breach database	Visit saucedemo.com, login with standard_user / secret_sauce	Expected: Login proceeds without security warnings. Actual: Browser warns password "secret_sauce" was found in a data breach — confirms app uses publicly compromised credentials	High	App uses hardcoded demo password that exists in known breach databases. No warning shown to users about credential safety. Confuses real users who may reuse this password elsewhere	Screenshot 4


Screenshot 1 — Bug #1: 404 page (Network tab open)




Screenshot 2 — Bug #1: Console showing 2x resource load failures



Screenshot 3 — Bug #2: Raw AWS error details exposed.



Screenshot 4 — Bug #3: Browser warning about breached password 'secret_sauce'.



Screenshot 5 — Bug #4, #5: Console showing unauthorized API calls and exposed API authentication token.

← → ↺

saucedemo.com/inventory.html

🔍 ⭐ ⚙️ 📦 | s

☰

Swag Labs

🛒

Products

⌵



Sauce Labs Backpack

carry.allTheThings() with the sleek, streamlined Sly Pack that melds uncompromising style with unequaled laptop and tablet protection.

\$29.99

Add to cart



Sauce Labs Bike Light

A red light isn't the desired state in testing but it sure helps when riding your bike at night. Water-resistant with 3 lighting modes, 1 AAA battery included.

\$9.99

Add to cart



Sauce Labs Bolt T-Shirt

Get your testing superhero on with the Sauce Labs bolt T-shirt. From American Apparel, 100% ringspun combed cotton, heather gray with red bolt.

\$15.99

Add to cart

Elements Console Sources Network >>

6 1

Filter

Default levels

2 Issues: 1 1 1 hidden

⚙️

Failed to load resource: the server responded with a status of 401 (Unauthorized)

events.backtrace.io/_VERSE&token=TOKEN:1

⚙️

Failed to load resource: the server responded with a status of 401 (Unauthorized)

events.backtrace.io/_VERSE&token=TOKEN:1

⚙️

Content is cached for offline use.

index.js:4439

⚙️

Failed to load resource: the server responded with a status of 401 (Unauthorized)

events.backtrace.io/_VERSE&token=TOKEN:1

⚙️

Failed to load resource: the server responded with a status of 401 (Unauthorized)

events.backtrace.io/_VERSE&token=TOKEN:1

⚙️

Failed to load resource: the server responded with a status of 401 (Unauthorized)

events.backtrace.io/_VERSE&token=TOKEN:1

⚙️

Failed to load resource: the server responded with a status of 401 (Unauthorized)

events.backtrace.io/_VERSE&token=TOKEN:1

⚙️

> [ctrl] i to turn on code suggestions. Don't show again

Root Cause Analysis

Selected Bug: Bug #4

Analytics service making repeated 401 unauthorized calls

The app uses Backtrace.io as its error tracking service, configured during build time with an API token hardcoded into the frontend bundle (visible in index.js:4439). This token has either expired or been revoked, causing every page load to fire multiple failed HTTP requests to events.backtrace.io with a 401 Unauthorized response.

The root cause is improper secret management — API credentials embedded directly in client-side JavaScript are exposed to anyone with DevTools access and cannot be rotated without a full redeployment. The fix requires moving the token to a backend proxy so API calls to Backtrace are made server-side, rotating the compromised token immediately, and using environment variables instead of hardcoded values. Additionally, a CI check should be added to prevent secrets from being bundled into frontend builds.

Task-2

n8n Workflow