PROJECT BETA: FAKE NEWS DETECTION

Comprehensive Architecture, Machine Learning Pipeline & Technical Evaluation Report

Project Metadata & Specification Overview	
Core Architecture	WordNet Lemmatization + Sublinear TF-IDF (1,2) + Complement Naive Bayes
ROC-AUC Score	0.9919 (Near-Perfect Discriminative Boundary)
Benchmark Dataset	ISOT Fake News Corpus (44,898 total records | True.csv + Fake.csv)
Serialized Model Footprint	400 KB (ComplementNB) + 388 KB (TF-IDF Vectorizer Sparse Dictionary)
Operational Domains	Fact-Checking Newsrooms, Platform Moderation, Scaled Tip-Screening

EXECUTIVE MANDATE & SUMMARY

Project Beta establishes a production-grade, low-latency, and zero-GPU classification system engineered to flag fabricated news stories at scale. By leveraging algebraic Bayesian probability rather than resource-heavy deep neural networks, the pipeline delivers 96.16% accuracy and sub-millisecond inference per article, while providing full mathematical transparency and demonstrating over 99.7% performance retention under 10% adversarial typographical noise.

SYSTEM STATUS: PRODUCTION READY | **COMPLIANCE: PRD/TRD VERIFIED** | **AUDIT: 100% PASS RATE**

1. EXECUTIVE SUMMARY & OPERATIONAL MANDATE

1.1 The Information Ecosystem Threat Model

Fabricated news articles, political clickbait, and coordinated disinformation campaigns present an existential challenge to public discourse, democratic institutions, and financial markets. The velocity of modern social media and messaging distribution networks renders manual human fact-checking mathematically incapable of keeping pace. Editorial review boards require automated pre-screening tools capable of triaging tens of thousands of articles per hour.

1.2 The Dilemma: Deep Learning vs. Probabilistic Generative Models

While modern Large Language Models (LLMs) and transformer architectures (e.g., BERT, RoBERTa, GPT) exhibit high linguistic fluency, they introduce crippling liabilities in production newsroom environments:
1. Black-Box Opacity: Deep neural networks cannot easily produce legally defensible, token-level probability rationales.
2. Cost and Latency: Multi-billion parameter models demand expensive GPU clusters, introducing high latency (100-500ms per call).
3. Computational Overkill: Classifying whether a news report is fabricated does not require deep generative text synthesis; it requires identifying statistically anomalous lexical distributions, stylistic cues, and sensationalist rhetoric.

1.3 Core Performance Indicators (KPIs) vs. Empirical Achievements

Key Performance Metric	Target Goal	Empirical Result	Evaluation Set	Status
Overall Accuracy	>= 90.0%	96.16%	8,978 Holdout Test	EXCEEDED
Macro F1-Score	**>= 0.88**	**0.9615**	**8,978 Holdout Test**	**EXCEEDED**
ROC-AUC Score	>= 0.92	0.9919	8,978 Holdout Test	EXCEEDED
Fake Class Precision	**>= 85.0%**	**96.13%**	**8,978 Holdout Test**	**EXCEEDED**
Fake Class Recall	>= 85.0%	96.17%	8,978 Holdout Test	EXCEEDED
Training Pipeline Time	**< 5.0 Minutes**	**3 min 48 sec**	**Full 44,889 Corpus**	**PASSED (CPU)**
Serialized Model Size	< 15 MB	400 KB (.pkl)	Disk Artifact	OPTIMIZED

2. PRD & TRD COMPLIANCE VERIFICATION

The project was engineered strictly against the specifications established in Team2_Fake_News_Detection_PRD_TRD_PD_2.md. Below is the verified requirements traceability matrix:

Req ID	Specification Description	Engineering Implementation	Verification Status
FR-1	CSV Dataset Ingestion & Merging	Ingests True.csv & Fake.csv, assigns labels 0/1, shuffles	PASSED (44,898 rows)
FR-2	Title + Body Feature Merge	Concatenates title and text into unified narrative column	PASSED (title_text)
FR-3	Regex Artifact & URL Cleaning	Strips http(s) links, HTML, and non-alphanumeric symbols	PASSED (0 web residue)
FR-4	WordNet Lemmatization & Stopwords	Reduces tokens to base roots; drops NLTK English stopwords	PASSED (Root normalized)
FR-5	Sublinear TF-IDF (1,2) N-Grams	10,000 feature sparse CSR matrix with log term-frequency	PASSED (10K features)

Req ID	Specification Description	Engineering Implementation	Verification Status
FR-6	MultinomialNB Baseline	Standard Laplace-smoothed generative baseline classifier	PASSED (95.56% Acc)
FR-7	ComplementNB Primary Model	Inverted class frequency estimation for imbalanced text	PASSED (95.66% Acc)
FR-8	5-Fold GridSearchCV Tuning	Exhaustive grid search across alpha [0.01, 0.1, 0.5, 1.0, 5.0]	PASSED (alpha=0.01 selected)
FR-9	Comprehensive Metric Logging	Computes Accuracy, Precision, Recall, Macro F1, and ROC-AUC	PASSED (Logged in stdout)
FR-10	Confusion Matrix Visualization	Seaborn heatmap with true/predicted label counts	PASSED (confusion_matrix.png)
FR-11	Multi-Model ROC Comparison	ROC curves plotting TPR vs FPR for all 3 model variants	PASSED (roc_curve.png)
FR-12	Learning Curve Diagnostic	Evaluates train vs validation scores across sample sizes	PASSED (learning_curve.png)
FR-13	Linguistic Word Clouds	Generates class-specific word frequency clouds	PASSED (wordcloud_*.png)
FR-14	Artifact Serialization	Joblib serialization of fitted model and vectorizer	PASSED (.pkl exported)
NFR-1	CPU Execution Constraint	Entire training pipeline completes in <5 minutes without GPU	PASSED (3 min 48 sec)
NFR-4	Cross-Validation Reliability	5-Fold CV standard deviation < 0.02 across folds	PASSED (std = 0.0028)
NFR-6	Deterministic Reproducibility	Fixed random_state=42 across all splits and models	PASSED (Fully deterministic)

3. DATASET TAXONOMY & NLP SANITATION PIPELINE

3.1 Corpus Overview & Class Distribution

The system utilizes the ISOT Fake News Dataset. The corpus is partitioned into authentic news articles (curated from Reuters news wires) and fabricated articles (flagged by PolitiFact, fact-checking organizations, and clickbait news aggregators).

Corpus Attribute	Authentic News (True.csv)	Fabricated News (Fake.csv)
Primary Ingestion Source	Reuters News Service	PolitiFact, Twitter, Clickbait Feeds
Article Record Count	21,417 articles (47.7%)	23,481 articles (52.3%)
Assigned Binary Label	Label 0 (Authentic / Real)	Label 1 (Fabricated / Fake)
Average Document Length	2,380 characters (~385 words)	2,540 characters (~420 words)
Linguistic Tone & Style	Neutral, institutional, declarative	Emotional, hyperbolic, sensationalist
Dominant Keyphrases	Reuters, said, government, official	Trump, video, shocking, watch, obama

3.2 The 6-Stage NLP Text Normalization Pipeline

Raw news articles contain substantial textual noise that inflates feature dimensionality without contributing semantic value. The clean_text_advanced() module executes six sequential transformations:

* **Stage 1: URL Stripping:** Regular expression pattern http[s]?://\S+ purges web links, protocol headers, and domain slugs.
* **Stage 2: Special Character Scrubbing:** Filters non-alphanumeric ASCII characters ([^a-zA-Z0-9\s]), removing punctuation marks, emojis, a
* **Stage 3: Case Folding:** Converts all tokens to lowercase, ensuring identical representations for 'President' and 'president'.
* **Stage 4: Stopword Elimination:** Cross-references tokens against NLTK's English stopword lexicon to filter structural filler words (e.g
* **Stage 5: WordNet Morphological Lemmatization:** Utilizes NLTK's WordNetLemmatizer to reduce plural inflections and tense conjugations to dictionary
* **Stage 6: Whitespace Compaction & Empty Row Pruning:** Collapses irregular spaces (\s+ -> ' ') and filters empty strings, retaining 44,889 high-quality docume

4. MATHEMATICAL FOUNDATIONS & MACHINE LEARNING ENGINE

4.1 Sublinear TF-IDF Feature Extraction

Text is converted into numerical feature vectors using Term Frequency-Inverse Document Frequency (TF-IDF). Standard linear term frequency is vulnerable to length distortion: an article repeating 'breaking' 25 times is not 25 times more fabricated than an article mentioning it once. Therefore, the pipeline applies Sublinear TF scaling:

```
TF_sublinear(t, d) = 1 + ln(TF(t, d))   if TF(t, d) > 0,   else 0
IDF(t, D) = ln[ (1 + |D|) / (1 + df(d, t)) ] + 1
```

By binding ngram_range=(1, 2), max_features=10000, min_df=2, and max_df=0.90, the pipeline captures informative bigram phrases (e.g., 'white house', 'breaking news', 'conspiracy theory') while purging rare typographical noise.

4.2 Complement Naive Bayes (CNB) Mathematical Formulation

Multinomial Naive Bayes estimates term probabilities theta_ci from within class c. In imbalanced text collections, weights become heavily skewed toward the majority class. Complement Naive Bayes (Rennie et al., 2003) overcomes this by estimating parameters using the complement of class c (all documents NOT belonging to class c):

```
theta_bar_ci = ( N_bar_ci + alpha ) / ( N_bar_c + alpha * |V| )
w_ci = ln(theta_bar_ci)   -->   Classify: c_pred = argmin_c [ sum_i ( t_i * w_ci ) ]
```

4.3 Why Naive Bayes Operates Without 'Epochs'

MATHEMATICAL CLARIFICATION: WHY NAIVE BAYES HAS NO TRAINING EPOCHS

The term 'epoch' applies exclusively to iterative gradient-based optimization algorithms (such as Neural Networks and SGD), which must repeatedly loop over data to adjust continuous weights via backpropagation. Naive Bayes is a closed-form probabilistic generative classifier based on Bayes' Theorem. It counts word co-occurrences in a single deterministic pass and solves likelihoods algebraically via simple division. Therefore, epochs do not exist for Naive Bayes; training completes instantaneously.

5. EMPIRICAL BENCHMARKS & VISUAL DIAGNOSTICS

5.1 Model Comparison on Unseen Holdout Test Partition (8,978 Samples)

Metric Parameter	MultinomialNB (Baseline)	ComplementNB (Default)	Best ComplementNB (Tuned)
Smoothing Parameter (alpha)	1.0 (Default)	1.0 (Default)	0.01 (Optimized)
Classification Accuracy	95.56%	95.66%	96.16% (+0.60%)
Precision (Macro Avg)	95.54%	95.63%	96.13% (+0.59%)
Recall (Macro Avg)	95.55%	95.67%	96.17% (+0.62%)
F1-Score (Macro Avg)	0.9555	0.9565	0.9615 (+0.0060)
ROC-AUC Score	0.9897	0.9897	0.9919 (+0.0022)
5-Fold Cross-Validation	0.9542 (+/- 0.0031)	0.9551 (+/- 0.0029)	0.9608 (+/- 0.0028)

5.2 Error Pattern Analysis: Confusion Matrix & ROC Curves

Below are the primary visual diagnostic artifacts generated by the pipeline. The confusion matrix confirms symmetrical, well-balanced error distributions (under 3.9% false positive and false negative rates), while the ROC curve demonstrates near-perfect discriminative capability across all decision thresholds.

Figure 1: Confusion Matrix (Holdout Test)






Figure 2: Multi-Model ROC Comparison



5.3 Overfitting vs. Underfitting Diagnosis: Learning Curve

The learning curve tracks training score and 5-fold cross-validation score as training data expands from 10% to 100%. The rapid convergence and narrow confidence band prove that the model does not suffer from high bias or high variance.

Figure 3: Learning Curve (5-Fold CV Convergence Diagnostic)


Learning Curve - Best ComplementNB
Training Score
Cross-Validation Score
F1-Macro Score
0.975
0.970
0.965
0.960
0.955
5000
10000
15000
20000
25000
30000
Training Set Size

5.4 Linguistic Feature Divergence: Lexical Word Clouds

Word clouds illustrate the distinct vocabulary features captured by the TF-IDF matrix. Fabricated articles rely heavily on informal political figures and hyperbolic media references ('trump', 'video', 'watch', 'hillary', 'obama'), whereas authentic news articles center on formal governance and wire reporting terms ('reuters', 'said', 'state', 'government').

Figure 4A: Fabricated News Vocabulary




Figure 4B: Authentic News Vocabulary



6. ADVERSARIAL NOISE & ROBUSTNESS STRESS TESTING

6.1 Noise Injection Methodology (src/generate_noisy_data.py)

Real-world data arriving from web scrapers, social media, and OCR contains typos, missing words, and spelling mistakes. To test system durability, 10% of all tokens in the dataset were subjected to random character swaps ('president' -> 'presdient'), letter omissions ('election' -> 'eletion'), or complete token deletions.

6.2 Robustness Benchmark on Unseen Noisy Test Set (8,978 Samples)

Evaluated Pipeline Model	Test Data Condition	Test Accuracy	Macro F1-Score
Clean Model (Base Reference)	Clean Holdout Test Set	96.16%	0.9615 (100% Ref)
Clean Model (Zero-Shot Noisy)	**10% Corrupted Holdout Test**	**95.95%**	**0.9594 (99.78% Retention)**
Noisy Model (Retrained)	10% Corrupted Holdout Test	95.87%	0.9586 (99.70% Retention)

Finding: The clean model retains 99.78% of its original performance even when exposed to heavy typographical noise. Because articles average 380-420 words, corrupting 10% leaves over 90% of distinctive unigrams and bigrams completely intact, allowing the Bayesian log-likelihood summation to make highly resilient, accurate classifications.

Figure 5A: Noisy Model Confusion Matrix





Figure 5B: Noisy Model ROC Curve



7. PROCESS FLOW & DUAL-PERSPECTIVE EXPLANATIONS

7.1 Real-World Article Walkthrough

Consider an incoming unverified article:
Headline: 'BREAKING: Secret Alien Treaty Signed By White House!'
Body: 'Washington (Reuters) - Reports surfaced on http://conspiracy-leak.net claiming officials finalized an unverified accord yesterday.'

Track A: Technical Engineering Explanation (Pointwise)

1. Ingestion: combine_features() null-coalesces title and body into a unified string.
2. URL Stripping: re.sub() strips http://conspiracy-leak.net, eliminating web noise.
3. Punctuation Scrubbing: Regex strips exclamation points, colons, and hyphens into whitespace.
4. Morphological Lemmatization: WordNetLemmatizer maps 'reports' -> 'report' and 'officials' -> 'official'.
5. Stopword Filtering: Structural tokens ('by', 'on', 'an') are filtered using NLTK English stopwords.
6. TF-IDF Projection: TfidfVectorizer scans the clean string against the 10,000-term dictionary, activating high-weight unigrams ('secret', 'alien', 'treaty') and bigrams ('white house').
7. Bayesian Inference: ComplementNB sums complement log-weights. The score for Fake (+142.8) surpasses Real (+118.2).
8. Output: Article is classified as Label 1 (Fabricated News) with 98.4% posterior probability confidence.

Track B: Executive & Conversational Pitch (Interview & Manager Points)

Q: What business problem does this project solve?
A: Fake news spreads faster than human fact-checkers can review it. While deep learning models can flag it, they are expensive black boxes requiring costly GPUs. We built an ultra-fast, interpretable AI system that runs on standard CPUs, processes thousands of articles in seconds, and achieves over 96% accuracy.

Q: How does the model turn words into numbers?
A: Computers cannot read text directly, so we use TF-IDF. Think of it as a smart word counter: it gives high weight to words that are rare and distinctive (like 'alien' or 'conspiracy') while down-weighting words that appear everywhere.

Q: Why Naive Bayes instead of a deep Neural Network?
A: Speed, cost, and explainability. Naive Bayes calculates word probabilities in a single pass -- it doesn't need iterative training loops or epochs. It trains across 45,000 articles in under 4 minutes, costs practically nothing to host, and allows editors to inspect the exact words that triggered the flag.

Q: How does it handle messy social media text with typos?
A: We stress-tested it by corrupting 10% of all words across the dataset. The accuracy barely dropped -- moving only from 96.16% to 95.95%. Because news articles contain hundreds of words, the model has plenty of uncorrupted text to make an accurate call.

8. CODEBASE ARCHITECTURE & ENGINEERING AUDIT LOG

8.1 Repository File Catalog

File Path	Component Role	Primary Operational Responsibility
src/main_pipeline.py	Core Pipeline	End-to-end ingestion, lemmatization, TF-IDF, GridSearchCV tuning, and exports
src/generate_noisy_data.py	Noise Synthesizer	Injects 10% adversarial typo and token corruption into raw CSVs
src/noisy_pipeline.py	Noisy Benchmark	Trains and evaluates models on corrupted datasets for stress-testing
src/evaluate_robustness.py	Harness Benchmark	Runs clean and noisy models head-to-head on the 20% holdout test partition
src/generate_report.py	PDF Publisher	Compiles metrics, architecture text, and PNG plots into executive reports
docs/PRD_TRD_PD_2.md	Specifications	Formal Product and Technical Requirements Documents with RACI matrix
docs/Final_Project_Report.md	Project Summary	Audit trail, executive summary, and verified hyperparameter records
docs/Model_Optimization_QnA.md	Strategic Review	Deep dive on concept drift, live web scraping, and LLM-generated fake news

8.2 Bug Audit & Engineering Resolutions

Defect Area	Root Cause Identified	Engineering Resolution Implemented
requirements.txt	Missing fpdf2 library	Added fpdf2; eliminates ModuleNotFoundError on clean checkout
NLP Preprocessing	WordNetLemmatizer instantiated 45,000x	Extracted LEMMATIZER and STOP_WORDS to module scope; 3.5x speedup
evaluate_robustness	df.sample(0.2) caused data leakage	Replaced with split_data(df) holdout split; ensures scientific rigor
generate_noisy_data	.astype(str) turned NaN into "nan"	Added .fillna("") prior to noise injection; purged unused imports
Directory Safety	Missing os.makedirs before writes	Embedded automatic recursive directory creation for models/, outputs/, docs/
Path Portability	CWD-dependent relative paths	Resolved all paths using Path(__file__).resolve().parent

9. STRATEGIC ROADMAP & PRODUCTION HARDENING

9.1 Out-of-Vocabulary (OOV) Vulnerability & Concept Drift

Because TF-IDF relies on a fixed 10,000-term vocabulary derived from 2016-2018 news, emerging terms (e.g., 'ChatGPT', 'COVID-19', modern political figures) will be ignored. Production deployments require automated weekly retraining pipelines and sub-word Byte-Pair Encoding (BPE).

9.2 Defending Against LLM-Generated Misinformation

Modern fake news produced by generative AI exhibits professional grammar and neutral tone, evading simple spelling

and exclamation-mark heuristics. Future iterations should incorporate stylometric meta-features (syntactic parse tree depth, perplexity scores) and hybrid ensemble voting with lightweight transformer backbones (DistilBERT).

9.3 Probability Calibration & Live Web Scraping

Naive Bayes is an aggressive estimator that pushes posterior probabilities to 0% or 100%. Before deploying live web scraping (via newspaper3k or BeautifulSoup), the classifier should be wrapped in CalibratedClassifierCV (Platt Scaling) to ensure confidence percentages reflect empirical probabilities, enabling fine-grained human review thresholds.