Unsupervised Visual Anomaly Detection for Industrial Quality Inspection

Teammate Presentation & Viva Preparation Guide (PatchCore vs. EfficientAD)

Subject: Computer Vision (AIM3003) | **Institution:** D Y Patil International University, Pune | **Team:** Vikrant Bendre, Puja Madan, Sourabh Tatiya, Prashant Dandade

Part 1: The 2-Minute Intuition (Explain Like I'm 10)

The Factory Dilemma: Imagine a plant producing 10,000 glass bottles every hour. A cracked bottle will explode on retail shelves; a contaminated bottle ruins liquid medicine. Human eyes get fatigued after 20 minutes and miss subtle micro-flaws.

Why Normal Supervised AI (YOLO) Fails: Supervised deep learning needs thousands of examples of both 'Good' and 'Defective' products. But in real factories, defect rates are <0.1% (defects are extremely rare). Furthermore, defects have infinite unpredictable shapes (cracks, bubbles, dirt, chips). An unseen flaw causes YOLO to fail silently.

The One-Class Unsupervised Solution: We train the AI *strictly on perfect (normal) bottles*. It memorizes normal clean glass, normal caps, and normal curves. When inspecting a new bottle, any region that deviates significantly from the memorized baseline is flagged as a **DEFECT** and pinpointed on a heatmap.

Part 2: Technical Computer Vision Concepts Demystified

Technical Term	Plain English Meaning	Why We Use It In This Project
Patch Token	A tiny local sub-window of an image (e.g. 16x16 pixels).	Flaws are local (a 2mm crack on a 200mm bottle). We must inspect patches, not just the whole photo.
Layer Hooks	Probes attached inside ResNet to intercept intermediate feature maps.	Final layers classify ImageNet objects. Intermediate layers (layer 2 & 3) store raw textures, edges, and shapes.
Memory Bank	A stored array of feature vectors representing normal patches.	Acts as the AI's golden reference library of what normal glass looks like.
Johnson-Lindenstrauss Projection	Compresses vectors from 384 dimensions to 128 dimensions.	Preserves Euclidean distances while slashing distance calculation overhead by ~66%.
Greedy k-Center Coreset	An iterative min-max algorithm that picks the 1% most diverse patches.	Compresses 163,856 normal vectors down to 1,638 representative centers without losing accuracy.
Euclidean Distance	Geometric distance between query patch and nearest memory patch.	Distance = Anomaly Score. Normal matches closely (~1.30); cracks have high distance (~3.28).
Gaussian Smoothing	Convolving a 2D Gaussian filter (sigma = 4) over the raw anomaly map.	Suppresses high-frequency single-pixel noise and unifies contiguous defect boundaries.
Distillation (EfficientAD)	A smaller Student network is trained to mimic a Teacher network.	Replaces memory search with a single forward CNN pass for sub-10ms conveyor inspection.

Part 3: Slide-by-Slide Presentation Scripts (Template-Compliant 14 Slides)

The presentation is divided across 4 speakers so all team members contribute equally:

Speaker 1: Vikrant Bendre (Slides 01 - 04)

Slide 01: Title Slide

"Good morning respected panel. Our team project is titled 'Unsupervised Visual Anomaly Detection for Industrial Quality Inspection: An Accuracy-Latency Comparison of PatchCore and EfficientAD' under our Computer Vision course. I am Vikrant Bendre, and my teammates are Puja Madan, Sourabh Tatiya, and Prashant Dandade."

Slide 02: Introduction

"Visual inspection is the primary barrier preventing defective products from reaching consumers. However, defects in factories are rare and unpredictable. Our project introduces an unsupervised visual inspection system: we train our model strictly on defect-free parts to automatically flag and localize anomalies on an explainable heatmap."

Slide 03: Problem Statement

"Currently, factories either use human visual inspectors—who suffer from eye fatigue and inconsistency—or supervised deep learning like YOLO. But supervised models fail because you cannot collect thousands of defective samples when the scrap rate is <0.1%. If an unseen crack appears, YOLO fails silently. Our project addresses this defect scarcity gap."

Slide 04: Motivation

"In aerospace fasteners or pharmaceutical vials, a single missed crack causes life-threatening disasters and expensive recalls. This project provides QA engineers with automated 24/7 inspection, zero defect data requirements, and complete traceability."

Speaker 2: Puja Madan (Slides 05 - 07)

Slide 05: Objectives

"Our project has five concrete objectives: First, design and implement PatchCore from scratch in PyTorch without using wrapper libraries. Second, optimize its memory bank by 99% using greedy k-Center subsampling. Third, validate it on MVTec AD and benchmark against EfficientAD. Fourth, calculate AUROC, latency, and memory metrics. And fifth, develop an interactive Streamlit UI with SQLite audit logging."

Slide 06: Scope

"In terms of scope: we implement PatchCore from scratch, evaluate across all 15 MVTec AD categories, benchmark EfficientAD on 5 representative categories, and build a working Streamlit dashboard. Physical hardware conveyor belts and 3D point cloud sensors are kept outside the 12-week mini-project scope."

Slide 07: Methodology

"Our methodology follows 5 steps: First, standardize MVTec images and align pixel ground-truth masks. Second, attach PyTorch hooks to ResNet layers 2 and 3 and pool local 3x3 neighborhoods. Third, compress over 163,000 patch features down to a 1% coreset using Johnson-Lindenstrauss projection and greedy k-Center clustering. Fourth, benchmark against EfficientAD's student-teacher network. And fifth, deploy into our Streamlit UI."

Speaker 3: Sourabh Tatiya (Slides 08 - 10)

Slide 08: Working Principle

"Here is how our system works step-by-step: The operator uploads an image. Our model extracts patch features and calculates their Euclidean distance to the nearest normal patch in our stored memory bank. Normal patches have low

distance (~1.30), while defects have high distance (~3.28). Distances are smoothed with a Gaussian filter and overlaid as a JET heatmap. If the maximum score exceeds our 2.5 threshold, it's flagged as DEFECT and logged into SQLite."

Slide 09: Applications

"This technology is directly applicable across high-reliability industries: inspecting aircraft engine turbine blades and fasteners in aerospace, checking cracked glass vials in pharmaceuticals, detecting missing solder joints in semiconductor PCBs, and inspecting automotive engine parts."

Slide 10: Advantages

"The key advantages are: 1) Zero defect training data needed; 2) Detects novel, unseen defect types; 3) 99% memory reduction through coreset selection; 4) Zero training epochs required for PatchCore; 5) Visual explainability via heatmaps; and 6) Automated SQLite logging for industrial compliance."

Speaker 4: Prashant Dandade (Slides 11 - 14)

Slide 11: Limitations

"We acknowledge current limitations honestly: First, PatchCore takes around 2.2 to 2.5 seconds per frame on CPU, which requires GPU or INT8 quantization for ultra-high-speed lines. Second, severe part rotation can cause false alarms. Third, EfficientAD requires around 70,000 iterations of GPU training per class. And fourth, 2D vision cannot inspect internal sub-surface voids."

Slide 12: Conclusion

"In conclusion, we achieved all our project objectives. We verified our from-scratch implementation on the MVTec bottle dataset: defective bottles scored 3.28, while normal bottles scored 1.30, providing a clear 1.98 decision margin against our 2.5 threshold. Our primary learning outcome was understanding the real-world trade-off between zero-shot memory banks and millisecond distillation models."

Slide 13: Future Scope

"For future work, we plan to apply INT8 quantization to achieve sub-50ms CPU inference on edge devices like Raspberry Pi, build a unified multi-class model covering all 15 classes at once, integrate 3D point clouds, and connect our database to industrial PLCs via Modbus to trigger physical pneumatic rejection arms."

Slide 14: References

"Here are our peer-reviewed references from CVPR, WACV, ICPR, and ECCV. Thank you for your time, and we are now ready for your questions."

Part 4: Professor Viva Defense (Tough Questions & Exact Answers)

Q1: Why not just use Anomalib? Anyone can pip install anomalib!

Answer: Sir/Ma'am, Anomalib is an evaluation library that hides inner mechanics behind high-level wrappers. To demonstrate thorough architectural understanding for this Computer Vision course, we implemented PatchCore from scratch in pure PyTorch. We wrote the custom layer hooks, neighborhood pooling, Johnson-Lindenstrauss random projection, and greedy k-Center subsampling ourselves. We only reference Anomalib as an external gold standard to verify our numbers.

Q2: Why compare two existing models instead of proposing a new one?

Answer: In industrial computer vision, the bottleneck is not inventing arbitrary architectures, but solving the Accuracy vs. Latency engineering trade-off. PatchCore gives near-perfect 99.1% AUROC with zero training

epochs, but query latency and memory are high. EfficientAD claims sub-10ms latency using student-teacher distillation, but requires heavy training. Our project provides an empirical engineering evaluation under lighting shifts and few-shot data to help manufacturing engineers choose the right architecture for their hardware budget.

Q3: What is the difference between Image-level AUROC and Pixel-level AUROC?

Answer: Image-level AUROC measures classification: Did the model correctly tell whether the entire bottle is defective or good? Pixel-level AUROC measures localization: Did the model correctly identify the exact pixels belonging to the crack? We also evaluate Per-Region Overlap (PRO) so small micro-cracks are evaluated fairly against large background areas.

Q4: Why do you use intermediate layers (layer 2 and layer 3) instead of the final layer?

Answer: The final layer of ResNet is trained on ImageNet to output abstract object categories (like 'dog' or 'bottle'). It throws away fine spatial details. Intermediate layers retain spatial coordinates: layer 2 captures low-level edge and texture details, while layer 3 captures mid-level structural geometry. Combining both gives us the best representation of normal surfaces.

Q5: What is the purpose of the Johnson-Lindenstrauss lemma in your coreset algorithm?

Answer: Our extracted patch vectors have 384 dimensions. Running greedy k-center clustering on 163,000 vectors in 384 dimensions is computationally slow. By the Johnson-Lindenstrauss lemma, we can project these vectors into a 128-dimensional space using a sparse random matrix while preserving pairwise Euclidean distances with negligible distortion. This speeds up coreset subsampling by over 60%.

Q6: Why do you apply a Gaussian filter to the anomaly map?

Answer: Raw nearest-neighbor distances are calculated on a coarse 28x28 grid. Upsampling this directly to 224x224 produces blocky pixelated artifacts and isolated single-pixel false alarms. A 2D Gaussian filter (sigma = 4) smooths out high-frequency noise spikes, creating a continuous, coherent defect boundary that factory operators can easily interpret.

Q7: Why did you use SQLite? Why not a CSV file or MongoDB?

Answer: In aviation and medical manufacturing (referencing standards like GE Aerospace), inspection records must be ACID-compliant, structured, and auditable. A flat CSV file can suffer from file-lock corruption during rapid parallel writes, whereas full client-server databases like MongoDB or PostgreSQL introduce unnecessary server overhead. SQLite is self-contained, serverless, zero-configuration, and embeds directly into industrial edge inspection terminals.

Part 5: 60-Second Live Demonstration Script

1. Open PowerShell and run: cd C:\Users\Lenovo\.gemini\antigravity\scratch\industrial_ad followed by streamlit run app.py.
2. The app opens at http://localhost:8501.
3. **Select Defect Sample:** Choose bottle/test/broken_large/000.png from the dropdown. Point out the Anomaly Score (**3.28**) and the red alert **DEFECT** verdict, pointing to the red heatmap spot over the broken rim.
4. **Select Normal Sample:** Choose bottle/test/good/000.png. Point out the low score (**1.30**) and green **PASS** verdict with a cold blue heatmap.
5. **Log to Database:** Click *'Log Inspection Verdict to SQLite Audit Database'* and show the new row instantly appear in the audit trail table below.