

Product Specifications

Electric Vehicle Charger

C2BK480018 48V/18A Charger

Type: Off-board Charger

Applications: EV battery charger



C2BK480018 48V/18A Charger





SALIENT FEATURES



Battery reverse protection

Protects charger as well as battery when connected with reverse polarity.



All weather design

Hot, cold, humid or rainy, our products can be designed to meet any requirements.



Temperature based profile selection Change the charging profile automatically to suit different ambient temperatures.



Zero start mode

Charge a deep discharged battery automatically.



Over charge protection

Protect the battery against over charging with auto cut-off feature.



Auto cut-off

Turn off the charging when battery is fully charged.

C2BK480018 48V/18A Charger



SPECIFICATIONS

AC Input

Voltage - Range : 170 - 275 VAC

Nominal Voltage : 230 VAC

Frequency : 47Hz -63 Hz

Maximum Current : ≤9A @170 VAC & O/P at full load

DC Output

Maximum Voltage : $65V \pm 0.5V$ Maximum Current : $18A \pm 0.5A$

Line & Load Regulation : <2V%

Protections

Output over load : Available
Output short Circuit : Available
Output Over Voltage : Available
Over Temp. with auto Recovery : Available
Reverse Polarity : Available

Environmental

Operating Temperature : 0°C To + 50°C

Mechanical

Dimensions : TBD Weight : TBD

AXIOM ENERGY CONVERSION LTD.

Plot No.207/4&5, Phase-II, IDA, Cherlapally, Hyderabad-500051, Telangana, INDIA.

Toll Free: 1800-572-4748. Mobile: 99590 55158 Email:sales@axiomevproducts.com