

# Product Specifications

Electric Vehicle Charger

C2AK600015  
60V/15A Charger

Type: Off-board Charger

Applications: EV battery charger




# C2AK600015

## 60V/15A Charger



### SALIENT FEATURES



#### Battery reverse protection

Protects charger as well as battery when connected with reverse polarity.



#### Over charge protection

Protect the battery against over charging with auto cut-off feature.




#### Surge capability

Withstand the input power fluctuation even in the most thunder prone regions of the country



#### Auto cut-off

Turn off the charging when battery is fully charged.



#### Over temperature protection

Protects the charger from extreme temperatures with auto cut-off.



#### Bump and Vibration

Capable of meeting the bumps and vibrations of Indian village roads.

# C2AK600015

## 60V/15A Charger



### SPECIFICATIONS

#### AC Input

Voltage - range	: 170 - 275 VAC
Nominal Voltage	: 230 VAC
Frequency	: 47Hz - 63Hz
Maximum Current	: <11A rms @ 170 VAC & O/P at full load

#### DC Output

Maximum Voltage	: 81V $\pm$ 0.5V
Maximum Current	: 15A $\pm$ 0.5A
Line & Load Regulation	: <2%

#### Protections

Output over load	: Available
Output short Circuit	: Available
Output Over Voltage	: Available
Over Temp. with auto recovery	: Available
Reverse Polarity	: Available

#### Environmental

Operating Temperature	: 0°C to +50°C
-----------------------	----------------

#### Mechanical

Dimensions	: L-275mm, W-150mm, H-90mm
Weight	: 3.5kg appx

---

### AXIOM ENERGY CONVERSION LTD.

Plot No.207/4&5, Phase-II, IDA, Cherlapally, Hyderabad-500051, Telangana, INDIA.

Toll Free: 1800-572-4748. Mobile: 99590 55158 Email:sales@axiomevproducts.com