

Usenet Ultimate v1.4.0

Enterprise Grade Performance, Reliability, and Compatibility

Hey everyone! I'm back with the latest update for Usenet Ultimate. It's a big one!

For those that don't know, Usenet Ultimate is a self-hosted Stremio add-on for streaming Usenet content. It searches indexers (Newznab/Prowlarr/NZBHydra) and EasyNews, sends NZBs to NZBDav for virtual mounting, and streams the resulting video files back through Stremio (or other Stremio add-on supported apps) via a WebDAV proxy or a direct redirect to the WebDAV mounted address.

Usenet Ultimate is the original home of features like NZB Fallback, Proxy-less WebDAV Streaming Mode, Dedicated Season Pack Support, Smart Mode Health Checking, Auto Indexer Capability Discovery, NZB Databases, Reboot/Remake Detection, NZB Fallback Auto-Resolve, and more!

The GitHub repository for this project is here:

<https://github.com/DSmart33/Usenet-Ultimate>

If you're interested in this project, I would love it if you joined the Discord community here:

<https://discord.gg/6RPVSeg56v>

If you're interested in supporting my development of Usenet Ultimate, you can do so here:

<https://ko-fi.com/dsmart33>

v1.4.0 brings enterprise grade performance, reliability, and compatibility to Usenet Ultimate, while also adding an extensive list of features and improvements. As always, thank you to the Usenet Ultimate community and beta testers for making development so much fun!

First, for those that don't want to know the specifics, here's the TLDR:

Flagship Features:

- **Ultimate Fallback**

- Ultimate Library
- Regex and SEL Rules Engines (& tamtaro Movie/TV Compatibility)
- Apple Device: Fusion → Infuse Compatibility
- Series Pack Support
- Anime+Non-English Remake / Reboot Detection Filtering
- Alias Title Fallback
- Series Pack Support

Other Features:

- WebDav Is The Single Source Of Truth
- Dynamic Base URL - Port Awareness
- BF: Significant reduction in system resources on dashboard
- UI Improvements
- PWA back-button reliability
- Proxy performance improvements and more configurations
- In-Progress Playback Survives Addon Restarts
- Ultimate Text Search improvements
- Absolute Episode-Numbering Fallback for Ultimate Text Search
- Parallel Alternate Title Search
- Display Library In Results
- Per-Indexer Search Timeouts
- TVDB API Key Auto Update
- Always Resolve TVDB Title in English
- NZB Fallback removed, replaced by Ultimate Fallback
- 416 recovery on mid-stream fallback redirects
- Clear Search Cache also drops resolved UF sessions
- 7z Archive parsing Improvements
- Archive inspection full provider support
- Smart Mode Minimum Healthy Threshold
- Expanded batch size range
- Cross-batch counter
- Episode-specific dead files no longer ban the whole season pack
- Dead NZB DB Shows Indexer + Size
- Cache 0-result searches toggle
- Baseline Junk Filter
- Title Filter Updates
- Prefer Season Packs
- Metadata Parser Improvements
- Remake Detection log fix
- Prefer Library Results toggle (Global)
- Max Series / Season Packs cap (TV-only)
- Indexer buffered logging
- Parallel Searches Across All Searchers

- **Per-Indexer Search Method fixes and improvements**

1) General

- **Apple Device: Fusion → Infuse Compatibility**

- v1.4.0 fixes an iOS external-player compatibility issue where streams would fail with "Failed to open input stream in the demuxing stream" when Fusion handed the URL off to Infuse on Apple devices.
- URL truncation at the first &
 - Fusion's handoff chain to Infuse truncates the stream URL at the first & separator.
 - UU was packing 7+ query parameters (?nzb=...&title=...&type=...&indexer=...&fbg=...&sk=...&user_pick=1), so everything after nzb=... was dropped by the time the request reached the server. The handler couldn't resolve the click and returned a 400.
 - Usenet Ultimate URLs are now packed into a single t query parameter:
 - /stream/<filename>?t=<fbg>.<idx>.<sessionKey>.<season>.<episode>.<sp>.<epcount>
 - Candidate data (nzbUrl, title, indexer) is resolved server-side from the fallback group using the packed fbg hash and candidate index.
 - t-param survives fallback-group expiry
 - The packed t parameter also carries base64url-encoded url/title/indexer after the positional fields.
 - If the in-memory fallback group has been evicted by the time a tile is clicked (e.g. the search page sat open longer than the group TTL), the handler decodes those trailing fields and still attempts a single-shot resolution instead of returning 400.

- **Logging**

- A new /stream entry log surfaces the tile type, filename, query keys, and User-Agent for every hit:
 -  /stream hit: kind=user_pick filename=... q=[t] ua=Infuse/8.4.5628
 - This is the log that identified Infuse as the truncation culprit in the first place (the log showed q=[i] where we expected q=[i, type, fbg, sk, user_pick]). Throttled to first-hit-per-15s per (kind, filename) so Range-probe bursts during playback don't spam logging.

- **Net effect**

- Fusion → Infuse on Apple devices now plays both Ultimate Fallback tiles and individual stream tiles with full functionality. VLC, IINA, Android ExoPlayer, Stremio's other internal players, etc are unaffected.

- **WebDav Is The Single Source Of Truth**

- WebDAV is the single source of truth for every cache layer
 - In v1.3 the library check was authoritative at the prepare step, but every cache layer sitting in front of it could still serve a stale video path after NZBDav evicted a file. The readyCache returned cached StreamData immediately on hit, the lobby's cached primary, the 10-minute dedup map, and the UF backup filter all trusted their stored entries and only fell back through an in-memory broken-path marker that was set after a 5xx.
 - In v1.4 every cache layer verifies live against WebDAV before serving. The readyCache short-circuit is removed, and the dedup map, lobby primary, and UF backup filter all gate on a live videoPathExists PROPFIND.
 - The in-memory broken-path marker is gone.
 - If a file was just removed from NZBDav, the next request self-heals through a fresh candidate loop instead of serving stale bytes.

- **Dynamic Base URL - Port Awareness**

- When running behind a reverse proxy on a non-standard HTTPS port, the addon was constructing stream URLs without the port number, assuming 443.
- Base URL resolution now uses X-Forwarded-Port when the Host header doesn't already include one, builds the correct host:port combination, and skips the port if it's the default for the protocol (443 for HTTPS, 80 for HTTP).
- IPv6 hosts are handled correctly: bracketed addresses like `:::1` are detected as port-less and `:::1:8080` as port-bearing.
- `BASE_URL` is still the explicit override when set.

- **Series Pack Support**

- The library scans now support series packs, which are multiple seasons packed into one nzb.
- Series Pack searching is an additional query option.

2) Existing UI Changes

- Better filter stream titles
 - The Stream Filter titles are updated to better represent what they actually are.
- Health Checks Overlay
 - The connection count in the Health Checks overlay now reflects batch size × number of enabled pool providers. Previously, it showed just the batch size, which understated the real connection load when multiple providers were enabled.
- Health Checks
 - Add auto-queue dedup and serialization to prevent silent (harmless) NZBDav 500s

- Reboot / Remake Detection
 - Moved to the filters overlay within the stream filters section
- Allow Multi-Episode Files
 - Moved to the filters overlay within the stream filters section
- Max Filters
 - The 3 Max Filters now exist within a Max Filters box to match the aesthetic of the rest of the filters.
- Provider Manager (Ultimate Fallback + Health Checks overlays)
 - Provider rows use a compact pill toggle in the overlay's accent color (amber for Ultimate Fallback, pink for Health Checks).
 - The per-row connection-test dot was removed, the full status still shows in the expanded edit form.
 - Provider description shortened and "Add Provider" restyled as an accent-tinted button.
 - The delete-confirmation dialog now correctly centers on the viewport (it was being trapped by the parent overlay's animation transform).
- Health Checks Overlay
 - The entire overlay now dims when disabled.
- Index Manager Overlay
 - Reorganized into discrete titled cards:
 - Season Packs and Results Deduplication (URL + Indexer Priority) are now their own boxes matching EasyNews.
 - All primary controls converted from checkboxes to pill toggles for consistency, and the Season Packs / EasyNews pagination toggles follow the same label-left / toggle-right layout.
 - Anime is now its own card

- Results deduplication is its own card containing both:
 - URL Deduplication
 - Indexer Priority Deduplication
- Season packs visual display in nzb databases were including the regex
 - This visual bug is fixed and you'll no longer see the regexes in the db
- The Dashboard tile now displays the active method next to the NZBDav label (e.g., "NZBDav + Pipe"). The tile updates live when you change the method in any overlay.
- PWA back-button reliability
 - Pressing back twice to leave overlays that are 2 from the dashboard in standalone PWA mode would exit the app instead of closing the second-to-last open layer.
 - The history sentinel that guards against accidental exit is now pushed at the moment a layer is opened (overlays, modals, indexer panels, tab switches) rather than from inside the back-button handler, so the guard is in place before the next press arrives instead of racing it. Each open layer gets its own sentinel, each back press consumes one, and the cascade unwinds cleanly through nested overlays without the previous timing edge case.
- Pagination steppers everywhere
 - Season-pack, series-pack, EasyNews session-wide pagination, and per-indexer pagination (Newznab, Prowlarr-synced, NZBHydra-synced rows) now use the same +/- stepper as the timeout fields, replacing raw number inputs. TimeoutStepper gained unit/ariaLabel/compact props for reuse, and a thin PagesStepper wraps it with row-bound hold-repeat.
- Dashboard performance draw
 - The dashboard previously ran an infinite animate-gradient on the root viewport, multiplied by backdrop blur on every .card, the sticky header, ambient glow blobs, and animate-pulse decorative overlays.

- To give the tiles more life static gradient panels and per-tile colored icon chips are added. The animate-gradient root, backdrop-blur-xl on cards/headers, ambient blur-3xl glow blobs, and decorative animate-pulse overlays are removed. Status pulses on the green dots are removed too.
- Install Tab: The nested backdrop-blur has been removed. Each manifest row gets a cast icon chip.
- Ko-fi support link in install tab
 - The install tab now carries a Ko-fi support link.
- Naming consistency: NzbDAV everywhere
 - NzbDAV was rendered as a mix of "NZBDav" and "NzbDav" across the dashboard, overlays, and modals. All user-visible strings now read NzbDAV consistently. The redundant "(Hosted)" suffix on the streaming-mode option is dropped so the dropdown reads just "NzbDAV".
- Pack naming alignment
 - All "Season Pack" labels have been updated to "Season Pack" / "Series Pack" labels along with tooltips.

3) Streaming Methods and Performance Improvements

- The Proxy/Direct toggle has been replaced with a three choice Streaming Method selector:
 - Pipe, Dual-Stage Proxy, and Direct.
- With the inclusion of NZB backups it allows lower resource instances to have an similar experience to those with more resources.
 - The ability to resolve backups proactively with a restriction on the container type means instant fallback.
 - **Pipe:**
 - Added for broader compatibility. This streams through a local pipe with buffering (1–16 MB, default 8 MB) and automatic reconnection. Node handles backpressure automatically. This

proxy uses the fewest resources and has no request manipulation or suppression.

- **Dual-Stage Proxy (was and still is the default proxy method):**
 - The existing two-stage buffered proxy with manual flow control (8–256 MB, default 128 MB).
 - The existing two-stage buffered proxy with manual flow control (8 to 256 MB, default 128 MB).
 - Stage 1 pre-fetches upstream bytes into the buffer ahead of the player.
 - Stage 2 delivers from the buffer with soft backpressure.
 - The pre-fetch absorbs upstream stalls (WebDAV hiccups, slow articles, brief network blips) so they never reach the player.
- **Direct:**
 - The player is redirected to the WebDAV URL directly.
 - Only select Stremio applications support this as the player must support credentials (WebDav credentials) embedded in the URL.
- The Streaming Method selector appears in the Ultimate Fallback overlay.
- Pipe and Dual-Stage Proxy have a shared buffer slider that dynamically adjusts its range (1–16 MB for Pipe, 8–256 MB for Dual-Stage Proxy) and is hidden entirely in Direct mode.
 - Buffer values are shared across all overlays, changes in one are reflected in the others.
- Appears in both the Ultimate Fallback and Streaming Mode overlays.
- The Dashboard tile now displays the active method next to the NZBDav label (e.g., "NZBDav + Dual-Stage Proxy"). The tile updates live when you change the method in any overlay.
- Direct mode confirmation prompt.
 - Selecting Direct as the streaming method now opens a small confirmation modal that explains what direct mode does and lists the two best practices to follow when your NzbDav is accessible remotely:
 - keep your NzbDav admin login and WebDAV user on different credentials.

- Leave NzbDav's "Enforce Read Only" WebDAV option enabled.
The streaming-method description below the radios also calls out that WebDAV credentials are embedded in the redirect URL.
- Migration is automatic:
 - NZBDAY_PROXY_ENABLED=true → Dual-Stage Proxy
 - NZBDAY_PROXY_ENABLED=false → Direct
 - (unset) → Dual-Stage Proxy
- The legacy NZBDAY_PROXY_ENABLED env var still works.
 - True is still Dual-Stage
 - False is still Direct
- New env vars:
 - NZBDAY_STREAMING_METHOD (pipe | proxy | direct)
 - NZBDAY_PIPE_BUFFER_MB (1–16).
- Proxy Correctness:
 - Always advertise Accept-Ranges: bytes.
 - This is used to know the stream is seekable.
 - Guarded 200 → 206 upgrade:
 - if NZBDav returns 200 OK with a parseable Content-Range header AND the client sends a Range request, /v upgrades to 206 Partial Content so range-aware players don't reject the status/header mismatch.
 - The guard is strict, without a client Range, a 200 + Content-Range from NZBDav is treated as "full file with a cosmetic range header" and passes through as 200 so demuxers that read from the advertised offset don't land in the wrong place.
- **Proxy Performance Improvements**
 - In 1.3.0, Node's HTTP keep-alive pool reused the most-recently-freed socket for the next range request. If a socket silently degrades (NAT timeout, TCP congestion-window collapse, transient network hiccup), it stays alive-but-slow and the pool keeps handing it back to every new

request until the HTTP idle timer eventually evicts it. Healthier sockets lower in the pool sit unused in the meantime, so every range request suffers even though faster connections were available the whole time.

- To fix this the following changes were made:
 - **FIFO scheduling:**
 - sockets rotate across range requests instead of pinning the most-recently-freed one at the top of the pool.
 - **TCP-level SO_KEEPALIVE:**
 - Idle WebDAV sockets get an OS keepalive probe 10 seconds after going idle. If the connection is dead (NAT timeout, TLS half-open, route loss), the probe fails, the kernel closes the socket, and the HTTP agent drops it from the pool automatically. The next range request grabs a fresh socket instead of stalling on a zombie.
 - **Shorter HTTP idle timer:**
 - The HTTP keep-alive idle timer drops from 30 seconds to 15 seconds. Idle sockets cycle out of the pool twice as fast, working alongside TCP keepalive to shrink the window where a silently-dead socket can sit at the top of the pool waiting for the next range request.
- **Net Effect Of All Changes:**
 - Large streaming sessions stay healthy, responsive, and fast. The fixes layer with the existing mid-stream reconnect loop, each covering a different failure mode:
 - TCP keepalive catches socket-level death (NAT timeout, TLS half-open).
 - 30-second upstream request timeout catches in-flight stalls where a request started but never makes progress.
 - Mid-stream reconnect loop recovers from mid-data WebDav failures.

- **In-Progress Playback Survives Addon Restarts**

- When the Usenet Ultimate addon is restarted. In-progress streams do not die, the reconnect resumes the entire session when the addon is back online.
 - With Dual-Stage proxy enabled the buffer integrates seamlessly with the reconnect so the user never even knows a restart occurred.
- This is possible with the following additions:

- **Ultimate Fallback sessions and Fallback Groups survive addon restarts**

- Resolved Ultimate Fallback sessions and active fallback groups are now persisted to disk and restored on startup.
 - This means restarting the addon mid-playback does not break playback or Ultimate Fallback Functionality
 - Sessions write to config/uf-sessions.json (with backupStreams, backupUrls, and lastVettedUrl).
 - Fallback groups write to config/fallback-groups.json.
 - Per-session cleanup timers re-schedule at the remaining TTL window on restore, so total session lifetime is preserved across restarts.
 - Save points are bounded (on resolve, on finally exit, on cleanup-timer fire for sessions; on create / clear / expired access for groups), and each save rewrites the full file from the current Map state so the disk never drifts from memory.

- **Stream request deduplication is extended from 10 seconds to 10 minutes**

- This covers a typical play session's seeks and parallel probes without re-running library checks. If WebDAV evicts content mid-session, the next request self-heals automatically.

4) Index Manager

Ultimate Text Search:

Absolute Episode-Numbering Fallback for Ultimate Text Search:

- When a series UTS query for Title S03E07 returns zero results, the orchestrator retries every enabled non-timed-out indexer (including EasyNews) using absolute episode numbering.
- Where the absolute number comes from (four-tier source chain):
 1. TVDB absoluteNumber when TVDB has it explicitly set for the requested episode. This is canonical for shows that officially use absolute numbering.
 2. TVDB-derived cumulative count (sum of episodes from prior aired seasons, plus the current episode) when TVDB has the show but no canonical absoluteNumber.
 3. Cinemeta cumulative count (sum of meta.videos entries for prior seasons, plus the current episode) when no TVDB API key is configured OR TVDB doesn't have the show. For a 3-season show with 12 episodes per prior season, S03E07 becomes E31 (12 + 12 + 7), and the retry query is Title E31.
 4. Per-season E{episode} when neither TVDB nor Cinemeta has prior-season counts available.
- Tiers 1 and 2 require a TVDB API key configured in the Index Manager.
 - When set, TVDB is the primary source. Cinemeta is the fallback when TVDB doesn't have the show.
 - Anime IDs without an IMDB mapping also get the TVDB chain. When the request comes in with no IMDB ID and skips the standard title-resolution flow, the addon uses the TVDB ID from the anime database to query TVDB directly.
- A new toggle "Absolute Episode Fallback" lives in the Index Manager overlay near the other UTS settings. Default on.
- Env: ABSOLUTE_EPISODE_FALLBACK (true/false).

Alias Title Fallback:

- When a search returns zero results, the addon now retries once per English alias from TVDB whose normalized form is a strict substring of the canonical title and substantially shorter than it.
 - The alias becomes both the indexer query and the post-result filter target, so releases that match the alias but not the canonical title are kept.
 - Helps shows whose release groups publish under a shortened name rather than the full canonical title.
- For series with a known TVDB episode air date, the alias query uses the date-numbered format (e.g. alias YYYY.MM.DD) instead of SxxExx, and accepts results by prefix-match so guest-name-suffixed episode releases pass the title filter. Falls back to SxxExx when no air date is published.
- Default ON. Toggle in Index Manager directly under Absolute Episode Fallback.
- ALIAS_TITLE_FALLBACK env var overrides the saved setting.
- Applies to Ultimate Text Search only
 - anime path uses its own Kitsu / Cinemeta fan-out and is unaffected.

Parallel Alternate Title Search:

- When enabled, Ultimate Text Search fires the primary title and every alternate title query concurrently across all enabled indexers (and EasyNews), instead of running alts only as a zero-result fallback. Eliminates the sequential retry latency for non-English content where TVDB/TMDB and Cinemeta return different titles, since both queries hit the indexers at the same time and merge into the result pool.
- Roughly doubles indexer query volume for shows where alts exist, so it's gated off by default. Opt in via the toggle in the Ultimate Text Search card.
- The absolute-episode fallback iterates [primary, ...alts] in parallel mode so alts still get the E{absolute} probe when the union returns 0.
- Cross-searcher parity:

- parallel alt-title now applies to Prowlarr, NZBHydra, and EasyNews in addition to Newznab. The absolute-episode fallback iterates [primary, ...alts] in parallel mode in every searcher.
- TVDB native-title preservation under "Always Resolve in English": when the English-title preference replaces the canonical title, the TVDB native title is preserved as one of the alts.
- This feature allows you to search both the content's native language and English at the same time for a complete results list.
- Applies to Ultimate Text Search only

Display Library In Results:

- A new toggle in the Index Manager overlay (below Results Deduplication) marks search results that already exist in your WebDAV library with the  icon. After search results pass filters and before they're sent to Stremio, each result is parallel-probed against the library; matches get the  status badge so you can prefer already-downloaded copies at a glance.
- Library hits are also skipped by auto-queue (auto-queueing them would re-grab content already on disk).
- Default on. Disable via the toggle if you want clean results without library annotation.
- Env: DISPLAY_LIBRARY_IN_RESULTS.

Ultimate Library:

- A new card in the Index Manager overlay (above Results Deduplication) that runs a live WebDAV library scan before any indexer query.
- When the scan returns at least the configured number of matches, indexer searches are skipped entirely and results are built from library hits alone, saving indexer rate-limit budgets for content already on disk.
- **All-or-nothing:**

- If the scan returns fewer matches than the threshold, library results are discarded rather than merged into the indexer flow. You can see the results already in the library with the "Display Library In Results" feature.
- Default off. Set the threshold (1 to 10) via the toggle and stepper.
- Env: LIBRARY_SEARCH_THRESHOLD.
- **Skip Ultimate Library Stream Tile**
 - After a short-circuit, the results list includes a "Skip Ultimate Library" tile.
 - Clicking it queues a one-shot bypass:
 - Your next search of that content will skip Ultimate Library and query your indexers instead. The bypass is keyed per content, auto-expires after 5 minutes if unused, and clears the moment the next search consumes it.
 - This tile lets you escape unwanted library results without changing any settings.
 - Tile Position selector (Top / Last):
 - Choose whether the skip tile appears at the top of the results list (or second if Ultimate Fallback is enabled) or at the very end. Default is Top.
- **Apply To Toggles**
 - Ultimate Library has Apply to Movies and Apply to TV toggles in the settings panel. Defaults are both enabled. Toggling off disables UL for that content type.
- **Scan Uncategorized toggle**
 - Inside the Ultimate Library card, a toggle (default ON when Ultimate Library is enabled) extends the WebDAV scan to /content/uncategorized in addition to the configured category root.
 - This allows you to manually upload/drag&drop nzbs that are instantly viewable by Ultimate Library.

- This is especially handy for complete series packs
 - This is NzbDav's default dir for manually uploaded content.
 - Env override: `LIBRARY_SEARCH_SCAN_UNCATEGORIZED=true|false`.
- **Run on Cache Hit toggle**
 - When enabled, the WebDAV library scan runs on every request, including cache hits. If the post-filter scan meets your threshold, library results replace the cached results for that request (short-circuit like fresh searches). If below the threshold, the cached indexer results are returned.
 - When this toggle is on, the "Skip Ultimate Library" stream tile and all three "Delete from WebDAV" tiles (per-stream file, per-stream season pack, delete-all) preserve the search cache instead of clearing it, so the next request hits cache and serves cached indexer results without re-querying.
 - The Skip tile bypasses Ultimate Library for that next one search.
 - `displayLibraryInResults` re-validation still drops the  marker on entries that no longer exist in the library, so deletes reflect immediately on the next request even with cache preserved.
 - UI-only setting; no env var. Default is off.
- **WebDAV Delete Stream Tiles**
 - Three opt-in toggles inside the Ultimate Library card (all default off, all gated behind UL being enabled). Manage your WebDAV library directly from the results list.
 - Each delete tile also deletes the associated NZB from NzbDav's processing history after completion.
- **Stream Tile: Delete All Results From WebDAV**
 - Adds a single "Delete All Results From WebDAV" tile to the results list. Clicking it deletes every Ultimate Library result for the current request from your WebDAV mount.

- The tile is placed immediately after the Skip Ultimate Library tile, so its position follows whichever slot you chose above (Top or Last).
- The pack scope sub-selector decides how series / season pack results are handled:
 - Episode (default): only the per-episode file is deleted.
 - Pack: the entire release folder is deleted.
- **Stream Tile: Delete Result From WebDAV**
 - Adds a delete tile after each library result.
 - Non-pack results get one tile that deletes the matched file.
 - Series / season pack results get two tiles: one deletes the individual episode, one deletes the entire pack folder.
 - How To Enable modal:
 - Enabling either delete toggle opens a confirmation modal that walks you through the two NzbDav prerequisites:
 - Ensure your NzbDav instance is not publicly exposed.
 - Disable "Enforce Read-Only" in NzbDav (Settings > WebDAV > uncheck > Save).
 - Pack-folder deletes use WebDAV's standard Depth: infinity header (RFC 4918) so the entire release directory is removed in a single request.
 - After file deletes, empty parent folders are pruned automatically up to (but not including) /content/<root>/, so deleting a file also removes the now-empty directory it lived in.
- Ultimate Fallback integration:
 - Delete tiles are never added to the Ultimate Fallback candidate list, so Ultimate Fallback never tries to grab or play a delete URL.
- Three new placeholder videos in ui/public/ play the result of a click ("All Ultimate Library results have been deleted from WebDAV", "The selected result has been deleted", "The selected series / season pack has been deleted").

- Failures continue to reuse the existing nzb_failure_video.mp4.
- **Live state, no cache:**
 - Search cache writes are bypassed when the short-circuit fires. Library state is the live source of truth.
 - The scan log shows every directory inspected with ✓ (matched), ✗ (no video found), or ∅ (filtered by season) markers for full visibility.
- Alias + date filename matching:
 - when a TV request has TVDB aliases and a known air date, the library scan also matches files named by alias + date (e.g. Show Name 2024.05.10). Catches daily shows and talk-show releases that don't carry an SxxExx token. Mirrors the search-side alias fallback so the library and indexer paths see the same set of files.
- Supports Ultimate Fallback and is powered by Ultimate Text Search. Pairs best with Series / Season Packs enabled.

Per-Indexer Search Timeouts:

- v1.4.0 adds configurable request timeouts across every search path, Newznab, Prowlarr, NZBHydra, and EasyNews. Previously, indexer calls used hardcoded 30s timeouts with no visibility or per-indexer control.
- Timeouts are configurable at three levels:
 - Per-indexer (Newznab):
 - Each indexer in the Index Manager has its own Request timeout toggle + stepper.
 - Top-level:
 - Prowlarr, NZBHydra, and EasyNews each have their own timeout settings in the Index Manager overlay (one setting per service since each service fronts a single connection to many indexers).
 - Env override:

- SEARCH_TIMEOUT (1–45s) forces timeouts on and overrides everything else.
- Range 1–45 seconds, default 15 seconds.
- Retry Suppression vs Independent Queries
 - When an indexer times out, UU sets a per-search timedOut flag. That flag suppresses retries: text fallback (retry the same query as text instead of ID) and alternative-title retry (retry the same query with an alt title). These are just redo's of the same search on the same backend, so paying another 15s wait is wasteful.
 - Season-pack search is NOT a retry. It's a genuinely different query (S01 whole-season vs S01E01 episode), so it runs independently with its own fresh timeout budget.
- Pagination Consistency
 - Pagination pages now uniformly distinguish from other errors across all four searchers. A page that times out mid-pagination sets the timedOut flag, logs a 🕒 Prowlarr pagination page 3 timed out after 15s instead of the generic ⚠️ Pagination page 3 failed: timeout of 15000ms exceeded, and breaks the loop preserving any partial results already fetched.
- Newznab Per-Indexer Retry Skip
 - For Newznab indexers, each indexer runs its own parallel search. The orchestrator collects the names of indexers that timed out into a timedOutIndexers set scoped to the current search cycle, then filters those out of the zero-result text fallback and alt-title retry passes.
 - Healthy indexers in the same search still run the retries, only the timed-out ones get skipped. Summary log: 🕒 Skipping text fallback for 2 indexer(s) — prior timeout: "Acme News", "Beta Indexer".
- UI: Stepper + Reset
 - The 4 timeout fields (3 in the Index Manager overlay, 1 in the Edit Indexer modal) use the same +/- stepper pattern as Ultimate Fallback wait-times.
 - The Edit Indexer modal's remaining checkboxes (Enabled, Paginated search) were also converted to the same toggle-switch pattern so the whole modal is consistent with the rest of the app.

- Logging
 - A boot-time summary lays out the effective defaults so any later timeout can be traced back to a known baseline:
 - 🕒 Search timeouts - Prowlarr: 15s, NZBHydra: 15s, EasyNews: 15s (Newznab: per-indexer, default 15s)
 - 🕒 SEARCH_TIMEOUT=3s override active - forcing all indexer timeouts
- Every search entry line is annotated with the effective timeout:
 - 🔍 Prowlarr TV text search for 4 indexer(s) [timeout=15s]: "Example Show"
 - 🔍 Searching Acme News (via Zyclops, [timeout=15s])
 - 🔍 EasyNews movie search [timeout=15s]: "Example Title 2023"
- Timeout events log a single 🕒 line per timed-out request. Retry-skip decisions log one line per suppressed branch (e.g. 🕒 Prowlarr: skipping text fallback (prior timeout)). Settings changes are audited (🕒 Prowlarr timeout updated: enabled=true, timeout=12s), with per-indexer edits logged by name.
- Env vars
 - SEARCH_TIMEOUT (1–45, seconds) — global force-override. See .env.example.+
- Default lowered to 15s
 - The default per-indexer search timeout is reduced from 30s to 15s. 15s balances responsiveness on fast networks with enough headroom for slower indexers.

TVDB API Key Auto Update:

- TVDB API key changes apply on the spot. No restart is required anymore after editing the key in the Index Manager overlay, The cached token clears automatically on save.

Always Resolve TVDB Title in English:

- When TVDB's canonical title is in a non-English language (e.g. originalLanguage=fra), the addon previously fed that foreign-language title into

Newznab text search. A new UTS-section toggle (default ON) fetches the English translation from TVDB's `/v4/{series|movies}/{id}/translations/eng` endpoint when one exists and substitutes it for the canonical name.

- Improves indexer match rates dramatically for shows whose original language isn't English.
- Auto cache clear on preference change. Resolved titles are cached for 24h. Flipping the new toggle now flushes the TVDB title and translation caches automatically so the change applies on your next search instead of waiting for natural TTL expiry. Mirrors the existing behavior when the TVDB API key is changed.
- Env override: `TVDB_PREFER_ENGLISH_TITLE=true|false`.

Series Packs

- Distinct from Season Packs, which queries individual Sxx releases. Series Packs catches what Season Packs misses: multi-season ranges (S01-S06) and keyword-only releases without Sxx tokens (Show Complete, Show Boxset).
 - A new card in the Index Manager overlay with its own toggle, keyword chip selector, and pagination knobs (independent from Season Pack pagination so the two can be tuned separately).
 - Two query types, both gated by the master toggle:
 - Multi-season fanout: an extra Title S01 query on non-S01 searches, which release groups commonly use as the umbrella name for a multi-season pack.
 - Keyword queries: per-keyword Titlem chip-driven (Complete, Boxset, Collection, Anthology, Saga, All Seasons). Empty chip selection disables the keyword pass entirely.
 - Ultimate Library scan and the indexer query path treat the same folders as series packs.
 - Supported with all four searchers (Newznab/Prowlarr/NZBHydra/EasyNews).
 - No env vars: the feature is configured via the UI only.

Per-Indexer Search Method Honored

- In v1.3 the orchestrator could fire text-shaped fallback queries against indexers that the user had explicitly opted out of "text" search (id-only indexers). v1.4 plumbs the text opt-in through every fallback path in every searcher:
 - Newznab:
 - parallel-alt fan-out, alias, absolute-episode, and sequential alt-title retry skip indexers without the text method.
 - Prowlarr / NZBHydra TV:
 - the canonical text query, parallel-alt, sequential retry, absolute, and alias fallbacks all suppress when no text-method indexer or pack feature can serve them. Each text-shaped fallback is restricted to text-method indexers only.
 - Bug Fix:
 - Prowlarr / NZBHydR Movie path:
 - alt-title and alias fallbacks were running text-shaped queries against id-only indexers via the textMethod + idSearched union; now restricted to text-method indexers only.
 - Each skip emits a warn log so misconfigurations are visible.

Parallel Searches Across All Searchers

- The whole search flow is now parallel end-to-end:
 - Newznab:
 - per-method ID searches and searchTVShowPacks fire inside one Promise.all per indexer, replacing the prior method-by-method await loop.
 - Prowlarr / NZBHydra / EasyNews:
 - every method search and pack query fires inside a single Promise.all per call. Pack queries no longer wait for the first method's response.
 - Pack queries are nested in parallel as well.

Within-indexer dedup:

- indexers with multiple methods returned the same physical release through each method's call, and URL-dedup missed these because Prowlarr's proxy generates a fresh download URL per request.
- A new indexerName | title | size | pubDate-as-epoch dedup runs before URL dedup. Re-uploads with the same release name but different post timestamps stay distinct. Always on logs, log a per-indexer breakdown of removed duplicates.

Structured Per-Task Logging

- Concurrent search tasks would interleave their console output as their responses returned, making logs unreadable. v1.4 routes every search-flow log through a per-task buffer:
 - A per-search banner replaces the bare "Searching for..." line, with labeled sections (Title Resolution, Search Setup, Ultimate Library, Results Processing, Ranked Rules, Final Results) that delimit each phase.
 - Final Results dumps a capped 30-entry view of the sorted result list with an "and N more" tail when truncated.
 - All fallbacks (alias / absolute / alt-title) render inside the per-indexer cluster instead of as top-level lines, with the magnifying glass emoji used for query-issue events.
 - Buffer logging applies to all index managers

5) Ultimate Fallback

- **NZB Fallback removed, replaced by Ultimate Fallback**
 - Ultimate Fallback is a new feature in v1.4 that replaces NZB Fallback. It's the fastest way to resolve a healthy NZB and start streaming, while giving the user full control over NZB selection.

- Ultimate Fallback supersedes it with a richer pipeline plus the option to roll back to the same sequential behavior via the Legacy NZB Fallback preset.
- Existing NZB Fallback config is auto-migrated on first startup to UF's minimal baseline (described below) rather than mapping the old toggles into UF settings, so UF starts in a clean known-state regardless of how NZB Fallback was previously configured.
- The deprecated env vars NZBDAV_FALLBACK_ENABLED, NZBDAV_MAX_FALLBACKS, NZBDAV_FALLBACK_ORDER, AUTO_RESOLVE_ON_SEARCH, AUTO_RESOLVE_TARGETS, NZBDAV_LIBRARY_CHECK, NZBDAV_MOVIES_TIMEOUT, NZBDAV_TV_TIMEOUT, NZBDAV_SEASON_PACK_TIMEOUT, and NZBDAV_JOB_TIMEOUT emit a startup warning if set. Replace them with the equivalent ULTIMATE_FALLBACK_* vars or remove them.

- **What is Ultimate Fallback**

- It's a five-layer parallel pipeline that combines a 302 redirect lobby, WebDAV library lookups, priority-aware indexer grabs, optional NNTP health checking with archive inspection, and NZBDav submission to resolve a healthy NZB.
- After the primary resolves, the pipeline can keep running to pre-cache container-matched backup NZBs (when configured), so if the primary throws an error mid-stream, the fallback is instant.
- Standalone Health Checks can coexist with Ultimate Fallback if desired.
- Ultimate Fallback has its own dedicated stream tile. When enabled, the tile is the first result in the returned list.
- Clicking the Ultimate Fallback tile enters the redirect lobby.
- Clicking any other stream tile resolves that NZB first, then falls into whatever fallback behavior the user has selected.

- **Default baseline: minimal opt-in**

- Ultimate Fallback ships with a minimal default configuration. Every advanced behavior is opt-in. Turning on UF doesn't spend NNTP, nzbdav,

or backup-vetting resources until the user has actually chosen to enable each layer.

- Defaults out of the box:

Setting	Default
Health Checking	Off (submit straight to nzbdav)
When to Resolve	On Click (defer until the lobby tile is clicked)
Fallback Behavior on Individual Stream Failure	Show Failure Video
Parallel NZB Candidates	1 (single-NZB sequential)
Desired Backups	0
Primary Attempt Limit	All (unlimited)
Preference Mode	Priority

- The Reset to Default button applies this baseline.

- One-click presets

- A new Presets card in the Ultimate Fallback overlay applies a tuned configuration with a single click.
- Classic (Default):
 - Mirrors the new minimal opt-in baseline.
 - Use this to roll back to the same behavior as the previous NZB Fallback feature provided.
- Lite:
 - Health Checking on,
 - "On Search" pre-resolve,
 - Parallel NZB Candidates 2,
 - Desired Backups 1,
 - Backup Processing Limit 1,

- Show Failure Video on individual stream failure.
- Enhanced:
 - Health Checking on,
 - "On Search" pre-resolve,
 - Parallel NZB Candidates 3,
 - Desired Backups 1,
 - Backup Processing Limit 2,
 - Show Failure Video on individual stream failure.
- Each preset button blinks amber on click and shows a "✓ Applied" confirmation.
- Grab Estimate card
 - Shows how many NZBs the current configuration will grab during a single resolution attempt.
 - The card sits between Desired Backups and Health Checking and is always visible while UF is enabled.
 - It copy adapts to the live config:
 - it surfaces the Primary Attempt Limit cap when set ("capped at N total")
 - reflects the Backup Processing Limit when backups are on
 - Explicitly notes that no additional NZB grabs run after the primary when Desired Backups is off (free library hits still cache as backups regardless).
 - The Presets card points to it with a small amber note: "See Grab Estimate below for resource impact."

- The 5 Layers

- **Layer 1: 302 Redirect Lobby**

- When the lobby tile is selected, even during processing, the user enters a redirect lobby (the player's loading screen) where they sit until the stream-resolution promise of Ultimate Fallback fulfills. The resolved promise is cached for 2.5 hours for auto play, so a promise created during mid-episode background scraping still exists by the time you finish the current episode.

- **Layer 2: WebDAV Library Check**

- All candidates are checked against the NZBDav WebDAV library simultaneously. A library hit means the file is already available locally.
- Speed mode:
 - The first library hit is promoted to primary immediately. Library hits are by definition the fastest possible resolution since there's no NNTP grab or extraction to wait for.
- Priority mode:
 - A library hit on a lower-priority candidate is parked behind any earlier candidate still actively grabbing or running an nzbdav job. The hit is re-checked on every replacement-pull cycle and promoted only once no earlier candidate is in flight. Without this gating, the lower-priority library copy would always win simply by being instant, which would contradict the "highest-quality first" contract.
- If the primary resolves instantly via a library hit, the pipeline skips straight to the post-primary phase to pre-cache backups.
- Library hits during the post-primary phase are cached as instant backups when they match the primary's container.

- **Layer 3: Priority Grab Queueing**

- NZBs are grabbed from indexers in parallel. The queue is priority-aware, so NZBs enter the queue in priority order. Each grab caches the NZB and is shared with health checks and

NZBDav submissions, so there are no duplicate downloads. As each grab completes, it's immediately sent into Layers 4 and 5.

- **Layer 4: Health Checking and Container Type Extraction**

- Optional feature.
 - Off in the minimal baseline, on in the Recommended preset.
 - When enabled, each grab runs two jobs on the same archive-inspection pass:
 - Article verification.
 - Every article for the candidate is probed across the user's Usenet provider pool. If a candidate is dead, it's discarded, the next candidate from the results list is pulled in, and health-checked immediately (a rolling replacement). If the candidate currently in NZBDav fails its health check, the NZBDav job is cancelled instantly and the next candidate is submitted.
 - Container-type extraction.
 - The video container type (MKV, MP4, AVI, etc.) is extracted during the same pass.
 - First from the NZB subject line.
 - Then from the archive's file listing if the subject didn't have it.
 - If both fail, the container stays unknown and Layer 5 treats it as a speculative submit (the container is derived post-resolve once NZBDav finishes extracting).
 - The extracted container is saved on the candidate and becomes the gate for post-primary backup matching.

- Why container matching matters.
 - The video player initializes its demuxer for a specific container format when playback starts, guided by the Content-Type header and the stream's initial bytes. It doesn't re-probe mid-stream. For a backup to proxy seamlessly on fallback, it has to match the primary's container. Otherwise the bytes don't fit the format the player is already committed to, and playback breaks.
- When health checking is disabled, candidates submit directly to NZBDav and the container is detected from the resolved videoPath after extraction completes.

- **Layer 5: NZBDav Submission**

- One active NZBDav job at a time. Ultimate Fallback has direct API control for instant cancellation if a candidate fails its parallel health check.
- Priority preference:
 - waits for the highest-priority candidate's grab to complete before submitting, even if lower-priority candidates grabbed faster.
 - The best-quality NZB is always tried first.
- Speed preference:
 - The first NZB grab to complete is submitted to NZBDav immediately. If it's healthy, that's the fastest resolution. If it fails health checks, it's cancelled and swapped to the next available, preferring candidates that have already passed health checks.
- Infinite NZBDav Wait-Time Support
 - The six per-mode wait-time steppers in Ultimate Fallback now accept 0 for infinite, displayed as ∞ .
 - When set, Ultimate Fallback will wait as long as NZBDav needs to finish its job rather than rolling to the next candidate. Useful for slow extractions on

large NZBs packs where you'd rather wait it out. Health-check cancellation and Stremio's outer 60s lobby timeout still apply, so nothing spins forever without a safety net. All NZBs waited on are healthy.

- Priority and Speed Wait-Times
 - Both Priority and Speed mode support their own wait times. So you can set each for optimal use.

- **Post-primary phase: NZB Backups**

- Once the primary stream resolves, Ultimate Fallback reads the primary's video container type and locks it in. The pipeline then keeps running (when configured), pre-caching backups that match the primary's container so mid-stream fallback is instant instead of a cold re-resolve.
- Container matching.
 - Backups must match the primary's container type.
- Library hits are free.
 - Any remaining candidate already in the NZBDav library that matches the container is cached as an instant backup at zero NNTP cost.
- Deduplication.
 - Candidates that resolve to the same videoPath or share a title with an already-vetted source are marked as duplicates and skipped.
- Dead-candidate replacement.
 - If a candidate fails its health check, the next candidate from the results list is pulled in and tried. Backup slots keep filling until the budget is hit or the candidate list is exhausted.
- Speed mode pauses after the primary.
 - Before the primary resolves, Speed Preference sends the first grab to NZBDav. After the primary resolves, backups are always submitted in

strict priority order so you get the best-quality backups first, not the fastest.

- Mid-stream fallback.
 - If the primary stream throws an error (404, 410, or 5xx), Ultimate Fallback's loop loads pre-cached backups in priority order. If the backups are exhausted, NZBs are auto-resolved in priority order from the first candidate the pipeline hadn't yet reached.
- Library Pool Gating.
 - Library hits only promote to primary or backup once the pool actually reaches the candidate. Hits are promoted on initial pool fill, via replacement-pull snake-downs, or through a free post-drain sweep that fills remaining backup slots from any out-of-pool library hits (bounded only by Desired Backups, since library hits cost no NNTP grab).
 -
 - Library hits only promote to primary or backup once the pool actually reaches the candidate. This ensures the priority of your results list is respected.
 - Hits are promoted on initial pool fill, via replacement-pull snake-downs, or through a free post-drain sweep that gathers any out-of-pool library hits.
 - The post-drain library sweep is always exhaustive, regardless of desiredBackups. Library hits cost nothing, so the cap is treated as a target for grabbed backups, not a hard ceiling on total backups.
 - With desiredBackups=3 and 5 matching library hits available, you get up to 3 grabbed backups plus all 5 library hits cached for instant mid-stream fallback.
 - With desiredBackups=0, the sweep collects all library hits with no NZB grabs at all.
- Free library backups even at desiredBackups=0.
 - With desiredBackups=0 (the minimal default), Ultimate Fallback would otherwise skip the post-primary backup phase entirely. The post-drain library sweep runs unconditionally once the primary resolves, so any remaining candidate already in the NZBDav library and matching the primary's container still gets cached as an instant backup at zero cost.

- New NZB grabs are still fully blocked at desiredBackups=0; only library hits make it through.

- **NZB Backup Settings**

- Desired Backups (default 0 = disabled, max 10). How many container-matched backups to resolve after the primary resolves.
- Backup Processing Limit.
 - Hard cap on the number of new NZB grabs Ultimate Fallback issues after the primary resolves in search of additional backups.
 - Pre-primary refills (NZBs grabbed while still searching for the primary, e.g. when an early candidate fails its health check) flow through as free backups and don't charge against the cap.
 - Library hits don't count either (no NNTP grab).
 - Dead and duplicate post-primary candidates each cost a grab + health check, so they do count.
- Both settings are in the Ultimate Fallback overlay and support env-var overrides (ULTIMATE_FALLBACK_DESIRED_BACKUPS, ULTIMATE_FALLBACK_BACKUP_PROCESSING_LIMIT).
- The Dashboard's Ultimate Fallback tile displays the configured NZB Backup count next to "Enabled" (e.g. Enabled + 3 NZB Backups).

- **Configuration**

- **When to Resolve**

- Controls when the Ultimate Fallback pipeline fires.
- On Click (default):
 - defers UF until the user clicks the lobby tile. Saves resources for un-clicked content; the first click pays the resolve latency.

- On Search:
 - pre-resolves as soon as search results arrive. Clicks are instant, but some NNTP / nzbdav resources may be spent on titles you skip.
 - If Health Checks “Auto-queue to NzbDAV” is on, “On Search” will suppress it so the 2 don’t collide.
- Env: ULTIMATE_FALLBACK_WHEN_TO_RESOLVE (on-tile-selection | on-results).

- **Fallback Behavior on Individual Stream Failure**

- Controls behavior when a non-UF stream tile fails.
- Show Failure Video (default):
 - skip the fallback and show "Stream Unavailable" immediately.
- Use Ultimate Fallback to Resolve From Top of List:
 - redirect to the UF lobby so its pre-vetted backups can take over.
- Fallback to Next Stream:
 - walk the full results list sequentially from the clicked tile through the end, then wrap to the top through clicked-1, so every untried candidate gets a turn in sequential order from selected.
- Env: ULTIMATE_FALLBACK_USER_PICK_FALLBACK (failure-video | uf-lobby | fallback-chain).

- **Optional Health Checking phase**

- The Health Checking phase (Layer 4) can be toggled off.
 - With it off, Ultimate Fallback skips the parallel NNTP pre-flight entirely and submits candidates straight to nzbdav.
 - Container detection defers to the post-resolve path: each container is read from the resolved videoPath after nzbdav finishes extracting. Backup container matching still works, just

based on post-resolve container info instead of pre-flight inspection.

- The Provider Manager, Articles to Sample, and Archive Header Inspection controls dim when the toggle is off, and the "max NNTP connections" calc collapses to 0.
- Env: ULTIMATE_FALLBACK_HEALTH_CHECK_ENABLED (true/false).

- **Primary Attempt Limit**

- Caps the total number of NZBs Ultimate Fallback will try in pursuit of a primary stream before giving up. Useful for bandwidth-conscious setups, or to put a hard ceiling on how aggressive UF gets before falling through.
- Default "All" (unlimited). Range 1 to 20 when capped. Library hits don't count against the cap (they resolve for free).
 - Honored on both initial pool fill and replacement pulls, so candidateCount=3, maxAttempts=2 burns at most 2 nzbdav slots in the search for a primary.
 - The "Parallel NZB Candidates" stepper is nested under Primary Attempt Limit as a sub-setting and auto-clamped:
 - it cannot exceed the cap, and dropping the cap below the current candidate count snaps the candidate count down to match.
- A session-end recap line surfaces maxAttempts: all or N/M so the cap can be verified from logs.
- Env: ULTIMATE_FALLBACK_MAX_ATTEMPTS (0 = unlimited, 1 to 20 = cap).

- **Single-NZB sequential mode**

- Parallel NZB Candidates accept a minimum of 1.
 - With a count of 1, the pipeline processes one NZB at a time sequentially instead of in parallel. Useful for users with limited connection budgets or who prefer strict priority order without any parallel speculation.

- The overlay subtitle and Dashboard tile copy are plural-aware (1 candidate vs 3 candidates).

- **Archive Header Inspection always on**

- Archive header inspection is hardcoded "on" whenever Ultimate Fallback and the nested health check settings are both enabled.
- The container-matching guarantee (every backup matches the primary's container) performs optimally when reading archive headers at health-check time. With archive inspection off, archive candidates defer inspection until after NZBDav resolution.
- The UI shows an "Always On" badge.

- **Internal Improvements**

- **416 recovery on mid-stream fallback redirects.**

- When a primary stream fails mid-playback and falls over to a backup, the player's lingering Range header (pointed at the primary's byte position) frequently exceeds the backup's reported size and upstream returns 416. Ultimate Fallback flags every eviction-redirect with `_norange=1` so the player's Range header is stripped before the new backup is fetched, and the backup serves cleanly from byte 0.
- As a safety net, an in-flight 416 from upstream still triggers a one-shot no-Range retry. Empty-body 200 responses on the retry are treated as upstream errors instead of zero-byte fake successes.
- Same-file retries (lobby self-redirects, transient reconnect-loop blips) preserve Range, so manual seek positions still survive.

- **Clear Search Cache also drops resolved UF sessions.**

- Clicking Clear Search Cache now evicts any resolved Ultimate Fallback sessions from memory.
 - If UF's in-memory session map was independent of the search-result cache a user trying to "start fresh" could still land on a stale lobby that resolved to a now-evicted file.

- The two caches are now linked:
 - clearing the search cache also drops the resolved sessions, so "start fresh" actually means start fresh.
- In-flight resolutions are intentionally preserved, so anyone clicking Clear Cache mid-playback finishes their current resolve before the session is dropped.

- Walkthrough

- The example below assumes these settings: Primary Attempt Limit: All, Parallel NZB Candidates: 2, Desired Backups: 1, Backup Processing Limit: 1, Health Checking: on, Preference Mode: Priority.
 1. Search results are sorted and filtered.
 2. A fallback group is created for stream-error handling.
 3. The top 2 candidates (#1 and #2) fill the parallel pool and are checked against the NZBDav WebDAV library simultaneously.
 4. No library hits in the initial pool. NZB grabs start for both candidates in parallel.
 5. #2's grab completes first. Health check fires on the same archive-inspection pass that extracts container type.
 6. #2: Verified, archive available (MKV).
 7. Priority mode is selected, so even though #2 is ready, the pipeline waits for #1's grab to complete. Highest priority always tries first.
 8. #1's grab completes. Health check fires.
 9. #1: Blocked, 3/3 articles missing.
 10. #1 is dead. A rolling replacement pulls #3 into the pool to keep two candidates active. #3's grab starts.
 11. #2 is now the highest-priority healthy candidate. Submitted to NZBDav.

12. NZBDav downloads and extracts the NZB. Video file found (MKV). Results written to cache, the session promise resolves, the lobby is notified, and the user starts streaming.

- Behind the scenes, the pipeline keeps running for the post-primary phase:
 - The primary's container (MKV) is locked in.
 - #3's grab finishes. It was scheduled before the primary resolved (rolling replacement), so it doesn't count against the Backup Processing Limit. Health check fires.
 - #3: Verified, but extraction reveals the same videoPath as #2 → duplicate → skipped.
 - Desired Backups (1) not yet reached. The pipeline issues a new post-primary grab for #4, which charges 1/1 against BPL.
 - #4: Verified MKV. Submitted to NZBDav, resolved cleanly. Cached as backup. Desired Backups target reached.
 - BPL is now exhausted (1/1). No more new post-primary grabs allowed. Library hits don't need a grab, so the post-drain library sweep runs anyway.
 - Library check on #5 → hit, MKV → cached as a bonus library backup (free, no NNTP). Free library hits add on top of the Desired Backups target.
 - #6 is an MP4 → container mismatch → skipped, no bandwidth spent.
 - #7 → no library hit, BPL is exhausted so no NZB grab either. Pipeline moves on.
 - Sweep exhausts the remaining results list. Pipeline exits.
- Final backup pool: #4 (grabbed, MKV) and #5 (library hit, MKV). Two backups despite a Desired Backups target of 1 because of the free library hits after the pool.
- If upstream evicts #2 mid-stream, the fallback loop tries #4 first (priority order), then #5 (library hit, instant). No re-resolve, no buffering delay.

- The user got streaming with the highest-quality healthy NZB because Priority mode waited briefly for #1 before falling through to #2. After resolution, the pipeline's BPL-gated post-primary phase produced one grabbed backup, plus a bonus library backup at zero cost, so mid-stream failures are invisible.

6) NZB Fallback

- As mentioned above, NZB Fallback has been replaced by Ultimate Fallback
 - Users who had this enabled are auto-migrated to Ultimate Fallback
 - Existing fallback configs are one-shot-migrated to Ultimate Fallback on startup, mapped to settings that reproduce the old sequential behavior:
- Deprecated env vars
 - NZBDAV_FALLBACK_ENABLED, NZBDAV_MAX_FALLBACKS, NZBDAV_FALLBACK_ORDER, AUTO_RESOLVE_ON_SEARCH, AUTO_RESOLVE_TARGETS. A deprecation warning is emitted at startup if any of these are set; they're otherwise ignored. Replace them with the equivalent ULTIMATE_RESOLVE_* vars.

7) Health Checks

- **7z Archive parsing Improvements:**
 - 1.4.0 improves upon the prior limitations of the 7z parser.
 - **1) Offset calculations have been improved**
 - Instead of calculating the segments to download based on offset values, UU now downloads a tail buffer which is sized off the declared header size. At least 25 segments are grabbed to give us enough bytes to contain the header in addition to a little slack. Then the end header is extracted from the last nextHeaderSize bytes of that tail. If the first byte is 0x17 (kEncodedHeader) or 0x01 (kHeader), it's successful as those are the only two legal header types. If neither matches, UU scans the tail for a valid header.

- **2) Support added for LZMA2 compression and AES-256 Encryption**

- Previously, the 7z parser only handled LZMA1 with unencrypted headers. Modern 7z releases frequently use AES-256 to encrypt the header itself (hiding file names behind a password) and LZMA2 for compression, both of which caused the old parser to fall back to a bare "compressed/encrypted" flag with no file listing.
- UU now decompresses LZMA2. When a password is set, UU derives the AES-256 key using 7z's SHA-256 stretching KDF, decrypts the header, then decompresses the plaintext normally. This lets UU extract the full file listing, including container type, from password-protected archives without downloading the video payload.

- **3) Archive inspection full provider support**

- Previously, the health checker tried only one provider for archive inspection, the primary, and quit if it failed. It now walks through all enabled pool providers first, then all enabled backup providers, stopping on the first success. So archive inspection has full provider support now.

- **Smart Mode Minimum Healthy Threshold:**

- Having a healthy threshold makes smart-mode health checking more resilient on titles where the healthy-candidate pool is small.

- **Configurable stop threshold**

- Previously, smart mode stopped searching the moment it found a single healthy result. If that one candidate later hit a transient downstream failure (provider timeout, auto-queue rejection, etc.), the fallback pipeline had nothing to try.
- UU now exposes a smartMinHealthy setting (default 1, range 1–10) that controls how many verified candidates must accumulate before smart mode stops. At the default of 1 the behavior is identical to prior releases, no speed regression on titles with abundant healthy results.

- **Expanded batch size range**
 - The Batch Size dropdown now exposes values up to 6 (previously capped at 3). Higher thresholds would have been impractical with the old cap, a smartMinHealthy of 4 needed at least two batches of 3 to even be reachable.
 - With the expanded range, the threshold can be satisfied in a single batch when the candidate pool supports it.
- **Cross-batch counter**
 - The internal stop logic now uses a counter that accumulates healthy results across all batches, not just within the current batch. Library hits and cached pre-verifications count toward the threshold. If the threshold can't be satisfied after all configured batches run, smart mode emits a warning and proceeds with whatever verified candidates it found, no hang, no crash.
 - Hand-edited bad config values (0 or negative) are clamped to 1 at runtime.
- **Standalone Health Checks coexist with Ultimate Fallback**
 - Standalone Health Checks can now run alongside Ultimate Fallback. Previously, enabling UR locked the Health Checks card to "Managed" on the Dashboard and skipped the standalone pipeline entirely.
 - The two are complementary: Health Checks pre-filters known-dead NZBs out of search results before UR sees them, populating the dead-NZB DB and hiding blocked entries from the visible result list. UR still performs its own per-candidate verification during the resolve pipeline, but it never sees the NZBs Health Checks already pruned.
 - Auto-queue stays UR-managed when UR is enabled, since UR handles NZBDav submission internally and running auto-queue alongside it would conflict.
 - The Dashboard's Health Checks card is always clickable now and shows real Enabled/Disabled state plus provider summary regardless of UR.
- **Ultimate Fallback Auto-Queue Suppression**

- If Ultimate Fallback “On Search” is enabled it will suppress “Auto-queue to NzbDAV” so the 2 don’t collide.

8) NZB Database

- **Episode-specific dead files no longer ban the whole season pack**
 - Season packs that fail a multi-episode block on one episode used to mark the entire NZB URL as dead, hiding the pack from search results for every other episode in the season until the dead-NZB TTL expired.
 - Multi-episode blocks are now tagged as episode-specific. The pack stays visible for unaffected episodes, while the failed episode still benefits from the dead-NZB cache and skips a doomed re-fetch on retry.
 - The dead-NZB DB UI surfaces an S01E02 only label on episode-specific entries so it’s obvious why a pack is hidden for one episode but not others.
 - Side fix: the dead-NZB disk roundtrip preserves the size field now (was dropped on legacy entries, breaking the size pill on dead-NZB rows after a restart).
- **Dead NZB DB Shows Indexer + Size**
 - Dead NZB entries now persist and display the indexer name and release size (the healthy DB tile already had both). Both fields appear as pills in the NZB Database overlay alongside the existing error and expiry info, making it easy to spot which indexer / which size class is producing dead entries.
 - Backward-compatible on disk, existing dead entries lacking either field load cleanly and render without the missing pill; new entries written after the upgrade carry both.

9) Search Cache

- **Cache 0-result searches toggle**

- A new toggle in the Search Cache overlay controls whether empty-result searches are cached.
- Default is on, matching prior behavior. When off, searches that return zero results skip the cache write entirely, so retries re-query the indexers live. Useful when adding a new indexer or fixing a misconfigured one mid-session, since a freshly-fixed indexer would otherwise get masked by a stale empty cache entry until the cache TTL elapses.
- The skip path emits a debug log ( Skipping cache write, 0 results for <type> <imdbid>) so it can be distinguished from a normal cache expiry.
- Env: CACHE_EMPTY_RESULTS (true/false).

10) Filters, Rules & Sorting

- **UI additions:** (As stated in **Section 2**)
 - Reboot / Remake Detection
 - Moved to the filters overlay within the stream filters section
 - Allow Multi-Episode Files
 - Moved to the filters overlay within the stream filters section
- **Anime+Non-English Reboot / Remake Detection Filtering Support**
 - Reboot/Remake Detection now works on anime and other non-English-primary shows.
 - The translated english title is now always used for comparison when available.
 - The yearless episode substring check inside the remake filter was also running against the original language episode name.
 - The targeted episode name is now translated to English when available, so the substring match runs against the form release groups actually publish.
- **Baseline Junk Filter:**

- Older indexer databases occasionally surface stray entries that are bare archive parts or NZB containers, things like somefile.par2, xyz.r05, pack.001, or blob.nzb, rather than actual releases. These aren't valid content, they're fragments that slipped into the indexer without proper title-level metadata.
- Usenet Ultimate now drops these at the very top of the search pipeline, before URL dedup, indexer-priority dedup, remake filtering, quality filtering, or any user-defined rules. These results never reach parsing, never compete with real releases, and never waste a slot on the stream list.
- The filter is anchored to the title-end so only bare filename patterns are caught. Legitimate titles that happen to contain "rar" or "nzb" mid-string (e.g. The.Rarest.Person.2024.1080p.BluRay-GROUP or Some.Movie.NZB.2024-GROUP) are retained.
- Drops are logged in the existing filter format:
 - 🧹 Junk filter: removed 4 non-release(s) (128 remaining)
 - ✂ "somefile.par2" (par2)
 - ✂ "xyz.r05" (rar)
 - ✂ "pack.001" (vol)
 - ✂ "blob.nzb" (nzb)
- Filtered Extensions:
 - par2 · nzb · rar · r01–r99 · 001–999
- Toggleable
 - Default is on
 - The toggle takes effect immediately on cache hits, since the strip step runs per-request instead of inside the cached pre-processing stage.
- Env: JUNK_FILTER (true/false).

- Title Filter Update

- Title matcher edition stripping covers Theatrical Cut, Director's Cut variants, DC, and DirCut.
- Improvements:

- Theatrical Cut / Theatrical Edition - previously stripped only Theatrical and left the trailing Cut / Edition word in the title, causing the comparison to fail. Now binds them as a unit.
- Director's Cut with apostrophes and hyphen separators - previously failed because the pattern couldn't span the apostrophe. Now uses an optional apostrophe in the matcher and pre-replaces hyphens with spaces before the regex runs.
- Multi-word director cuts like Director's Definitive Cut or Director's Final Cut - added an optional middle word to the pattern.
- DC and DirCut abbreviations - handled in a second end-anchored pass so they only strip when they appear as the last token of the extracted title.
 - Avoids false negatives on titles that legitimately contain DC as a content token.

- **Prefer Season Packs:**

- A new toggle in the Filters overlay, visible on the Global and TV tabs, hidden on Movies.
- When on, season packs are sorted to the top of the results list.
 - The defined sort order applies to both the season pack and episode groups, so within each group your normal sort criteria (quality, size, video tag, etc.) still apply.
- Cache hits pick up the new ordering on the next request, no manual cache clear needed.
- Pure UI preference, no env var. Defaults to off so existing configs load with no behavior change.
- Note: season packs deprioritized by Remake Detection remain at the bottom regardless of this toggle.

- **Metadata Parser Improvements**

- HDR10+ preserved alongside DV:

- previously HDR10+ was collapsed into HDR when Dolby Vision was also present. Now both visual tags survive independently.
- HDR10P alias fallback:
 - titles using HDR10P (without the plus sign) are recognized and normalized.
- DCP source detection:
 - the source parser recognizes DCP release tags (theatrical-master transcodes). Previously DCP titles registered as Unknown and got bucketed alongside other unparseables.
- Better audio parsing:
 - DD+ is renamed from the v1.3 token DDP to match community-template naming. Atmos (DDP) is correspondingly renamed to Atmos (DD+).
 - DTS-HD MA, DTS:X, DTS-HD, DTS-ES now parse as distinct tokens instead of collapsing into the coarse DTS Lossy / DTS Lossless categories the underlying library produced in v1.3.
 - Channel-attached variants like DTSMA, MA5.1, MA7.1, HRA7.1, ES5.1 map to the right tokens.
- Trailing-dash strip:
 - release-group extraction now strips a trailing dash, fixing parse errors on titles like Release-GroupName- that occasionally leak into indexer databases.
- Default priorities updated to match: audioTagPriority is aligned to the community-scoring tier (Atmos TrueHD → DTS:X → Atmos DD+ → TrueHD → DTS-HD MA → FLAC → DTS-HD → DD+ → DTS-ES → DTS → AAC → DD → Opus → PCM → MP3).
- UU detects h.266, h266, x266, vvc, and vvenc release tags and normalizes them to vvc.
 - In the Filters overlay, VVC appears in the Encode Filters & Priorities list as VVC (h266 / x266), alongside HEVC, AV1, and the others. You can reorder it, toggle it on or off per-type (Global /

Movie / TV), and it behaves identically to every other codec in the list.

- Default Position
 - VVC defaults to the top of the priority list (above AV1), since it's the newest and most compression-efficient codec.
- Migration
 - Existing configs have vvc inserted at the bottom of their encode priority list automatically on first startup after upgrade. New users and the defaults button place it at the top of the list.
- videoPriority: DCP support and position:
 - DCP has been added to the list of supported filter/sort qualities
 - DCP sits right above WEBCap (between BRRip and WEBCap)
- **Regex and SEL Rules Engine**
 - v1.4.0 introduces a rules engine that lets you score and filter streams with two complementary rule types, powering the new regexScore and seScore sort methods.
 - Regex rules apply per-rule based on a Mode dropdown.
 - Score (default): adds the rule's score on match (positive boosts, negative penalizes). Sets a tag so SEL expressions can reference the rule by name.
 - Keep matches:
 - acts as an include filter. If any enabled keep-rule matches a candidate, it survives. Candidates that match no keep-rule are dropped from the pool.
 - Drop matches:

- acts as an exclude filter. Matching candidates are removed and further rule evaluation short-circuits for them.
- Tags are set in all modes so SEL can reference filter rules by name regardless of mode. The SEL pass operates on the visible (post-filter) pool, so set-level functions like largest(streams) compute over what the user actually sees.
 - SEL rules are a community template compatible Stream Expression Language, a small DSL with comments, ternary, function calls, word operators (and/or/not/in), and arrays.
 - Usenet Ultimate supports 18 built-in filter functions:
 - regexMatched
 - rseMatched
 - resolution
 - quality
 - encode
 - visualTag
 - audioTag
 - releaseGroup
 - language
 - indexer
 - size
 - age
 - bitrate
 - seasonPack
 - negate
 - merge
 - slice
 - count
- This implementation brings complete TV and Movie coverage of Tamtaro / Vidhin scoring rules. (Anime, which requires seadex integration, is not yet supported).
- Rank engine runs a two-pass evaluation (regex rules tag first, SEL expressions then score against those tags). Compiled rules are cached by rules hash. Per-request wallclock budget and title cap keep rule evaluation from runaway. Positive scores boost, negative penalize. (Exclusion lives in keep/drop modes) Both regexScore and seScore are added as new sort methods and are

disabled by default, enabling either (or both) to have rules drive ranking.

- Rules import: paste JSON or a URL.
 - The importer follows template-style URLs with a two-phase variant picker (preview → resolve + follow synced URLs), includes a DSL-aware input narrower so you only see inputs that actually gate rule loading, and is SSRF-guarded (15s timeout, 1MB cap, loopback/private/link-local blocked). Array-root and sentinel-skip handling for community-template imports. Validation rejects ReDoS patterns and malformed SEL at save time so bad rules never reach the pipeline.
- Rules Section UI:
 - Lives in the Filters overlay (renamed to "Filters, Rules & Sorting"). New RulesSection with ImportDialog, LiveTestField, RegexRuleRow, and SelRuleRow. Auto-collapses when the rule count exceeds 20. The live-test field lets you paste a title and see the rule evaluation result immediately, without saving. The import dialog is portaled to document.body so it isn't clipped by parent transforms.
- Filter-rule attribution log
 - When keep/drop rules drop candidates, a  Filters dropped 6/14 candidate(s), HDR: 4, NoSpanish: 2 line summarizes per-rule attribution (sorted by drop count). Empty pattern in keep/drop mode is rejected at save time so a misconfigured rule can't nuke the entire pool. The live-test pane labels matches as (drops) / (keeps) / (+score) instead of treating them identically.

Rules Section UX upgrade

- Each rule list (Regex / SEL) gets a left-edge drag handle for mouse/touch reorder, alongside the existing chevron up/down buttons for keyboard reorder. Drag is on the handle alone so text input drag-select still works inside the row.
- Each row has a checkbox plus Select All / Deselect All and a "Delete Selected (N)" button at the top of the list, gated by a confirmation modal

with focus-on-Cancel, ESC dismiss, and backdrop-click dismiss. Mirrors the Sort Priorities pattern.

- The outer "Ranked Rules" collapsible wrapper is removed; the Regex and SEL cards already collapse independently.
- The live-test field accepts a release title and shows rule evaluation immediately, without saving.
 - Scope is title-derived attributes:
 - resolution
 - codec
 - releaseGroup
 - visualTag
 - audioTag
 - videoTag
 - edition,
 - language
 - seasonPack
 - all parsed from the sample title. Attributes that depend on live search results (size, age, bitrate, indexer, etc) can't be synthesized from a title alone and remain at their zero/null defaults, so rules that gate on those functions need to be validated against a real search.
- Default sort order: regexScore first, seScore second
 - Fresh installs and Reset-to-Default produce a sort order where regexScore ranks above seScore, which ranks above the standard quality/encode/etc methods.
 - Both regexScore and seScore remain disabled by default; enable either (or both) in the Filters overlay to have rules drive ranking.
- **Max Series / Season Packs cap (TV-only)**
 - A new TV-tab filter caps how many pack results survive the filter pass. The cap is applied in priority order so the highest-quality packs are kept. Yearless packs deprioritized by Remake Detection don't count against the cap and remain at the end of the list.
 - No env var; UI-only setting.
- **Prefer Library Results toggle (Global)**

- When on, results that already exist in your WebDAV library () are sorted to the top of the list. Pairs with the existing "Display Library In Results" toggle, which provides the library annotation this sort needs.
- No env var; UI-only setting.
- **Remake Detection log fix**
 - detectRemake's 24h cache TTL meant the logging line vanished on every cache hit. The detected years are now cached alongside the boolean so the cached-path log matches the cache-miss format.

11) Migrations

- VVC (h.266)
 - Upgrading users get it appended to the end of encodePriority. enabled by default. Customized codec ordering is preserved
 - New installs and "Reset to Default" still get VVC at the top of the canonical encode list (highest priority).
 - Use Reset to Default or drag and drop to opt into the top-tier position.
- DCP
 - Upgrading users get DCP appended at the bottom of videoPriority. Same approach. enabled by default. Customized ordering is preserved
 - New installs and "Reset to Default" get DCP at its canonical position just above WEBCap.
 - Use Reset to Default for the canonical mid-tier position.
- NZB Fallback → Ultimate Fallback
 - v1.3.0 users with nzbdavFallbackEnabled: true are auto-enrolled into Ultimate Fallback with sequential single candidate, no health checks, no backups, priority mode, on-tile-selection, and "Use Ultimate Fallback to Resolve From Top of List" as the failure behavior. This is the 1:1 match for v1.3.0's NZB Fallback:

- When a stream tile fails, the addon falls into the UF lobby and resolves from the top of the candidate list, the same end-result as v1.3.0's automatic next-NZB chaining.
- The existing nzbdavMaxFallbacks cap carries over to ultimateFallback.maxAttempts.
- Legacy fields (nzbdavFallbackEnabled, nzbdavMaxFallbacks, nzbdavFallbackOrder, autoResolveOnSearch, autoResolveTargets) are stripped on first boot.
- Dead-NZB DB reclassification
 - Upgrading users with a populated dead-NZB DB on disk get a one-time reclassification on next startup.
 - Entries previously stored under the url::episodePattern key shape but flagged isEpisodeSpecific: false (a pre-existing tagging bug) are upgraded to isEpisodeSpecific: true, so they no longer trigger as URL-wide bans across other episodes of the same pack. DB contents are preserved, only the per-entry flag changes.
 - No action needed. New installs and entries written from this version onward set the flag correctly at write time via the defensive auto-tag in setDeadNzbEntry.
- Series Packs
 - Fresh installs default the toggle on with no keywords; upgrade migration leaves the toggle off so existing configs are unchanged.

12) Environment Variables

Added in v1.4.0

#	New Env Var	Type	Default	What it does
1	NZBDAV_STREAMING_METHOD	enum	proxy	Selects streaming delivery: pipe, proxy (dual-stage buffer), or direct (WebDAV redirect). Replaces NZBDAV_PROXY_ENABLED (legacy still accepted)

2	NZBDAV_PIPE_BUFFER_MB	int	8	Pipe-mode buffer size in MB (range 1-16)
3	SEARCH_TIMEOUT	int	15	Universal indexer search timeout (seconds, 1-45). Forces timeouts on and overrides per-indexer + top-level values
4	DISPLAY_LIBRARY_IN_RESULTS	bool	true	Mark search results that already exist in the WebDAV library with the  icon
5	ABSOLUTE_EPISODE_FALLBACK	bool	true	Series text-search retry with absolute episode numbering (Title E31) when the seasonal SxxExx query returns zero results. UTS only
6	PARALLEL_ALTERNATE_TITLE_SEARCH	bool	false	Query primary + each alternate title concurrently instead of using alts as a zero-result fallback. Doubles indexer load on title mismatches. UTS only
7	JUNK_FILTER	bool	true	Strip bare archive parts and NZB containers from search results
8	CACHE_EMPTY_RESULTS	bool	true	Cache search responses that returned zero results
9	LIBRARY_SEARCH_THRESHOLD	int	0	Ultimate Library: scan WebDAV before indexer queries; if $\geq N$ matches found, skip indexers entirely. NZBDav streaming mode only. 0 = disabled, 1-10 = active
10	LIBRARY_SEARCH_SCAN_UNCATEGORIZED	bool	true	Include /content/uncategorized as a second Ultimate Library scan root so manually uploaded NZBDav content is searchable
11	TVDB_PREFER_ENGLISH_TITLE	bool	true	Substitute the English translation when TVDB's canonical title is in a non-English language; improves indexer match rates for English release groups
12	ULTIMATE_FALLBACK_ENABLED	bool	false	Enable the Ultimate Fallback pipeline
13	ULTIMATE_FALLBACK_HEALTH_CHECK_ENABLED	bool	false	Run NNTP health-check pre-flight before nzbdav submission
14	ULTIMATE_FALLBACK_WHEN_TILE_RESOLVE	enum	on-tile-selection	When UF fires: on-tile-selection or on-results
15	ULTIMATE_FALLBACK_USER_PICK_FALLBACK	enum	failure-video	Behavior when an individual stream tile fails: failure-video, uf-lobby, or fallback-chain

16	ULTIMATE_FALL BACK_CANDIDA TE_COUNT	int	1	Parallel NZB candidates (range 1-10)
17	ULTIMATE_FALL BACK_PREFER ENCE_MODE	enu m	priority	priority (highest quality first) or speed (first healthy wins)
18	ULTIMATE_FALL BACK_SAMPLE _COUNT	int	3	Article segments sampled per health check (3 or 7)
19	ULTIMATE_FALL BACK_MAX_ATT EMPTS	int	0	Cap on total primary search attempts (0 = unlimited, 1-20). Library hits don't count
20	ULTIMATE_FALL BACK_DESIRED _BACKUPS	int	0	Container-matched backups to pre-cache after the primary resolves (0 = off, 1-10)
21	ULTIMATE_FALL BACK_BACKUP _PROCESSING_ LIMIT	int	3	Hard cap on post-primary backup grabs (0 = no cap, 1-20)
22	ULTIMATE_FALL BACK_PRIORIT Y_MOVIES_TIM EOUT	int	30	Stream wait time per nzbdav job (priority mode, movies)
23	ULTIMATE_FALL BACK_PRIORIT Y_TV_TIMEOUT	int	15	Stream wait time per nzbdav job (priority mode, TV)
24	ULTIMATE_FALL BACK_PRIORIT Y_SEASON_PA CK_TIMEOUT	int	30	Stream wait time per nzbdav job (priority mode, season packs)
25	ULTIMATE_FALL BACK_SPEED_ MOVIES_TIMEO UT	int	20	Stream wait time per nzbdav job (speed mode, movies)
26	ULTIMATE_FALL BACK_SPEED_T V_TIMEOUT	int	10	Stream wait time per nzbdav job (speed mode, TV)
27	ULTIMATE_FALL BACK_SPEED_ SEASON_PACK _TIMEOUT	int	20	Stream wait time per nzbdav job (speed mode, season packs)

28	LIBRARY_DELETE_ALL_TILE	bool	false	searchConfig.libraryDeleteAllTile
29	LIBRARY_DELETE_PER_STREAM_TILE	bool	false	searchConfig.libraryDeletePerStreamTile
30	LIBRARY_SKIP_TILE_POSITION	enum	second	searchConfig.librarySkipTilePosition (top accepted as alias for second)
31	LIBRARY_DELETE_ALL_PACK_SCOPE	enum	episode	searchConfig.libraryDeleteAllPackScope
32	ALIAS_TITLE_FALLBACK	bool	true	Fallback UTS with an alias date search

Removed in v1.4.0

#	Removed Env Var	Replacement / Migration
1	NZBDV_FALLBACK_ENABLED	ULTIMATE_FALLBACK_ENABLED
2	NZBDV_FALLBACK_ORDER	ULTIMATE_FALLBACK_USER_PICK_FALLBACK
3	NZBDV_MAX_FALLBACKS	ULTIMATE_FALLBACK_MAX_ATTEMPTS
4	NZBDV_LIBRARY_CHECK	always on in ultimate fallback, gate removed
5	NZBDV_PROXY_ENABLED	NZBDV_STREAMING_METHOD (legacy still accepted: true→proxy, false→direct)
6	AUTO_RESOLVE_ON_SEARCH	ULTIMATE_FALLBACK_WHEN_TO_RESOLVE (true→on-results, false→on-tile-selection)
7	NZBDV_JOB_TIMEOUT	ULTIMATE_FALLBACK_PRIORITY_*_TIMEOUT / ULTIMATE_FALLBACK_SPEED_*_TIMEOUT
8	NZBDV_MOVIES_TIMEOUT	same as above

9	NZBDAV_TV_TIMEOUT	same as above
1 0	NZBDAV_SEASON_PACK_TIME OUT	same as above