

Prepared for:	
For Address:	
Date:	



Uniform Mitigation Verification Inspection Form

	his form and any do	ocumentation provi	ded with the insurance	e policy		
Inspection Date:						
Owner Information			1			
Owner Name:			Contact Person:			
Address:			Home Phone:			
City:	Zip:		Work Phone:			
County:			Cell Phone:			
Insurance Company:			Policy #:			
Year of Home:	# of Stories:		Email:			
NOTE: Any documentation used in valid accompany this form. At least one photo though 7. The insurer may ask additional to D. W. C. L. W. at least one photo the photo control of the property	ograph must accompa al questions regarding	ny this form to valida g the mitigated feature	te each attribute market e(s) verified on this form	l in questions 3		
 Building Code: Was the structure build the HVHZ (Miami-Dade or Broward co □ A. Built in compliance with the FB 	ounties), South Florida	Building Code (SFBC-	94)?			
a date after 3/1/2002: Building Perr	mit Application Date (M	M/DD/YYYY)		**		
 B. For the HVHZ Only: Built in corprovide a permit application with a C. Unknown or does not meet the results. 	date after 9/1/1994: Bu	uilding Permit Applicat		94, 1995, and 1996		
	•					
 Roof Covering: Select all roof covering OR Year of Original Installation/Replace covering identified. 						
•	it Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance		
1. Asphalt/Fiberglass Shingle /						
_						
·	/					
☐ A. All roof coverings listed above r installation OR have a roofing perm				ent at time of		
	B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.					
\Box C. One or more roof coverings do n	not meet the requiremen	nts of Answer "A" or "I	B".			
☐ D. No roof coverings meet the requ	irements of Answer "A	a" or "B".				
3. Roof Deck Attachment : What is the w	eakest form of roof dea	ck attachment?				
A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c. by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalen mean uplift less than that required for Options B or C below.						
24"inches o.c.) by 8d common nail other deck fastening system or trus maximum of 12 inches in the field	B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.					
24"inches o.c.) by 8d common nail decking with a minimum of 2 nails	C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR-Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent					
Inspectors Initials Property Addre	ess					

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155 $Page\ 1\ of\ 4$

		or greater res	sistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least
	П		ed Concrete Roof Deck.
			CONCINCT ROOF BOOK
	П		or unidentified.
		G. No attic a	
4			
4.		eet of the insid	tachment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within the or outside corner of the roof in determination of WEAKEST type)
	Ш	A. Toe Nails	
			Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or
			Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
	Miı	nimal conditio	ons to qualify for categories B, C, or D. All visible metal connectors are:
			Secured to truss/rafter with a minimum of three (3) nails, and
			Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.
		B. Clips	
			Metal connectors that do not wrap over the top of the truss/rafter, or
			Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.
		C. Single W	
			Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
		D. Double V	Vraps
			Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or
			Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.
		E. Structural	Anchor bolts structurally connected or reinforced concrete roof.
		F. Other:	
		G. Unknown	or unidentified
		H. No attic a	access
5.			What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
		A. Hip Roof	
		B. Flat Roof	
		C. Other Ro	less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft of Any roof that does not qualify as either (A) or (B) above.
6.	Sec	A. SWR (also sheathing dwelling B. No SWR.	er Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) so called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the from water intrusion in the event of roof covering loss.
_			
In	spec	tors Initials _	Property Address
*Т	hia .	wa wif iaatian f	arm is valid for up to five (5) years provided no metarial changes have been made to the ethysture or

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. <u>Opening Protection</u>: What is the <u>weakest</u> form of wind borne debris protection installed on the structure? **First**, use the table to determine the weakest form of protection for each category of opening. **Second**, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings **and** (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart Place an "X" in each row to identify all forms of protection in use for each opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings.		Glazed Openings				Non-Glazed Openings	
		Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors
N/A	Not Applicable- there are no openings of this type on the structure						
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)						
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)						
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007						
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance						
	Opening Protection products that appear to be A or B but are not verified						
N	Other protective coverings that cannot be identified as A, B, or C						
Х	No Windborne Debris Protection						

A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at
a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval
system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure
and Large Missile Impact" (Level A in the table above).

- Miami-Dade County PA 201, 202, and 203
- Florida Building Code Testing Application Standard (TAS) 201, 202, and 203

☐ A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist

- American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
- Southern Standards Technical Document (SSTD) 12
- For Skylights Only: ASTM E 1886 and ASTM E 1996
- For Garage Doors Only: ANSI/DASMA 115

☐ A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above
☐ A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above
B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):
• ASTM E 1886 and ASTM E 1996 (Large Missile – 4.5 lb.)
• SSTD 12 (Large Missile – 4 lb. to 8 lb.)
• For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.)
☐ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist
\square B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above
☐ B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above
C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).

C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in

C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist

☐ C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

the table above

Inspectors Initials _____ Property Address_

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter protective coverings not meeting the requirements of with no documentation of compliance (Level N in the	Answer "A", "B", or C" or s	tation) A systems th	Il Glazed openings are protected with at appear to meet Answer "A" or "B'		
N.1 All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no Non-Glazed openings exist					
N.2 One or More Non-Glazed openings classified as Leve table above			• •		
N.3 One or More Non-Glazed openings is classified as Le	evel X in the table above				
☐ X. None or Some Glazed Openings One or more Gla	ized openings classified and	Level X i	n the table above.		
MITIGATION INSPECTIONS MUST Section 627.711(2), Florida Statutes, pro	~				
Qualified Inspector Name:	License Type:		License or Certificate #:		
Inspection Company:		Phone:	<u> </u>		
Qualified Inspector – I hold an active license as	a: (check one)				
Home inspector licensed under Section 468.8314, Florida Statitraining approved by the Construction Industry Licensing Board	rd and completion of a proficien		per of hours of hurricane mitigation		
Building code inspector certified under Section 468.607, Florid					
General, building or residential contractor licensed under Section A71 015. Florida					
 □ Professional engineer licensed under Section 471.015, Florida □ Professional architect licensed under Section 481.213, Florida 					
Any other individual or entity recognized by the insurer as pos		tions to pro	nerly complete a uniform mitigation		
verification form pursuant to Section 627.711(2), Florida Statu		areno te pre	porty compress a anniorm manganon		
Individuals other than licensed contractors licensed under					
under Section 471.015, Florida Statutes, must inspect the Licensees under s.471.015 or s.489.111 may authorize a dexperience to conduct a mitigation verification inspection	irect employee who possess				
	- · and I personally perform	ed the ins	nection or (<i>licensed</i>		
(print name)			-		
contractors and professional engineers only) I had my emp	oloyee ((print name		rform the inspection		
and I agree to be responsible for his/her work.	•	e of mspe	ctor)		
Qualified Inspector Signature:	Date:				
An individual or entity who knowingly or through gross a subject to investigation by the Florida Division of Insurar appropriate licensing agency or to criminal prosecution. certifies this form shall be directly liable for the misconduperformed the inspection.	nce Fraud and may be subj (Section 627.711(4)-(7), Flo	ject to adı orida Stat	ministrative action by the utes) The Qualified Inspector who		
<u>Homeowner to complete</u> : I certify that the named Qualif residence identified on this form and that proof of identificat					
Signature:	Date:				
An individual or entity who knowingly provides or utters obtain or receive a discount on an insurance premium to of the first degree. (Section 627.711(7), Florida Statutes)					
The definitions on this form are for inspection purposes of as offering protection from hurricanes.	only and cannot be used to	certify ar	y product or construction feature		
Inspectors Initials Property Address					
*This verification form is valid for up to five (5) years proinaccuracies found on the form.	ovided no material changes	s have bee	en made to the structure or		

Page 4 of 4

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155