

Table 1. DRAFT blank template; no measurements. Planned scene-level cost of first reaching the VIGS-SLAM highest observed held-out PSNR on a common checkpoint grid and horizon. Baseline cost is the first checkpoint attaining that peak; proposed-method cost is the first checkpoint attaining or exceeding the same target. Every registered sequence is retained and all curve-derived measurements are blank.

Dataset	Sequence	VIGS peak PSNR	VIGS renders to peak	Ours renders to target	Saved renders	Reduction (%)	Final PSNR VIGS / Ours
RPNG	table_01	—	—	—	—	—	—
	table_02	—	—	—	—	—	—
	table_03	—	—	—	—	—	—
	table_04	—	—	—	—	—	—
	table_05	—	—	—	—	—	—
	table_06	—	—	—	—	—	—
	table_07	—	—	—	—	—	—
	table_08	—	—	—	—	—	—
UTMM	ego-centric-1	—	—	—	—	—	—
	ego-centric-2	—	—	—	—	—	—
	ego-drive	—	—	—	—	—	—
	fast-straight	—	—	—	—	—	—
	slow-straight-1	—	—	—	—	—	—
	slow-straight-2	—	—	—	—	—	—
	square-1	—	—	—	—	—	—
	square-2	—	—	—	—	—	—
Aria	aria1253	—	—	—	—	—	—
	aria1253rot	—	—	—	—	—	—
	aria301_12F	—	—	—	—	—	—
	aria301_305	—	—	—	—	—	—

— = unmeasured; NR will denote a target not reached within the shared horizon. Saved renders are $u_{V,s}^* - u_{O,s}^*$ and reduction is $100(1 - u_{O,s}^*/u_{V,s}^*)\%$; negative values will be retained. Scene-level median reduction and reached n/N will be summarized only after measurement. Checkpoint crossings are measured grid points, without unlabelled interpolation; zero baseline cost requires NA handling.