pi.dev — AI coding assistant with read, bash, edit, write tools

WRITE BETTER CODE.
SOLVE BIGGER PROBLEMS.
WITH PI.

1 USAGE

```
$ pi [options] [--] [@files...] [messages...]
```

Run pi with optional flags, file references, and a message or prompt.

2 COMMANDS

`pi install <source> [-l]`
Install a tool or extension

`pi remove <source> [-l]`
Remove a tool or extension

`pi uninstall <source> [-l]`
Uninstall a tool or extension

`pi update [source|self|pi]`
Update a tool, self, or pi

`pi list`
List installed tools and extensions

`pi config [-l]`
View or edit configuration

`pi auth <command>`
Authentication commands

`pi mcp <command>`
Model Context Protocol commands

`pi <command> --help`
Show help for a command

3 KEY OPTIONS

`--provider`	AI provider
`--model`	Model to use
`--api-key`	API key
`--system-prompt`	System prompt
`--append-system-prompt`	Append to system prompt
`--mode`	Operation mode
`--print/-p`	Print output
`--continue/-c`	Continue session
`--resume/-r`	Resume session
`--session`	Session name
`--session-id`	Session ID
`--fork`	Fork session
`--session-dir`	Session directory
`--no-session`	Disable sessions
`--name/-n`	Session name
`--models`	List available models
`--no-tools/-nt`	Disable tools
`--no-builtin-tools/-nbt`	Disable built-in tools
`--tools/-t`	Specify tools
`--exclude-tools/-xt`	Exclude tools
`--thinking`	Enable thinking mode
`-extension/-e`	
`--no-extensions/-ne`	Disable extensions
`--no-mcp`	Disable MCP
`--skill`	
`--no-skills/-ns`	Disable skills
`--prompt-template`	Prompt template
`--no-prompt-templates/-np`	Disable prompt templates
`--theme`	Theme name
`--use-theme`	Use theme
`--no-themes`	
`--no-context-files/-nc`	Disable context files
`--export`	Export session
`--list-models`	List models
`--verbose`	Verbose output
`--tui-mode`	Use TUI mode
`--approve/-a`	Auto-approve
`--no-approve/-na`	Disable auto-approve
`--offline`	Offline mode
`--help/-h`	Show help
`--version/-v`	Show version

4 EXAMPLES

Authenticate and print your API key

```
$ pi auth print-api-key --provider openai
```

Quickly list files

```
$ pi "List all .ts files in src/"
```

Use files as context and ask a question

```
$ pi @prompt.md @image.png "What color is the sky?"
```

Print output (non-interactive)

```
$ pi -p "List all .ts files in src/"
```

Use specific tools

```
$ pi --tools read,grep,find,ls -p "Review the code in src/"
```

Use codemode (specialized coding mode)

```
$ pi --tools +codemode
```

5 ENVIRONMENT VARIABLES

`PI_CODING_AGENT_DIR`	Base directory for coding agent data
`PI_CODING_AGENT_SESSION_DIR`	Session storage directory
`PI_PACKAGE_DIR`	Package directory
`PI_OFFLINE`	Disable network access
`PI_TELEMETRY`	Enable/disable telemetry
`PI_SHARE_VIEWER_URL`	URL for share viewer

6 BUILT-IN TOOLS

read — Read files and content
bash — Run shell commands
powershell — Run PowerShell commands
edit — Edit files in place
write — Create new files
grep — Search with patterns
ls — List files and directories





