Product:

High Performance Door

NIHVA RapidRoll® 392

Description:

Flexible High Performancel Door, opening in vertical direction, for interior and exterior use.

Self-supporting side frames of bended galvanized steel profiles. All steel parts galvanized, springs for curtain tension and counterbalance in the side frame.

Door curtain of transparent PVC with vertically applied side reinforcement stripes, ultramarine (similar to RAL 5002) or red (similar RAL 3002).

Wind protection: through wind taps on the door curtain.

Wind resistance: class 2 (EN 12424)

Bottom profile: anodized aluminium

Drive unit: gear motor

Protection: IP 55

Control system: ACS 50, electronic control system with mini contactors including main switch and open-stop-close switch, control voltage 24 V DC

Supply voltage:

ACS 50: 3L(N)PE/230/380/400/415V; 50 Hz

Transformator necessary for 440/480/500V; 50 Hz

Safety devices: electrical safety contact edge, stationary safety photocell, drop down protection by integrated balancing system.

Manual activation: by releasing the brake at ground level.

Opening/closing speed: up to max. 0.8 / 0.8 m/s

Size max.: (DWxDH) 6000 x 6000 mm

Make: ALBANY RapidRoll® 392

Options

Covers:.

Top roll cover made of galvanized steel

Motor cover made of plastic, colour grey (similar RAL 7040)

Door curtain (alternatively):

PVC with coloured reinforcement stripes

Beige (similar RAL 1014),
Yellow (similar RAL 1021),
Orange (similar RAL 2011),
Green (similar RAL 6018),
White (similar RAL 9016) or

Grey (similar RAL 7035).
PVC with silicone-free reinforcements stripes
RollTex® Plus (fabric stiff across the grain) – colour
Blue (similar RAL 5002),
Orange (similar RAL 2009) or
Grey (similar RAL 7001)
Window DWxDH 500x700 mm (only for RollTex® Plus curtain)
Window DWxDH 700x500 mm (only for RollTex® Plus curtain)

Control system (alternatively):

Frequency converter control system MCCVectorControl, based on vector control system including boost function for start-up,
(open/close) up to max. 2.2/0.9 m/s,
Supply voltage 3L(N)PE/380/400/415/440/480V;50/60Hz,
Transformer necessary for 220/230/500V; 50/60 Hz

Miscellaneous:

- Knock out function with sensor
- Chain drive
- Extended flexible seal
- Actuators
- Additional safety devices

Delivery:

Installation incl. wiring