Preventive Maintenance Manufacturer's Specification

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions

Enhance the durability of your High Performance Door Albany RR3000 ISO

Key benefit

Safety

Cost-Savings

Just as a car's tires and oil must be changed regularly, your Albany High Performance Doors have key components that periodically need replacing. Whether it's a spring or a sprocket, changing them before they break is an integral part of Pro-Active Care.

We at ASSA ABLOY Entrance Systems believe in Pro-Active Care. Letting us replace components before they fail keeps your warranty valid and your equipment compliant with regulations. Even more importantly, it ensures the safety and functionality of your equipment, so that you can avoid accidents and losses in productivity.



Instructions for table usage:

Qualified person
The manufacturer's recommendation for exchange of components is subject to the findings of a qualified person. We strongly recommend that inspections are performed by a qualified person within the recommended service intervals (according to the user manual of the door).

Recommendations for exchange
The manufacturer's recommendations are based on a door with average size, installed under regular environmental conditions. Doors dimensioned close to maximum size of the door type or doors installed in harsh environmental conditions, need particular observation by a qualified person as the recommended intervals might be shorter.

Components specified as wear and tear related do not have a recommended exchange interval, indications for exchange or wear can be derived from the corresponding fact sheets.

Subject to technical modifications without notice. Errors and omissions excepted.

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization

Preventive Maintenance
Manufacturer's Specification

ASSA ABLOY

Albany RR3000 ISO

Product group	Description	200.000 cycles	400.000 cycles	500.000 cycles	750.000 cycles	1.000.000 cycles	1.000.000 cycles or 5 years	5 years	10 years
Actuators	Photocell receiver re / tr								●
	Safety light grid re / tr								●
Sealing	Lamella sealing					●			
	Rubber spring top sealing	●							
	Guiding plate top sealing compl.	●							
Cable chain	Cable chain, complete with cable and bracket, only on safety edge			●					
Counterbalancing	Flat belt A 33-200 spare part compl.			●					
	Spring suspension top complete				●				
	Springs above 4,2 Meters height	●							
	Springs up to 4,2 Meters height		●						
	Belt, (Type A), L=6000, up to 4200 mm		●						
	Belt, (Type A), L=6000, above 4200 mm	●							
	Belt (Type B, C), L=7000	●							
	Belt idler 1 compl., above 4,2 Meters	●							
	Belt idler 1 compl., up to 4,2 Meters		●						
Top roll	Dampening profile 2, L=6000	●							
	Flange bearing					●			
	Top roll with lamellas complete (*)					●			
Lamella	Lamellas					●			
	Dampening profile 2., L=6000 for clamping blocks		●						
Bottom profile	Bottom profile safety edge compl.							●	
Sliding/Guiding	Sliding rail, middle/low guide cover area					●			
	Sliding rail, upper guide cover area			●					
Switch	Limit switch								●
	Proximity switch								●
Drive unit	Brake - frequency converter					●			
	Drive unit - frequency converter					●			
	Junction box								●
	Microswitch						●		
Chain drive	Chain drive unit - frequency converter					●			
	Locking element					●			
	Pinion chain drive barrel			●					
	Roller chain			●					
Encoder	Encoder 50 pulses, only electronic part								●
Damper	Vibration absorber			●					
Signals	LED-stripe red/green, 24V DC								●

≤150.000 cycles: ±10.000 cycles; >150.000 cycles: ±20.000 cycles
≤5 years: ±6 months; >5 years: ±1 year

© ASSA ABLOY Entrance Systems AB PL.MAN/RR3000 ISO/DEU,EN-1.1/1504 / 64 100 479 Technical data subject to change without notice

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization