Sectional Overhead Door Model 1042P



Description	➢ Overhead sectional door/sectional door with square grid design sandwich panels filled with CFC free polyurethane core, 42mmthick, 545mm high with standard colors. ➢ Double acrylic vision panels ➢ Integrated finger pinch protection ➢ Top, bottom and side seals and seals between door sections ➢ High Lift/Vertical track system in galvanized steel ➢ Spring balancing, 20,000 cycles ➢ Spring break device ➢ Lock bolt, step-handle ➢ Compliance with all operational and safety instructions in EU Directives and the standards of the European Standardization Committee (CEN) ➢ Operating system: Electric • Wind load (EN 12424) - Class 3 (700 N/m²) ➢ Thermal transmittance (EN 12428) – 1.1 W / (m² K) • Water penetration (EN 12425) - Class 3, 70 PA ➢ Air permeability (EN 12426) - Class 3
Bottom Sections	Sandwich panel across entire width, surface square grid, Section height 545mm plus bottom seal
Glazing	Optional Double acrylic double sealed oval/rectangular shaped.
Surface color:	1. Exterior RAL 9010 and interior natural aluminum finish 2. Interior and / or exterior painted in RAL-standard color buyer's choice at extra cost
Hardware	Vertical/High lift
Operator	Electronic operator: Operating voltage: 230 V AC, 50/60 HZ (internal supply 3-phase 230 V AC) Operating factor: ED = 30%, S3 10 min, non-continuous operation (Engine operation 3 min, pause 7 min, direct-inverting) Torque: 15-40 Nm, depending on reel type (value of given door shaft) Fusing: 10 A

	Brake: non-reversible worm gear Speed monitor: electronic monitoring Freewheel / clutch: mechanical engagement/disengagement Limit switch: electronic via torque (setting "Door open" during programming) Setting "Door closed" in processor board Gears: worm gear 1750 RPM yields approx. 24 rotations door shaft Shaft: ø35 mm or hexagonal Direct drive system No special wall reinforcement necessary Temperature range: -20°C to 60°C Soft stop, soft start Connection using "CEE plug" or lockable mains isolator Maximum door weight capacity 400 kg
Control units	a) Loading Area Integrated control unit 950 DLA SD to operate Sectional Door& Dock leveler with automatic return to cross traffic position after operational cycles. Push button control from inside b) Internal Doors Standard 950 controls equipped with UP DOWN STOP buttons and error displays. Additionally pull switch controller is provided Output 0.37 kW, input 1 x 230 V. Including control unit with standard actuator UP-STOP-DOWN. The door closes using pulse control incl. self-monitoring safety edge Operating speed 0.25 m/s, safety rating IP 55. If there is a power failure, the disengage device enables manual operation at any time