A guide to preventative maintenance for Albany High Performance Doors

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions



Rigid door blade

What is the function?

- To separate areas
- Handling wind load
- Reducing energy costs
- Protecting people
- Securing premises

How do they wear?

During the lifetime of the rigid door blade there will be wear and tear due to:

- Friction between curtain and side frame
- Wear of lamella sealing (hardening)
- Winding on the spiral discs (wear on end pieces)
- The wind load causing the lamellas to bend
- Crashes
- Cleaning agents on window lamellas (opacity)
- Forces on flat belt

What is the manufacturer's specification?

To make sure the manufacturer's specifications are observed, replace every:

- 750.000 cycles

Can I also replace it earlier?

- Yes, if the lamella sealing looses position
- Cracks and deflections in end pieces
- Cracks on the outer edges of the lamellas
- Partial or complete crack in the flat belt
- Rust on the flat belts with metal inlets
- Missing rivets or screws

What is the risk of not replacing?

When not following the manufacturer's specifications the customer is taking the responsibility for unintended breakdown, e.g.:

- There may be cracks in the curtain, which will reduce the wind load capabilities
- Loose of functionality, which can cause a safety issue
- Higher costs for repair
- Reduced opacity, which increases risk for injuries or accidents
- Higher air leakage and higher energy costs

Top reasons for preventive maintenance

- Keeps the warranty valid
- Prevents unexpected and expensive break-downs
- Prolongs lifetime
- Cost saving
- Minimises risk of personal injury
- Minimises energy loss
- Fulfills legal requirements
- Improves working environment

©ASSA ABLOY Entrance Systems AB/PL.MAP/DEU-EN-1.0/1504

ASSA ABLOY ENTRANCE SYSTEMS Maintenance & Modernization