A guide to preventative maintenance for Albany High Performance Doors

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions



Brush

What is the function?

- Sealing and reducing air leakage
- Guiding and stabilizing of the spring
- Vibration damping

What is the manufacturer's specification?

To make sure the manufacturer's specifications are observed, replace every:

- 150.000 cycles (RR300 Plus)
  500.000 cycles (RR600)

Can I also replace it earlier?

- Abrasion and lose of hairs indicating a need for replacement
- Dirt on the brush or curtain
- Hairs / or excessive dust on the bottom plate

How do they wear?

During the lifetime of the brush there will be wear and tear due to:

- Abrasion
- Loosing hairs due to mechanical movement over the brush

What is the risk of not replacing?

When not following the manufacturer's specifications the customer is taking the responsibility for unintended breakdown, e.g.:

If sealing function is reduced, energy loose increases, along with noises.

Top reasons for preventive maintenance

- Keeps the warranty valid
- Prevents unexpected and expensive break-downs
- Prolongs lifetime
- Cost saving
- Minimises risk of personal injury
- Minimises energy loss
- Fulfills legal requirements
- Improves working environment

©ASSA ABLOY Entrance Systems AB/PL.MAP/DEU-EN-1.0/1504

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization