

PRODUCED BY AN AUTODESK EDUCATIONAL PRODUCT




NOTES :–


1) Door Frame shall be fabricated from 1.2mmThk. Glav. steel sheets to form a double rebate profile & fixed to wall with Anchor bolts.
2) Shutter Panels shall be fabricated from 0.8mmThk. Galv.steel having Tray & Cover Construction to provide a nominal thickness of 43mm. Shutter flatness may vary till 5mm.& shutters shall have infill material with reinforcements at top, bottom edges & for hardware fitments.
3) 4nos. of SS Ball Bearing Butt Hinges shall be provided on each Shutter Size 4"x3"X3mm––
4) Dorma PHCR 1000 Panic bar with Outsie trim
5) SS D Handle Pair
6) Door Closer



SECTION 'S2–S2'



DEATIL–'A'



COLOUR: RED

RIGHT HAND DOORS.09Nos.

SINGLE LEAF 1200 X 2200 FIRE DOORS

This drawing & designing is the property of NIHVA TECHNOLOGIES. Not be sold or copy to any other concern.

TITLE: SPECIFICATIONS OF SINGLE LEAF FIRE DOOR			NIHVA TECHNOLOGIES PVT. LTD.
	SIGN	DATE	
DRAWN	ABHIJIT	12/09/15	CLIENT–ZAMIL STEEL BUILDINGS (I) PVT.LTD
CHECK	ANIL	12/09/15	PROJECT –
REV.	01		SITE –
CLIENT APPROVAL			DWG. NO. –NIHVA/15–16/75
			SCALE: 01 | Ref. No. | SHEET: 01
ALL DIMENSION ARE IN mm			If any queries contact : projects@nihva.com

NIHVA TECHNOLOGY PVT. LTD. PUNE.
Tel : 020 66304033
Email:– info@nihva.com
Website:– www.nihva.com

PRODUCED BY AN AUTODESK EDUCATIONAL PRODUCT

PRODUCED BY AN AUTODESK EDUCATIONAL PRODUCT