






MATERIAL HANDLING SOLUTIONS CATALOGUE - ARM SYSTEMS (Revision: A01)

#	Arm Type	Arm Capacity		Rotation Angle	Reach (Radius)		I-Beam Ht. (For Overhead) Pillar Ht. (For Floor Mtd.)		Vertical Travel		Max. CG Offset from Pivot point (mm)	Max Push/Pull Force (Kg)	Snapshot	Remarks	Recommended Over Head Rail Sys.
		Min (Kg)	Max (Kg)	(deg)	Min (mm)	Max (mm)	Min (mm)	Max (mm)	Min (mm)	Max (mm)					
1	**OFP** = Overhead rigid front pantograph	5	60	360	1500	2200	3900	4100	100	600	2400	8 - 12		# 360 deg. Rotation is non-continuous. # No dead weight for Arm Balancing # Can be used with single direction overhead Rail System Also. (Only Runways)	ZRS2
2	**FFP** = Floor mounted rigid front pantograph	5	80	360	1500	2200	3300	-	100	600	2400	8 - 10		# 360 deg. Rotation is non-continuous # No dead weight for Arm Balancing	
3	**ORP** = Overhead rigid rear pantograph	**5**	80	360	1500	2200	3900	4100	100	600	2400	8 - 15		# 360 deg. Rotation is non-continuous # Dead weight for Arm Balancing # Can be used with single direction overhead Rail System Also. (Only Runways)	ZRS2 ZRA1
4	**ORP** = Overhead rigid rear pantograph	**5**	120	360	800	1100	3900	4100	100	600	1250	8 - 12		# 360 deg. Rotation is non-continuous # Dead weight for Arm Balancing # Can be used with single direction overhead Rail System Also. (Only Runways)	ZRS2 ZRA1
5	**FRP** = Floor mounted rigid rear pantograph	5	120	360	1800	2200	3200	-	100	600	2400	8 - 12		# 360 deg. Rotation is non-continuous # Dead weight for Arm Balancing	
6	**ORT** = Overhead Rigid Telescopic	10	400	360	-	-	3900	4100	100	600	300	6 - 10		# 360 deg. Rotation is non-continuous. # X-Y Rail system required to cover Floor Area. # Suitable for high Loads with less human effort.	ZRS2
6	**ORR** = Overhead Rigid Rotating	**5**	50	360	1500	2200	3900	4100	100	600	2400	8 - 12		# 360 deg. Rotation is non-continuous # X-Y Rail system required to cover Floor Area. # Suitable for high Loads with less human effort.	ZRS2 ZRA1
7	**FRR** = Floor mounted Rigid Rotating	5	80	360	1500	2200	3000	-	100	600	2400	8 - 10		# 360 deg. Rotation is non-continuous # Suitable for light loads.	
8	**OFB** = Overhead Flexible with Wire rope Balancer	For selection of **overhead rail system** refer Catalouge no - **16598542** For selection of **Balancer** refer **Global Ergonomic Handling Systems Catalouge (IRITS-0309-035)**												-	

MATERIAL HANDLING SOLUTIONS CATALOGUE - ARM SYSTEMS (Revision: A01)

#	Arm Type	Arm Capacity		Rotation Angle	Reach (Radius)		I-Beam Ht. (For Overhead) Pillar Ht. (For Floor Mtd.)		Vertical Travel		Max. CG Offset from Pivot point (mm)	Max Push/Pull Force (Kg)	Snapshot	Remarks	Recommended Over Head Rail Sys.
		Min (Kg)	Max (Kg)	(deg)	Min (mm)	Max (mm)	Min (mm)	Max (mm)	Min (mm)	Max (mm)					
9	**FFB** = Floor mounted flexible with wire rope balancer	For selection of **Balancer & Jib Crane** refer **Global Ergonomic Handling Systems Catalouge (IRITS-0309-035)**												-	
10	**OVC** = Vertical Offset with Pn. Cylinder	**5**	150	360	-	-	3900	4100	100	600	400	6 - 10		# 360 deg. Rotation is non-continuous	ZRS2 ZRA1
11	**OVB** = Vertical Offset with Balancer	**10**	225^	360	-	-	3900	4100	100	1500	400	8 - 12		# 360 deg. Rotation is non-continuous ^ Capacity depends upon air pressure availability. (Refer Balancer Catalogue for more details)	ZRS2 with 500 Lbs Balancer ZRA1 with 500 Lbs Balancer
13	**OSS** = Overhead Rigid See-Saw Type	**180**	240	360	500	1500	3900	4100	+ 22.5 Degree	- 22.5 Degree	1600	8 - 12		# 360 deg. Rotation is non-continuous # Most suited for forging Industries.	ZRS2 ZRA1
14	**SSA** = 600 Series Arm	For selection of **Balancer & 600 Series Arms** refer **Global Ergonomic Handling Systems Catalouge (IRITS-0309-035)**												# 360 deg. Rotation is non-continuous	
15	**UBA** = Under Body Arm	5	60	360	1800	2200	3900	4100	100	600	2400	8 - 10		# 360 deg. Rotation is non-continuous. # Suitable for underbody applications. # Can be used as Torque Reaction Arm also.	ZRS2 ZRA1