Product:

High Performance Door ®

NIHVA RapidRoll 300 Plus

Description:

Flexible High Performance Door, opening in vertical direction for interior use in wind-protected areas.

Self-supporting side frames made of aluminium.

Door curtain made of transparent PVC with fabric reinforcement stripes, ultramarine (similar to RAL 5002) or red (similar to RAL 3002).

Top roll made of anodized aluminium.

Wind protection: wind tabs on the door curtain.

Wind resistance: class 1 (EN 12424).

Bottom profile: anodized aluminium.

Drive unit: Hollow shaft gear motor.

Protection: IP 55

Control system: ACS 50, electronic control system with mini contactors including main switch and open-stop-close switch, control voltage 24 V DC.

Supply voltage:
ACS 50: 3L(N)PE/230/380/400/415V, 50Hz
Transformator necessary for 440/480/500V 50Hz.

Safety devices:
electrical safety contact edge, evaluation via integrated cable chain, door line photocell in the side frames, drop down protection by integrated balancing system.

Manual activation:
by releasing the brake at ground level. Depending on width/height ratio the door opens up to max. 2.0 m.

Opening / closing speed: up to max. 1.2 / 1.2 m/s.

91 8551091333 ☎ +91 20 66304033

Email: marketing@nihva.com

Size max.: (DWxDH) 5000 x 5000 mm.

Make: ALBANY RapidRoll® 300 Plus Alu

Options

Surface / material:

Covers
Top roll cover required for doors DH < 2500 mm
Motor cover required for doors DH < 2500 mm

Door curtain (alternatively):

- PVC with coloured reinforcement stripes:
  Beige (similar RAL 1014),
  Yellow (similar RAL 1021),
  Orange (similar RAL 2011),
  Green (similar RAL 6018),
  White (similar RAL 9016) or
  Grey (similar RAL 7035).

- PVC with silicone-free reinforcement stripes – colour
  Blue (similar RAL 5010),
  Alu-grey (similar RAL 7037),
  Red (similar RAL 3002),
  Yellow (similar RAL 1021),
  Orange (similar RAL 2011),
  White (similar RAL 9010),
  Black (similar RAL 9005).

- Curtain made of RollTex® Plus – colour
  blue (similar RAL 5002),
  orange (similar RAL 2009) or
  grey (similar RAL 7001)

- Curtain made of RollTex® Original – colour
  Blue (similar RAL 5002),
  Orange (similar RAL 5002) or
  Grey (similar RAL 7001)

- Curtain made of NomaTex® – colour
  Grey (similar RAL 7038, varnishable on request)
- Window (DWxDH) 500x700mm (only for RollTex® or NomaTex®)
- Window (DWxDH) 700x500mm (only for RollTex® or NomaTex®)
- Vision panels for curtain NomaTex®

- Curtain made of NomaTex® flame retardant without vision panels or window- colour grey (similar RAL 7045)

- Curtain made of fabric type travitop - colour
  Blue (similar RAL 5010),
  red (similar RAL 3002) or
  grey (similar RAL 7035)
- vision panels for curtain type travitop

Control system (alternatively):
Frequency converter control system MCC^{VectorControl}, based on vector control including boost function at start-up. Graphic display and foil keypad for easy guided operation. Easy access to all important information for operation and service,
(open/close) up to max. 2,2/0,9 m/s,
Supply voltage 3L(N)PE/380/400/415/440/480V;50/60Hz,
Transformer necessary for 220/230/500V

Miscellaneous:
- Knock-out capability with sensor, only for version with coil cable (without interior cable chain),
- Not possible in combination with integrated light curtain
- Integrated light curtain not possible in combination with knock-out function
- Automatic egress on power failure
- Extended flexible seal
- Actuators

Option: Escape and rescue routes:

Size max.: (DWxDH) 4000 mm x 4000 mm

Wind resistance: class 1 (EN 12424) up to DH = 3500 mm, class 0 (EN 12424 at DH > 3500 mm

Control unit:
Solely frequency converter control MCC^{VectorControl} with extension and special software (configuration).

Drive unit: hollow shaft gear motor with operating current brake

Emergency opening: In case of power failure the door opens automatically, the door can be opened manually via the main switch/CEE plug.

A radar motion detector for the detection of people is included in delivery.

Key switches for the deactivation of the escape and rescue function is optionally available.

Delivery:
Installation incl. wiring