TENSILE ARCHITECTURE
TECHNICAL TEXTILES

LUCKY-TECH MEMBRANES

**Product** **TRANSPARENT PVC**

| | | | |
|---|---|---|---|
| Type of Coating and finish | | | |
| Type of Coating | Clear PVC | | |
| Total Weight | 2500 | $g/m^2$ | EN ISO 2286 - 2 |
| Thickness | 2 | mm | DIN EN ISO 2286 - 3 |
| Cold Resistance | -20 | $^0C$ | EN ISO 1876 - 1 |
| Dimensional Stability at 60 $^0C$ | MD <5 CD <2 | % | ASTM-D 1204 |
| High Temperature | +50 | $^0C$ | PA. 07.04 (intern) |
| Remarks | no Scrim | | |
| Tensile Strength $KG/cm^2$ | MD250: CD190 | $KG/cm^2$ | EN ISO 527-3 |
| WeiterreiBfestigkeit $KG/mm^2$ | MD 15,5:CD 15,5 | $KG/mm^2$ | EN ISO 6383 - 1 |

These Indicated technical data are based on average results.Due to production procedures deviations upto -10% can occur. All technical data in accordance with present standard of knowledge and give product information without legal binding. All data apply to new products. Application suggested do not release the customer to test the material for its intended application.

an exclusive partner of SICEN

Design & Engineering From Technet, Germany TECHNET
Automated, Accurate Cutting Machine From ZÜND
High Frequency Fabric Welding From FORSSTROM