Motorized Rolling Shutter

Sr .No.	Specification	Motorized Rolling Shutter
1	**Description:**	Motorised Rolling Shutter with GI Slats with thickness of 1.2 mm.
2	**Mounting Location area**	Inside area
3	**Mounting Surface**	On MS structure, need to submit staructure drawing
4	**Curtain Panel**	The panel made of 1.2 mm thick GI.
5	**Curtain panel size**	75mm wide
6	**Curtain Profile**	Curved with 450 mm Grill at center of the shutter height
7	**Bottom Profile**	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
8	**Side Guide Profile**	M.S." U" Shaped profile 65 mm -150 mm x 3 mm thick.
9	**Roller Shaft**	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Día -100 to 300 mm as per w x h
10	**Side Brackets**	MS Plate 3 mm to 10 mm thick, as per the opening dimension.
11	**Hood Cover**	Made of GI Sheet Thickness 0.9 mm
12	**Surface finish**	Powder coated
13	**Drive Unit & Mounting Type**	Electric Motor - Indirect Mounting - Sprocket chain arrangement – IP54 Protection

GI 1.2mm Single Skin Gear Opearated Rolling Shutter

Sr .No.	Specification	GI 1.2mm Single Skin Gear Opearated Rolling Shutter
1	**Description:**	GI 1.2mm Single Skin Gear Opearated Rolling Shutter
2	**Mounting Location area**	Inside area
3	**Mounting Surface**	Wall mounted
4	**Curtain Panel**	The panel made of 1.2 mm thick GI
5	**Curtain panel size**	75mm wide
6	**Curtain Profile**	Curved with 450 mm Grill at center of the shutter height
7	**Bottom Profile**	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
8	**Side Guide Profile**	M.S." U" Shaped profile 65 mm -150 mm x 3 mm thick.
9	**Roller Shaft**	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Día -100 to 300 mm as per w x h
10	**Side Brackets**	MS Plate 3 mm to 10 mm thick, as per the opening dimension.
11	**Hood Cover**	Made of GI Sheet Thickness 0.9 mm GF mm
12	**Surface finish**	Powder coated
13	**Drive Unit & Mounting Type**	Gear assembly