NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk,
MIDC, Chinchwad.
Pune – 411019

An ISO 9001:2015Certified Company

GST Pune : 27AAECN0437H1ZM

NIHVA Sales Quotation

Jindal Aluminium Ltd
KIADB Industrial Area, Yedihalli Village, Tumkur Road
Dobbaspet, Nelemangala Taluk
Bangalore Rural Dist. 562111

Date : **15.10.2019**
Quote NO : **SQT.19.20.2165**
Kind Attn : **Mr. Mohan Ram Manju**
Email Id : jrmpur@jindalaluminium.com
Contact No: **9900058284**

Subject : Quotation for High Speed Door HS9020G & Rolling Shutter

Dear Sir,

Thank you for your opportunity and trust shown on "NIHVA" your preferred partner for innovative solutions. This has reference to your above mentioned requirement, please find below our Solutions.

Sr. No	Description	Pages
A.	Commercial Offer	1
B.	Technical Specification	2
C.	General Conditions	3
D.	Terms & Condtions	3

A) Commercial Offer

Sr No	Description	Size		Qty	Supply Charges in INR		Installation Charges in INR	
		Clear Width (mm)	Clear Length (mm)	(Nos)	Unit Price	Total Amount	Unit Price	Total Amount
1	Albany Make Rapid Roll Up Door HS9020G	2438	3048	1	4,85,000	4,85,000	20,000	20,000
2	Motorised Rolling Shutter	4877	4877	1	1,85,000	1,85,000	20,000	20,000
				Total		**6,70,000**		**40,000**
3	P&F Charges			3%		**20,100**		
	Total Without Taxes					**6,90,100**		**40,000**
	GST Extra @ 18%			18%		1,24,218		7,200
	Total With Taxes					**8,14,318**		**47,200**
4	Transportation Charges					**In Client Scope**		
5	Unloading Charges @ Site					**In Client Scope**		

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk,
MIDC, Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

B) Technical Specification

ASSA ABLOY Make Rapid Roll Up Door HS9020G **(Supply + Installation + Interlocking between two doors)**	
• The HS9020G high speed door is designed for interior applications.	
Description	**Specification**
Drive System	Gravity Driven System
Opening Speed	up to 2.0 m/s depending on size of door.
Closing Speed	up to 0.5 m/s depending on size of door.
Photocells	Inside Columns
Wind Load Resistance	(EN 12424) Class 1 (300 Pa (N/m²)). Maximum wind load while closing 50 Pa (N/m²)
Water Penetration	(EN 12425) Class 2 (50 Pa (N/m²)) 20 minutes water spray
Air Permeability	(EN 12426) Class 1 (24 m³/m²/h at 50 Pa)
Thermal Resistance	(EN 12428) 6,02 W/(m²K)
Temperature Working Range	5 °C to +40 °C
Door Curtain	900 g/m² colored PVC, material thickness: 0,8 mm
Various Window	400 mm height single row
Operator	220V - 240V 1-phase 0,75 kW 16A
Operator Protection	IP65
Control Unit Protection	IP54
Lifetime Expectations	1,000,000 cycles
• Unique side column technology provides excellent seal on all 4 sides thereby reducing heat loss.	
• The door design withstands overpressure or underpressure in specific areas	
• Flexible door curtain without ridged parts.	
• Flexible soft bottom edge including wireless edge activator.	
• Break-away and self-repair function.	
• The door curtain is available in 8 standard colors.	
• The motor with frequency converter guarantees smooth and reliable operation.	
• Soft start/stop significantly prolongs motor lifespan.	
• Control unit with display, impulse Up and Down buttons, an emergency stop mushroom button and a mechanical main switch.	

Rolling Shutter	
Specification	**Description**
Rolling Shutter	Motorised Rolling Shutter with MS Laths with thickness of 1 mm.
Mounting Location area	Inside area / Outside area
Mounting Surface	Side Brackets: Optional = On Concrete /Steel & Side
Curtain Panel	The panel made of 1.0mm thick MS.
Curtain panel size	75mm wide
Curtain Profile	Curved
Bottom Profile	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
Side Guide Profile	M.S." U" Shaped profile 65 mm -150 mm x 3 mm thick (as per the opening width dimension)
Roller Shaft	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Dia - 100 to 300 mm as per w x h
Side Brackets	MS Plate 3 mm to 10 mm thick, as per the opening dimension.
Hood Cover	Made of MS Sheet Thickness 0.9 mm with 25x25x3mm angle stiffener
Surface finish	PU paint or Powder coated
Drive Unit & Mounting Type	Indirect Drive, Electric Motor - Direct Mounting - Sprocket chain arrangement – IP54 Protection

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk,
MIDC, Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

C) General Conditions

1 Installation will start after receiving of Site Readyness Photographs or written Email communication.

2 We will mobilize the Installation Team in 3 - 4 working days, after reciept of Site Readyness Confirmation

3 For any reason if we need to stop our Installation and demobilize the Team without completing the Work, then extra cost will be applicable for Remobilizing the Team.

4 If Lifting Equipements are in NIHVA Scope, then those will be used for Installation purpose only and not for any other works.

Note: Please find below List which are in Client Scope

Sr. No	Description	Remark
1	Secured and fully covered Store area to keep the material	In Client Scope
2	Scaffolding/Hydra/Crane/Forklift etc - Required for Installation at Site	In Client Scope
3	Electrical Supply on the site single phase/three phase points at different places.	In Client Scope
4	Any civil / masonry/structural work required	In Client Scope
5	All structure support required	In Client Scope
6	In Case of any changes in the layout as per site requirements after the shipment of material , the additional quantities and the wastage.	In Client Scope
7	Conduits, Cables required	In Client Scope

D) Terms & Conditions

Price : Ex Works Pune

Delivery : 12-13 Weeks for High Speed Door from the date of receipt of confirmed purchase order, Advance Payment & Drawing approval.

Payment : 80% Advance along with Confirmed Purchase Order & Balance before dispatch.

Validity : Validity of Offer is 15 days from the date of quotation

Warranty : 12 months from the date of supply.

For any further Clarification /Information in this Concern, Please feel free to Contact **Mr. Arjun Patil on 8551096333**

With Best Regards
Vivek
8530370333
For NIHVA Technologies Pvt Ltd